



Standard Specification for Reach-in Refrigerators, Freezers, Combination Refrigerator/ Freezers, and Thaw Cabinets¹

This standard is issued under the fixed designation F2520; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers the basic design and function of temperature regulated, continuous duty commercial, and marine refrigerators, freezers, combination refrigerator/freezers and thaw cabinets. The equipment will be stationary and of a vertical or horizontal type.

1.2 Equipment covered under this specification may contain a substance (or be manufactured with a substance) that harms public health and environment by destroying ozone in the upper atmosphere. This specification does not purport to address environmental regulations. It is the responsibility of the user of this specification to comply with environmental regulations.

1.3 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

- A167 Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
- B280 Specification for Seamless Copper Tube for Air Conditioning and Refrigeration Field Service
- D3951 Practice for Commercial Packaging
- F760 Specification for Food Service Equipment Manuals
- F1166 Practice for Human Engineering Design for Marine Systems, Equipment, and Facilities

¹ This specification is under the jurisdiction of ASTM Committee F26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.03 on Storage and Dispensing Equipment.

Current edition approved May 1, 2012. Published August 2012. Originally approved in 2005. Last previous edition approved in 2005 as F2520 – 05. DOI: 10.1520/F2520-05R12.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

2.2 ANSI/UL Standards:³

- ANSI/UL 303 Refrigeration and Air-Conditioning Condensing and Compressor Units
- ANSI/UL 471 Commercial Refrigerators and Freezers
- ANSI/UL 866 Outlet Boxes and Fittings for Use in Hazardous Locations, Class I, Groups A, B, C, and D and Class II, Groups E, F, and G
- ANSI/UL 969 UL Standard for Marking and Labeling Systems

2.3 NSF/ANSI International Standards:⁴

- NSF/ANSI 7 Food Service Refrigerators and Freezers
- NSF/ANSI 51 Plastic Materials and Components Used in Food Service

2.4 ASHRAE Standard:⁵

- ASHRAE 15 Safety Code for Mechanical Refrigeration

2.5 NFPA Standard:⁶

- NFPA 70 National Electrical Code, Article 500, Hazardous Locations

2.6 Canada National Standard/Canadian Standard:⁷

- CAN/CSA C22.2 #120-M91 Refrigeration Equipment

2.7 Federal and Military Documents:⁸

- MIL-STD-167/1 Mechanical Vibrations of Shipboard Equipment (Type I—Environmental and Type II—Internally Excited)
- MIL-STD-461 Requirements For the Control of Electromagnetic Interference Characteristics of Subsystems and Equipment
- MIL-STD-1399/300 Interface Standard For Shipboard Systems Section 300A Electric Power, Alternating Current
- MIL-R-12323 Refrigerators and Related Equipment, Packaging and Packing

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

⁴ Available from NSF International, P.O. Box 130140, 789 N. Dixboro Rd., Ann Arbor, MI 48113-0140.

⁵ Available from American Society of Heating, Refrigerating, and Air-Conditioning Engineers, Inc. (ASHRAE), 1791 Tullie Circle, NE, Atlanta, GA 30329.

⁶ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02269-9101.

⁷ Available from Canadian Standards Association (CSA), 178 Rexdale Blvd., Toronto, ON M9W1R3, Canada.

⁸ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098.

3. Terminology

3.1 Definitions:

3.1.1 *ambient air temperature*—temperature of the air surrounding the exterior of the cabinet or machinery compartment.

3.1.2 *automatic defrost*—process where heat is automatically introduced into the cooling coils to dissipate any ice or frost buildups on the coil.

3.1.3 *capacity*—term that refers to the total cubic foot area of the interior storage.

3.1.4 *condensing units*—each unit shall consist of a compressor, condenser, receiver (if required), fan, and motor.

3.1.5 *evaporator coils (forced air)*—forced circulation type cooling unit consists of a cooling coil, fan with motor, and enclosing casing.

3.1.6 *evaporator coils (static)*—refrigerated inner liner with the refrigerating coils incorporated in or attached to the walls of the unit.

3.1.7 *explosion proof*—refers to a specific requirement for equipment used in hazardous atmospheres.

3.1.8 *horizontal cabinet*—any cabinet of undercounter or counter height design.

3.1.9 *modular*—particular method of cabinet construction, which allows the cabinet and all of its components to be disassembled and reassembled for ease of installation.

3.1.10 *positive latching hardware*—any latching mechanism that requires that the latch be disengaged before the door can be opened.

3.1.11 *thaw*—equipment designed to accelerate the defrosting process of perishable products.

3.1.12 *undercounter*—cabinet which has a maximum height of no more than 36 in. (916 mm).

3.1.13 *unitary*—single piece cabinet construction.

3.1.14 *vertical cabinet*—any cabinet with single or multiple door arrangements whose height is its greatest dimension and is in excess of 36 in. (914 mm).

4. Classification

4.1 *General*—Refrigerators, freezers, combination refrigerator/freezers or thaw cabinets covered by this specification are classified by types, grades, classes, styles, and sizes.

4.2 Type:

4.2.1 *Type I*—Refrigerator.

4.2.2 *Type II*—Freezer.

4.2.3 *Type III*—Combination refrigerator/freezer.

4.2.4 *Type IV*—Thaw cabinet.

4.3 Grades:

4.3.1 *Grade 1*—Vertical cabinet.

4.3.2 *Grade 2*—Horizontal cabinet.

4.4 Classes:

4.4.1 *Class 1*—Modular construction.

4.4.2 *Class 2*—Unitary (single piece) construction.

4.5 *Sizes*—The following tables depict the sizes of the various types of units. This specification does not purport to address all of the sizes that may be available, but is an overview of the most common sizes used in the industry today.

4.5.1 Vertical Cabinet, Style 1 (Refrigerator or Freezer):

Sizes ft ³ (L)	Net Capacity Storage ft ³ (L)	Maximum Width in. (mm)	Maximum Overall Depth in. (mm)	Maximum Height without Legs in. (mm)
5 (142)	4 (113)	33 (838)	27 (686)	64 (1626)
10 (283)	9 (255)	32 (813)	29 (737)	66 (1676)
15 (425)	14 (396)	39 (991)	29 (737)	72 (1829)
20 (566)	19 (538)	51 (1295)	29 (737)	74 (1880)
30 (850)	29 (821)	58 (1473)	32 (813)	74 (1880)
40 (1133)	39 (1104)	68 (1727)	34 (864)	74 (1880)
65 (1841)	64 (1812)	86 (2184)	34 (864)	74 (1880)
85 (2407)	84 (2379)	112 (2845)	34 (864)	74 (1880)

4.5.1.1 Depth shown is maximum overall with door installed.

4.5.1.2 Height does not include legs when applicable.

4.5.2 Horizontal Cabinet, Style 2 (Refrigerator or Freezer):

Sizes ft ³ (L)	Net Capacity Storage ft ³ (L)	Maximum Width in. (mm)	Maximum Overall Depth in. (mm)	Maximum Height without Legs in. (mm)
5 (142)	4.5 (127)	40 (1016)	28 (711)	28 (711)
10 (283)	8 (227)	49 (1245)	28 (711)	28 (711)
20 (566)	18 (510)	84 (2134)	28 (711)	28 (711)
30 (850)	27 (765)	115 (2921)	28 (711)	28 (711)

4.5.2.1 Depth shown is maximum overall with door installed.

4.5.2.2 Height does not include legs when applicable.

4.5.3 Combination Refrigerator/Freezer Cabinet:

Sizes ft ³ (L)	Total Capacity Storage ft ³ (L)	Low Temperature Capacity ft ³ (L)	Maximum Width in. (mm)	Maximum Overall Depth in. (mm)	Maximum Height without Legs in. (mm)
10 (283)	9 (255)	3 (85)	31 (787)	29 (737)	66 (1676)
15 (425)	14 (396)	6 (170)	39 (991)	29 (737)	72 (1829)
20 (566)	19 (538)	8 (227)	51 (1295)	29 (737)	74 (1880)
30 (850)	29 (821)	13 (368)	64 (1626)	32 (813)	74 (1880)
40 (1133)	39 (1104)	18 (510)	68 (1727)	34 (864)	74 (1880)

4.5.3.1 Depth shown is maximum overall with door installed.

4.5.3.2 Height does not include legs when applicable.

4.5.4 Thaw Cabinets:

Size	Maximum Width in. (mm)	Maximum Depth in. (mm)	Maximum Height in. (mm)
One Section	48 (1219)	32 (813)	84 (2134)
Two Section	72 (1829)	32 (813)	84 (2134)

4.6 Styles:

4.6.1 *Style 1*—Manual loading, stationary or fixed shelving.

4.6.2 *Style 2*—Roll-in cart loading.

5. Ordering Information

5.1 *Ordering Data*—Purchasers shall select refrigerators, freezers, combination refrigerator/freezers or thaw cabinet equipment and any preferred options and include the following information in the purchasing document:

5.1.1 Title, number, and date of this specification,

5.1.2 Type, grade, class, style, and size of unit required,

5.1.3 Desired exterior and interior finishes,

5.1.4 Quantity to be furnished,

5.1.5 Electrical power supply characteristics; voltage, phase, frequency,

5.1.6 Number of doors, swing, type (solid or glass),

5.1.7 Accessory equipment: such as spare parts, maintenance parts required, or other options available by the manufacturer, or a combination thereof,

5.1.8 When Federal/Military procurement is required, review and implement the applicable supplementary requirements (see S1 through S8.8.3),

5.1.9 When specified, the purchaser shall be furnished certification that samples representing each lot have been either tested or inspected as directed in this specification and the requirements have been met. When specified, a copy of the test results shall be furnished, (see 14.1 through 14.3),

5.1.10 Level of preservation and packing required if other than as stated in Practice D3951 (see 17.1),

5.1.11 Other custom features or requirements desired, and

5.1.12 Labeling requirements (if different than 15.1).

6. Materials and Manufacture

6.1 *General*—Refrigerators, freezers, combination refrigerator/freezers or thaw cabinets shall conform to NSF/ANSI No. 7. Materials used shall be new and free from defects or reclaimed and recycled conforming to the same quality standards for new materials.

6.1.1 *Corrosion-Resistant Steel*—Corrosion-resistant steel shall conform to Specification A167 and the requirements on 300 or 430 series of stainless steels as applicable.

6.1.2 *Non-Corrosion Resistant Steel*—Mild steel used shall have been treated with a coating of either zinc, chrome, nickel, paint, or similar material to inhibit corrosion.

6.1.3 *Aluminum*—Aluminum alloys shall conform to the requirements of NSF/ANSI No. 7.

6.1.4 *Seamless Copper Tubing*—All refrigerant lines used in the system shall be of seamless copper tubing conforming to Specification B280.

6.1.5 *Hardware, Fittings, Fasteners*—All materials used as hardware, fittings, and fasteners shall be of a corrosion-resistant material.

6.1.6 *Ozone Depleting Compounds*—Type one ozone depleting compounds shall not be used as a refrigerant or as a component of foam insulation and shall be the manufacturer's standard chemicals.

7. Design and Construction

7.1 *General*—Refrigerators, freezers, combination refrigerator/freezers, or thaw cabinets shall be the manufacturer's standard product delivered assembled, ready for mounting, and connected to electricity and used as applicable. Storage temperatures of units shall meet the requirements specified by NSF/ANSI No. 7.

7.2 Refrigeration Equipment:

7.2.1 *Condensing Unit*—Each condensing unit shall conform to the requirements of ANSI/UL 303. Service lines for the attachment of manifold gages and accessories, shall be pro-

vided on both the low and high sides of the system. The capacity of each condensing unit shall be adequate for the intended application.

7.2.2 *Condensing Unit Location*—On vertical type cabinets, the condensing unit may be located on either the top or bottom of the storage compartment. With a horizontal configuration, the condensing unit can be located either to the left or right of the storage compartment unless it is remote.

7.2.3 *Refrigerated Metering*—If a thermal expansion valve is used, it shall adhere to the ASHRAE 15, which addresses system working pressures.

7.2.4 *Evaporated Coil Assembly (Forced Air)*—The coiling coil shall be finned tube construction using copper tubes. The coil tube sheets shall be aluminum, copper, or brass. The fan hub shall be corrosion resistant. The fan and motor shall be direct mounted. The grill opening, shroud, and enclosing casing shall be corrosion resistant.

7.2.5 *Condensate Drain*—All models incorporating forced air evaporators shall provide a thermostatically controlled vaporizer pans as means of disposing of evaporator runoff. An alternate means of condensate evaporation, which allow connection to plumbing, is acceptable. When condensate evaporators are used, they shall have a minimum capacity of 32 oz.

7.3 Modular Construction:

7.3.1 *Panel Construction*—Modular units consisting of panel construction must fit together in such a way that, when reassembled, the panels cannot move more than 1/16 in. (1.6 mm) in any direction.

7.3.2 *Fastening Methods*—For modular constructed units, in the assembly process, only those types of fastening methods can be used which would allow the unit to be disassembled at a future date without the use of special tools or methods which might damage or disfigure the unit. No permanent fastening means of the sub-components to one another, such as welding, brazing, soldering, or the use of epoxies or other adhesives is acceptable.

7.3.3 *Access Caps*—The caps used to seal the panel fastener access hole, when installed shall be watertight and have flared edges. Access caps, as installed, shall conform to NSF/ANSI No. 7.

7.3.4 *Modular Refrigeration Systems*—The refrigeration system shall be furnished fully assembled, and operational. It will have been previously charged, tested, and all controls properly adjusted. The system shall have the capability, if being partially disassembled and reassembled, at the time of installation, without the need of an additional refrigerant charge or control adjustments. The condensing unit shall be able to be removed from the condensing unit compartment for ease in moving the cabinet base section.

7.3.5 *Modular Refrigerant Couplings*—The refrigeration lines shall be connected by using self-sealing refrigerant couplings. The couplings are to be specifically designed for refrigeration applications and shall be used in sets (liquid and suction lines). There shall be a minimum of two sets in a system. Larger systems may require additional sets. The refrigerant couplings are to be a type, which would allow for future system opening at the coupling without its failure.