ISO/TC 22/SC 37/WG5

Secretariat: DIN

Date: 2023-9-1812-19

Electrically propelled road vehicles—___Functional and safety requirements for power transfer between vehicle and external electric circuit—___

Part 1:

General requirements for conductive power transfer

(https://standards.iteh.ai) **Document Preview**

ISO/FDIS 5474-1

https://standards.iteh.ai/catalog/standards/iso/60d7thdd-9564-4701-9c39-317efef77cx1/iso-fdis-5474-1

FDIS stage

Edited DIS MUST BE USED
FOR FINAL
DRAFT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11

Email E-mail: copyright@iso.org

Website: www.iso.org

Published in Switzerland

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 5474-1

https://standards.iteh.ai/catalog/standards/iso/60d7fbdd-9564-4701-9c39-317efef72c81/iso-fdis-5474-1

Contents

6.2.1 General. 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 34 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.3.4 Arc protection 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Functional requirements 18 10 Additional requirements for reverse power transfer 18 11 Owner's manual and marking 19 11.2 Marking	Forev	word	v
1 Scope 1 2 Normative references 1 3 Terms and definitions 2 3.1 General 2 3.2 AC and DC power transfer 6 4 System architecture 9 5 Environmental and operational conditions 11 6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.1 General 12 6.2.2 Insulation resistance 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3	Intro	ductionduction	vi
2 Normative references 1 3 Terms and definitions 2 3.1 General 2 3.2 AC and DC power transfer 6 4 System architecture 9 5 Environmental and operational conditions 11 6. Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disco	Part 1	1: General requirements for conductive power transfer	1
3 Terms and definitions 2 3.1 General 2 3.2 AC and DC power transfer 6 4 System architecture 9 5 Environmental and operational conditions 11 6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after d	1	Scope	1
3.1 General 2 3.2 AC and DC power transfer 6 4 System architecture 9 5 Environmental and operational conditions 11 6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation resistance 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.4 Vehicle movement 18 6.5 </td <td>2</td> <td>Normative references</td> <td>1</td>	2	Normative references	1
3.2 AC and DC power transfer 6 4 System architecture 9 5 Environmental and operational conditions 11 6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18	3	Terms and definitions	2
4 System architecture 9 5 Environmental and operational conditions 11 6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.3.4 Arc protection power at the same contacts<	3.1	General	2
5 Environmental and operational conditions 11 6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.3.4 Arc protection 17 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatib	3.2	AC and DC power transfer	6
6 Safety requirements 12 6.1 General 12 6.2 Protection of persons against electric shock 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.4.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 9 Functional requir	4	System architecture	9
6.1 General 12 6.2 Protection of persons against electric shock. 12 6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.4.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 9 Functional requirements for reverse power transfer 18 10	5	Environmental and operational conditions	11
6.2 Protection of persons against electric shock	6	Safety requirements	12
6.2.1 General 12 6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 10 Additional requirements 18 11 Owner's manual and marking 19 11.1 Owner's manual 19 11.2 Marking 19 11.2 Marking 19	6.1	General	12
6.2.2 Compatibility with external safety devices 12 6.2.3 Insulation resistance 12 6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 9 Functional requirements 18 10 Additional requirements for reverse power transfer 18 11 Owner's manual and marking 1 11.2 Marking 19 12	6.2	Protection of persons against electric shock	12
6.2.3 Insulation resistance	6.2.1	General	12
6.2.4 Touch current 12 6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.3.4 Arc protection 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 9 Functional requirements 18 10 Additional requirements for reverse power transfer 18 11 Owner's manual and marking 19 11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	6.2.2	Compatibility with external safety devices	12
6.2.5 Insulation coordination 12 6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.3.4 Arc protection 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 9 Functional requirements 18 10 Additional requirements for reverse power transfer 18 11 Owner's manual and ma Hing 19 11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	6.2.3	Insulation resistance	12
6.2.6 Protective conductor 12 6.2.7 Basic protection when connected to an external electric circuit 14 6.2.8 Requirements for unmated vehicle contacts 15 6.3 Protection against thermal incident 16 6.3.1 Requirements for normal operation 16 6.3.2 Overcurrent protection 17 6.3.3 Residual energy after disconnection related to thermal incident 17 6.3.4 Arc protection 17 6.4 Vehicle movement 18 6.5 AC or DC electric power at the same contacts 18 7 Electromagnetic compatibility (EMC) 18 8 Protection in case of unintended power transfer 18 9 Functional requirements 18 10 Additional requirements for reverse power transfer 18 11 Owner's manual and marking 19 11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	6.2.4	Touch current	12
6.2.7Basic protection when connected to an external electric circuit146.2.8Requirements for unmated vehicle contacts156.3Protection against thermal incident166.3.1Requirements for normal operation166.3.2Overcurrent protection176.3.3Residual energy after disconnection related to thermal incident176.3.4Arc protection176.4Vehicle movement186.5AC or DC electric power at the same contacts187Electromagnetic compatibility (EMC)188Protection in case of unintended power transfer189Functional requirements1810Additional requirements for reverse power transfer1811Owner's manual and marking1911.1Owner's manual1911.2Marking1912Test19	6.2.5	Insulation coordination	12
6.2.8 Requirements for unmated vehicle contacts. 4.4	6.2.6	Protective conductor	12
Protection against thermal incident60d7/bdd-9564-4701-9639-317efet72c81/so-fds-5474-16 6.3.1 Requirements for normal operation	6.2.7	Basic protection when connected to an external electric circuit	14
6.3.1Requirements for normal operation166.3.2Overcurrent protection176.3.3Residual energy after disconnection related to thermal incident176.3.4Arc protection176.4Vehicle movement186.5AC or DC electric power at the same contacts187Electromagnetic compatibility (EMC)188Protection in case of unintended power transfer189Functional requirements1810Additional requirements for reverse power transfer1811Owner's manual and marking1911.1Owner's manual1911.2Marking1912Test19	6.2.8	Requirements for unmated vehicle contacts	15
6.3.2Overcurrent protection	6.3	Protection against thermal incident	5474-16
6.3.3Residual energy after disconnection related to thermal incident176.3.4Arc protection176.4Vehicle movement186.5AC or DC electric power at the same contacts187Electromagnetic compatibility (EMC)188Protection in case of unintended power transfer189Functional requirements1810Additional requirements for reverse power transfer1811Owner's manual and marking1911.1Owner's manual1911.2Marking1912Test19	6.3.1	Requirements for normal operation	16
6.3.4 Arc protection	6.3.2	Overcurrent protection	17
6.4 Vehicle movement	6.3.3	Residual energy after disconnection related to thermal incident	17
6.5 AC or DC electric power at the same contacts	6.3.4	Arc protection	17
Function in case of unintended power transfer	6.4	Vehicle movement	18
8 Protection in case of unintended power transfer	6.5	AC or DC electric power at the same contacts	18
9 Functional requirements 18 10 Additional requirements for reverse power transfer 18 11 Owner's manual and marking 1 CO 1 19 11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	7	Electromagnetic compatibility (EMC)	18
Additional requirements for reverse power transfer	8	Protection in case of unintended power transfer	18
11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	9	Functional requirements	18
11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	10	Additional requirements for reverse power transfer	18
11.1 Owner's manual 19 11.2 Marking 19 12 Test 19	11	Owner's manual and marking.	19
12 Test 19	11.1	Owner's manual	19
	11.2	Marking	19
12.1 General	12	Test IVIUS I DE USEL	19
	12.1	General	19



Riblio	granhy	21
12.3	Insulation resistance	. 20
12.2	Resistance of protective conductor	. 20

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 5474-1

https://standards.iteh.ai/catalog/standards/iso/60d/tbdd-9564-4701-9c39-317etef/2c81/iso-tdis-5474-1

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawnISO draws attention to the possibility that some of the elements implementation of this document may be involve the subjectuse of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents-. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22 *Road vehicles*, Subcommittee SC 37 *Electrically propelled vehicles*.

A list of all parts in the ISO 5474 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.



Introduction

The ISO 5474 series reorganizes, cancels and replaces ISO 17409:2020 and ISO 19363:2020, both standards have been technically revised.

The ISO 5474 series consists of:

Part 1: General requirements for conductive power transfer

Part 2: AC power transfer

Part 3: DC power transfer

Part 4: Magnetic field wireless power transfer -- Safety and interoperability requirements for light-duty vehicles

Part 5: Automated conductive power transfer

Part 6: Magnetic field wireless power transfer -- Safety and interoperability requirements for heavy-duty vehicles

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 5474-1

https://standards.iteh.ai/catalog/standards/iso/60d/tbdd-9564-4701-9c39-317etef/2c81/iso-tdis-5474-1

Electrically propelled road vehicles — Functional and safety requirements for power transfer between vehicle and external electric circuit — Part 1: General requirements for conductive power transfer —

<u>Part 1:</u>

General requirements for conductive power transfer

1 Scope

This document specifies general requirements for conductive power transfer with a voltage up to 1 000 V ACa.c. (alternative current) and up to 1 500 V DCd.c. (direct current) between electrically propelled road vehicles and external electric circuits.

This document provides general requirements for conductive charging in modes 2, 3 and 4 according to IEC 61851-1, and for reverse power transfer. This document does not provide requirements for mode 1. For mode 4, this document provides requirements regarding the power transfer only with isolated DC EV supply equipment according to IEC 61851-23.

NOTE External electric circuits are not part of the vehicle.

This document applies to the vehicle power supply circuits.

This document does not provide:

- requirements for simultaneous operation of multiple power transfer interfaces, and
- requirements for power transfer while driving (electric road systems),

but they are under consideration.

This document does not provide:

- requirements for mopeds and motorcycles (which are specified in ISO 18246), and
- comprehensive safety information for manufacturing, maintenance and repair personnel.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6469-<u>-</u>3, Electrically propelled road vehicles — Safety specifications — Part 3: Electrical safety

IEC 60364-<u>-</u>5-54, Low-voltage electrical installations — Part 5-54: Selection and erection of electrical equipment — Earthing arrangements and protective conductors

ISO 20653:2023[‡], Road vehicles — Degrees of protection (IP code) — Protection of electrical equipment against foreign objects, water and access

⁺ Third edition under preparation. Stage at the time of publication: ISO/FDIS 20653:2023.

IEC 60479-2:2019, Effects of current on human beings and livestock — Part 2: Special aspects Low-voltage electrical installations

IEC 60664 (all parts), Insulation coordination for equipment within low-voltage supply systems

IEC 61032, Protection of persons and equipment by enclosures — Probes for verification

Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ——ISO Online browsing platform: available at https://www.iso.org/obp
- ——IEC Electropedia: available at https://www.electropedia.org/

3.1 General

3.1.1

basic insulation

insulation of hazardous live parts which provides basic protection

Note 1 to entry: This concept does not apply to insulation used exclusively for functional purposes.

[SOURCE: IEC 60050-195:2021, 195-06-06, modified — The phrase "hazardous live parts" has been added.]

3.1.2

conductive part

part which can carry electric current

[SOURCE: IEC 60050-195:2021, 195-01-06] SO/FDIS 5474standards.iteh.ai/catalog/standards/iso/60d7fbdd-9564-4701-9c39-317efef72c81/iso-fdis-5474-1

3.1.3

degree of protection

protection provided by an enclosure against access, foreign objects and/or water and verified by standardized test methods

[SOURCE: ISO 20653:—2:2023, 3.2]

3.1.4

electrically propelled vehicle

vehicle with one or more *electric drive(s)* (3.1.6(3.1.6)) for vehicle propulsion

Note 1 Note 1 to entry: Electrically propelled vehicle is called electric vehicle in IEC standards.

[SOURCE: ISO 6469-3:2021, 3.15, modified — "EV" added as an equivalent term and Note 1 to entry added.]

² Third edition under preparation. Stage at the time of publication: ISO/DIS 20653:2022.

3.1.5

electric chassis

conductive parts (3.1.2(3.1.2)) of a vehicle that are electrically connected and whose potential is taken as reference

[SOURCE: ISO 6469-3:2021, 3.12]

3.1.6

electric drive

combination of traction motor, power electronics and their associated controls for the conversion of electric to mechanical power and vice versa

[SOURCE: ISO 6469-3:2021, 3.13]

3.1.7

electric power source

system that provides electric energy

Note 1 to entry: The electric power source can also be the power source for reverse power.

EXAMPLE *Rechargeable energy storage system (RESS)* (3.1.20), fuel cell system, photovoltaic system, motor/generator, *EV charging station* (3.2.6-).

[SOURCE: ISO 6469-3:2021, 3.37, modified — Note 1 to entry added, EV charging station added in Example].]

3.1.8

electric shock

physiological effect resulting from an electric current through a human body or animal body

[SOURCE: IEC 60050-195:2021, 195-01-04, modified — "animal body" replaces "livestock".]

3.1.9s://standards.iteh.ai/catalog/standards/iso/60d7fbdd-9564-4701-9c39-317efef72c81/iso-fdis-5474-1

exposed conductive part

conductive part (3.1.2(3.1.2)) of equipment which can be touched and which is not normally live, but which can become live when *basic insulation* (3.1.1(3.1.1)) fails

[SOURCE: IEC 60050-442:1998, 442-01-21, modified — "equipment" replaces "electric equipment" and Note 1 to entry deleted.]

3.1.10

external electric circuit

electric circuit external to the vehicle which exchanges energy with the vehicle

Note 1 to entry: <u>The</u> external electric circuit includes <u>a</u> conductively connected external electric circuit (3.2.5) and magnetically coupled external electric circuit.

3.1.11

hazard

potential source of harm

[SOURCE: ISO/IEC Guide 51:2014, 3.2]

3.1.12

insulation resistance

resistance between *live parts* (3.1.15(3.1.15)) of an electric circuit and the *electric chassis* (3.1.5(3.1.5)) as well as other electric circuits which are insulated from this electric circuit

Note 1 to entry: In UN R100, the equivalent term for "insulation resistance" is "isolation resistance".

[SOURCE: ISO 6469-3:2021, 3.23, modified — <u>AlternativeEquivalent</u> term "isolation resistance" deleted, note 1 to entry added.]

3.1.13

live conductor

conductor which is energized in normal operation and capable of contributing to the transmission or distribution of electric energy

Note 1 to entry: Live conductors include line conductors (including DC+ conductors and DC- conductors) and neutral conductors.

3.1.15

live part

conductor or *conductive part* (3.1.2(3.1.2)) intended to be energized in normal use, but by convention not the *electric chassis* (3.1.5(3.1.5))

[SOURCE: ISO 6469-3:2021, 3.25]

3.1.16

overcurrent protection

protection intended to operate when the current is in excess of a predetermined value

Note 1 to entry: A charge control function is not considered an overcurrent protection.

[SOURCE: IEC 60050-448:1995, 448-14-26, modified — Note 1 to entry added.]

https://standards.iteh.ai/catalog/standards/iso/60d7fbdd-9564-4701-9c39-317efef72c81/iso-fdis-5474-

3.1.17

overload protection

protection intended to operate in the event of overload on the protected section

[SOURCE: IEC 60050-448:1995, 448-14-31]

3.1.18

protective conductor

conductor provided for purposes of safety, for example, protection against *electric shock* (3.1.8(3.1.8))

<u>EXAMPLE</u> <u>Examples of a protective conductor include a protective EXAMPLE Protective</u> bonding conductor, protective earthing conductor and an earthing conductor when used for protection against electric shock (3.1.8).

[SOURCE: IEC 60050-581:2008, 581-27-26]

3.1.19

rated current

current assigned by the manufacturer for a specified operating condition

[SOURCE: IEC 60050-442:1998, 442-01-02, modified — The phrase "of an accessory" was removed from end of definition.]