

---

---

**Cutting tool data representation and  
exchange —**

**Part 4:  
Reference dictionary for adaptive  
items**

**iTeh STANDARD PREVIEW**  
*Représentation et échange des données relatives aux outils  
coupants —*  
**(standards.iteh.ai)**

*Partie 4: Dictionnaire de référence pour les éléments relatifs aux  
attachements*

ISO/TS 13399-4:2021

<https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/TS 13399-4:2021](https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021)

<https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|  |            |
|--|------------|
| Foreword.....  | iv         |
| Introduction.....  | v          |
| <b>1 Scope.....</b>  | <b>1</b>   |
| <b>2 Normative references.....</b>   | <b>2</b>   |
| <b>3 Terms and definitions.....</b>  | <b>2</b>   |
| <b>4 Abbreviated terms.....</b>  | <b>4</b>   |
| <b>5 Representation of the ontology concepts as dictionary entries.....</b>                                  | <b>4</b>   |
| 5.1 General.....   | 4          |
| 5.2 adaptive_item_type.....  | 5          |
| 5.2.1 General.....   | 5          |
| 5.2.2 collet.....  | 5          |
| 5.2.3 converter.....   | 5          |
| 5.2.4 driver.....  | 5          |
| 5.2.5 extender.....  | 5          |
| 5.2.6 reducer.....   | 6          |
| 5.3 Reference system for adaptive items.....   | 6          |
| 5.3.1 General.....   | 6          |
| 5.3.2 prismatic_adaptive_item_position.....  | 6          |
| 5.3.3 round_adaptive_item_position.....  | 7          |
| 5.4 adaptive_item_feature.....   | 7          |
| 5.5 General feature types.....   | 7          |
| <b>6 Properties for adaptive items.....</b>  | <b>7</b>   |
| <b>Annex A (normative) Principles of the ISO 13399 series.....</b>   | <b>12</b>  |
| <b>Annex B (informative) Classification table.....</b>   | <b>15</b>  |
| <b>Annex C (informative) Class definitions.....</b>  | <b>16</b>  |
| <b>Annex D (informative) Adaptive item property definitions.....</b>   | <b>42</b>  |
| <b>Annex E (informative) ISYC pictures.....</b>  | <b>170</b> |
| <b>Annex F (informative) Illustration of properties.....</b>   | <b>191</b> |
| <b>Annex G (informative) Principles for applying body parameters of rotational symmetrical adapters.....</b> | <b>194</b> |
| <b>Bibliography.....</b>   | <b>199</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 29, *Small tools*.

This third edition cancels and replaces the second edition (ISO/TS 13399-4:2014), which has been technically revised.

The main change is as follows:

- update of the classes and properties in line with the modifications in the cutting tool dictionary.

A list of all parts in the ISO 13399 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This document defines the terms used for adaptive items. The purpose of this document is to provide a reference dictionary to support the use of the general information model defined in ISO 13399-1.

A cutting tool with defined cutting edges is used on a machine to remove material from a workpiece by a shearing action at the cutting edges of the tool. Cutting tool data that can be described by the ISO 13399 series include, but are not limited to, everything between the workpiece and the machine tool. Information about inserts (e.g. regular and irregular shaped replaceable cutting items), solid tools (e.g. solid drill and solid end mill), assembled tools (e.g. boring bars, indexable drills and indexable milling cutters), adaptors (e.g. milling arbor and drilling chuck), components (e.g. shims, screws and clamps) and their relationships can be represented by the ISO 13399 series. The principles of the ISO 13399 series are given in [Annex A](#), and possible assemblies of the components of a cutting tool are illustrated in [Figure A.1](#).

The objective of the ISO 13399 series is to provide the means to represent the information that describes cutting tools in a computer-sensible form that is independent from any particular computer system. The representation facilitates the processing and exchange of cutting tool data within and between different software systems and computer platforms and supports the application of this data in manufacturing planning, cutting operations, and the supply of tools. The nature of this description makes it suitable not only for neutral file exchange but also as a basis for implementing and sharing product databases and for archiving. The methods used for these representations are those developed by ISO/TC 184/SC 4 for the representation of product data by using standardized information models and reference dictionaries.

An information model is a formal specification of types of ideas, facts, and processes which together describes a portion of interest of the real world and which provides an explicit set of interpretation rules. Information is knowledge of ideas, facts, and/or processes. Data are symbols or functions that represent information for processing purposes. Data are interpreted to extract information by using rules for how that should be done and a dictionary to define the terms that identify the data. Everyone in a communication process is expected to use the same information model, the same set of explicit rules and the same dictionary in order to avoid misunderstanding. If an information model and its dictionary are written in a computer-sensible language, then there is the additional benefit that they can be computer processable.

An engineering information model is therefore a specification for data that establishes the meaning of that data in a particular engineering context. A model has to be developed by formal methods to ensure that it meets the needs of the situation that it represents. An engineering information model defines the information objects that represent the concepts in an engineering application, the attributes of the objects, their relationships, and the constraints that add further meaning. An information model is an abstract concept that can be used repeatedly for any example of the real-world situation that it represents. An instance of the model is produced when it is populated with the data items and their values that are applicable to a particular example of that situation.

This document uses the following International Standards developed by ISO/TC 184/SC 4:

- the EXPRESS language defined in ISO 10303-11 for defining the information model in ISO 13399-1;
- the file format for data exchange derived from the model and defined in ISO 10303-21;
- the data dictionary defined in the ISO 13584 series.

Each class, property, or domain of values of this application domain constitutes an entry of the reference dictionary defined in this document. It is associated with a computer-sensible and human-readable definition and with a computer-sensible identification. Identification of a dictionary entry allows unambiguous reference to it from any application that implements the information model defined in ISO 13399-1.

Definitions and identifications of dictionary entries are defined by means of standard data that consist of instances of the EXPRESS entity data types defined in the common dictionary schema, resulting from

## ISO/TS 13399-4:2021(E)

a joint effort between ISO/TC 184/SC 4 and IEC SC 3D, and in its extensions defined in ISO 13584-24 and ISO 13584-25.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/TS 13399-4:2021](https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021)

<https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>

# Cutting tool data representation and exchange —

## Part 4: Reference dictionary for adaptive items

### 1 Scope

This document specifies a reference dictionary for adaptive items, together with their descriptive properties and domains of values.

This document specifies a reference dictionary containing:

- definitions and identifications of the classes of adaptive items, with an associated classification scheme;
- definitions and identifications of the data element types that represents the properties of adaptive items;
- definitions and identifications of domains of values for describing the above-mentioned data element types.

The following are within the scope of this document:

- standard data that represent the various classes of adaptive items;
- standard data that represent the various properties of adaptive items;
- standard data that represent domains of values used for properties of adaptive items;
- one implementation method by which the standard data defined in this document can be exchanged.

NOTE 1 The implementation method by which the standard data defined in this document can be exchanged is specified in ISO 10303-21.

The following are outside the scope of this document:

- specialized or expert knowledge in the design and use of cutting tools;
- rules to determine what information should be communicated;
- applications where these standard data can be stored or referenced;
- implementation methods other than the one defined in this document by which the standard data can be exchanged and referenced;
- information model for cutting tools;
- definitions of classes and properties for cutting items;
- definitions of classes and properties for tool items;
- definitions of classes and properties for assembly items;
- definitions of classes and properties for connection systems;
- definitions of classes and properties for reference systems.

NOTE 2 The information model for cutting tools is defined in ISO 13399-1.

NOTE 3 The definitions of classes and properties for cutting items, tool items, and assembly items are provided in ISO/TS 13399-2, ISO/TS 13399-3, and ISO/TS 13399-5.

NOTE 4 The definitions of classes and properties for connection systems and reference systems are provided in ISO/TS 13399-50.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 13399-50, *Cutting tool data representation and exchange — Part 50: Reference dictionary for reference systems and common concepts*

ISO/TS 13399-100, *Cutting tool data representation and exchange — Part 100: Definitions, principles and methods for reference dictionaries*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/TS 13399-50, ISO/TS 13399-100 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

**3.1** **applicable property** ISO/TS 13399-4:2021  
<https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a1001010101>  
property (3.17) that is defined for some family of items and that applies to any member of this family

[SOURCE: ISO 13584-24:2003, 3.3, modified — "family of parts" has been replaced by "family of items"; "shall apply" has been replaced by "applies"; "any part" has been replaced by "any member"; the EXAMPLE has been removed.]

**3.2** **basic semantic unit**  
*entity* (3.10) that provides an absolute and universally unique identification of a certain object of the application domain that is represented as a *dictionary* (3.9) element

[SOURCE: ISO 13584-42:2010, 3.4, modified — The 3 EXAMPLES and note 1 to entry have been removed.]

**3.3** **chip**  
material removed from a *workpiece* (3.19) by a cutting process

**3.4** **cutting tool**  
device or assembly of items for removing material from a *workpiece* (3.19) through a shearing action at the defined cutting edge or edges of the device

Note 1 to entry: A cutting tool can be the assembly of one or more adaptive items, a tool item, and several cutting items on a tool item. See [Figure A.1](#).

[SOURCE: ISO 13399-1:2006, 3.1]



**3.5****data**

representation of *information* (3.13) in a formal manner suitable for communication, interpretation, or processing by human beings or computers

[SOURCE: ISO 10303-1:2021, 3.1.29]

**3.6****data element type**

unit of *data* (3.5) for which the identification, description, and value representation have been specified

[SOURCE: ISO 13584-42:2010, 3.13, modified — Note 1 to entry has been removed.]

**3.7****data exchange**

storing, accessing, transferring, and archiving of *data* (3.5)

[SOURCE: ISO 10303-1:2021, 3.1.31]

**3.8****data type**

domain of values

[SOURCE: ISO 10303-11:2004, 3.3.5]

**3.9****dictionary**

table consisting of a series of entries with one meaning corresponding to each entry in the dictionary and one dictionary entry identifying a single meaning

Note 1 to entry: In the ISO 13399 series, a dictionary is a formal and computer-sensible representation of an *ontology* (3.16). <https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>

[SOURCE: ISO 13584-511:2006, 3.1.9, modified — The original notes 1 to 3 to entry have been replaced by a new note 1 to entry.]

**3.10****entity**

class of *information* (3.13) defined by its attributes which establishes a domain of values defined by common attributes and constraints

**3.11****entity data type**

representation of an *entity* (3.10)

**3.12****implementation method**

means for computers to exchange *data* (3.5)

**3.13****information**

facts, concepts, or instructions

[SOURCE: ISO 10303-1:2021, 3.1.41]

**3.14****information model**

formal model of a bounded set of facts, concepts, or instructions to meet a specific requirement

**3.15****machine side**

identification of a direction pointing towards the machine

### 3.16

#### **ontology**

explicit and consensual specification of concepts of an application domain independent of any use of these concepts

Note 1 to entry: In the ISO 13399 series, a *dictionary* (3.9) is the formal and computer-sensible representation of ontology.

[SOURCE: ISO 13584-511:2006, 3.1.20, modified — In note 1 to entry, the reference to "ISO 13584" has been replaced by "the ISO 13399 series".]

### 3.17

#### **property**

defined parameter suitable for the description and differentiation of products

[SOURCE: ISO 13584-42:2010, 3.37, modified — Notes 1 to 5 to entry have been removed.]

### 3.18

#### **visible property**

*property* (3.17) that has a definition meaningful in the scope of a given characterization class but does not necessarily apply to the various products belonging to this class

[SOURCE: ISO 13584-42:2010, 3.46]

### 3.19

#### **workpiece**

object on which a cutting action is performed

[SOURCE: ISO/TS 13399-2:2021, 3.21] (standards.iteh.ai)

### 3.20

#### **workpiece side**

identification of a direction pointing towards the *workpiece* (3.19)

Note 1 to entry: The xzw-plane, the xyw-plane, and the yzw-plane are mutually perpendicular.

## 4 Abbreviated terms

BSU basic semantic unit

DET data element type

## 5 Representation of the ontology concepts as dictionary entries

### 5.1 General

The generic family of adaptive items is divided into several simple families and classes determined by their main function.

NOTE An adaptive item can have one or more than one function.

A concept in the ontology is identified by a name in lower-case characters. The name of a class that represents the concept in the dictionary is identified by lower-case characters with multiple words joined by an underscore character.

EXAMPLE "round shape conversion" is the name for a function of an adaptive item. "round\_shape\_conversion" is the identifier of the class in the dictionary that represents the concept.

Some of the definitions of properties that are applicable to adaptive items are defined in terms of a primary coordinate system. The coordinate system is the same for adaptive items, cutting items, and

tool items and is defined in ISO/TS 13399-50. The applications of this system to adaptive items are described in this document.

Each entry in the dictionary, either a class or a property, is identified with a numerical code (BSU) that is generated at random when the dictionary is compiled. A BSU can be made unique by the addition of a code that is a reference to the supplier of the dictionary. Each classified item in the following subclasses is associated with its definition from the dictionary.

The ISO 13399 series shall follow the principles in [Annex A](#). The structure of the classification is summarized in [Annex B](#). The complete definitions of the adaptive item classes are provided in [Annex C](#). The properties applicable to adaptive items are defined in [Annex D](#).

## 5.2 adaptive\_item\_type

### 5.2.1 General

Family of objects for the assembly of a cutting tool classified by their main function.

NOTE An adaptive item can have one or more functions.

adaptive\_item\_type has the following subclasses:

- collet;
- converter;
- driver;
- extender;
- reducer.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>

### 5.2.2 collet

A collet is a segmented band that can be expanded or contracted to grip a shaft.

NOTE 1 This class is for general engineering use and is not specific to cutting tools.

NOTE 2 This class can become an item\_class\_case\_of an entry in another dictionary conforming to the ISO 13584 series.

### 5.2.3 converter

A converter is an adaptive item with a different connection type, style, and size on the machine side from the workpiece side.

### 5.2.4 driver

A driver is an adaptive item with the capability to rotate a cutting tool for cutting operations not on the main machine spindle axis.

### 5.2.5 extender

An extender is an adaptive item that increases the length of an assembled cutting tool.

NOTE The adaptive item has the same connection type, style, and size on both the machine side and workpiece side.

### 5.2.6 reducer

A reducer is an adaptive item that diminishes the size of a connection in an assembled cutting tool.

NOTE The adaptive item has the same connection type and style on the machine side and workpiece side.

The connections on either side of an item shall be different in gender, i.e. male and female.

## 5.3 Reference system for adaptive items

### 5.3.1 General

The primary coordinate system used for adaptive items in this document is defined in ISO/TS 13399-50. The additional reference entities relevant for adaptive items are:

- `prismatic_adaptive_item_position`;
- `round_adaptive_item_position`.

`adaptive_item_type` has the following simple families of items as subclasses:

- `dependency`;
- `mirror plane`;
- `mounting coordinate system`;
- `coordinate system workpiece side`;
- `primary coordinate system`;
- `xy-plane`;
- `xyw-plane`;
- `xz-plane`;
- `xzw-plane`;
- `yz-plane`;
- `yzw-plane`.

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

[ISO/TS 13399-4:2021](https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021)

<https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>

### 5.3.2 `prismatic_adaptive_item_position`

A `prismatic_adaptive_item_position` identifies the location of a prismatic adaptive item where:

- the base of the adaptive item shall be coplanar with the XZ-plane;
- the normal for the base of the item shall be in the  $-Y$  direction;
- the rear backing surface shall be coplanar with the YZ-plane;
- the normal for the rear backing surface shall be in the  $-X$  direction;
- the end of the item shall be coplanar with the XY-plane;
- the normal for the end of the item shall be in the  $-Z$  direction;
- if with a bore, then the vector of the bore of the item that points in the Z direction shall also point towards the workpiece side.

NOTE The conditions listed above apply to right-handed adaptive items. Left-hand items are defined as for right-hand items but mirrored through the YZ-plane.

### 5.3.3 round\_adaptive\_item\_position

A round\_adaptive\_item\_position identifies the location of a round adaptive item where:

- the axis of the adaptive item shall be colinear with the Z axis;
- the vector of the shank that points in the Z direction shall also point towards the workpiece side;
- the drive slots or clamping flats if present shall be parallel with the XZ-plane;
- the contact surface of the coupling, the gauge plane, or the end of the cylindrical shank shall be coplanar with the XY-plane;
- if with a bore, then the vector of the bore of the item that point in the Z direction shall also point towards the workpiece side.

NOTE The conditions listed above apply to right-handed adaptive items. Left-handed adaptive items are defined as for right-handed items but mirrored though the YZ-plane.

### 5.4 adaptive\_item\_feature

- torque bracing.

### 5.5 General feature types

- adjustment: **iTeh STANDARD PREVIEW**  
(standards.iteh.ai)
- adjustment axial;
- adjustment radial.
- bolt hole circle: [ISO/TS 13399-4:2021](https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021)
- coolant supply; <https://standards.iteh.ai/catalog/standards/sist/5f89b261-a4d4-4bb0-8a6f-3a855d961247/iso-ts-13399-4-2021>
- cutting data association;
- flange;
- keyway;
- locking mechanism;

## 6 Properties for adaptive items

The properties of adaptive items are defined in [Annex D](#), where the association of a property with a class is specified. In the compilation of the dictionary, all properties are visible properties at the root class of the dictionary and are made applicable properties at the class level where they apply. The names of properties that can be applicable for adaptive item types, with their identification codes (BSU), are shown in [Table 1](#). The order of names in the table should be read in rows from left to right.

NOTE The BSU can be made unique by the addition of the supplier of the dictionary as a prefix to the identification code.

EXAMPLE The unique BSU for adaptor clamp would be: 0112/1///13399\_\_2-71CED04F3300A for version two of the dictionary.

**Table 1 — Names of properties for adaptive items**

| Property name | Symbol | Identification code (BSU) |
|---------------|--------|---------------------------|
| adaptor clamp | ADC    | 71CED04F3300A             |

Table 1 (continued)

| Property name                            | Symbol  | Identification code (BSU) |
|--|---------|---------------------------|
| adaptor tool clamp                       | ATC     | 71CED04F920EC             |
| adjusting screw protrusion               | ASP     | 71EAC0F0EFDB6             |
| balance device                           | BLDEV   | 726E3E971B954             |
| balance quality code                     | BLQ     | 71DF151EA5CF1             |
| balancing method code                    | BLMC    | 71EAC0CAB861F             |
| body angle workpiece side                | BAWS    | 72C4A71D1B94B             |
| body diameter                            | BD      | 71ED6A9AF7D1D             |
| body diameter maximum                    | BDX     | 71D08462F8185             |
| body half taper angle                    | BHTA    | 71EAC472BD116             |
| body height                              | HTB     | 71EBB332C60EB             |
| body length                              | LB      | 71ED6AA478A3D             |
| body length maximum                      | LBX     | 71DCD3B16750B             |
| body material code                       | BMX     | 71DF1523224D8             |
| body section count                       | BSC     | 72C5C9C07963B             |
| body taper end diameter                  | BTED    | 726E3E85D4D0A             |
| body taper end length                    | BTEL    | 71EADEA2BF8DF             |
| body width                               | WB      | 71EBB33230236             |
| bracing                                  | BRC     | 728C565985774             |
| brand                                    | BRAND   | 728ECFD658014             |
| cartridge size code                      | CASC    | 71DF1523EE184             |
| clamping force maximum                   | MXC     | 71CED05149532             |
| clamping length machine side             | LSCMS   | 71EBAF896BE9A             |
| clamping length maximum machine side     | LSCXMS  | 71ED6E54B15C4             |
| clamping length minimum machine side     | LCSNMS  | 71EBB339ED2BD             |
| clamping length minimum workpiece side   | LSCNWS  | 72E33DEACC133             |
| clamping length workpiece side           | LSCWS   | 72996F3DC8E8A             |
| clamping method connection interface     | CMCS    | 72C96D143532C             |
| clamping width                           | WSC     | 71EBAF85006BD             |
| collet length                            | LCOL    | 72724DF38CB41             |
| collet slope type                        | COLST   | 726E4223BA018             |
| connection arrangement workpiece side    | CONARWS | 728C565E652E2             |
| connection code form output side         | CCFOP   | 727212846FDA5             |
| connection code form type machine side   | CCFMS   | 726E3E84DD902             |
| connection code form type workpiece side | CCFWS   | 726E3E8558953             |
| connection code input side               | CCIP    | 728C565EDCAD              |
| connection code machine side             | CCMS    | 71D102AE3B252             |
| connection code output side              | CCOP    | 7272128615A59             |
| connection code type machine side        | CCTMS   | 726E3E82E53A6             |
| connection code type output side         | CCTOS   | 727212869DDE2             |
| connection code type workpiece side      | CCTWS   | 726E3E83D7357             |
| connection code workpiece side           | CCWS    | 71D102AE8A5A9             |
| connection count workpiece side          | CCONWS  | 71EDD2C17746F             |
| connection depth                         | CBDP    | 71EAC48CAD407             |
| connection diameter machine side         | DCONMS  | 71EBDBF5060E6             |

Table 1 (continued)

| Property name   | Symbol  | Identification code (BSU) |
|---|---------|---------------------------|
| connection diameter maximum workpiece side            | DCONXWS | 72807E35DE582             |
| connection diameter minimum workpiece side            | DCONNWS | 72807E3576AAE             |
| connection diameter workpiece side                    | DCONWS  | 7272379A5F325             |
| connection protruding length                          | LPCON   | 726E3E863255C             |
| connection retention knob thread size                 | CRKS    | 71CF298A76B66             |
| connection size code (deprecated)                     | CZC     | 71FC193318002             |
| connection size code machine side                     | CZCMS   | 727C2BCCC5596             |
| connection size code maximum workpiece side           | CZCXWS  | 72807E36B6C92             |
| connection size code minimum workpiece side           | CZCNWS  | 72807E366B041             |
| connection size code output side                      | CZCOP   | 727233FBAC835             |
| connection thread nominal size machine side           | THSZMS  | 727BE508AAB46             |
| connection thread nominal size workpiece side         | THSZWS  | 727BE5090F9AA             |
| connection unit base precision machine side           | CUBPMS  | 7280553C9A894             |
| connection unit base precision maximum workpiece side | CUBPXWS | 729A91AC5433F             |
| connection unit base precision minimum workpiece side | CUBPNWS | 729A91ABE3690             |
| connection unit base precision workpiece side         | CUBPWS  | 7280605902AD1             |
| connection unit basis                                 | CUB     | 71ED6E16D5978             |
| contact surface diameter machine side                 | DCSFMS  | 71D087D97FCE3             |
| contact surface diameter workpiece side               | DCSFWS  | 71EAC0DD5D650             |
| coolant supply property                               | CSP     | 71EBB342CC751             |
| cutting diameter cutting tool maximum                 | DCCTX   | 727237959C51F             |
| damping property                                      | DPC     | 71CED03D70452             |
| data chip provision                                   | DCP     | 71CF29869CA0F             |
| designation   | DES     | 728ECFD4A0629             |
| diameter access hole                                  | DAH     | 71EBB2F865924             |
| diameter collet length clamp                          | DCLC    | 7272379935018             |
| diameter collet offset bore                           | DCOB    | 7272379998737             |
| distance to face                                      | LFSF    | 727BE4DF9AF4A             |
| drive method  | DRVMETH | 72807E232B06B             |
| drive size  | DRVSC   | 71E03063ABD6E             |
| driver slot width                                     | DRVSLW  | 728C5662F4DC6             |
| driving key type                                      | DKTY    | 71EC5E1ECC776             |
| functional diameter                                   | DFC     | 7272379AD9C85             |
| functional height                                     | HF      | 71CF29994E737             |
| functional length                                     | LF      | 71DCD39338974             |
| functional length minimum                             | LFN     | 71EBC1EB8456A             |
| functional width                                      | WF      | 71CF29984CDA7             |
| gauge diameter distance                               | LDG     | 727BA921CDF0C             |
| groove width  | GW      | 72724DEA4CF84             |
| guide diameter  | DGUI    | 726E3EB45D478             |
| guide length  | LGUI    | 726E3EB54F909             |
| height adjustability                                  | ADJHT   | 726E3E95EEC5D             |
| interlocking capability                               | ILC     | 727C2F58CB275             |
| item style code                                       | ISYC    | 726E424FE9EC2             |