

© ISO 2023/2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: + 41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Formatted: Font: Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Left

Formatted: Left: 1.9 cm, Right: 1.9 cm, Bottom: 1 cm, Gutter: 0 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Formatted: Default Paragraph Font

Formatted: French (France)

Formatted: French (France)

Formatted: French (France)

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO/FDIS 13473-4

<https://standards.itih.ai/catalog/standards/iso/73a4f4cf-23dc-4371-b8fa-61ffe12f776d/iso-fdis-13473-4>

Formatted: FooterPageRomanNumber

Contents

Foreword iv

Introduction..... v

1 Scope 1

2 Normative references 1

3 Terms and definitions..... 2

4 Symbols and abbreviated terms..... 5

5 Basic outline of methodologies of spatial frequency analysis..... 6

6 Sampling of surface profiles 8

6.1 Requirements concerning profilometers and data preparations..... 8

6.2 Sampling of road sections..... 8

6.3 Measurement of laboratory samples..... 8

6.4 Texture profile levels (logarithmic scale) 9

6.5 Anti-aliasing filtering 9

6.6 Drop-out correction and interpolation 10

6.7 Resampling to a constant spatial resolution 11

6.8 Spike identification and reshaping the profile 12

7 Spectral analysis in constant-percentage bandwidth bands (octave- or one-third-octave bands) by digital filtering 12

8 Uncertainty of analysis results 13

9 Reporting of analysis results..... 14

Annex A (normative) Uncertainty of spectral analysis results 16

Annex B (informative) Spectral analysis and profile asymmetry..... 22

Annex C (informative) Spectral analysis by means of discrete (fast) Fourier transform methods 24

Annex D (normative) Spike removal procedure 34

Annex E (informative) Testing the calculation procedure 38

Annex F (normative) Profile conditioning before filtering 40

Bibliography 43

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Left

Formatted: FooterPageRomanNumber

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO/TS 13473-4:2008), which has been technically revised.

The main changes are as follows:

- the pre-processing of the input data to the spectral analysis has been improved and is in line now with the procedure of ISO 13473-1
- an old analogue technique has been removed and there is one normative method of the spectral analysis defined;
- significant improvements have been made to the uncertainty analysis.

A list of all parts in the ISO 13473 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Formatted: Font: Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Left

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Commented [eXtyle1]: Invalid reference: "ISO 13473 series"

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

Introduction

Pavement texture is a basic road surface characteristic and is related to many important functional characteristics, such as noise emission from tyre-road interaction, friction between tyre and road, rolling resistance, tyre wear and the technical condition of the road surface.

Spectral analysis is commonly used in various fields of signal processing and has been found to be a useful method of pavement characterization for pavement surface profiles including texture measurements.

There are many ways to perform spectral analysis. The current document describes the spectral analysis, in octave and one-third-octave bands.

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Left

iTeh Standards (<https://standards.itih.ai>) Document Preview

ISO/FDIS 13473-4

<https://standards.itih.ai/catalog/standards/iso/73a4f4cf-23dc-4371-b8fa-61ffe12f776d/iso-fdis-13473-4>

Formatted: FooterPageRomanNumber

Characterization of pavement texture by use of surface profiles

Part 4: Spectral analysis of surface profiles

Formatted: Left: 1.9 cm, Right: 1.9 cm, Bottom: 1 cm, Gutter: 0 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Part 4: One third octave band spectral analysis of surface profiles

1 Scope

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

This document describes the methods that are available to perform a spectral analysis of a pavement surface profile. It specifies a method for performing spatial frequency analysis (or texture wavelength analysis) of two-dimensional surface profiles that describe the pavement texture amplitude as a function of the distance along a straight or curved trajectory over the pavement. It also details an alternative (non-preferred) method to obtain these spectra:

a) ~~a)~~ constant-percentage bandwidth obtained by digital filtering (normative method);

Formatted: Numbered + Level: 1 + Numbering Style: a, b, c, ... + Start at: 1 + Alignment: Left + Aligned at: 0 cm + Indent at: 0 cm, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

b) ~~b)~~ constant narrow bandwidth frequency analysis by means of discrete Fourier transform (DFT), followed by a transformation of the narrow-band spectrum to an octave- or one-third-octave-band spectrum (informative).

The result of the frequency analysis will be a spatial frequency (or texture wavelength) spectrum in constant-percentage bandwidth bands of octave or one-third-octave bandwidth.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

The objective of this document is to standardize the spectral characterization of pavement surface profiles. This objective is pursued by providing a detailed description of the analysis methods and related requirements for those who are involved in pavement characterization but are not familiar with general principles of frequency analysis of random signals. These methods and requirements are generally applicable to all types of random signals; however, they are elaborated in this document for their use in pavement surface profile analysis.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

NOTE ~~ht~~ The spectral analysis as specified in this document cannot express all characteristics of the surface profile under study. In particular, the effects of asymmetry of the profile, e.g. the difference of certain functional qualities for "positive" and "negative" profiles cannot be expressed by the power spectral density, as it disregards any asymmetry of the signal (see ~~Annex B~~ Annex B).

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

2 Normative references

Formatted: Default Paragraph Font

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Formatted: Default Paragraph Font

~~ISO 13473-ISO 13473-2~~, Characterization of pavement texture by use of surface profiles — Part 2: Terminology and basic requirements related to pavement texture profile analysis ~~ISO 13473-2~~

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

~~ISO 13473-ISO 13473-3~~, Characterization of pavement texture by use of surface profiles — Part 3: Specification and classification of profilometers ~~ISO 13473-3~~

Formatted: Default Paragraph Font

~~IEC 61260-1~~, Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications ~~IEC 61260-1~~

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Commented [eXtyle2]: Not found: "IEC 61260-1"

~~ISO/IEC Guide 98-3~~ ISO/IEC Guide 98-3, Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13473-2 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org>

3.1 drop-out

data in the measured profile indicated by the sensor as invalid

3.2 drop-out rate

percentage (%) of measured points within the *evaluation length* (3.3) which are identified as being invalid

3.3 evaluation length

l
length of a portion of a profile which has been or is to be analysed

Note_1-to-entry: The evaluation length may or may not be equal to the *profile measurement length* (3.5) (but never greater).

Note_2-to-entry: Evaluation length is normally expressed in metres (m) or millimetres (mm).

3.4 measurement speed

v
speed at which the *profilometer* (3.7) sensor traverses the surface to be measured

Note_1-to-entry: Measurement speed is normally expressed in kilometres per hour (km/h) or metres per second (m/s).

3.5 profile measurement length

l_p
length of an uninterrupted profile measurement

Note_1-to-entry: Profile measurement length is normally expressed in metres (m) or millimetres (mm).

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Commented [eXtyle3]: The URL <https://www.iso.org/obp> has been redirected to <https://www.iso.org/obp/ui>. Please verify the URL.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: FooterPageRomanNumber

**3.7
profilometer**

device used for measuring the two-dimensional (2D) profile of a pavement surface

Note_1-to entry:-Any design of profilometer could be used if the requirements in ISO 13473-3 is fulfilled for the specific purpose of the analysis.

Note_2-to entry:-Profilometers can be divided into stationary, mobile low speed or mobile high speed devices.

**3.8
power spectral density
PSD**

quantity expressing the power contained in a signal per unit frequency or per unit wavelength as a function of frequency or wavelength

Note_1-to entry:-In the case of a discrete Fourier transform of a sampled signal, the PSD may be defined as the squared magnitude of the components of the Fourier series divided by the effective bandwidth of the (narrow) bands of the Fourier spectrum (see 6.4-C.4).

Note_2-to entry:-In the case of spectral analysis of a pavement surface profile, the signal is not a function of time but of evaluation length *l*. The Power Spectral Density may then be given as a function of the spatial frequency or the (texture) wavelength and will be expressed in the unit $m^2/m^{-1} = m^3$ or in the unit m^2/mm , respectively.

Note_3-to entry:-The word "Power" in this designation originates from electric and acoustic signal terminology where signals incorporate actual power and where the squared amplitude is a measure of this power.

**3.9
sampling interval**

~~Δx~~
 ~~Δx~~
distance between two adjacent data points of the surface profile, which is equal to the measurement speed divided by the sampling frequency of the sensor

Note_1-to entry:-Sampling interval is normally expressed in millimetres (mm).

**3.10
spatial frequency**

~~f_{sp}~~
 ~~f_{sp}~~
number of sinusoidal cycles per unit length

Note 1-to entry:-Spatial frequency is normally expressed in reciprocal metres (m^{-1}); see also 3.13, 3.13, Note 3.

Note_2-to entry:-The term "frequency" used in the time domain, corresponds to "spatial frequency" in the space domain.

**3.11
surface profile
texture profile**

~~$Z(X)$~~
 ~~$Z(X)$~~
upper contour of a vertical cross-section through a pavement

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Left

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: French (France)

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

Note_1-to entry:- Texture profile is similar to surface profile but limited to the texture range.

Note_2-to entry:- The profile of the surface is described by two coordinates: one in the surface plane, called distance (the abscissa), and the other in the direction normal to the surface plane, called vertical displacement (the ordinate). The distance may be in the longitudinal or lateral (transverse) directions in relation to the travel direction on a pavement, or in a circle or any other direction between these extremes.

3.12 surface profile spectrum texture spectrum

spectrum obtained when a profile curve has been analysed by either digital filtering or Digital Fourier Transform (DFT) techniques to determine the magnitude of its spectral components at different wavelengths (3.13)(3.13) or spatial frequencies (3.10)(3.10)

Note_1-to entry:- Wavelengths between 0,5 mm and 500 mm belongs to the texture spectrum and 0,5 m to 50 m belongs to the unevenness spectrum (3.11)(2).

Note_2-to entry:- A texture spectrum presents the magnitude of each spectral component as a function of either texture wavelength or spatial frequency.

3.13 texture wavelength

quantity describing the horizontal dimension of the amplitude variations of a surface profile (3.11)(3.11)

Note_1-to entry:- (Texture) wavelength is normally expressed in metres (m) or millimetres (mm).

Note_2-to entry:- Wavelength is a quantity commonly used and accepted in electrotechnical and signal processing vocabularies. Since many users of this document might not be accustomed to use the term wavelength in pavement applications, and because electrical signals are often used in the analyses of road surface profiles, there is a possibility of confusion. Hence, the expression "texture wavelength" is preferred here to make a clear distinction in relation to other applications.

Note_3-to entry:- Texture wavelength in ISO 13473 is the reciprocal of the spatial frequency, the unit of which is reciprocal metre (equivalent to cycles per metre). See also 3.10-3.10.

Note_4-to entry:- Wavelengths are represented physically as the various lengths of periodically repeated parts of the profile.

3.14 texture profile level

logarithmic transformation of an amplitude representation of a surface profile curve Z(X), the latter expressed as a root mean square value

EXAMPLE: $L_{TX,80}$ denotes the texture profile level for the one-third-octave band having a centre wavelength of 80 mm, see ISO 13473-2:2002, Table 1

Note_1-to entry:- Octave-band and one-third-octave-band filters are specified in ISO 13473-2:2002, 4.4.

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Italic

Formatted

Formatted

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: FooterPageRomanNumber

Symbol or term	unit	Explanation
Z_k	m	Discrete Fourier Transformation of the windowed profile
$Z_{PSD,k}$	m	Power Spectral Density of narrow band m
$Z_{p,m}$	m	Power within fractional-octave band m
j	-	Imaginary unit ($j^2 = -1$)
m	-	Index for the fractional-octave band
n	-	Bandwidth designator

5 Basic outline of methodologies of spatial frequency analysis

Principally, there are two alternative methods to obtain a spatial frequency spectrum in constant-percentage bandwidth bands of octave- or one-third-octave width. These two methods are:

- a) Method 1 – digital constant-percentage bandwidth filtering.
- b) Method 2 – constant narrow bandwidth frequency analysis by means of Discrete Fourier Transform, followed by a transformation of the narrow band spectrum to an octave - or one-third-octave band spectrum.

Method 1 is the main normative method. Both methods yield similar results (within the confidence intervals arising from measurement and analysis uncertainty), on condition that the signal quality is high and that in each of the methods, all signal processing components fulfil the requirements specified in this document. In addition, the narrow bands (method 2) should be appropriately combined into the wider bands, which may be a problem at lower spatial frequencies. Method 2 also includes more steps than Method 1.

The signal processing steps are shown in the scheme of [Figure 1](#). The calculation steps are described in more detail in [Chapter 6](#), [Clause 6](#), [Clause 7](#) and [Annex C](#).

NOTE Method 1 and [Method 2](#) yield very similar results for all texture wavelengths^{[10], [11]}.

13473_4_cd2fig1.EPS

<https://standards.iteh.ai/catalog/standards/iso/73a4f4cf-23dc-4371-b8fa-611111111111/iso-fdis-13473-4>

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted: Font: Not Bold

Formatted

Formatted: Font: Not Italic

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted

Formatted: Font: Not Italic

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: Not Italic

Formatted: Font: 10 pt

Formatted

Formatted: Font: Not Italic

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted

Formatted: Font: Not Italic

Formatted: Font: 10 pt

Formatted: Font: 10 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: FooterPageRomanNumber