

INTERNATIONAL STANDARD

ISO
3046-3

Second edition
1989-11-15

Reciprocating internal combustion engines — Performance —

Part 3 :

Test measurements

iteh Standards
(<https://standards.iteh.ai>)
Moteurs alternatifs à combustion interne — Performances —
Partie 3 : Mesures pour les essais
Document Preview

[ISO 3046-3:1989](#)

<https://standards.iteh.ai/catalog/standards/iso/185654a9-0e89-4572-9ec7-4be0c16fb86d/iso-3046-3-1989>



Reference number
ISO 3046-3 : 1989 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 3046-3 was prepared by Technical Committee ISO/TC 70, *Internal combustion engines*.

Document Preview

This second edition cancels and replace the first edition (ISO 3046-3: 1979), of which it constitutes a technical revision.

[ISO 3046-3:1989](https://standards.iteh.ai)

ISO 3046 consists of the following parts, under the general title *Reciprocating internal combustion engines — Performance*:

- *Part 1: Standard reference conditions and declarations of power, fuel consumption and lubricating oil consumption*
- *Part 2: Test methods*
- *Part 3: Test measurements*
- *Part 4: Speed governing*
- *Part 5: Torsional vibrations*
- *Part 6: Overspeed protection*
- *Part 7: Codes for engine power*

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Reciprocating internal combustion engines — Performance —

Part 3 : Test measurements

1 Scope

This part of ISO 3046 summarizes the common measurement techniques of the main performance parameters of reciprocating internal combustion engines to ensure that the required accuracy of measurement is achieved for comparison of the measured values with those values specified by the engine manufacturer. Where necessary, individual requirements may be given for particular engine applications.

It applies to reciprocating internal combustion engines for land, rail-traction and marine use, excluding engines used to propel agricultural tractors, road vehicles and aircraft.

It may be applied to engines used to propel road construction and earth-moving machines, industrial trucks and for other applications where no suitable International Standards for these engines exist.

ISO 3046-3:1989

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this part of ISO 3046. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this part of ISO 3046 are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2710:1978, *Reciprocating internal combustion engines — Vocabulary*.

3 Other regulations and requirements

3.1 For engines used on board ships and offshore installations which have to comply with rules of a classification society, the additional requirements of the classification society shall be observed. If this applies, the classification society shall be stated by the customer before placing the order.

For non-classed engines, such additional requirements are in each case subject to agreement between the manufacturer and customer.

3.2 If special requirements from regulations of any other authority, for example inspecting and/or legislative authorities, have to be met, the authority shall be stated by the customer before placing the order.

Any further additional requirements shall be subject to agreement between the manufacturer and customer.

4 Requirements

4.1 Accuracy of measurement

The accuracy of measurement depends on a number of factors. Therefore, for all parameters measured it is necessary to specify permissible deviations to cover the following factors which result in measurement uncertainty :

- error of the measuring instrument;
- correctness of the location of the measuring instrument;
- conditions under which the measuring instrument is used;
- accuracy of the readings;
- scatter of the readings of the measuring instrument during the measuring period.

The permissible deviations define the allowable range between the extreme values of the measurement.

4.2 Operating conditions

4.2.1 Before a set of measurements is commenced, the engine shall have operated at the particular conditions of load and speed for a sufficient period of time to ensure that it has reached stable operating conditions as specified by the engine manufacturer.

4.2.2 During the period in which a set of measurements is being made, the load, speed and all fluid temperatures and pressures shall be maintained constant within the permissible deviations given in column 6 of table 1 which gives the list of parameters (see clause 5).

4.3 Measurement methods

4.3.1 Measurement methods shall be selected by the engine manufacturer and, if necessary, may be subject to contractual agreement between the engine manufacturer and customer and/or inspecting authority.

4.3.2 The location of measurement points shall be selected by the engine manufacturer.

4.4 Permissible deviation of parameters

4.4.1 The permissible deviations given in column 6 of table 1 apply only to the declared power.

4.4.2 The permissible deviation quoted is that considered adequate for most acceptance test purposes. Engine manufacturers may adopt reduced permissible deviations

- a) for type tests;
- b) for special contractual or legislative requirements.

4.4.3 All measuring instruments and apparatus used during tests shall be tested and calibrated periodically over the range

of expected readings at time intervals specified by the engine manufacturer unless otherwise agreed.

4.4.4 Where the total measurement uncertainty involves measurements of a number of quantities each with its own measurement uncertainty or where individual measurement is dependent on several parameters, each with its own measurement uncertainty, the overall measurement uncertainty is taken as the square root of the sum of the squares of the separate measurement uncertainties each multiplied by an appropriate factor equal to the exponent of its parameter in the formula.

Where measurements are used in subsequent calculations, measurement uncertainties on the measured parameters shall be selected so that the deviation of the final calculated parameter complies with the corresponding permissible deviation.

5 List of parameters

The parameters of engine performance for test measurements are given in table 1.

NOTE — All footnotes appear at the end of the table.

Table 1 — List of parameters

No.	Parameter	Definition	Symbol	Unit	Permissible deviation
1	2	3	4	5	6
5.1	General parameters				
5.1.1	Engine brake torque ¹⁾	Mean torque delivered by the engine, measured at the engine driving shaft extremity.	T_{tq}	kN·m	± 2 %
5.1.2	Engine speed ²⁾	Number of revolutions of the crankshaft in a given period of time.	n	s^{-1} min ⁻¹ r/min	± 2 %
5.1.3	Engine driving shaft speed	Number of revolutions of the engine driving shaft in a given period of time.	n_d	s^{-1} min ⁻¹ r/min	± 2 %
5.1.4	Turbocharger speed	Number of revolutions of the turbocharger shaft in a given period of time.	n_t	s^{-1} min ⁻¹ r/min	± 2 %
5.1.5	Brake power ³⁾	Power or sum of the powers measured at the driving shaft or shafts.	P ⁴⁾	kW	± 3 %
5.2	Pressures^{5),6)}				
5.2.1	Ambient pressure ⁷⁾	Pressure level of the atmosphere in the vicinity from where the engine takes its air.	p_a	kPa	± 0,5 %
5.2.2	Compression pressure in a cylinder ⁸⁾	Maximum pressure of the working medium present in a cylinder at momentary fuel cut-off.	p_{co}	MPa	± 5 %
5.2.3	Maximum cylinder pressure ⁸⁾	Maximum pressure of the working medium present in a cylinder attained during a working cycle.	p_{max}	MPa	± 5 %
5.2.4	Intake depression	Arithmetic mean intake depression at engine or pressure-charger inlet.	Δp_d	kPa	± 5 %
5.2.5	Intake pressure	Arithmetic mean absolute intake pressure at engine or pressure-charger inlet.	p_d	kPa	± 1 %
5.2.6	Boost pressure	Arithmetic mean charge air pressure after a pressure-charger.	p_b	kPa	± 2 %
5.2.7	Boost pressure before cylinder inlet	Arithmetic mean of the air pressure before the cylinder inlet.	p_{ba}	kPa	± 2 %