



Designation: **D5025—11 D5025 – 12**

Standard Specification for Laboratory Burner Used for Small-Scale Burning Tests on Plastic Materials¹

This standard is issued under the fixed designation D5025; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers the physical dimensions and characteristics of a laboratory burner to be used as an ignition source for small-scale burning tests on plastic materials. The burner is used with methane, propane, or butane supply gases for flame heights of 20 to 125 mm.

1.2 *Fire testing of products and materials is inherently hazardous, and adequate safeguards for personnel and property shall be employed in conducting these tests.*

1.3 The burner described in this specification is suitable for use in the following ASTM standards: Specification **C509**, Test Method **D229**, Test Method **D635**, Test Method **D876**, Test Method **D3014**, Test Method **D3801**, Test Method **D4804**, Test Method **D4986**, and Test Method **D5048**. Safety hazards and known limitations on applicability of fire-test-response standards are addressed in the individual test methods.

NOTE 1—This specification is equivalent to the ignition source specified in IEC 60695-11-3, Annex A and IEC 60695-11-4, Annex A.

NOTE 2—This specification is equivalent to the P/PF2 ignition source specified in ISO 10093.

2. Referenced Documents

2.1 ASTM Standards:²

C509 Specification for Elastomeric Cellular Preformed Gasket and Sealing Material

D229 Test Methods for Rigid Sheet and Plate Materials Used for Electrical Insulation

D635 Test Method for Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position

D876 Test Methods for Nonrigid Vinyl Chloride Polymer Tubing Used for Electrical Insulation

D883 Terminology Relating to Plastics

D1600 Terminology for Abbreviated Terms Relating to Plastics

D3014 Test Method for Flame Height, Time of Burning, and Loss of Mass of Rigid Thermoset Cellular Plastics in a Vertical Position

D3801 Test Method for Measuring the Comparative Burning Characteristics of Solid Plastics in a Vertical Position

D4804 Test Method for Determining the Flammability Characteristics of Nonrigid Solid Plastics

D4986 Test Method for Horizontal Burning Characteristics of Cellular Polymeric Materials

D5048 Test Method for Measuring the Comparative Burning Characteristics and Resistance to Burn-Through of Solid Plastics Using a 125-mm Flame

D5207 Practice for Confirmation of 20-mm (50-W) and 125-mm (500-W) Test Flames for Small-Scale Burning Tests on Plastic Materials

E176 Terminology of Fire Standards

2.2 ISO Standards:³

ISO 10093 Plastics—Fire Tests—Standard Ignition Sources

2.3 IEC Standards:³

IEC TS 60695-11-3 Fire Hazard Testing—Part 11-3: Test Flames—50W Flames—Apparatus and Confirmational Test Methods

IEC TS 60695-11-4 Fire Hazard Testing—Part 11-4: Test Flames—500W Flames—Apparatus and Confirmational Test Methods

¹ This specification is under the jurisdiction of ASTM Committee **D20** on Plastics and is the direct responsibility of Subcommittee **D20.30** on Thermal Properties. Current edition approved Dec. 1, 2011; Aug. 1, 2012. Published January 2012/September 2012. Originally approved in 1989. Last previous edition approved in 2005/2011 as D5025 - 05. DOI: 10.1520/D5025-11-10.1520/D5025-12.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

*A Summary of Changes section appears at the end of this standard