FINAL DRAFT

INTERNATIONAL STANDARD

ISO/FDIS 22434

ISO/TC 58/SC 2

Secretariat: AFNOR

Voting begins on: **2022-12-09**

Voting terminates on: 2022-02-03

Gas cylinders — Inspection and maintenance of valves

Bouteilles à gaz — Contrôle et maintenance des robinets

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 22434 https://standards.iteh.ai/catalog/standards/sist/615990e6-3c47-43be-9744be574e476f4c/iso-fdis-22434

ISO/CEN PARALLEL PROCESSING

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNO-LOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STAN-DARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 22434:2022(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 22434 https://standards.iteh.ai/catalog/standards/sist/615990e6-3c47-43be-9744be574e476f4c/iso-fdis-22434



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword			
Intro	ductio	n	v
1	Scope	9	1
2	Normative references Terms and definitions		
3			
4	Gene 4.1 4.2 4.3	ral requirements Frequency of inspection and maintenance Personnel Safety concerns	2 2 2 2
5	Inspe 5.1 5.2 5.3	ction and maintenance General Inspection 5.2.1 General 5.2.2 Cleaning 5.2.3 External examination — Valve remaining in the gas cylinder 5.2.4 Additional external examination — Valve removed from gas cylinder 5.2.5 Acceptance criteria Maintenance S.3.1 S.3.2 Major repairs S.3.3 Refurbishment and ards.iteh.ai Testing Testing	3 3 3 3 3 3 3 3 4 4 4 4 4 4 4 5 6
6	Marking		
 Packaging https://standards.iteh.ai/catalog/standards/sist/615990e6-3c47-43be-9744- be574e476f4c/iso-fdis-22434 Scrapping Bibliography 			6 6 7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 23, *Transportable gas cylinders*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 22434:2006), which has been technically revised. The main changes are as follows:

- the Scope has been revised;
- the Normative references have been updated;
- the Terms and definitions have been updated;
- <u>subclauses 5.1</u>, <u>5.2.2</u> and <u>5.3.2</u> have been modified;
- <u>Clause 6</u> "Testing" has been moved to <u>5.4</u> and has been modified;
- marking requirements have been modified;
- the Bibliography has been updated.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

This document has been written so that it is suitable to be referenced in the UN Model Regulations^[1].

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 22434 https://standards.iteh.ai/catalog/standards/sist/615990e6-3c47-43be-9744be574e476f4c/iso-fdis-22434

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 22434 https://standards.iteh.ai/catalog/standards/sist/615990e6-3c47-43be-9744be574e476f4c/iso-fdis-22434

Gas cylinders — Inspection and maintenance of valves

Scope 1

This document specifies requirements for the inspection and maintenance of valves [including ball valves and valves with integrated pressure regulator (VIPRs)] for

- refillable transportable gas cylinders, a)
- cylinder bundles, b)
- pressure drums and tubes, c)

which convey compressed, liquefied or dissolved gases.

This document does not apply to valves for LPG.

NOTE Where there is no risk of ambiguity, gas cylinders, cylinder bundles, pressure drums and tubes are addressed with the collective term "gas cylinders" within this document.

This document is applicable to valves reused at the time of the periodic inspection of gas cylinders, cylinder bundles, pressure drums and tubes, and can be applied at any other time, e.g. at a change of gas service (see ISO 11621) I en SI ANDARD PREVIEV

This document does not apply to the routine inspection of valves, e.g. carried out at the time of a gas cylinder filling.

ISO/FDIS 22434

Normative references 2

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10286, Gas cylinders — Terminology

ISO 14246, Gas cylinders — Cylinder valves — Manufacturing tests and examinations

Terms and definitions 3

For the purposes of this document, the terms and definitions given in ISO 10286 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at <u>https://www.electropedia.org/</u>

3.1

inspection

procedure to determine if a valve is suitable for further service

3.2

dismantling

separation of the valve into its component parts, such that the main pressure barrier of the valve is breached

3.3

removal

disconnection of the valve from the gas cylinder

3.4

maintenance

operations required to keep the valve in working condition

Note 1 to entry: Note to entry: This covers *minor repairs* (<u>3.4.1</u>), *major repairs* (<u>3.4.2</u>) and *refurbishment* (<u>3.4.3</u>).

3.4.1

minor repair

operation including cleaning and replacement of non-pressure-retaining components

EXAMPLE Handwheel, outlet flow restrictor.

3.4.2

major repair

operation including replacement of valve accessories which are incorporated within the pressure boundary, but do not require *dismantling* (3.2) of the valve

EXAMPLE Pressure relief device (PRD), pressure gauges, flowmeter, residual pressure device.

3.4.3

refurbishment

operation involving *dismantling* (3.2) of the valve, evaluation and re-use or replacement (if necessary) of its internal components, and reassembly to make it suitable for further service

(standards.iteh.ai)

4 General requirements

ISO/FDIS 22434

4.1 Frequency of inspection and maintenance rds/sist/615990e6-3c47-43be-9744-

be574e476f4c/iso-fdis-22434

If a valve is deemed to require maintenance at any time, e.g. at the time of periodic inspection and testing of a gas cylinder, it shall either be subject to maintenance in accordance with <u>5.3</u> or scrapped in accordance with <u>Clause 8</u>.

4.2 Personnel

Valves shall be inspected, maintained and removed from gas cylinders by competent personnel only.

4.3 Safety concerns

Prior to removing the valve from a gas cylinder, it shall be verified that no pressure above atmospheric pressure remains in the cylinder.

NOTE ISO 25760 provides guidance for the safe removal of cylinder valves and assessment related to gas hazards.

Inspection and minor repairs may be carried out on valves while they are connected to a pressurized gas cylinder, but this requires special procedures.

Major repairs and refurbishment shall only be performed on a valve in a de-pressurized gas cylinder or on a removed valve.

5 Inspection and maintenance

5.1 General

Inspection will determine if a valve is suitable for continued service or if maintenance is required, and the level of that maintenance.

If the manufacturer has declared a service life for a valve and when that service life has expired, the valve shall

- a) not be put back in service, or
- b) if the intention is to extend the service life of the valve for an additional period, the valve shall be inspected and maintained in accordance with this document and in accordance with a specification agreed with the manufacturer or successor.

NOTE Applicable regulations can affect an extension of the service life.

5.2 Inspection

5.2.1 General

Inspection of valves comprises external examination preceded by cleaning, if necessary.

5.2.2 Cleaning **iTeh STANDARD PREVIEW**

WARNING — Used valves can **contain bazardous substances** (e.g. toxic). A safety assessment should be performed to address any hazards associated with cleaning the cylinder valves. A procedure should be in place to protect personnel from any hazards identified in the safety assessment before cleaning the valves. Disposal of contaminates from the cleaning process can be subject to local regulations.

The external parts of the valve shall be clean to facilitate inspection.

Contamination, foreign bodies and corrosion products shall be removed from the valve outlet taking care not to damage any sealing surfaces.

If any cleaning media are used, they shall be suitable for the intended gas service (e.g. medical, oxygen), the materials of construction of the valve, the gas cylinder and the associated downstream equipment. Cleaning media shall be completely removed.

The cleaning agent shall be compatible with the materials of the valve. For example, for brass components, the cleaning agent shall not contain ammonia or amine radicals, which could lead to stress corrosion cracking.

5.2.3 External examination — Valve remaining in the gas cylinder

Valves shall be examined for defects including the following:

a) the spindle does not move smoothly or is difficult to turn;

NOTE This verification is also carried out under pressure during the first filling checks.

- b) bent, deformed, corroded, illegibly marked and scored bodies or those with cracks;
- c) bent or damaged spindles;
- d) cross-threaded, damaged, worn, corroded or stripped valve outlet and filling connections;
- e) damaged, corroded or worn outlet sealing surfaces and/or any non-metallic sealing element;

ISO/FDIS 22434:2022(E)

- f) any indication of having been subjected to excessive heat or having been in a fire;
- g) foreign matter obstructing or blocking ports;
- h) distorted wrenching flats on key operated valves;
- i) evidence of abuse or tampering;
- j) evidence of damaged gauges;
- k) damage to handwheels;
- l) missing or potentially damaged residual pressure device;
- m) incorrect rating of the PRD;
- n) inappropriate valve for the gas service;
- o) contamination or suspect improper lubrication or sealant at the valve to gas cylinder interface;
- p) loose gland nuts.

5.2.4 Additional external examination — Valve removed from gas cylinder

In addition to the above requirements, if the valve has been removed from the gas cylinder, it shall be visually examined for the following additional defects after all residual jointing compound has been removed from the valve inlet **connection: TANDARD PREVIEW**

- a) contamination, foreign bodies and corrosion products in the valve stem bore;
- b) cross-threaded, damaged, worn, deformed or stripped inlet connection;

<u>ISO/FDIS 22434</u>

- c) damaged dip tube, eductor/tube or retaining threads:/sist/615990e6-3c47-43be-9744be574e476f4c/iso-fdis-22434
- d) damaged inlet filter;
- e) damaged liquid or pressure level indicating device;
- f) damaged overfill prevention device;
- g) damaged excess flow prevention device.

5.2.5 Acceptance criteria

Valves not exhibiting the defects listed in 5.2.3 (and 5.2.4 if applicable) may re-enter service.

Valves with any of the defects listed above shall either be subject to maintenance in accordance with 5.3 or scrapped in accordance with <u>Clause 8</u>.

5.3 Maintenance

5.3.1 Minor repairs

Handwheels and other non-pressure retaining parts (e.g. outlet flow restrictor) shall be assessed for reuse, repair or replacement as appropriate.

5.3.2 Major repairs

If the design of the gland nut requires re-torquing, gland nuts shall be re-torqued to the original manufacturing value and using the recommended procedures.