



**SLOVENSKI STANDARD**  
**SIST-TS ISO/TS 18621-11:2022**

**01-oktober-2022**

**Nadomešča:**

**SIST-TS ISO/TS 18621-11:2021**

---

**Grafična tehnologija - Metode ocenjevanja kakovosti slike za tiskovine - 11. del:  
Analiza barvnega obsega**

Graphic technology - Image quality evaluation methods for printed matter - Part 11:  
Colour gamut analysis

iteh STANDARD PREVIEW  
(standards.iteh.ai)

Technologie graphique - Méthodes d'évaluation de la qualité d'image pour les imprimés  
Analyse de la gamme des couleurs - Partie 11: Analyse de la gamme des couleurs

<https://standards.iteh.ai/catalog/standards/sist/a66900d722e0/sist-ts-iso-ts-18621-11-2022>

**Ta slovenski standard je istoveten z: ISO/TS 18621-11:2022**

---

**ICS:**

37.100.10      Reprodukcijska oprema      Reproduction equipment

**SIST-TS ISO/TS 18621-11:2022      en**



TECHNICAL  
SPECIFICATION

ISO/TS  
18621-11

Second edition  
2022-04

---

---

**Graphic technology — Image  
quality evaluation methods for  
printed matter —**

**Part 11:  
Colour gamut analysis**

*Technologie graphique — Méthodes d'évaluation de la qualité  
d'image pour les imprimés —  
Partie 11: Analyse de la gamme des couleurs*

[SIST-TS ISO/TS 18621-11:2022](https://standards.iteh.ai/catalog/standards/sist/00ed2cc2-924a-43fc-b81d-a66900d722e0/sist-ts-iso-ts-18621-11-2022)

<https://standards.iteh.ai/catalog/standards/sist/00ed2cc2-924a-43fc-b81d-a66900d722e0/sist-ts-iso-ts-18621-11-2022>



Reference number  
ISO/TS 18621-11:2022(E)

© ISO 2022

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST-TS ISO/TS 18621-11:2022

<https://standards.iteh.ai/catalog/standards/sist/00ed2cc2-924a-43fc-b81d-a66900d722e0/sist-ts-iso-ts-18621-11-2022>



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Describing a colour gamut</b> .....	<b>2</b>
4.1 General.....	2
4.2 Requirements of a gamut boundary description.....	2
4.3 Device gamut and usable gamut.....	3
4.4 Procedures for describing a colour gamut.....	3
4.4.1 General.....	3
4.4.2 Procedure for describing the colour gamut of a reproduction system based on its ICC profile.....	4
4.4.3 Procedure for describing the device gamut of a reproduction system based on its characterization model.....	5
4.4.4 Procedure for describing the device gamut of a reproduction system based on measurement of a printed gamut target.....	5
4.4.5 Procedure for describing the device gamut of a reproduction system based on characterization data.....	5
<b>5 Computing the volume of a colour reproduction gamut</b> .....	<b>6</b>
5.1 General.....	6
5.2 Volume of a single gamut.....	6
5.2.1 Volume calculation.....	6
5.2.2 Verifying the volume calculation.....	7
5.3 Volume of the intersection of two gamuts.....	8
5.3.1 General.....	8
5.3.2 Determining if a coordinate is inside or outside a gamut.....	8
<b>6 Comparing colour gamuts</b> .....	<b>9</b>
6.1 General.....	9
6.2 GCI.....	9
6.3 Gamut coverage.....	9
6.4 Out-of-gamut volume proportion.....	9
<b>7 Encoding and communicating a colour gamut description</b> .....	<b>9</b>
<b>Annex A (informative) Images for use in determining the gamut boundary of RGB and CMYK printing processes</b> .....	<b>11</b>
<b>Annex B (informative) Gamut volumes for a set of reference profiles</b> .....	<b>12</b>
<b>Annex C (informative) Errors in triangulation</b> .....	<b>13</b>
<b>Annex D (normative) Media-relative colour gamuts</b> .....	<b>15</b>
<b>Bibliography</b> .....	<b>16</b>

## ISO/TS 18621-11:2022(E)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

This second edition cancels and replaces the first edition (ISO/TS 18621-11:2019), which has been technically revised.

The main changes are as follows:

- [Formula \(1\)](#) has been corrected;
- requirements for conformance were clarified throughout;
- the list of example gamut volumes in [Table B.1](#) has been revised.

A list of all parts in the ISO 18621 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

The colour gamut that can be achieved by a reproduction system is an important attribute. It enables users to compare the colour reproduction capabilities of different printing systems and to determine whether one system can simulate all the colours available in another. This document describes procedures to define and compare colour gamuts.

Given a set of coordinates known to lie on the surface of a colour gamut, the volume of the gamut can be determined by segmenting the gamut into a series of tetrahedra, computing the volume of each tetrahedron and summing the results. For a reproduction process with three colour components, a colour will lie on the surface if it satisfies the condition that at least one component has a value of 0 or 1, where 1 represents the maximum amount of the colour component. However, printing processes usually have four or more colour components (e.g. Cyan, Magenta, Yellow and Black in four-colour process printing), and determining which coordinates lie on the gamut boundary cannot be done solely from the relative amounts of the colour components. For CMYK processes, in almost all cases, the Black colorant extends the gamut below the gamut vertex at each hue angle. This makes it possible to identify a set of coordinates which are expected to lie on the gamut surface from the relative colorant amounts and the coordinates of the two- and three-colour overprints. For processes with more than four colour components, some knowledge of the colorimetry of a sample of colours from the colour data encoding is needed in order to determine which colours lie on the boundary.

For these reasons, coordinates on the surface of the gamut of RGB and CMYK printing processes can be determined by printing a test chart with suitable colorant combinations, and measuring the colours; while for other printing processes, it is necessary to model the colorant-to-colorimetry relationship in order to identify colours on the gamut boundary. (RGB here refers to the input signal and supports the common situation where the printer driver accepts RGB instead of CMYK.)

[SIST-TS ISO/TS 18621-11:2022](https://standards.iteh.ai/catalog/standards/sist/00ed2cc2-924a-43fc-b81d-a66900d722e0/sist-ts-iso-ts-18621-11-2022)

<https://standards.iteh.ai/catalog/standards/sist/00ed2cc2-924a-43fc-b81d-a66900d722e0/sist-ts-iso-ts-18621-11-2022>





# Graphic technology — Image quality evaluation methods for printed matter —

## Part 11: Colour gamut analysis

**IMPORTANT** — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

### 1 Scope

This document defines procedures to measure and compare the colour gamuts of RGB and CMYK printing processes.

It is not applicable to other printing processes.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ISO 15076-1, *Image technology colour management — Architecture, profile format and data structure — Part 1: Based on ICC.1:2010*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1

##### colour gamut

range of colours that can be reproduced by an output device on a given medium, represented in a CIE-based colour space

Note 1 to entry: The CIE colour space for representation of colour gamuts is normally CIELAB.

#### 3.2

##### gamut vertex

coordinate in a CIE-based colour space which represents a point on a *colour gamut* (3.1) surface and which is used in defining the surface of the gamut

## ISO/TS 18621-11:2022(E)

### 3.3

#### gamut face

planar sub-division of the *colour gamut* (3.1) surface formed by three or more coplanar *gamut face edges* (3.4)

Note 1 to entry: The colour gamut of most output devices can be described in terms of a set of gamut faces that completely enclose all the colours that can be reproduced by the device, with no gaps or overlaps.

Note 2 to entry: In this document, gamut faces are defined as having three gamut vertices.

### 3.4

#### gamut face edge

line connecting two adjacent vertices of a *gamut face* (3.3)

Note 1 to entry: In a continuous gamut surface, each gamut face edge is shared by two gamut faces.

### 3.5

#### characterization model

mathematical model that converts between coordinates in a device colour encoding and a CIE-based colour space

### 3.6

#### device gamut

range of colours that corresponds to all possible combinations of colour channels of the device within the device data encoding, when printed on a substrate

### 3.7

#### usable gamut

subset of the *device gamut* (3.6) that corresponds to the set of combinations of colour channels of the device in practical use, when reproduced on an output medium

Note 1 to entry: The usable gamut of an output device is normally smaller than the device gamut owing to practical limitations in the combinations of colour channels. Most CMYK devices cannot produce a print in which all channels are set to the maximum. The usable gamut is applicable when the gamut to be determined is that of the system when used as part of a reproduction workflow, using an ICC profile to convert to output channels; while the device gamut is applicable when the gamut to be determined is that of the reproduction device independently of the profile and its colour separation method.

Note 2 to entry: In practice, some printers do not allow all possible combinations of ink to be printed, and an ink-limiting procedure is applied automatically in the printer. Where this is done, this "ink-limited" mode of printing still should be considered to be the "device gamut".

## 4 Describing a colour gamut

### 4.1 General

The colour gamut of a reproduction system is a volume in 3D colour space. It shall be mathematically described as a closed set of triangular faces on the surface of the gamut which completely encloses the gamut volume.

### 4.2 Requirements of a gamut boundary description

Each face should be defined by three colorimetric coordinates, and the set of faces shall be defined in such a way that it encloses the volume of the gamut without gaps or overlaps. The surface shall be encoded as an  $n \times 3$  array of vertices (in which there are  $n$  vertices and each row represents the colour space coordinates of a gamut vertex) and an  $m \times 3$  face array of indices into the vertices array (where there are  $m$  faces and each row of the array identifies the three row numbers in the vertex array which correspond to a gamut face). Each gamut vertex shall be described as a CIELAB  $L^*$ ,  $a^*$ ,  $b^*$  value computed from spectral reflectance or tristimulus values according to ISO 13655, and when this is done it shall be stated which ISO 13655 measurement mode applies to the data. If the colour space used to describe

the gamut vertices is not CIELAB computed according to ISO 13655, details of the colour space used (including the CIE colorimetric observer and illuminant) shall be reported as metadata associated with the gamut description. Where it is desired that the gamut description or comparison is media-relative, CIELAB  $L^*$ ,  $a^*$ ,  $b^*$  coordinates shall be scaled as described in [Annex D](#).

In order to satisfy the requirement to enclose the gamut volume without gaps or overlaps, the following conditions shall be met.

- a) The three indices identifying each face shall identify vertices in clockwise order, when viewed from the exterior of the volume.
- b) Each gamut face edge shall be common to two gamut faces.

CIELAB  $L^*$ ,  $a^*$ ,  $b^*$  computed according to ISO 13655 should be used where it is important to be able to compare colour gamuts or where the gamut is derived from an ICC profile.

It is acknowledged that CIELAB is an approximately perceptually uniform colour space. The CIELAB space over-predicts perceived chroma at higher values of  $C^*_{ab}$  chroma, and hence at the gamut boundary, and this affects the gamut size.

Determining a set of faces that meet the conditions listed above from an arbitrary set of vertices is non-trivial. For this reason, this document provides a set of well-spaced coordinates in device space, and an associated triangulation. Full details of these data are given in [Annex A](#).

### 4.3 Device gamut and usable gamut

The device gamut can be determined either from the characterization model (usually represented by an ICC profile) or by direct measurement of colours that lie on the gamut boundary. To compute the usable gamut, an additional step is required in which the device coordinates are restricted to those available in the reproduction workflow. If an ICC profile is used to define the usable gamut, CIELAB gamut surface coordinates in the device gamut can be transformed to device coordinates and then back to CIELAB coordinates to obtain the usable gamut.

NOTE In some cases, the device or its driver can limit the range of colorant combinations, regardless of whether an ICC profile is used.

The procedure in [4.4](#) should be used for determining the gamut boundary vertex and face arrays. If a different procedure is used, it shall be stated when communicating the gamut boundary description which procedure was used to determine the gamut vertices, and whether the device gamut or usable gamut is described.

## 4.4 Procedures for describing a colour gamut

### 4.4.1 General

One of the following procedures should be used to describe the colour gamut of a reproduction system.

NOTE 1 In most cases, results obtained from these procedures, using the set of well-spaced coordinates in device space described in this document, give very similar results<sup>[2]</sup>. Certain factors affect the reproducibility of the gamut description, such as when the black in a toner-based printer results in a lower  $L^*$  value than any of the other colorant combinations.

NOTE 2 An ICC profile is a convenient means of converting data between the device data encoding and the corresponding colorimetry, and it defines the colour gamut available in a workflow based on ICC profile conversions. Other methods of obtaining colorimetric values for coordinates on the gamut surface, such as direct measurement or a characterization model, is also used.