FINAL DRAFT

INTERNATIONAL STANDARD

ISO/FDIS 5688

ISO/TC 38/SC 23

Secretariat: KATS

Voting begins on: **2023-11-08**

Voting terminates on:

2024-01-03

Textiles — Synthetic filament yarns — Test method for crimp properties of textured yarns

Textiles — Fils de filaments synthétiques — Méthode d'essai des propriétés de frisure des fils texturés

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 5688

https://standards.iteh.ai/catalog/standards/sist/549f1d38-70db-4dd6-8ad3-03f997f7afa2/iso-fdis-5688

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 5688:2023(E)

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 5688

https://standards.iteh.ai/catalog/standards/sist/549f1d38-70db-4dd6-8ad3-03f997f7afa2/iso-fdis-5688



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Con	itents F	Page
Fore	word	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	1
5	Reagent	2
6	Apparatus	2
7	Sampling	4
8	Standard atmosphere for conditioning and testing	4
9	Preparation of test specimen 9.1 Tension for reeling. 9.2 Turns of reel. 9.3 Reeling. 9.4 Numbers of tests 9.5 Conditioning. Test procedure	4 5 5 6
10	10.1 Crimp development 10.1.1 Method A — Hot air method 10.1.2 Method B — Hot water method 10.2 Measuring lengths	6 6 6
11	Calculation and expression of results	8
	11.1 Crimp contraction	8
	11.2 Crimp modulus 11.3 Crimp stability	
	11.4 Test results <u>ISO/FDIS 5688</u> andards.jten.ai/catalog/standards/sist/549f1d38-70db-4dd6-8ad3-03f997f7afa2/iso-fdis-5688	
12	Precision	9
13	Test report	9
Anne	ex A (informative) Precision experiments	10
Bibli	ography	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 38, *Textiles*, Subcommittee SC 23, *Fibres and yarns*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Textiles — Synthetic filament yarns — Test method for crimp properties of textured yarns

1 Scope

This document specifies a test method for crimp properties of synthetic textured filament yarns.

Two treatment methods for crimp development are provided:

- Method A: Hot air method, and
- Method B: Hot water method.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 139, Textiles — Standard atmospheres for conditioning and testing

ISO 3534-1, Statistics — Vocabulary and symbols — Part 1: General statistical terms and terms used in probability

ISO 3696, Water for analytical laboratory use — Specification and test methods

ISO 10132, Textiles — Textured filament yarn — Definitions

3 // **Terms and definitions** dards/sist/549f1d38-70db-4dd6-8ad3-03f997f7afa2/iso-fdis-5688

For the purposes of this document, the terms and definitions given in ISO 10132 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp/ui
- IEC Electropedia: available at https://www.electropedia.org/

3.1

crimp modulus

ratio of difference between the straightened length $(L_{\rm g})$ and the length $(L_{\rm f})$ of the yarn under a low tension, to the straightened length $(L_{\rm g})$, as to characterize the elongation behaviour of a textured yarn in the range of crimp elasticity

Note 1 to entry: It is expressed as a percentage.

4 Principle

Textured filament yarns have a certain crimp trend. By certain methods, the crimp is gradually revealed. The variations in lengths, measured in crimped state and in straightened state, are used to calculate crimp contraction and other parameters, as to characterise crimp properties of textured filament yarns. The test specimen is in the form of a skein or a simple loop.

5 Reagent

5.1 Aqueous solution

If crimp development Method B (see 10.1.12) is selected, distilled water or grade 3 water in accordance with ISO 3696 shall be used, to which a non-ionic surfactant to a concentration of $0.1 \, \text{g/l}$ has been added. Different concentrations of non-ionic surfactant may be allowed on agreement between the interested parties.

6 Apparatus

6.1 Skein winding reel

- a) Reel, with a circumference of (1000 ± 2.5) mm, driven either automatically or manually;
- b) Traversing mechanism, to avert overlapping while a number of skeins being wound at the same time;
- c) Tensioning device, maintaining the specified tension to an accuracy of ±10 %;
- d) Device to count the turns of the reel, preferably warning or stopping winding automatically, just prior to the specified number of reel revolutions;
- e) Suitable mechanism to reduce the reel circumference for easy removal of the skein.

6.2 Test specimen holder

- a) Frame, with a row of hooks separately on the upper and lower ends, for hanging test specimens vertically (see Figure 1). In order to prevent slipping inside the knotted ends, especially for coarse yarn test specimens, the upper hooks possibly to be replaced by a clamping mechanism, while every test specimen consisting of a simple loop in "U" shape, as to eliminate the need for knot;
- b) Upper hooks or clamps fixed on the frame;
- c) Lower hooks subjected to applied tension, moving without friction along the wires on both sides to avoid test specimens twisting;
- d) Over 600 mm in height, with test specimens adequately spaced apart so as not to touch each other.