# INTERNATIONAL STANDARD



First edition 2022-10

## Respiratory protective devices — Human factors —

Part 1: Metabolic rates and respiratory flow rates

Partie 1: Métabolismes énergétiques et régimes des débits respiratoires

<u>ISO 16976-1:2022</u> https://standards.iteh.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8b0ad9b92d0c6/iso-16976-1-2022



Reference number ISO 16976-1:2022(E)

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 16976-1:2022

https://standards.iteh.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8b0ad9b92d0c6/iso-16976-1-2022



### **COPYRIGHT PROTECTED DOCUMENT**

#### © ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

## Contents

Forew	ordi	V
Introd	luction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Activity and metabolic rate	2
5	Metabolic rate and oxygen consumption	4
6	Oxygen consumption and minute ventilation	5
7	Minute ventilation and peak inspiratory flow rates	7 7 9 9 0
8	Individual variation and gender aspects	1
Annex	A (informative) Examples for the use of data	4
Biblio	graphy	7

## (standards.iteh.ai)

<u>ISO 16976-1:2022</u>

https://standards.iteh.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8b0ad9b92d0c6/iso-16976-1-2022

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by ISO/TC 94, *Personal safety* — *Protective clothing and equipment*, Subcommittee SC 15, *Respiratory protective devices*.

This first edition of ISO 16976-1 cancels and replaces ISO/TS 16976-1:2015, which has been technically revised.

The main changes are as follows:

— the document has been editorially revised.

A list of all parts in the ISO 16976 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

### Introduction

For an appropriate design, selection, and use of respiratory protective devices, it is important to consider the basic physiological demands of the user. The type and intensity of work affect the metabolic rate (energy expenditure) of the wearer. The mass and mass distribution of the device on the human body also may influence metabolic rate. Metabolic rate is directly correlated with oxygen consumption, which determines the respiratory demands and flow rates. The work of breathing is influenced by the air flow resistances of the device and the lung airways. The work (or energy cost) of a breath is related to the pressure gradient created by the breathing muscles and the volume that is moved in and out of the lung during the breath. Anthropometric and biomechanical data are required for the appropriate design of various components of a respiratory protective device, as well as for the design of relevant test methods.

This document is the first part of a series of documents providing basic physiological and anthropometric data on humans. It contains information about metabolic rates and respiratory flow rates for various types of physical activity.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 16976-1:2022 https://standards.iteh.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8b0ad9b92d0c6/iso-16976-1-2022

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 16976-1:2022</u> https://standards.iteh.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8b0ad9b92d0c6/iso-16976-1-2022

## **Respiratory protective devices — Human factors —**

## Part 1: Metabolic rates and respiratory flow rates

### 1 Scope

This document provides information on factors related to human anthropometry, physiology, ergonomics, and performance for the preparation of standards for performance requirements, testing, and use of respiratory protective devices.

This document contains information related to respiratory and metabolic responses to rest and work at various intensities. Information is provided for the following:

- metabolic rates associated with various intensities of work;
- oxygen consumption as a function of metabolic rate and minute ventilation for persons representing three body sizes;
- peak inspiratory flow rates during conditions of speech and no speech for persons representing three body sizes as a function of metabolic rates.

The information contained within this document represents data for healthy adult men and women of approximately 30 years of age, but is considered to be applicable for the age range of the worker population.

### <u>ISO 16976-1:2022</u>

### https://standards.iteh.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8-

## 2 Normative references <sub>00ad9b92d0c6/iso-16976-1-2022</sub>

There are no normative references in this document.

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at <u>https://www.electropedia.org/</u>

### 3.1

### aerobic energy production

biochemical process in the human cells that delivers energy by combustion of fat, carbohydrates and, to a lesser extent, protein in the presence of oxygen, with water and carbon dioxide as end products

### 3.2

## ambient temperature pressure saturated ATPS

standard condition for the expression of ventilation parameters related to expired air

Note 1 to entry: Actual ambient temperature and atmospheric pressure; saturated water vapour pressure.

### 3.3

### ambient temperature pressure humidity

### **ATPH**

standard condition for the expression of ventilation parameters related to inspired air

Note 1 to entry: Actual ambient temperature, atmospheric pressure and water vapour pressure.

### 3.4

### body temperature pressure saturated

### **BTPS**

standard condition for the expression of ventilation parameters

Note 1 to entry: Body temperature (37 °C), atmospheric pressure 101,3 kPa (760 mmHg), and water vapour pressure (6,27 kPa) in saturated air.

### 3.5

### peak inspiratory flow rate

### PIFR

highest instantaneous flow rate during the inhalation phase of a respiratory period comprising an inhalation and an exhalation phase

Note 1 to entry: It is expressed in l/s BTPS.

Note 2 to entry: l/s is the preferred unit as the flow takes place during only a short fraction of the respiratory period comprising an inhalation and an exhalation phase.

#### 3.6

### minute ventilation

 $V_{\rm E}$ 

total volume of air inspired (or expired) in the lungs during 1 min

Note 1 to entry: It is expressed in l/s BTPS.

3.7

### oxygen consumption

 $V(0_{2})$ 

amount of oxygen consumed by the human tissues for *aerobic energy production* (3.1)

Note 1 to entry: It is expressed in l/min STPD.

### 3.8

### physical work capacity

ability of a person to engage in muscular work

3.9

### standard temperature pressure dry

**STPD** 

standard conditions for expression of *oxygen consumption* (3.7)

Note 1 to entry: Standard temperature (0 °C) and pressure (101,3 kPa, 760 mmHg), dry air (0 % relative humidity).

#### Activity and metabolic rate 4

Users of respiratory protective devices (RPD) perform physical work at various intensities. Physical work, in particular when associated with large muscle groups as is the case with firefighting, requires high levels of metabolic energy production (metabolic rate). The energy is produced in human cells by aerobic or anaerobic processes.

Aerobic energy production is by far the most common form of energy yield for all types of human cells. It is also the normal form of energy production for the muscles. Depending on physical fitness and other

factors, humans can sustain high levels of aerobic energy production for long periods of time. Very high activity levels, however, can only be sustained for short periods of time (minutes) and they also engage the anaerobic energy yielding processes. The associated production of lactic acid is one reason for the early development of fatigue and exhaustion.

Aerobic energy production is strictly dependent on the constant delivery of oxygen to the active cells. Oxygen is extracted from inspired air, bound to haemoglobin in red blood cells in the alveolar capillaries and transported to the target tissues via the circulation. Consequently, there is a direct, linear relationship between the rate of oxygen consumption and the metabolic rate. The relationship is described in ISO 8996.

Table 1 is derived from ISO 8996:2021, Table A.1, which defines five classes of metabolic rate. This table forms the basis for developing a standard for the assessment of heat stress. The classes represent types of work found in industry. The figures represent average metabolic rates for work periods or full work shifts, generally including breaks. Metabolic rate shall not be confused with external work rates, such as those defined on a bicycle ergometer.

Rescue work and firefighting are by nature temporary and often unpredictable. Activities may become very demanding and high levels of metabolic rate have been reported in References [1], [13], [14], [16], [17], [21], [23], and [25]. According to Reference [21] mean values for oxygen uptake of between 40 ml/ (kg × min) and 45 ml/(kg × min) are reported for the most demanding tasks in firefighting drills (see References [6], [8], and [13]). Assuming an average body mass of 80 kg, the absolute oxygen uptake is between about 3,2 l/min and 3,6 l/min. In Reference [21], mean values of  $(2,4 \pm 0,5)$  l/min for a 17-min test drill exercise were reported; References [16] reported a mean value of  $(2,75 \pm 0,3)$  l/min for a 22-min test drill. The average value for the most demanding task (ascending a tower) was  $(3,55 \pm 0,27)$  l/min. The range of values for this task was between 3,24 l/min and 4,13 l/min. This corresponded to average metabolic rates of 474 W/m<sup>2</sup> and 612 W/m<sup>2</sup>, respectively.

Class https://stand	<u>ISO 16976-1:2022</u> ards.iteh.ai/catalog/standards/sist/a8504b52-4	Average metabolic rate
1	b0ad9b92cResting-16976-1-2022	65
2	Light work	100
3	Moderate work	165
4	Heavy work	230
5	Very heavy work	290
6	Very, very heavy work (2 h)	400
7	Extremely heavy work (15 min)	475
8	Maximal work (5 min)	600
NOTE The first five class	see in this table are derived from ISO 2006. These class	as are valid for repeated activities during

Table 1 —	· Classification of work based on meta	bolic rate (	MR)
-----------	--	--------------	-----

NOTE The first five classes in this table are derived from ISO 8996. These classes are valid for repeated activities during work shifts in every day occupational exposure. Classes 6 to 8 are added as examples of metabolic rates associated with temporary activities of an escape and rescue nature while wearing RPD.

Table 1 contains three additional classes compared with ISO 8996:2021, Table A.1, in order to cover work that is, by its nature, limited by time, such as firefighting and rescue. One class refers to sustained rescue action, as can be found in mining or in wild land firefighting, with time periods of up to 2 h of work (class 6). The other two classes refer to firefighting or rescue operations of short duration and very high intensity, i.e. 15 min (class 7) and 5 min (class 8), respectively. Table 1 presents values expected from individuals with a high level of physical fitness. The highest class (class 8) represents maximal or close to maximal work and can only be endured by fit men for durations of 3 min to 5 min. The three new classes are defined by metabolic rates at 400 W/m<sup>2</sup>, 475 W/m<sup>2</sup>, and 600 W/m<sup>2</sup>, respectively. The values represent the average metabolic rate for the specified period of time, excluding any breaks.

For natural reasons, many types of rescue and emergency work are carried out with personal protective equipment. This adds to the physical workload and is one reason for the high values of metabolic rate

in classes 6 to 8. The data given for the types of work shown in classes 1 to 5 are carried out without wearing RPD and/or personal protective equipment.

### 5 Metabolic rate and oxygen consumption

The energetic equivalent ( $E_E$ ) of oxygen as described in ISO 8996:2021, 9.1.2, is determined using Formula (1):

$$E_{\rm E} = (0,23 \times \rm RQ + 0,77) \times 5,88 \tag{1}$$

where RQ is the respiratory quotient [the ratio of the amount of carbon dioxide produced to the amount of oxygen consumed ( $\dot{V}(CO_2)/\dot{V}(O_2)$ )] and the energetic equivalent of oxygen is 5,88 Wh/l O<sub>2</sub>, which corresponds approximately to the value of 5 kcal/l O<sub>2</sub>, a value that is commonly found in the physiological literature.

Assuming a value of 5 kcal/l O<sub>2</sub> (equal to 5,815 Wh/l O<sub>2</sub>), Formula (2) apply for the conversion of metabolic rates (in W/m<sup>2</sup>) to  $\dot{V}$  (O<sub>2</sub>) (in l/min):

$$\dot{V}(O_2) = \frac{M \times A_{Du}}{EE} = \frac{M \times A_{Du}}{60 \times 5,815} = \frac{M \times A_{Du}}{349}$$
(2)

where

 $\dot{V}(O_2)$  is the oxygen consumption, in l/min;  $\Delta$  R  $\Delta$  R  $\Delta$  R  $\Delta$ 

$$M$$
 is the metabolic rate, in  $W/m^2$ ;

 $A_{\rm Du}$  is the Dubois body surface area, in m<sup>2</sup>;

60 is the conversion factor for min/h;  $O_16976-1:2022$ https://standards.itel.ai/catalog/standards/sist/a8504b52-41d7-421e-80c8and the energy equivalent of oxygen is 5,815 Wh/l O<sub>2</sub>. 6976-1-2022

For the same metabolic rate, the oxygen consumption will vary dependant on body size. Examples are given in <u>Tables 3</u>, <u>4</u>, and <u>5</u> for persons representing three body sizes. See also <u>Annex A</u>.

The associated body surface area is 1,69 m<sup>2</sup>, 1,84 m<sup>2</sup>, and 2,11 m<sup>2</sup>, respectively. As defined in ISO 8996, a person's body surface area,  $A_{Du}$ , is determined on the basis of values for body mass,  $m_b$ , in kg, and body height,  $H_b$ , in m, by Formula (3):

$$A_{\rm Du} = 0,202 \times W_{\rm b}^{0,425} \times H_{\rm b}^{0,725} \tag{3}$$

Values for  $\dot{V}(O_2)$  in Tables 3, 4, and 5 are based on Formulae (4), (5), and (6).

A small-sized person is defined by  $m_b = 60 \text{ kg}$ ,  $H_b = 1,7 \text{ m}$ , and  $A_{Du} = 1,69 \text{ m}^2$ . The oxygen consumption,  $\dot{V}(O_2)$ , is calculated by Formula (4):

$$\dot{V}(O_2) = \frac{M}{207} \tag{4}$$

A medium-sized person is defined by  $m_b = 70$  kg,  $H_b = 1,75$  m, and  $A_{Du} = 1,84$  m<sup>2</sup>. The oxygen consumption,  $\dot{V}(O_2)$ , is calculated by Formula (5):

$$\dot{V}(O_2) = \frac{M}{190}$$
 (5)

A large-sized person is defined by  $m_b = 85 \text{ kg}$ ,  $H_b = 1,88 \text{ m}$ , and  $A_{Du} = 2,11 \text{ m}^2$ . The oxygen consumption,  $V_{O_2}$ , is calculated by Formula (6):

$$\dot{V}(O_2) = \frac{M}{160}$$
 (6)

### 6 Oxygen consumption and minute ventilation

Oxygen transport to tissues requires its extraction from inspired air in the lungs. Concentration of oxygen in inspired air is equivalent to atmospheric concentration of 20,93 % by volume in dry air. Normally, only 15 % to 30 % of this fraction is consumed. The expired air still contains approximately 15 % to 18 %  $O_2$  by volume. This means that the minute ventilation of air,  $\dot{V}_E$ , required for most levels of oxygen consumption, is about 20 to 25 times higher (see Reference [3]). At high activity levels, the value may be even higher, as there is a tendency for hyperventilation.

Reference [9] contains a review of 19 papers published in the relevant literature. The data for 14 nonrespirator studies are plotted again in Figure 1, together with data from References [7], [17] and [18]. Each data point represents the mean value of several individual subjects. The linear regression line for the mean values is plotted. A power function regression line differs only marginally from the linear model. The Hagan equation (at the bottom of the graph) provides an exponential regression that overestimates  $V_E$  at low and very high  $\dot{V}(O_2)$  levels and underestimates at medium levels. Exponential relations have also been proposed by others (see References [1] and [12]). All three of the studies mentioned used incremental exercise as a means of increasing the workload. It can be questioned if  $V_E$  and  $\dot{V}(O_2)$  equilibrate in such a short time. In particular, it is expected that  $\dot{V}(O_2)$  will have a time constant of more than a minute. In the Hagan study, workload was increased every minute.

From a physiological point of view, one would not expect an exponential relationship. Indeed, individual curves show that, up to 60 % to 70 % of maximum  $\dot{V}(O_2)$ , the relation is almost linear. At higher levels of  $\dot{V}(O_2)$ , hyperventilation increases  $V_E$  in a curvilinear manner (see Reference [3]). Respiratory adaptation to increased workloads is likely to represent a two-component equation: one linear and one power or exponential. The model equation would be described by Formula (7):

$$y = (a \times x) + e^{b \times x} \tag{7}$$

where

- *a*, *b* are constants;
- *y* represents  $\dot{V}_{\rm E}$ ;
- x represents  $\dot{V}(0_2)$ .

At low values of *x*, the first term is determinant. With increasing *x*, the second component becomes more and more important. The highest correlation coefficient is obtained for a = 27,1 and b = 0,839. The value of  $R^2 = 0,90$ .

Applying a linear regression forced through zero provides a value of  $R^2 = 0.90$ . For simplicity, the linear regression is selected. The regression equation for the mean values is given by Formula (8). Calculating  $V_{\rm E}$  for two times the standard error ( $S_{\rm E}$ ) of the average  $V_{\rm E}$ , representing 95 % of the populations, gives Formula (9).  $S_{\rm E}$  defines the error in the prediction of  $\dot{V}_{\rm E}$ , based on the regression equation, Formula (7). These equations are subsequently used for estimations of  $\dot{V}_{\rm E}$  and peak flows (see Tables 3 to 5).

$$\dot{V}_E = 31,85 \times \dot{V}(O_2)$$
 (8)