



SLOVENSKI STANDARD

SIST EN 300 407 V1.2.1:2003

01-december-2003

:]_gb]`fUX]`g_]`g]ghYa]`È`CdfYa U`hjdU`lc _U`lc _U`È`DUfUa Yf]`nUX][]hU`bY`fUX]`g_Y`g]ghYa Y`nU`dfYbcg`X][]hU`b]`g][bU`cj`ž_]`XYi`^`c`bU`Z`Y_]`YbW`))` ; <n

Fixed Radio Systems; Point-to-point equipment; Parameters for digital radio systems for the transmission of digital signals operating at 55 GHz

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 407 Version 1.2.1**

SIST EN 300 407 V1.2.1:2003
<https://standards.iteh.ai/catalog/standards/sist/add8c7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003>

ICS:

33.040.20	Prenosni sistem	Transmission systems
33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems

SIST EN 300 407 V1.2.1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 407 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003>

ETSI EN 300 407 V1.2.1 (2000-10)

European Standard (Telecommunications series)

**Fixed Radio Systems;
Point-to-point equipment;
Parameters for digital radio systems
for the transmission of digital signals
operating at 55 GHz**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 300 407 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003>



Reference

REN/TM-04095

Keywords

DRRS, transmission, point-to-point, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 407 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	7
3 Symbols and abbreviations.....	9
3.1 Symbols.....	9
3.2 Abbreviations	9
4 General characteristics	10
4.1 Frequency bands and channel arrangements	10
4.1.1 Channel arrangements.....	10
4.1.2 Co-polar channel spacing for systems operating on the same route	10
4.2 Compatibility requirements between systems	10
4.3 Performance and availability requirements	10
4.4 Environmental conditions.....	11
4.4.1 Equipment within weather protected locations (indoor locations).....	11
4.4.2 Equipment for non-weather protected locations (outdoor locations)	11
4.5 Power supply	11
4.6 Electromagnetic compatibility.....	11
4.7 System block diagram	11
4.8 Telecommunications Management Network (TMN) interface.....	12
4.9 Branching/feeder/antenna characteristics	12
4.9.1 Antenna radiation patterns	12
4.9.2 Antenna cross-Polar Discrimination (XPD)	12
4.9.3 Antenna Inter-Port Isolation (IPI)	12
4.9.4 Waveguide flanges (or other connectors)	12
4.9.5 Return Loss (RL)	12
5 Parameters for digital systems.....	12
5.1 Transmission capacity	12
5.2 Baseband parameters	13
5.2.1 Plesiochronous interfaces	13
5.2.2 SDH baseband interface.....	13
5.3 Transmitter characteristics.....	13
5.3.1 Transmitter power range	13
5.3.2 Transmit power and frequency control	14
5.3.2.1 Automatic Transmit Power Control (ATPC)	14
5.3.2.2 Remote Transmit Power Control (RTPC)	14
5.3.2.3 Remote Frequency Control (RFC)	14
5.3.3 Transmitter output power tolerance	14
5.3.4 Transmit Local Oscillator (LO) frequency arrangements	14
5.3.5 RF spectrum mask	14
5.3.6 Spectral lines at the symbol rate	15
5.3.7 Spurious emissions	16
5.3.7.1 Spurious emissions - external.....	16
5.3.7.2 Spurious emissions - internal	16
5.3.8 Radio frequency tolerance	16
5.4 Receiver characteristics	16
5.4.1 Input level range	16
5.4.2 Receiver local oscillator frequency arrangements	16
5.4.3 Spurious emissions	16
5.4.3.1 Spurious emissions - external.....	17
5.4.3.2 Spurious emissions - internal	17
5.5 System performance without diversity	17
5.5.1 BER as a function of Receiver input Signal Level (RSL).....	17

5.5.2	Residual BER.....	18
5.5.3	Interference sensitivity.....	18
5.5.3.1	Co-channel interference sensitivity.....	18
5.5.3.2	Adjacent channel interference.....	19
5.5.3.3	Continuous Wave (CW) spurious interference.....	19
5.5.3.4	Front-end non-linearity requirements (two-tone CW spurious interference).....	20
5.5.4	Distortion sensitivity.....	20
5.6	System characteristics with diversity.....	20
Annex A (informative): Additional information.....		21
A.1	Radio frequency channel arrangement.....	21
A.2	RBER.....	21
A.3	Co-channel and adjacent channel interference.....	22
Annex B (normative): Essential requirements for the EC Council Directive 89/336 (EMC Directive).....		24
Annex C (normative): System type codes for regulatory procedures.....		25
History.....		26

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 407 V1.2.1:2003

<https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-050d6b7aa636/sist-en-300-407-v1-2-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Transmission and Multiplexing (TM).

The present document specifies the minimum performance parameters for radio equipment operating in the frequency ranges as detailed in subclause 4.1.1.

The former title of the present document was "Transmission and Multiplexing ; Digital Radio Relay Systems; Parameters for DRRS for the transmission of digital signals operating at 55 GHz".

iTeh STANDARD PREVIEW (standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	18 August 2000
Date of latest announcement of this EN (doa): <small>https://standards.iteh.ai/catalog/standards/sist/add8e7e7-8255-4a24-90a1-656117a12623/sist-en-300-407-v1-2-1-2003</small>	30 November 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2001
Date of withdrawal of any conflicting National Standard (dow):	31 May 2001

1 Scope

The present document specifies the minimum performance parameters for terrestrial digital fixed service radio communications equipments operating in the 55 GHz frequency band and is a complete revision of the existing ETS 300 407 (March 1997) specification in the areas of:

- introduction of unique system type codes for regulatory reference to the various system types detailed in the present document, refer to new annex C (normative) and related categories of equipment classes of spectral efficiency;
- additional systems with higher spectrum efficiency in the new classes 1 to 4;
- removal of Analogue services;
- digital services restricted to frequency division duplex (FDD) operation only;
- technical specifications relevant to the EMC Directive, detailed in annex B (normative);
- specific antenna radiation patterns (now superseded by EN 300 833 [12]).

Harmonized channel spacings lower than 14 MHz are not defined in the 55 GHz band at the drafting date of the present document as there is still a pending decision on the WRC2000 agenda item 1.4. However the present document includes 7 MHz and 3,5 MHz channel spacings and can only be considered as a guideline until a decision at WRC2000 is taken and ERC harmonized channel arrangements would possibly be enlarged to include those smaller channel spacings.

Digital systems are intended to be used for point-to-point connections in local and regional networks at data rates between 2 Mbit/s and Synchronous Transport Module, level 1 (STM-1).

Digital systems considered in the present document will be able to meet the error performance objectives of the ITU-R national portion of the reference path, i.e. ITU-R Recommendation F.1189 [19] and the error performance objectives detailed in ITU-T Recommendation G.826 [26].

The parameters to be specified fall into two categories:

- a) those that are required to provide compatibility between channels from different sources of equipment on the same route, connected to separate antennas;
- b) parameters defining the transmission quality of the proposed system.

The present document deals with Radio Frequency (RF) and baseband characteristics relevant to low, medium and high capacity Plesiochronous Digital Hierarchy (PDH) transmission systems, and STM-0 and STM-1 Synchronous Digital Hierarchy (SDH) transmission systems. Antenna/feeder system requirements are covered in EN 300 833 [12].

The present document does not contain aspects related to test procedures and test conditions however they are to be found in EN 301 126-1 [3].

As the maximum transmission rate in a given bandwidth depends on system spectral efficiency, different equipment classes are defined:

- | | |
|----------|---|
| Class 1: | equipment spectral efficiency based on typically 2-states modulation scheme (e.g. 2-FSK, Gaussian Minimum Shift Keying (GMSK) with discriminator detection, or equivalent); |
| Class 2: | equipment spectral efficiency based on typically 4-states modulation scheme (e.g. 4-FSK, 4-QAM, or equivalent); |
| Class 3: | equipment spectral efficiency based on typically 8-states modulation scheme (e.g. 8PSK, or equivalent); |
| Class 4: | equipment spectral efficiency based on typically 16 or 32-states modulation scheme (e.g. 16-QAM, 32-QAM, or equivalent). |

The above classes are indicative only and do not imply any constraint to the actual modulation format, provided that all the requirements in the present document are met.

Safety aspects are not considered in the present document. However compliance to CENELEC EN 60950 [34] will be required to comply with the 99/5/EC [35] Directive (R&TTE).

Technical background for most of the parameters and requirements referred in the present document may be found in TR 101 036-1 [14]

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] CEPT /ERC Recommendation 12-12 E (Luxembourg 1999): "Radio frequency channel arrangement for fixed service systems operating in the band 55,78 GHz – 57,0 GHz".
- [2] CEPT/ERC Recommendation 74-01: "Spurious emissions".
- [3] ETSI EN 301 126-1 (V1.1): "Fixed Radio Systems; Conformance testing; Part 1: Point-to-Point equipment - Definitions, general requirements and test procedures".
- [4] ETSI ETS 300 019: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment".
- [5] ETSI ETS 300 132-1: "Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 1: Operated by alternating current (ac) derived from direct current (dc) sources".
- [6] ETSI ETS 300 132-2: "Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated by direct current (dc)".
- [7] ETSI EN 300 385: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment".
- [8] ETSI ETS 300 407 (Edition 1): Transmission and Multiplexing (TM); Digital Radio Relay Systems (DRRS); Parameters for DRRS for the transmission of digital signals and analogue video signals operating around 55 GHz".
- [9] ETSI ETS 300 635: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH); Radio specific functional blocks for transmission of Mx STM-N".
- [10] ETSI EN 300 645: "Telecommunication Management Networks (TMN); Synchronous Digital Hierarchy (SDH) radio relay equipment; Information model for use on Q-interfaces".
- [11] ETSI ETS 300 785: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH); Radio specific functional blocks for transmission of M x sub-STM-1".
- [12] ETSI EN 300 833: "Fixed Radio Systems; Point to Point Antennas; Antennas for point-to-point fixed radio systems operating in the frequency band 3 GHz to 60 GHz".
- [13] ETSI TR 101 035: "Transmission and multiplexing (TM); Synchronous Digital Hierarchy (SDH) aspects regarding Digital Radio Relay Systems (DRRS)".
- [14] ETSI TR 101 036-1 (V1.2): "Fixed Radio Systems; Point-to-point equipment; Generic wordings for standards on digital radio systems characteristics; Part 1: General aspects and point-to-point equipment parameters".

- [15] IEC Publication 154-2: "Flanges for waveguides. Part 2: Relevant specifications for flanges for ordinary rectangular waveguides".
- [16] ITU-R Recommendation F.750: "Architectures and functional aspects of radio-relay systems for SDH-based networks".
- [17] ITU-R Recommendation F.751: "Transmission characteristics and performance requirements of radio-relay systems for SDH-based networks".
- [18] ITU-R Recommendation F.1102: "Characteristics of radio-relay systems operating in frequency bands above about 17 GHz".
- [19] ITU-R Recommendation F.1189: "Error performance objectives for constant bit rate digital paths at or above the primary rate carried by digital radio-relay systems which may form part or all of the national portion of a 27 500 km hypothetical reference path".
- [20] ITU-R Recommendation F.1191: "Bandwidths and unwanted emissions of digital radio-relay systems".
- [21] ITU-T Recommendation G.703: "Physical/electrical characteristics of hierarchical digital interfaces".
- [22] ITU-T Recommendation G.707: "Network node interface for the synchronous digital hierarchy (SDH)".
- [23] ITU-T Recommendation G.773: "Protocol suites for Q-interfaces for management of transmission systems".
- [24] ITU-T Recommendation G.783: "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks".
- [25] ITU-T Recommendation G.784: "Synchronous digital hierarchy (SDH) management".
- [26] ITU-T Recommendation G.826: "Error performance parameters and objectives for international, constant bit rate digital paths at or above the primary rate".
- [27] ITU-T Recommendation G.828: "Error performance parameters and objectives for international synchronous digital paths".
- [28] ITU-T Recommendation G.861: "Principles and guidelines for the integration of satellite and radio systems in SDH transport networks".
- [29] ITU-T Recommendation G.957: "Optical interfaces for equipments and systems relating to the synchronous digital hierarchy".
- [30] ITU-T Recommendation O.151: "Error performance measuring equipment operating at the primary rate and above".
- [31] ITU-T Recommendation O.181: "Equipment to assess error performance on STM-N interfaces".
- [32] ITU-R Recommendation P.530-6: "Propagation data and prediction methods required for the design of terrestrial line-of-sight systems".
- [33] "Council Directive 89/336/EEC of 3 May 1989 on the approximation of the laws of the Member States relating to electromagnetic compatibility".
- [34] CENELEC EN 60950: "Safety of information technology equipment".
- [35] "Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications equipment and the mutual recognition of their conformity".
- [36] ITU-R Recommendation SM.329: "Spurious emissions".

3 Symbols and abbreviations

3.1 Symbols

For the purposes of the present document, the following symbols apply:

dB	decibel
dBi	decibel relative to isotropic radiator
dBm	decibel relative to 1 mW
dBu	decibel relative to 1microVolt
dBW	decibel relative to 1 W
GHz	GigaHertz
kHz	kiloHertz
Mbit/s	Mega-bits per second
MHz	MegaHertz
ppm	parts per million
mW	milliWatt
Ω	Ohm

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
ATPC	Automatic Transmit Power Control
AU	Administrative Unit
BBER	Background Block Error Rate
BER	Bit Error Rate
C/I	Carrier to Interference ratio
CMI	Coded Mark Inversion
CW	Continuous Wave
dc	direct current
DRRS	Digital Radio Relay Systems
EIRP	Equivalent Isotropically Radiated Power
EMC	ElectroMagnetic Compatibility
ESR	Errored Second Rate
FDD	Frequency Division Duplex
FSK	Frequency-Shift Keying (modulation)
GMSK	Gaussian Minimum Shift Keying (modulation)
IEC	International Electrotechnical Committee
IF	Intermediate Frequency
IPI	Inter-Port Isolation
LO	Local Oscillator
n.a.	not applicable
PDH	Plesiochronous Digital Hierarchy
PRBS	Pseudo Random Binary Sequence
QAM	Quadrature Amplitude Modulation
RBER	Residual Bit Error Rate
RF	Radio Frequency
RFC	Remote Frequency Control
RL	Return Loss
RSL	Receive Signal Level
RTPC	Remote Transmit Power Control
SDH	Synchronous Digital Hierarchy
SOH	Section OverHead
STM-N	Synchronous Transport Module, level N
STM-0	medium capacity SDH radio transport module (51,840 Mbit/s AU-3 equivalent, also referred as STM-0 by ITU-T Recommendation G.861 [28])
TC	ETSI Technical Committee
TM	ETSI TC-Transmission and Multiplexing