



# Standard Specification for Magnesium-Alloy Extruded Bars, Rods, Profiles, Tubes, and Wire<sup>1</sup>

This standard is issued under the fixed designation B107/B107M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

## 1. Scope\*

1.1 This specification covers magnesium-alloy extruded bars, rods, profiles, tubes, and wire of the composition given in [Table 1](#).

1.2 The values stated in either inch-pound or SI units are to be regarded separately as standards. The SI units are shown in brackets or in separate tables or columns. The values stated in each system are not exact equivalents; therefore, each system must be used independent of the other. Combining values from the two systems may result in nonconformance with the specification.

1.3 Unless the order specifies the “M” specification designation, the material shall be furnished to the inch-pound units.

## 2. Referenced Documents

2.1 The following documents of the issue in effect on date of order acceptance form a part of this specification to the extent referenced herein.

2.2 *ASTM Standards:*<sup>2</sup>

[B296 Practice for Temper Designations of Magnesium Alloys, Cast and Wrought](#)

[B557 Test Methods for Tension Testing Wrought and Cast Aluminum- and Magnesium-Alloy Products](#)

[B557M Test Methods for Tension Testing Wrought and Cast Aluminum- and Magnesium-Alloy Products \(Metric\)](#)

[B660 Practices for Packaging/Packing of Aluminum and Magnesium Products](#)

[B666/B666M Practice for Identification Marking of Aluminum and Magnesium Products](#)

[B951 Practice for Codification of Unalloyed Magnesium and Magnesium-Alloys, Cast and Wrought](#)

[B953 Practice for Sampling Magnesium and Magnesium Alloys for Spectrochemical Analysis](#)

[B954 Test Method for Analysis of Magnesium and Magnesium Alloys by Atomic Emission Spectrometry](#)

[E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications](#)

[E35 Test Methods for Chemical Analysis of Magnesium and Magnesium Alloys \(Withdrawn 2008\)](#)<sup>3</sup>

[E55 Practice for Sampling Wrought Nonferrous Metals and Alloys for Determination of Chemical Composition](#)

[E527 Practice for Numbering Metals and Alloys in the Unified Numbering System \(UNS\)](#)

## 3. Terminology

3.1 *Definitions:*

3.1.1 *extruded bar*—a solid extrusion, long in relation to its cross-sectional dimensions, having a symmetrical cross section that is square or rectangular with sharp or rounded corners or edges, or is a regular hexagon or octagon, and whose width or greatest distance between parallel faces is over 0.375 in. [10 mm].

3.1.2 *extruded profile*—a hollow or solid extrusion, long in relation to its cross-sectional dimensions, whose cross section is other than that of wire, rod, bar, or tube.

3.1.3 *extruded rod*—a solid round extrusion, long in relation to its diameter, whose diameter is over 0.375 in. [10 mm].

3.1.4 *extruded tube*—a hollow extrusion, long in relation to its cross-sectional dimensions, which is symmetrical and is round, square, rectangular, hexagonal, octagonal, or elliptical with sharp or rounded corners, and has a uniform wall thickness except as affected by corner radii.

3.1.5 *producer*—the primary manufacturer of a material.

3.1.6 *supplier*—includes only the category of jobbers and distributors as distinct from producer.

\*A Summary of Changes section appears at the end of this standard

TABLE 1 Chemical Requirements<sup>A</sup>

NOTE 1—Analysis shall regularly be made only for the elements specifically mentioned in this table. If, however, the presence of other elements is suspected or indicated in the course of routine analysis to be in amounts greater than the specified limits, further analysis shall be made to determine that the total of these other elements is not in excess of the limits specified in the last column of the table.

NOTE 2—The following applies to all specified limits in this table: For purposes of acceptance and rejection, an observed value or a calculated value obtained from analysis should be rounded-off to the nearest unit in the last right-hand place of figures used in expressing the specified limit.

Alloy <sup>B</sup>		Composition, %															
UNS No.	ASTM No.	Magnesium	Aluminum	Calcium	Copper	Iron	Lithium	Manganese	Neodymium	Nickel	Rare Earths	Silicon	Yttrium	Zirconium, min	Zinc	Other Impurities, each	Total Other <sup>C</sup> Impurities
M11311	AZ31B	remainder	2.5-3.5	0.04	0.05	0.005		0.20-1.0		0.005		0.10		...	0.6-1.4		0.30
M11312	AZ31C	remainder	2.4-3.6	...	0.10	...		0.15-1.0 <sup>D</sup>		0.03		0.10		...	0.50-1.5		0.30
M11610	AZ61A	remainder	5.8-7.2	...	0.05	0.005		0.15-0.5		0.005		0.10		...	0.40-1.5		0.30
M11800	AZ80A	remainder	7.8-9.2	...	0.05	0.005		0.12-0.5		0.005		0.10		...	0.20-0.8		0.30
M15100	M1A	remainder	...	0.30	0.05	...		1.2-2.0		0.01		0.10		...	...		0.30
M18432	WE43B	remainder	...	...	0.02	0.010	0.2	0.03	2.0-2.5	0.005	1.9 <sup>E</sup>	...	3.7-4.3	0.40-1.0	<sup>F</sup>	0.01	...
M18410	WE54A	remainder	...	...	0.03	...	0.2	0.03	1.5-2.0	0.005	2.0 <sup>E</sup>	0.01	4.75-5.5	0.40-1.0	0.20	0.2	...
M16400	ZK40A	remainder	...	...	...	...		...		...		...		0.45	3.5-4.5		0.30
M16600	ZK60A	remainder	...	...	...	...		...		...		...		0.45	4.8-6.2		0.30

<sup>A</sup> Limits are in weight percent maximum unless shown as a range or otherwise stated.

<sup>B</sup> These alloy designations were established in accordance with Practice B951 (see also Practice E527).

<sup>C</sup> Includes listed elements for which no specific limit is shown.

<sup>D</sup> Manganese minimum limit need not be met if iron is 0.005 %, or less.

<sup>E</sup> Other Rare Earths shall be principally heavy rare earths, for example, Gadolinium, Dysprosium, Erbium, and Ytterbium. Other Rare Earths are derived from the Yttrium, typically 80 % Yttrium 20 % heavy rare earths.

<sup>F</sup> Zinc + Silver content shall not exceed 0.20 % in WE43B.

3.1.7 *wire*—a solid section long in relation to its cross-sectional dimensions, having a cross section that is round, hexagonal, or octagonal, and whose diameter, width, or greatest distance between parallel faces is up through 0.375 in. [10 mm], or having a symmetrical cross section that is square or rectangular (excluding flattened wire) with sharp or rounded corners or edges.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *capable of*—means that the test need not be performed by the producer of the material. However, should subsequent testing by the purchaser establish that the material does not meet these requirements, the material shall be subject to rejection.

#### 4. Ordering Information

4.1 Orders for material to this specification shall include the following information:

4.1.1 This specification number,

4.1.2 Quantity in pieces or pounds [kilograms],

4.1.3 Alloy (Section 6),

4.1.4 Temper (Section 7),

4.1.5 Nominal cross-sectional dimensions as follows:

4.1.5.1 For rod and round wire—diameter,

4.1.5.2 For square corner bars and wire—depth and width,

4.1.5.3 For sharp cornered hexagonal or octagonal bars and wire—distance across flats,

4.1.5.4 For round tube—outside or inside diameter and wall thickness,

4.1.5.5 For square or sharp cornered other than round tube—distance across flats and wall thickness,

4.1.5.6 For round cornered bars and wire; profiles; tube other than round, square, rectangular, hexagonal or octagonal with sharp corners—drawing required,

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee B07 on Light Metals and Alloys and is the direct responsibility of Subcommittee B07.04 on Magnesium Alloy Cast and Wrought Products.

Current edition approved June 1, 2007; Nov. 1, 2012. Published June 2007; November 2012. Originally approved in 1936. Last previous edition approved in 2006 as B107/B107M – 06; B107/B107M – 07. DOI: 10.1520/B0107-B0107M-07; 10.1520/B0107-B0107M-12.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- 4.1.6 Length,
- 4.1.7 Surface finish (see 9.2),
- 4.1.8 Whether inspection or witness of inspection and tests by the purchaser's representative is required prior to material shipment (Section 10),
- 4.1.9 Whether certification is required (Section 12),
- 4.1.10 Whether marking for identification is required (Section 13 and Practice B660).
- 4.1.11 Whether special packaging is required for shipment (Section 14).

## 5. Quality Assurance

5.1 *Responsibility for Inspection*—Unless otherwise specified in the contract or purchase order, the producer or supplier is responsible for the performance of all inspection and test requirements specified herein. Except as otherwise specified in the contract or order, the producer or supplier may use his own or any other suitable facilities for the performance of the inspection and test requirements specified herein, unless disapproved by the purchaser at the time the order is placed. The purchaser shall have the right to perform any of the inspections and tests set forth in this specification where such inspections are deemed necessary to assure that material conforms to prescribed requirements.

## 6. Chemical Composition

6.1 *Limits*—The bars, rods, profiles, tubes, or wire shall conform to the chemical requirements in Table 1.

6.2 *Number of Samples*—The number of samples taken for determination of chemical composition shall be as follows:

6.2.1 When samples are taken at the time extrusion ingots are cast for determination of conformance to Table 1, one sample shall be taken for each group of ingots of the same alloy, poured at the same time, from the same source of molten metal when a batch process is employed. In cases where a continuous casting process is employed, one sample shall be taken for each quantity of material cast equivalent in size (weight or volume) to the last holding vessel before casting or 5000 lb [2270 kg], whichever is less. Ingots not conforming to Table 1 shall be rejected.

6.2.2 Unless compliance is established by 6.2.1, sampling of the finished product shall be in accordance with Practice E55. One sample shall be taken for each 4000 lb (2000 kg) or less of material comprising the lot, except that not more than one analysis shall be required per piece.

6.3 *Methods of Chemical Analysis*—Any suitable method of chemical analysis may be used. In case of dispute, the analysis shall be made by methods given in Test Method E35B954 or any other standard methods of analysis approved by ASTM unless some other method is agreed upon.

## 7. Tensile Requirements

7.1 *Limits*—The bars, rods, profiles, tubes, and wire shall conform to the tensile properties requirements in Table 2 unless other agreement is made between producer or supplier and purchaser. Properties for sizes and tempers not shown in Table 2 shall be as agreed by producer or supplier and purchaser.

7.2 *Number of Specimens*—From material having nominal weight of less than 1 lb/linear ft [through 1.7 kg/linear m], one tension test sample shall be taken for each 1000 lb [500 kg] or fraction thereof in the shipment. For material having a nominal weight of 1 lb/linear ft [over 1.7 kg/linear m] or more, one tension test shall be taken for each 1000 ft [300 m] or fraction thereof in the shipment. Other procedures for selecting samples may be employed if agreed upon by the seller and the purchaser.

7.3 Geometry of test specimens and the location in the product from which they are taken shall be as specified in Test Methods B557 and B557M.

7.4 *Test Methods*—The tension tests shall be made in accordance with Test Methods B557 and B557M.

7.5 *Retests*—If any tension specimen fails to conform to the requirements prescribed in Table 2, two additional specimens shall be selected and tested from other bars, rods, profiles, tubes, or wire in the lot. If either of these specimens fails to conform to the applicable requirements, the material may be rejected. If, however, the failure of the specimens to conform to the requirements is the result of an inadequate thermal treatment, the material may be reheat treated and resampled in accordance with 7.2.

**TABLE 2 Tensile Requirements**

NOTE 1—For purposes of determining conformance with this specification, each value for tensile strength and yield strength shall be rounded to the nearest 100 psi and each value for elongation shall be rounded to the nearest 0.5 %, both in accordance with the rounding method of Practice E29.

Alloy <sup>A</sup>		Temper <sup>A</sup>	Form	Specified Diameter or Thickness	Over-Through	Specified Cross-Sectional Area;	Tensile Strength;	Yield Strength;	Elongation in
UNS No.	ASTM No.			in. <sup>D,E</sup>	[mm]	in. <sup>2</sup> or OD of Tube, in.	ksi [MPa]	(0.2 % offset); ksi [MPa]	2 in. [50 mm] or 4 × Dia., min., % <sup>B,C</sup>
M41314	AZ31B	F	bars, rods, profiles, and wire	0.249 and under	[...-6.30]	all	35.0 [240]	21.0 [145]	7

**B107/B107M - 12****TABLE 2—Continued**

Alloy <sup>A</sup>		Temper <sup>A</sup>	Form	Specified Diameter or Thickness	Over-Through	Specified Cross-Sectional Area,	Tensile Strength,		Yield Strength (0.2% offset),		Elongation in 2 in. [50 mm] of 4-x-Dia., min., % <sup>B,C</sup>
UNS No.	ASTM No.			in. <sup>D,E</sup>	[mm]	in. <sup>2</sup> or OD of Tube, in.	ksi	[MPa]	ksi	[MPa]	
				0.250–1.499	{6.30–40.00}	all	35.0	[240]	22.0	[150]	7
				1.500–2.499	{40.00–60.00}	all	34.0	[235]	22.0	[150]	7
				2.500–4.999	{60.00–130.00}	all	32.0	[220]	20.0	[140]	7
			hollow profiles	all		all	32.0	[220]	16.0	[110]	8
			tubes	0.028–0.250	{0.70–6.30}	6.000 [150.00]—and under	32.0	[220]	20.0	[140]	8
				0.250–0.750	{6.30–20.00}		32.0	[220]	16.0	[110]	4
M11610	AZ61A	F	bars, rods, profiles, —and wire	0.249 and —under	{...–6.30}	all	38.0	[260]	21.0	[145]	8
				0.250–2.499	{6.30–60.00}	all	40.0	[275]	24.0	[165]	9
				2.500–4.999	{60.00–130.00}	all	40.0	[275]	22.0	[150]	7
			hollow profiles	all		all	36.0	[250]	16.0	[110]	7
			tubes	0.028–0.750	{0.70–20.00}	6.000 [150.00]—and under	36.0	[250]	16.0	[110]	7
M11800	AZ80A	F	bars, rods, solid —profiles, and wire	0.249 and —under	{...–6.30}	all	43.0	[295]	28.0	[195]	9
				0.250–1.499	{6.30–40.00}	all	43.0	[295]	28.0	[195]	8
				1.500–2.499	{40.00–60.00}	all	43.0	[295]	28.0	[195]	6
				2.500–4.999	{60.00–130.00}	all	42.0	[290]	27.0	[185]	4
M11800	AZ80A	T5	bars, rods, solid —profiles, and wire	0.249 and —under	{...–6.30}	all	47.0	[325]	30.0	[205]	4
				0.250–2.499	{6.30–60.00}	all	48.0	[330]	33.0	[230]	4
				2.500–4.999	{60.00–130.00}	all	45.0	[310]	30.0	[205]	2
M15100	M1A	F	bars, rods, profiles, —and wire	0.249 and —under	{...–6.30}	all	30.0	[205]	<i>E</i>	<i>E</i>	2
				0.250–1.499	{6.30–40.00}	all	32.0	[220]	<i>E</i>	<i>E</i>	3
				1.500–2.499	{40.00–60.00}	all	32.0	[220]	<i>E</i>	<i>E</i>	2
				2.500–4.999	{60.00–130.00}	all	29.0	[200]	<i>E</i>	<i>E</i>	2
			hollow profiles	all		all	28.0	[195]	<i>E</i>	<i>E</i>	2
			tubes	0.028–0.750	{0.70–20.00}	6.000 [150.00]—and under	28.0	[195]	<i>E</i>	<i>E</i>	2
M18430	WE43B	T5	bars, rods, solid —profiles and wire	0.250–1.999	{6.3–50.00}	all	36.0	[250]	23.0	[160]	4
M18430	WE43B	T5	bars, rods, solid —profiles and wire	2.00–5.00	{50–130.00}	all	35.0	[240]	22.0	[150]	4
M18430	WE43B	T6	bars, rods, solid —profiles and wire	0.250–1.999	{6.3–50.00}	all	36.0	[250]	22.0	[150]	4
M18430	WE43B	T6	bars, rods, solid —profiles and wire	2.00–5.00	{50–130.00}	all	35.0	[240]	20.0	[140]	4
M18410	WE54A	T5	bars, rods, solid —profiles and wire	0.250–1.999	{6.3–50.00}	all	36.0	[250]	26.0	[180]	4
M18410	WE54A	T5	bars, rods, solid —profiles and wire	2.00–5.00	{50–130.00}	all	36.0	[250]	25.0	[170]	4
M18410	WE54A	T6	bars, rods, solid —profiles and wire	0.250–1.999	{6.3–50.00}	all	38.0	[260]	26.0	[180]	4
M18410	WE54A	T6	bars, rods, solid —profiles and wire	2.00–5.00	{50–130.00}	all	36.0	[250]	25.0	[175]	4
M16400	ZK40A	T5	bars, rods, profiles, —and wire	all		3.000 [1900]—and under	37.0	[255]	34.0	[235]	—4.0
			hollow profiles	all		all	40.0	[275]	37.0	[255]	—4.0



B107/B107M – 12

TABLE 2—Continued

Alloy <sup>A</sup>		Temper <sup>A</sup>	Form	Specified Diameter or Thickness	Over-Through	Specified Cross-Sectional Area, in. <sup>2</sup> or OD of Tube, in.	Tensile Strength, min		Yield Strength (0.2 % offset), min		Elongation in 2 in. [50 mm] of 4 x Dia., min, % <sup>B,C</sup>		
UNS No.	ASTM No.			in. <sup>D,E</sup>	[mm]	in. <sup>2</sup> or OD of Tube, in.	ksi	[MPa]	ksi	[MPa]			
			tubes	0.062–0.500	{1.60–12.50}	3.000 [80.00]—and under	40.0	[275]	36.0	[255]	—4.0		
M16600	ZK60A	F	bars, rods, profiles, —and wire	all		4.999 [3200]—and under	43.0	[295]	31.0	[215]	5		
						5.000–39.999 —{3201–26 000}	43.0	[295]	31.0	[215]	6		
						hollow profiles	all	all	40.0	[275]	28.0	[195]	5
			tubes	0.028–0.750	{0.70–20.00}	3.000 [80.00]—and under	40.0	[275]	28.0	[195]	5		
M16600	—ZK60A	—T5	bars, rods, profiles, —and wire	all		4.999 [3200]—and under	45.0	[310]	36.0	[250]	4		
						5.000–24.999 —{3201–16 000}	45.0	[310]	34.0	[235]	6		
						25.000–39.999 —{16 001–26 000}	43.0	[295]	31.0	[215]	6		
						hollow profiles	all	all	46.0	[315]	38.0	[260]	4
						tubes	0.028–0.250	{0.70–6.30}	3.000 [80.00]—and under	46.0	[315]	38.0	[260]
			tubes	0.094–1.188	{2.50–30.00}	3.001 [80.00]—8.500 [215]	44.0	[305]	33.0	[230]	4		

<sup>A</sup> See Practice B296.

<sup>B</sup> Elongation of full-section and machined sheet-type specimens is measured in 2 in. [50 mm] of machined round specimens, in 4 x specimen dia. [5 x dia. in metric].

<sup>C</sup> For material of such dimensions that a standard test specimen cannot be obtained, for wire less than 0.125 in. diameter [3.2 mm diameter], or for material thinner than 0.062 in. [1.60 mm] the test for elongation is not required.

<sup>D</sup> Intermediate dimensions shall be rounded off to the third decimal place in accordance with Practice E29.

<sup>E</sup> Wall thickness of tubes.

<sup>F</sup> Not required.

iteh Standards  
<https://standards.iteh.ai/>  
 Document Preview

ASTM B107/B107M-12

<https://standards.iteh.ai/catalog/standards/sist/129ae14d-0cf6-405c-847a-6652c4e71d40/astm-b107-b107m-12>





TABLE 2—Continued




TABLE 2 Continued

Specified Dimension, in.		Tolerance <sup>B,C</sup> in. ±																																																																																																																																																																																																							
Metal Dimensions		Space Dimensions																																																																																																																																																																																																							
Allowable Deviation from Specified Dimension Where 75% or More of the Dimension is Metal <sup>D</sup>		Allowable Deviation from Specified Dimension Where More than 25% of the Dimension is Space <sup>E,F</sup>																																																																																																																																																																																																							
UNS No.	ASTM No.	Wall Thickness <sup>G,H</sup>	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	Yield Strength (0.2 % offset), min	At Dimensioned Points	At Dimensioned Points																																																																																																																																																																																														
												0.625–1.249	1.250–2.499	2.500–4.999	5.000–9.999	10.000–14.999	15.000–19.999	20.000–24.999	25.000–29.999	30.000–34.999	35.000–39.999	40.000–44.999	45.000–49.999	50.000–54.999	55.000–59.999	60.000–64.999	65.000–69.999	70.000–74.999	75.000–79.999	80.000–84.999	85.000–89.999	90.000–94.999	95.000–99.999	100.000–104.999	105.000–109.999	110.000–114.999	115.000–119.999	120.000–124.999	125.000–129.999	130.000–134.999	135.000–139.999	140.000–144.999	145.000–149.999	150.000–154.999	155.000–159.999	160.000–164.999	165.000–169.999	170.000–174.999	175.000–179.999	180.000–184.999	185.000–189.999	190.000–194.999	195.000–199.999	200.000–204.999	205.000–209.999	210.000–214.999	215.000–219.999	220.000–224.999	225.000–229.999	230.000–234.999	235.000–239.999	240.000–244.999	245.000–249.999	250.000–254.999	255.000–259.999	260.000–264.999	265.000–269.999	270.000–274.999	275.000–279.999	280.000–284.999	285.000–289.999	290.000–294.999	295.000–299.999	300.000–304.999	305.000–309.999	310.000–314.999	315.000–319.999	320.000–324.999	325.000–329.999	330.000–334.999	335.000–339.999	340.000–344.999	345.000–349.999	350.000–354.999	355.000–359.999	360.000–364.999	365.000–369.999	370.000–374.999	375.000–379.999	380.000–384.999	385.000–389.999	390.000–394.999	395.000–399.999	400.000–404.999	405.000–409.999	410.000–414.999	415.000–419.999	420.000–424.999	425.000–429.999	430.000–434.999	435.000–439.999	440.000–444.999	445.000–449.999	450.000–454.999	455.000–459.999	460.000–464.999	465.000–469.999	470.000–474.999	475.000–479.999	480.000–484.999	485.000–489.999	490.000–494.999	495.000–499.999	500.000–504.999	505.000–509.999	510.000–514.999	515.000–519.999	520.000–524.999	525.000–529.999	530.000–534.999	535.000–539.999	540.000–544.999	545.000–549.999	550.000–554.999	555.000–559.999	560.000–564.999	565.000–569.999	570.000–574.999	575.000–579.999	580.000–584.999	585.000–589.999	590.000–594.999	595.000–599.999	600.000–604.999	605.000–609.999	610.000–614.999	615.000–619.999	620.000–624.999	625.000–629.999	630.000–634.999	635.000–639.999	640.000–644.999	645.000–649.999	650.000–654.999	655.000–659.999	660.000–664.999	665.000–669.999	670.000–674.999	675.000–679.999	680.000–684.999	685.000–689.999	690.000–694.999	695.000–699.999	700.000–704.999	705.000–709.999	710.000–714.999	715.000–719.999	720.000–724.999	725.000–729.999	730.000–734.999	735.000–739.999	740.000–744.999	745.000–749.999	750.000–754.999	755.000–759.999	760.000–764.999	765.000–769.999	770.000–774.999	775.000–779.999	780.000–784.999	785.000–789.999	790.000–794.999	795.000–799.999	800.000–804.999	805.000–809.999	810.000–814.999	815.000–819.999	820.000–824.999	825.000–829.999	830.000–834.999	835.000–839.999	840.000–844.999	845.000–849.999	850.000–854.999	855.000–859.999	860.000–864.999	865.000–869.999	870.000–874.999	875.000–879.999	880.000–884.999	885.000–889.999	890.000–894.999	895.000–899.999	900.000–904.999	905.000–909.999	910.000–914.999	915.000–919.999	920.000–924.999	925.000–929.999	930.000–934.999	935.000–939.999
–0.500–0.749	0.009	±0.010 min	0.016	0.018	0.020	0.022	...	...	...	...	...																																																																																																																																																																																														
M11610	AZ61A	F	bars, rods, profiles, and wire	0.249 and under	[...–6.30]	all	38.0	[260]	21.0	[145]	8																																																																																																																																																																																														
–0.750–0.999	0.010		0.018	0.020	0.022	0.025	0.30	...	...	...	...																																																																																																																																																																																														
–1.000–1.499	0.012		0.021	0.023	0.026	0.030	0.035	...	24.0	[165]	9																																																																																																																																																																																														
–1.500–1.999	0.014		0.024	0.026	0.031	0.036	0.042	0.050	24.0	[165]	9																																																																																																																																																																																														
–2.000–3.999	0.024		0.034	0.038	0.048	0.057	0.068	0.080	22.0	[150]	7																																																																																																																																																																																														
–4.000–5.999	0.034		0.044	0.050	0.064	0.078	0.094	0.110	16.0	[110]	7																																																																																																																																																																																														
–6.000–7.999	0.044		0.054	0.062	0.082	0.099	0.120	0.140	16.0	[110]	7																																																																																																																																																																																														
–8.000–9.999	0.054		0.064	0.074	0.100	0.120	0.145	0.170	16.0	[110]	7																																																																																																																																																																																														
			tubes	0.028–0.750	[0.70–20.00]	6.000 [150.00] and under	36.0	[250]	16.0	[110]	7																																																																																																																																																																																														
Circumscribing Circle Sizes 40 in. in Dia and Over																																																																																																																																																																																																									
M11800	AZ80A	F	bars, rods, solid profiles, and wire	0.249 and under	[...–6.30]	all	43.0	[295]	28.0	[195]	9																																																																																																																																																																																														
				0.250–1.499	[6.30–40.00]	all	43.0	[295]	28.0	[195]	8																																																																																																																																																																																														
				1.500–2.499	[40.00–60.00]	all	43.0	[295]	28.0	[195]	6																																																																																																																																																																																														
				2.500–4.999	[60.00–130.00]	all	42.0	[290]	27.0	[185]	4																																																																																																																																																																																														



TABLE 2—Continued




TABLE 2 Continued

Specified Dimension, in.		Tolerance <sup>B,C</sup> in. ±										
Metal Dimensions		Space Dimensions										
Allowable Deviation from Specified Dimension Where 75% or More of the Dimension is Metal <sup>D</sup>		Allowable Deviation from Specified Dimension Where More than 25% of the Dimension is Space <sup>E,F</sup>										
UNS No.	ASTM No.	Wall Thickness <sup>G,H</sup>	At Dimensioned Points	At Dimensioned Points		At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	Yield Strength (0.2 % offset), min	At Dimensioned Points	At Dimensioned Points	
				Specified	At Dimensioned Points							Over-Through
All Alloy <sup>A</sup> Except These Covered By Column 3		Completely per <sup>A</sup> enclosing Space 0.14 in. <sup>2</sup> and Over (Eccentricity)	0.625–1.249	in. from Base <sup>D</sup>	in. from Base of Leg	in. from Base of Leg	in. <sup>2</sup> from Base or OD of Leg Tube, in.	ksi	[MPa]	ksi	[MPa]	%
M11800	AZ80A	T5	bars, rods, solid profiles, and wire	0.249 and under	[...–6.30]	all	all	47.0	[325]	30.0	[205]	4
				0.250–2.499	[6.30–60.00]	all	all	48.0	[330]	33.0	[230]	4
				2.500–4.999	[60.00–130.00]	all	all	45.0	[310]	30.0	[205]	2
M15100	M1A	F	bars, rods, profiles, and wire	0.249 and under	[...–6.30]	all	all	30.0	[205]	F	F	2
				0.250–1.499	[6.30–40.00]	all	all	32.0	[220]	F	F	3
				1.500–2.499	[40.00–60.00]	all	all	32.0	[220]	F	F	2
				2.500–4.999	[60.00–130.00]	all	all	29.0	[200]	F	F	2
			hollow profiles	all	all	all	all	28.0	[195]	F	F	2
			–0.124 and under tubes	0.014	±15 % of specified	0.018	0.020	...	...	...	...	...
				0.028–0.750	[0.70–20.00]	6.000 [150.00] and under	28.0	[195]	F	F	F	2
–0.125–0.249	0.015	— dimension:	0.019	0.022	0.028	...	...	...	...	...	...	...
–0.250–0.499	0.016	±0.090 max	0.020	0.024	0.030	0.050	...	...	...	...	...	...
M18430	WE43B	T5	bars, rods, solid profiles and wire	0.250–1.999	[6.3–50.00]	all	all	36.0	[250]	23.0	[160]	4
–0.500–0.749	0.017	±0.015 min	0.022	0.027	0.040	0.060	...	...	...	...	...	...
–0.750–0.999	0.018		0.023	0.030	0.050	0.070	0.090	...	...	...	...	...





TABLE 2—Continued




TABLE 2 Continued

Specified Dimension, in.		Tolerance <sup>B,C</sup> in. ±									
Metal Dimensions		Space Dimensions									
Allowable Deviation from Specified Dimension Where 75% or More of the Dimension is Metal <sup>D</sup>		Allowable Deviation from Specified Dimension Where More than 25% of the Dimension is Space <sup>E,F</sup>									
All Alloy <sup>A</sup> Except These Covered By Column 3	ASTM No.	Wall Thickness <sup>G,H</sup>	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	Yield Strength (0.2 % offset), min	At Dimensioned Points	At Dimensioned Points
UNS No.	ASTM No.	Tem- <sup>I</sup>	bars, rods, solid profiles and wire	in. from Base of Leg	in. from Base of Leg	in. from Base of Leg	in. from Base of Leg	in. from Base of Leg	ksi	in. from Base of Leg	in. from Base of Leg
				in. <sup>D,E</sup>	[mm]	ksi	[MPa]	ksi	[MPa]	% <sup>B,C</sup>	% <sup>B,C</sup>
M18430	WE43B	T5	bars, rods, solid profiles and wire	2.00-5.00	[50-130.00]	all	35.0	[240]	22.0	[150]	4
-1.000-1.499	019		0-024	0-034	0-060	0-080	0-100	---			
-1.500-1.999	024		0-034	0-044	0-070	0-090	0-110	0-170			
M18430	WE43B	T6	bars, rods, solid profiles and wire	0.250-1.999	[6.3-50.00]	all	36.0	[250]	22.0	[150]	4
-2.000-3.999	034		0-044	0-054	0-080	0-100	0-120	0-180			
-4.000-5.999	044		0-054	0-064	0-090	0-110	0-130	0-190			
M18430	WE43B	T6	bars, rods, solid profiles and wire	2.00-5.00	[50-130.00]	all	35.0	[240]	20.0	[140]	4
-6.000-7.999	054		0-064	0-074	0-100	0-120	0-140	0-200			
-8.000-9.999	064		0-074	0-084	0-110	0-130	0-150	0-240			
M18410	WE54A	T5	bars, rods, solid profiles and wire	0.250-1.999	[6.3-50.00]	all	36.0	[250]	26.0	[180]	4
10.000-11.999	074		0-084	0-094	0-120	0-140	0-160	0-220			
12.000-13.999	084		0-094	0-104	0-130	0-150	0-170	0-230			
M18410	WE54A	T5	bars, rods, solid profiles and wire	2.00-5.00	[50-130.00]	all	36.0	[250]	25.0	[170]	4
14.000-15.999	094		0-104	0-114	0-140	0-160	0-180	0-240			
16.000-17.999	104		0-114	0-124	0-150	0-170	0-190	0-250			



TABLE 2—Continued




TABLE 2 Continued

Specified Dimension, in.		Tolerance <sup>B,C</sup> in. ±									
Metal Dimensions		Space Dimensions									
Allowable Deviation from Specified Dimension Where 75% or More of the Dimension is Metal <sup>D</sup>		Allowable Deviation from Specified Dimension Where More than 25% of the Dimension is Space <sup>E,F</sup>									
UNS No.	ASTM No.	Wall Thickness <sup>G,H</sup>	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	At Dimensioned Points	Yield Strength (0.2 % offset), min	At Dimensioned Points	At Dimensioned Points
M18410	WE54A	T6	bars, rods, solid profiles and wire	0.250-1.999	[6.3-50.00]	all	38.0	[260]	26.0	[180]	4
18.000-19.999	14			0.124	0.134	0.160	0.180	0.200	0.260		
20.000-21.999	24			0.134	0.144	0.170	0.190	0.210	0.270		
22.000-23.999	34			0.144	0.154	0.180	0.200	0.220	0.280		
M18410	WE54A	T6	bars, rods, solid profiles and wire	2.00-5.00	[50-130.00]	all	36.0	[250]	25.0	[175]	4
M16400	ZK40A	T5	bars, rods, profiles, and wire	all		3.000 [1900] and under	37.0	[255]	34.0	[235]	4.0
			hollow profiles	all		all	40.0	[275]	37.0	[255]	4.0
			tubes	0.062-0.500	[1.60-12.50]	3.000 [80.00] and under	40.0	[275]	36.0	[255]	4.0
M16600	ZK60A	F	bars, rods, profiles and wire	all		4.999 [3200] and under	43.0	[295]	31.0	[215]	5
						5.000-39.999 [3201-26 000]	43.0	[295]	31.0	[215]	6
			hollow profiles	all		all	40.0	[275]	28.0	[195]	5
			tubes	0.028-0.750	[0.70-20.00]	3.000 [80.00] and under	40.0	[275]	28.0	[195]	5