

**ISO/FDIS 19882**

ISO/TC 197

Date: 2024-08-25

ISO/DIS 19882:2024(E)

ISO TC 197/WG 13

Secretariat: SCC

Date: 2024-10-31

**Style Definition**

**Formatted:** Left: 1.5 cm, Right: 1.5 cm, Top: 1.4 cm, Bottom: 1 cm, Do not suppress endnotes, Width: 21 cm, Height: 29.7 cm

**Gaseous hydrogen — Thermally activated pressure relief devices for compressed hydrogen vehicle fuel containers**

*Hydrogène gazeux — Dispositifs limiteurs de pression thermiquement activés pour les conteneurs de carburant de véhicules à hydrogène comprimé*

**Formatted:** Cover Title\_A1

**Formatted**

Itch Standards  
(<https://standards.itech.ai>)  
Document Preview

ISO/FDIS 19882

<https://standards.itech.ai/catalog/standards/iso/3dbff71f-f9cd-4654-a1c6-81e3cae0ae71/iso-fdis-19882>

**FDIS stage**

Edited DIS - MUST BE USED FOR FINAL DRAFT

**ISO/DISDIS 19882:2023(E)2024(en)**

© ISO 2023/2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

Formatted: Font: 11 pt

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: French (Switzerland)

Formatted: French (Switzerland)

Formatted: French (Switzerland)

Formatted: English (United Kingdom)

Formatted: English (United Kingdom)

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO/FDIS 19882

<https://standards.iteh.ai/catalog/standards/iso/3dbff71f-f9cd-4654-a1c6-83e3cae0ae71/iso-fdis-19882>

Formatted: FooterPageRomanNumber

Contents—Page

**Foreword** ..... vi

**Introduction** ..... vii

**1 Scope** ..... 1

**2 Normative references** ..... 1

**3 Terms and definitions** ..... 2

**4 Service conditions** ..... 4

**5 Quality assurance** ..... 5

**6 General requirements** ..... 5

**7 Design qualification testing** ..... 8

**8 Inspection and acceptance testing** ..... 18

**9 Production batch testing** ..... 19

**10 Marking** ..... 20

**11 Component literature** ..... 21

**Annex A (informative) Subsystem and vehicle level considerations** ..... 23

**Annex B (informative) Design qualification test rationale** ..... 27

**Bibliography** ..... 30

**1 Scope** ..... 1

**2 Normative references** ..... 1

**3 Terms and definitions** ..... 2

**4 Service conditions** ..... 4

**4.1 General** ..... 4

**4.2 Design service life** ..... 4

**4.3 Nominal working pressure** ..... 4

**4.4 Durability test cycles** ..... 4

**4.5 Temperature range** ..... 5

**5 Quality assurance** ..... 5

**6 General requirements** ..... 5

**6.1 Material requirements** ..... 5

**6.1.1 General** ..... 5

**6.1.2 Metallic materials** ..... 5

**6.1.3 Non-metallic materials** ..... 6

**6.2 Design requirements** ..... 6

**6.3 Flow capacity** ..... 6

**6.4 Failure modes and effects analysis (FMEA)** ..... 7

**7 Design qualification testing** ..... 7

**7.1 General** ..... 7

**7.1.1 Test gases** ..... 11

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: Font: Bold

Formatted: HeaderCentered, Left

Formatted: Font: Bold

Formatted: Don't suppress line numbers, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 17.2 cm

Formatted: FooterPageRomanNumber

ISO/DISFDIS 19882:2023(E2024(en)

7.2	Pressure cycling	11
7.2.1	Sampling	11
7.2.2	Procedure	11
7.2.3	Acceptable results	12
7.3	Accelerated life	12
7.3.1	Sampling	12
7.3.2	Procedure	12
7.3.3	Acceptable results	13
7.4	Thermal cycling	13
7.4.1	Sampling	13
7.4.2	Procedure	13
7.4.3	Acceptable results	14
7.5	Accelerated cyclic corrosion	14
7.5.1	Sampling	14
7.5.2	Procedure	14
7.5.3	Acceptable results	16
7.6	Automotive fluids exposure	16
7.6.1	Sampling	16
7.6.2	Procedure	16
7.6.3	Acceptable results	17
7.7	Atmospheric exposure	17
7.7.1	General	17
7.7.2	Oxygen aging	17
7.7.3	Ozone	17
7.8	Stress corrosion cracking resistance	18
7.8.1	Sampling	18
7.8.2	Procedure	18
7.8.3	Acceptable results	18
7.9	Impact due to drop and vibration	18
7.9.1	Impact due to drop	18
7.9.2	Vibration	19
7.10	Leakage	19
7.10.1	Sampling	19
7.10.2	Procedure	19
7.10.3	Acceptable results	20
7.11	Bench top activation	20
7.11.1	Pressure relief devices	20
7.11.2	Pilot activated PRDs	21
7.12	Flow capacity	22
7.12.1	Sampling	22
7.12.2	Procedure	22
7.12.3	Acceptable results	22
7.13	High pressure activation and flow	22
7.13.1	Sampling	22
7.13.2	Procedure	23
7.13.3	Acceptable results	23
7.14	Excess torque resistance	23
7.14.1	Sampling	23
7.14.2	Procedure	23
7.14.3	Acceptable results	23
7.15	Hydrostatic strength	24

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered

Formatted: Font: 11 pt

Formatted: Font: Bold

Formatted: FooterPageRomanNumber

7.15.1 Sampling..... 24  
7.15.2 Procedure..... 24  
7.15.3 Acceptable results..... 24  
7.16 Water jet protection..... 24  
7.16.1 Sampling..... 24  
7.16.2 Procedure..... 25  
7.16.3 Acceptable results..... 25  
8 Inspection and acceptance testing..... 25  
8.1 Inspection and acceptance testing plan..... 25  
8.2 Inspector's responsibilities..... 25  
8.3 Inspection of system critical components..... 25  
8.4 Leak testing..... 25  
9 Production batch testing..... 26  
9.1 General..... 26  
9.2 Production batch sizes..... 26  
9.2.1 General..... 26  
9.2.2 Fusible materials..... 26  
9.2.3 Pressure relief devices..... 26  
9.3 Pressure relief device components..... 26  
9.4 Pressure cycle verification..... 26  
9.4.1 General..... 26  
9.4.2 Procedure..... 26  
9.4.3 Acceptable results..... 27  
9.5 Bench top activation..... 27  
9.5.1 General..... 27  
9.5.2 Procedure..... 27  
9.5.3 Acceptable results..... 27  
10 Marking..... 27  
10.1 Required information..... 27  
10.2 Marking methods..... 27  
11 Component literature..... 27  
11.1 General..... 27  
11.2 Component literature recommendations for pilot-operated PRD valves..... 28  
Annex A (informative) Subsystem and vehicle level considerations..... 30  
Annex B (informative) Design qualification test rationale..... 35

- Formatted: Font: 11 pt
- Formatted: HeaderCentered, Left
- Formatted: Font: 11 pt
- Formatted: Font: 11 pt
- Formatted: Font: Bold

Formatted: Font: 11 pt  
Formatted: Font: 11 pt  
Formatted: Font: Bold  
Formatted: HeaderCentered  
Formatted: Font: 11 pt  
Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Formatted: English (United Kingdom)

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

Formatted: English (United Kingdom)

This document was prepared by Technical Committee ISO/TC 197, *Hydrogen technologies*.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

This second edition cancels and replaces the first edition (ISO 19882:2018), which has been technically revised. <https://standards.iteh.ai/catalog/standards/iso/3dbf171f-19cd-4654-a1c6-83e3cae0ae71/iso-fdis-19882>

The main changes are as follows:

- Addition of pilot TPRDs and PRD valve coverage;
- Updates to design qualification test procedures;
- Additional test requirements for excess torque resistance, hydrostatic strength and waterjet protection.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

Formatted: English (United Kingdom)  
Field Code Changed

Formatted: FooterPageRomanNumber

## Introduction

The purpose of this document is to promote the implementation of hydrogen powered land vehicles through the creation of performance-based testing requirements for thermally-activated pressure relief devices for compressed hydrogen fuel containers. The successful commercialization of hydrogen land vehicle technologies requires standards pertaining vehicle fuel system components and the global homologation of standards requirements for technologies with the same end use. This will allow manufacturers to achieve economies of scale in production through the ability to manufacture one product for global use.

~~This document does not apply to reseating, resealing, or pressure activated devices.~~

Documents which apply to hydrogen fuel vehicles and hydrogen fuel subsystems include IEC 62282-4-101, SAE J2578, SAE J2579, UN ECE R134, or UN GTR No. 13.

Annex A presents an informative record of recommended fuel container, fuel storage subsystem and vehicle level requirements. The statements in Annex A are intended as recommendations for consideration of inclusion by the organizations and committees developing standards on these sub-system and vehicle level standards.

Annex B presents a rationale for the design qualification tests in this document.

This document is based on the CSA Standard CSA/ANSI HPRD 1:21.

- Formatted: Font: 11 pt
- Formatted: Font: 11 pt
- Formatted: Font: 11 pt
- Formatted: Font: Bold
- Formatted: HeaderCentered, Left
- Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

- Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font
- Formatted: Default Paragraph Font

ITeC Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO/FDIS 19882

<https://standards.iteh.ai/catalog/standards/iso/3dbff71f-f9cd-4654-a1c6-83e3cae0ae71/iso-fdis-19882>

- Formatted: FooterPageRomanNumber





# Gaseous hydrogen — Thermally activated pressure relief devices for compressed hydrogen vehicle fuel containers

Formatted: Main Title 1, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

## 1 Scope

This document establishes minimum requirements for pressure relief devices intended for use on hydrogen fuelled vehicle fuel containers that comply with ISO 19881, IEC 62282-4-101, CSA/ANSI HGV 2, EC79/EU406, SAE J2579, UN ECE R134, or the UN GTR No. 13.

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Space Before: 0 pt

The scope applicability of this document is limited to thermally activated pressure relief devices installed on fuel containers containing gaseous hydrogen according to ISO 14687 for fuel cell and internal combustion land vehicles. This document contains requirements for thermally activated pressure relief devices acceptable for use on-board the following types of land vehicles:

— light-duty vehicles;

— heavy-duty vehicles and;

— industrial powered trucks, such as forklifts and other material handling vehicles.

Requirements for other types of land vehicles such as rail, off-road, etc., can be derived with due consideration of appropriate service conditions.

This document does not apply to reseating, resealing, or pressure-activated devices.

Pressure relief devices can be of any design or manufacturing method that meets the requirements of this document.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1431-1, *Rubber, vulcanized or thermoplastic — Resistance to ozone cracking — Part 1: Static and dynamic strain testing*

ISO 188, *Rubber, vulcanized or thermoplastic — Accelerated ageing and heat resistance tests*

ISO 6270-2, *Paints and varnishes — Determination of resistance to humidity — Part 2: Condensation (in-cabinet exposure with heated water reservoir)*

## ISO/DIS 19882:2023(E)

ISO 14687, *Hydrogen fuel quality — Product specification*

ISO 19881, *Gaseous hydrogen — Land vehicle fuel containers*

ASTM D572, *Standard Test Method for Rubber — Deterioration by Heat and Oxygen*

ASTM D1149, *Standard Test Methods for Rubber Deterioration — Cracking in an Ozone Controlled Environment*

ASTM D1193, *Standard Specification for Reagent Water*

CSA/ANSI HGV 2, *Compressed hydrogen gas vehicle fuel containers*

EC79 (EU406), *Type approval of hydrogen-powered motor vehicles*

UN GTR No. 13, *UN Global Technical Regulation on Hydrogen and Fuel Cell Vehicles*

SAE J2579, *Standard for Fuel Systems in Fuel Cell and Other Hydrogen Vehicles*

SAE J2719, *Hydrogen Fuel Quality for Fuel Cell Vehicles*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1 3.1

##### flow capacity

<pressure relief device> capacity in volume per unit time at specified conditions

#### 3.2 3.2

##### fusible material

metal, alloy, or other material capable of being melted by heat where the melting is integral to the function of the *pressure relief device* (3.7)(3.7)

#### 3.3 3.3

##### manufacturer's specified activation temperature

temperature, as specified by the pressure relief device manufacturer, at which the *pressure relief device* (3.7)(3.7) is designed to release pressure

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font, Font: Italic

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: TermNum2, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

**3.4 3.4****manufacturer's specified nominal working pressure**

highest settled pressure at a uniform gas temperature of 15 °C of the container or container assembly with which the *pressure relief device* (3.7)(3.7) may be used, as specified by the pressure relief device manufacturer

**3.5 3.5****normal cubic centimetre**

Ncm<sup>3</sup>

dry gas that occupies a volume of 1 cm<sup>3</sup> at a temperature of 293,15 K (20 °C) and an absolute pressure of 101,325 kPa

**3.6 3.6****pilot-activating device**

valve or device designed to be used as a trigger for pilot-activated *pressure relief device* (3.7)(3.7) valves, other than pilot TPRDs

**3.7 3.7****pressure relief device**

PRD

device that, when activated under specified performance conditions, is used to vent the container contents

Note 1 to entry: Reseating and resealing devices are not addressed by this document.

**3.8 3.8****thermally-activated pressure relief device**

TPRD

*pressure relief device* (3.7)(3.7) activated by temperature

**3.8.1 3.8.1****direct-acting TPRD**

*TPRD* (3.8)(3.8) having a heat-reactive element that acts directly with the gas control portion of the *PRD* (3.7)(3.7)

**3.8.2 3.8.2****long-trigger TPRD**

*TPRD* (3.8)*TPRD* (3.8) having a heat-reactive element that is more than 10 times longer than the longest dimension of the *PRD* (3.7)(3.7) body

**3.8.3 3.8.3****pilot TPRD**

*TPRD* (3.8)(3.8) designed to be used as the trigger for the *pilot-activated PRD valve* (3.9.2)(3.9.2)

**3.8.4 3.8.4****remote-sensing TPRD**

*TPRD* (3.8)*TPRD* (3.8) having one or more remote heat-reactive element(s) such that it can be heated separately from, and acts indirectly with, the gas control portion of the PRD

**Formatted:** Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

**Formatted:** TermNum2, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

**3.9 3.9**

**pressure relief device (PRD)-valve**

**PRD valve**

single-use valve that is intended to be opened to empty a hydrogen container-

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

**3.9.1 3.9.1**

**negative-acting pilot-activated PRD valve**

~~PRD (3.7)PRD (3.7)~~ that is designed to be triggered by a remote heat-sensing element or device and that will react to a decrease in pressure being applied to the *pilot-activated PRD valve* ~~(3.9.2)(3.9.2)~~ activation port

**3.9.2 3.9.2**

**pilot-activated PRD valve**

single-use valve that is intended to be opened to empty a hydrogen container by the action of an attached *PRD* ~~(3.7)(3.7)~~

**3.9.3 3.9.3**

**positive-acting pilot-activated PRD valve**

~~PRD (3.7)PRD (3.7)~~ that is designed to be triggered by a remote heat-sensing element or device and that will react to a positive pressure applied to the *pilot-activated PRD valve* ~~(3.9.2)(3.9.2)~~ activation port

**4 Service conditions**

**4.1 General**

Fuel containers can accidentally be exposed to fire or elevated temperature. These conditions can act to increase the contained-pressure or to degrade the structural materials, depending on the container type and materials of construction. A pressure relief device provides a means to vent the fuel container under these conditions.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

A pressure relief device may not be suitable for all container types, sizes or installations. Fuel container or installation standards may require that a pressure relief device be tested in conjunction with other components.

The service conditions in [4.24.2](#) through [4.54.5](#) are representative of what can be seen in an automotive service. These service conditions are provided as a basis for the design, manufacture, inspection and testing of pressure relief devices used in compressed hydrogen vehicle fuel containers.

**4.2 Design service life**

The design service life of the pressure relief device shall be specified by the manufacturer.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

NOTE The testing described in this document is based on an expected service life of 20 years. Service life values can be extended by adjusting the filling or duty cycles, as applicable, by the appropriate factor (ratio). For example, a service life of 25 years will require cycling to be multiplied by 1,25.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm