

ISO\_8124-3-~~DAmd:2020/Amd.1:2022~~2023(E)

ISO TC 181/WG 8

Secretariat: DS

Date: 2023-01-18

Safety of toys — Part 3: Migration of certain elements — Amendment 1

Limits for boron and other elements in slime, and barium in modelling clay

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 8124-3:2020/PRF Amd 1

<https://standards.iteh.ai/catalog/standards/sist/c4a97f47-0269-4dcb-afa4-8151afbd918/iso-8124-3-2020-prf-amd-1>

© ISO ~~20XX~~2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva

Phone: +41 22 749 01 11

Fax: +41 22 749 09 47

Email: [copyright@iso.org](mailto:copyright@iso.org)

Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

ISO 8124-3:2020/PRF Amd 1

<https://standards.iteh.ai/catalog/standards/sist/c4a97f47-0269-4dcb-afa4-8151afbd918/iso-8124-3-2020-prf-amd-1>

## **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 181, *Safety of toys*.

A list of all parts in the ISO 8124 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).



# Safety of toys — Part 3: Migration of certain elements — Amendment 1: Limits for boron and other elements in slime, and barium in modelling clay

-

## Introduction

Add the following content below "~~—~~" 25,0 µg for barium;"

~~—~~ 30,0 µg for boron;

-

## Clause 3

Add the following terminological entries.

-

### 3.13

#### slime

water-based gel or gel like material, clear or coloured, which is viscous, slippery, and often non-Newtonian fluids, intended for play by hand manipulation, kneading and stretching

Note 1 to entry: A material behaving in a non-Newtonian manner will have a change in viscosity, i.e., become more or less viscous, when subjected to shear forces such as manipulation, with such a change being reversible when the shear forces cease to be applied.

### 3.14

#### modelling clay and putty

flexible solid or semi-solid mixtures that retain their shape and form when moulded into a shape, intended to create representations of objects by hand manipulation or to be extruded into profiles by the toy.

-

-

## 4.2

Replace Table 1 with the following table.

**Table 1 — Maximum acceptable element migration from toy materials**

Values in milligrams per kilogram of toy material

Toy material	Element
--------------	---------

	<b>Sb</b>	<b>As</b>	<b>Ba</b>	<b>Cd</b>	<b>Cr</b>	<b>Pb</b>	<b>Hg</b>	<b>Se</b>	<b>B</b>
Any toy material given in Clause 1, except modelling clay and putties, finger paint, and slime	60	25	1-00 0	75	60	90	60	500	-
Modelling clay and putties	60	25	350	50	25	90	25	500	3-750
Finger paint	10	10	350	15	25	25	10	50	-
Slime	10	10	350	15	25	25	10	50	1-250

Replace Table-2 with the following table.

**Table-2 — Analytical correction**

<b>Element</b>	<b>Sb</b>	<b>As</b>	<b>Ba</b>	<b>Cd</b>	<b>Cr</b>	<b>Pb</b>	<b>Hg</b>	<b>Se</b>	<b>B</b>
Analytical correction (%)	60	60	30	30	30	30	50	60	60

**9.8.1, second paragraph**

Add the following note after the second paragraph.

NOTE -Dewaxing is only applied if hydrocarbon plasticizers/extenders have been confirmed to be present using Fourier Transform Infrared Spectroscopy (FTIR) or other suitable method; hydrophobic compounds such as polysiloxanes and similar are not dewaxed.

**D.3**

Add the following text after the list item.

The maximum acceptable level of soluble barium in modelling clays has been raised from 250-mg/kg to 350-mg/kg for the following reasons:

- Previous versions of this document have had an anomaly whereby the maximum acceptable element migration for barium in modelling clays was lower than for finger paints.
- The exposure from modelling clay is likely to be lower than from finger paints due to the nature of the material and the age at which children start playing with clay.
- The increase to 350-mg/kg of toy material is a pragmatic solution to resolve the anomaly and based on the accepted maximum intake of barium from toy sources, the adjusted limit still provides an acceptable margin of safety determined by bioavailability and risk models.

The maximum acceptable level of boron has been added in modelling clay, putties and slime for the following reasons:

- Boron may be present in certain types of toy material in the form of boric acid or borates and is used to facilitate cross-linking of polymers as seen in certain putties and slime toys.
- The critical adverse effect of boron is reproductive and developmental toxicity, and it is therefore appropriate to provide safe limits for the exposure of children to boron in toys.
- The tolerable daily intake (TDI) of boron has been determined by the World Health Organisation to be 160-µg/kg of bodyweight per day [9].