

FINAL
DRAFT

INTERNATIONAL
STANDARD

ISO/FDIS
18646-2

ISO/TC 299

Secretariat: SIS

Voting begins on:
2023-10-27

Voting terminates on:
2023-12-22

Robotics — Performance criteria and related test methods for service robots —

Part 2: Navigation

*Robotique — Critères de performance et méthodes d'essai
correspondantes pour robots de service —*

Partie 2: Navigation

*IT Standards
(<https://standards.iteh.ai>)
Document Preview*

[ISO/FDIS 18646-2](https://standards.iteh.ai/catalog/standards/sist/094a0bed-56f2-4588-a3b4-984d5bfda272/iso-fdis-18646-2)

<https://standards.iteh.ai/catalog/standards/sist/094a0bed-56f2-4588-a3b4-984d5bfda272/iso-fdis-18646-2>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 18646-2:2023(E)

© ISO 2023

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 18646-2](https://standards.iteh.ai/catalog/standards/sist/094a0bed-56f2-4588-a3b4-984d5bfda272/iso-fdis-18646-2)

<https://standards.iteh.ai/catalog/standards/sist/094a0bed-56f2-4588-a3b4-984d5bfda272/iso-fdis-18646-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	4
4.1 General.....	4
4.2 Environmental conditions.....	5
4.3 Travel surface conditions.....	5
4.4 Operating conditions.....	5
4.5 Test paths.....	5
5 Pose characteristics	7
5.1 Purpose.....	7
5.2 Relevant characteristics.....	7
5.2.1 Pose accuracy.....	7
5.2.2 Pose repeatability.....	9
5.3 Test facility.....	10
5.4 Test procedure.....	10
5.5 Test result.....	11
6 Obstacle detection	11
6.1 Purpose.....	11
6.2 Test facility.....	11
6.3 Test procedure.....	13
6.4 Test result.....	13
7 Obstacle avoidance	14
7.1 Purpose.....	14
7.2 Test facility.....	14
7.3 Test procedure.....	15
7.4 Test result.....	16
8 Path deviation	16
8.1 Purpose.....	16
8.2 Test facility.....	16
8.3 Test procedure.....	17
8.4 Test result.....	17
9 Narrow passage	18
9.1 Purpose.....	18
9.2 Test facility.....	18
9.3 Test procedure.....	18
9.4 Test result.....	19
10 Mapping accuracy	19
10.1 Purpose.....	19
10.2 Test facility.....	19
10.3 Test procedure.....	21
10.4 Test result.....	21
Annex A (informative) Outdoor navigation	22
Bibliography	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 299, *Robotics*.

This second edition cancels and replaces the first edition (ISO 18646-2:2019), which has been technically revised.

The main changes are as follows:

- [Clauses 8](#) to [10](#) have been added for path deviation, narrow passage and mapping accuracy.

A list of all parts in the ISO 18646 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document is intended to specify performance criteria and test methods for navigation of mobile service robots. It defines performance characteristics, describes how they are specified and recommends how to test them.

The characteristics for which test methods are given in this document are those considered to affect robot performance significantly. It is intended that the reader of this document selects which performance characteristics are to be tested, in accordance with the specific requirements.

The performance criteria specified in this document are not intended to be interpreted as the verification or validation of safety requirements.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 18646-2](#)

<https://standards.iteh.ai/catalog/standards/sist/094a0bed-56f2-4588-a3b4-984d5bfda272/iso-fdis-18646-2>

Robotics — Performance criteria and related test methods for service robots —

Part 2: Navigation

1 Scope

This document describes methods of specifying and evaluating the navigation performance of mobile service robots. Navigation performance in this document is measured by pose accuracy and repeatability, ability to detect and avoid obstacles, path deviation, narrow passage, and mapping accuracy. Other measures of navigation performance are available but are not covered in this document.

The criteria and related test methods are applicable only to mobile platforms that are in contact with the travel surface. For evaluating the characteristics of manipulators, ISO 9283 applies.

This document deals with indoor environments only. However, the depicted tests can also be applicable for robots operating in outdoor environments, as described in [Annex A](#).

This document is not applicable for the verification or validation of safety requirements. It does not deal with safety requirements for test personnel during testing.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7176-13, *Wheelchairs — Part 13: Determination of coefficient of friction of test surfaces*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

robot

programmed actuated mechanism with a degree of autonomy to perform locomotion, manipulation or positioning

Note 1 to entry: A robot includes the control system.

Note 2 to entry: Examples of mechanical structure of robots are manipulator, *mobile platform* (3.3) and wearable robot.

[SOURCE: ISO 8373:2021, 3.1]

3.2

mobile robot

robot (3.1) able to travel under its own control

Note 1 to entry: A mobile robot can be a *mobile platform* (3.3) with or without manipulators.

Note 2 to entry: In addition to autonomous operation, a mobile robot can have means to be remotely controlled.

[SOURCE: ISO 8373:2021, 4.15]

3.3

mobile platform

assembly of the components which enables locomotion

Note 1 to entry: A mobile platform can include a chassis which can be used to support a *load* (3.6).

Note 2 to entry: A mobile platform can provide the structure by which to affix a manipulator.

Note 3 to entry: Mobile platform following a predetermined *path* (3.14) indicated by markers or external guidance commands, typically used for logistic tasks in industrial automation is also referred to as Automated Guided Vehicle (AGV) or Driverless Industrial Truck. Standards for such vehicles are developed by ISO/TC 110.

[SOURCE: ISO 8373:2021, 4.16]

3.4

service robot

robot (3.1) in personal use or professional use that performs useful tasks for humans or equipment

Note 1 to entry: Tasks in personal use include handling or serving of items, transportation, physical support, providing guidance or information, grooming, cooking and food handling, and cleaning.

Note 2 to entry: Tasks in professional use include inspection, surveillance, handling of items, person transportation, providing guidance or information, cooking and food handling, and cleaning.

[SOURCE: ISO 8373:2021, 3.7]

3.5 <https://standards.iteh.ai/catalog/standards/sist/094a0bed-56f2-4588-a3b4-984d5bfda272/iso-fdis-18646-2>

navigation

process which includes path planning, *localization* (3.17), *mapping* (3.18), and providing the direction of travel

Note 1 to entry: Navigation can include path planning for pose-to-pose travel and complete area coverage.

[SOURCE: ISO 8373:2021, 8.6]

3.6

load

force, torque or both at the mechanical interface or *mobile platform* (3.3) which can be exerted along the various directions of motion under specified conditions of velocity and acceleration

Note 1 to entry: The load is a function of mass, moment of inertia, and static and dynamic forces supported by the *robot* (3.1).

[SOURCE: ISO 8373:2021, 7.2]

3.7

rated load

maximum *load* (3.6) that can be applied to the mechanical interface or *mobile platform* (3.3) in *normal operating conditions* (3.9) without degradation of any performance specification

Note 1 to entry: The rated load includes the inertial effects of the end effector, accessories and workpiece, where applicable.

[SOURCE: ISO 8373:2021, 7.2.1]

3.8 rated speed

maximum speed of *mobile platform* (3.3) equipped with *rated load* (3.7) in *normal operating conditions* (3.9)

[SOURCE: ISO 18646-1:2016, 3.11]

3.9 normal operating conditions

range of environmental conditions and other parameters within which the *robot* (3.1) is expected to perform as specified by the manufacturer

Note 1 to entry: Environmental conditions include temperature and humidity.

Note 2 to entry: Other parameters include electrical supply instability and electromagnetic fields.

[SOURCE: ISO 8373:2021, 7.1]

3.10 task program

set of instructions for motion and auxiliary functions that define the specific intended task of the *robot* (3.1) or robot system

Note 1 to entry: This type of program is generated by the task programmer.

Note 2 to entry: An application is a general area of work; a task is specific within the application.

[SOURCE: ISO 8373:2021, 6.1]

3.11 pose

combination of position and orientation in space

Note 1 to entry: Pose for the manipulator normally refers to the position and orientation of the end effector or the mechanical interface.

Note 2 to entry: Pose for a *mobile robot* (3.2) can include the set of poses of the *mobile platform* (3.3) and of any manipulator attached to the mobile platform, with respect to the mobile platform coordinate system.

Note 3 to entry: For mobile robots in contact with a flat surface, orientation is typically a scalar angle about the normal to the flat surface, with respect to a reference direction.

[SOURCE: ISO 8373:2021, 5.5, modified —Note 3 to entry has been added.]

3.12 command pose

programmed pose
pose (3.11) specified by the *task program* (3.10)

[SOURCE: ISO 8373:2021, 5.5.1]

3.13 attained pose

pose (3.11) achieved by the *robot* (3.1) in response to the *command pose* (3.12)

[SOURCE: ISO 8373:2021, 5.5.2]

3.14 path

route that connects an ordered set of *poses* (3.11)

[SOURCE: ISO 8373:2021, 5.5.4]

3.15
cluster

set of measured points used to calculate the accuracy and the repeatability characteristics

[SOURCE: ISO 9283:1998, 3.1]

3.16
barycentre

point whose coordinates are the mean values of a *cluster* (3.15) of points

Note 1 to entry: For a cluster of n points defined by their coordinates $(x_j - y_j - z_j)$, the barycentre of that cluster of points is calculated as follows:

$$\bar{x} = \frac{1}{n} \sum_{j=1}^n x_j, \bar{y} = \frac{1}{n} \sum_{j=1}^n y_j, \bar{z} = \frac{1}{n} \sum_{j=1}^n z_j$$

[SOURCE: ISO 9283:1998, 3.2, modified]

3.17
localization

recognizing *pose* (3.11) of *mobile robot* (3.2), or identifying it on the environment map

[SOURCE: ISO 8373:2021, 8.2]

3.18
mapping

map building

map generation

constructing the environment map to describe the environment with its geometrical and detectable features, landmarks and obstacles

[SOURCE: ISO 8373:2021, 8.5]

3.19
test configuration

particular arrangement of test objects

3.20
trial

single instance of test procedure performed under identical *test configuration* (3.19)

Note 1 to entry: A trial can be repeated multiple times.

4 Test conditions

4.1 General

The robot shall be completely assembled, fully charged and operational, based on the manufacturer specification. Appropriate precautions should be taken to protect the personnel during the test.

The tests shall be preceded by the preparations for operation as specified by the manufacturer. These preparations shall be reported in the test report.

All conditions specified in [Clause 4](#) should be satisfied for the tests described in this document, unless it is stated otherwise in the specific clauses.

The tests described in this document may have multiple test configurations which require separate test procedures. For each test configuration, multiple trials should be conducted if specified in the test procedure.

4.2 Environmental conditions

The following typical indoor environmental conditions should be maintained during all tests:

- ambient temperature: 10 °C to 30 °C;
- relative humidity: 0 % to 80 %;
- illumination: 100 lux to 1 000 lux.

The environmental conditions shall be declared in the test report. The manufacturer may specify environmental conditions outside these ranges (see [Annex A](#)).

NOTE Even though reflectivity can affect performance, it is not included in these environmental conditions.

4.3 Travel surface conditions

A hard, even and horizontal travel surface with a coefficient of friction between 0,6 and 1,0, measured in accordance with ISO 7176-13, shall be used.

4.4 Operating conditions

All performance shall be measured under normal operating conditions. When the performance is measured in other conditions, those conditions shall be declared in the test report.

For all tests, the robot shall be tested at the rated speed and equipped with the rated load, unless otherwise specified.

For the navigation of mobile platforms, external equipment, such as landmarks, shall be supplied according to the specifications of the manufacturer. Information on the external equipment, such as locations and types of landmarks, shall be provided in the test report.

4.5 Test paths

All test paths are parameterized with respect to the sizes of mobile platforms. Length unit, L_U , is defined as the multiples of 500 mm according to the width, w , the distance across the forward direction, of the mobile platform, as shown in [Figure 1](#). The width, w , shall take into account not only the mobile platform but also any protruding part of the mobile robot, for example, arm or shelf. The L_U value used for the test shall be declared in the test report.

$$L_U = \left\lceil \frac{w}{500} \right\rceil \times 500 \text{ mm}$$

$\lceil x \rceil$ is the ceiling function that maps real number x to the least integer greater than or equal to x .

Length unit, L_U , may be increased from the above value for each test specified in this document if it is determined necessary to accommodate the test. For instance, when the length of mobile robot does not allow the proper motion in [Clause 10](#), the larger value of L_U can be used for the test.