

ISO/TC 67/SC 7

Date: 2023-~~05-30~~08-08

ISO/FDIS 19901-3:2023(E)

ISO/TC 67/SC 7/WG 3

Secretariat: NEN

Petroleum and natural gas industries — Specific requirements for offshore structures — Part 3: Topsides structure

Industries du pétrole et du gaz naturel — Exigences spécifiques relatives aux structures en mer — Partie 3: Superstructures

(standards.iteh.ai)

ISO/FDIS 19901-3

<https://standards.iteh.ai/catalog/standards/sist/63e1105e-bfe1-4959-8bce-58ae864b79e8/iso-fdis-19901-3>

Edited DIS - MUST BE USED FOR FINAL DRAFT

ISO/FDIS 19901-3:2023(E)

© ISO ~~2022~~2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva

Phone: +41 22 749 01 11

Fax: +41 22 749 09 47

Email: copyright@iso.org

Website: www.iso.org

Published in Switzerland

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 19901-3

<https://standards.iteh.ai/catalog/standards/sist/63e1105e-bfe1-4959-8bce-58ae864b79e8/iso-fdis-19901-3>

Contents

Foreword.....	15
Introduction.....	18
1 — Scope.....	1
2 — Normative references.....	2
3 — Terms and definitions.....	3
4 — Symbols and abbreviated terms.....	5
4.1 — Symbols.....	5
4.2 — Abbreviated terms.....	6
5 — Overall requirements.....	7
5.1 — Conceptual design.....	7
5.2 — Codes and standards.....	7
5.3 — Deck elevation.....	8
5.4 — Exposure level.....	8
5.5 — Operational requirements.....	9
5.6 — Design physical environmental conditions.....	9
5.7 — Critical structure.....	9
5.8 — Assessment of existing topsides structure.....	10
5.9 — Reuse of topsides structure.....	10
5.10 — Repairs, modifications and refurbishment.....	10
6 — Design requirements.....	11
6.1 — General.....	11
6.2 — Design/assessment situations.....	11
6.3 — Material selection.....	11
6.4 — Structural interfaces.....	11
6.5 — Design for serviceability.....	11
Table 1 — Serviceability limits for vertical deflections.....	12
6.6 — Design for strength.....	14
6.7 — Design for fatigue.....	14
Table 2 — Partial damage design factors for topsides structure, γ_{FD}	14
6.8 — Robustness.....	15
6.9 — Confirmation of execution of design requirements.....	15
6.10 — Corrosion control.....	16
6.11 — Design for fabrication and inspection.....	16
6.12 — Design for loadout, transportation and installation.....	17
6.13 — Design for structural integrity management.....	17
6.14 — Design for decommissioning, removal and disposal.....	17
7 — Actions and analysis methods.....	18
7.1 — General.....	18
7.2 — In-service actions.....	19
7.3 — Action factors.....	20
7.4 — Vortex induced vibrations.....	21
7.5 — Indirect actions and resulting forces (action effects).....	22
7.6 — Metocean and ice actions.....	22

ISO/FDIS 19901-3:2023(E)

7.7	Seismic actions	24
7.8	Actions during fabrication, loadout, transportation, and installation	25
7.9	Actions arising from accidental events	25
Figure 1	Example hazard curves (not to be used for design)	27
Table 3	Drag coefficients for component shapes (1=Flow)	29
Figure 2	Overpressure time history	30
Figure 3	Variability in pulse duration versus peak overpressure	31
Figure 4	Structural interaction between roof, wall, and floor	32
7.10	Other actions	34
8	Strength and resistance of structural components	37
8.1	Correspondence factor K_c	37
Table 4	Values of correspondence factor K_c	37
8.2	Design of cylindrical tubular sections	37
8.3	Design of non-cylindrical sections	38
8.4	Connections	39
Table 5	Connection class – CC	39
Table 6	Nominal clearance for bolts and pins (allowable additional hole diameter)	41
8.5	Castings and forgings	43
8.6	Design for structural stability	44
9	Limit state verification	45
9.1	Limit state verification approach	45
9.2	Limit state verification for fire and explosion events	45
9.3	Approaches for limit state verification for fire and explosion events	46
9.4	Risk and risk targets	46
Figure 5	Example risk matrix and example risk curve (based on UK HSE terminology and limits)	48
9.5	Limit state verification for fire and explosion events by semi-probabilistic approach	49
10	Structural systems	50
10.1	Topsides design	50
10.2	Topsides structure design models	51
10.3	Substructure interface	53
10.4	Flare towers, booms, vents and similar structure	53
10.5	Helicopter landing facilities (helidecks)	54
Table 7	Combinations of actions	58
10.6	Crane support structure and crane boom rest	60
10.7	Derrick equipment set	66
10.8	Bridges	66
10.9	Bridge bearings	67
10.10	Anti-vibration mountings for modules and major equipment skids	67
10.11	System interface assumptions	67
10.12	Fire protection systems	68
10.13	Penetrations	68
10.14	Difficult-to-inspect areas	69
10.15	Drainage	69
10.16	Strength reduction due to heat	69
10.17	Walkways, laydown areas and equipment maintenance	69

10.18	Muster areas and lifeboat stations	70
11	Materials	70
11.1	General	70
11.2	Carbon steel	70
Table 8	Material category — Material selection for topsides	71
Table 9	Design class approach — Typical minimum selection for topsides structures	72
Figure 6	Main deck — example	74
Figure 7	Main row — example	75
Figure 8	Node detail — example	76
11.3	Stainless steel	76
11.4	Aluminium alloys	77
11.5	Fibre-reinforced polymers (FRP)	78
11.6	Timber	78
12	Fabrication, quality control, quality assurance and documentation	79
12.1	Assembly	79
12.2	Welding	79
12.3	Fabrication inspection	80
12.4	Quality control, quality assurance and documentation	80
12.5	Corrosion protection	80
12.6	In-service inspection, monitoring and maintenance of corrosion control	81
13	Loadout, transportation and installation	81
14	In-service inspection and structural integrity management	81
14.1	General	81
14.2	Requirements applying to topsides structures	81
Annex A (informative)	Additional information and guidance	83
A.1	Guidance on scope	83
A.2	Guidance on normative references	83
A.3	Guidance on terms and definitions	83
A.4	Guidance on symbols and abbreviated terms	83
A.5	Guidance on overall requirements	83
A.5.1	Conceptual design	83
A.5.2	Codes and standards	83
A.5.3	Deck elevation	83
A.5.4	Exposure level	84
A.5.5	Operational requirements	84
A.5.6	Design physical environmental conditions	84
A.5.7	Critical structure	84
A.5.8	Assessment of existing topsides structures	84
A.5.9	Reuse of topsides structure	84
A.5.10	Repairs, modifications and refurbishment	84

ISO/FDIS 19901-3:2023(E)

A.6 — Guidance on design requirements	84
A.6.1 — General	84
A.6.2 — Design/assessment situations	84
A.6.3 — Materials selection	84
A.6.4 — Structural interfaces	84
A.6.5 — Design for serviceability	84
A.6.5.1 Serviceability limits	84
A.6.5.2 Vibrations	84
A.6.5.2.1 Sources of vibration	84
A.6.5.2.2 Design limits on vibrations	85
A.6.5.2.3 Long-period vibrations	85
A.6.5.2.4 Dynamic analysis and avoidance of resonance	85
A.6.5.3 Deflections	85
A.6.6 — Design for strength	85
A.6.7 — Design for fatigue	86
A.6.8 — Robustness	86
A.6.9 — Confirmation of execution of design requirements	87
A.6.10 Corrosion control	87
A.6.11 Design for fabrication and inspection	87
A.6.12 Design for loadout, transportation and installation	87
A.6.13 Design for structural integrity management	87
A.6.14 Design for decommissioning, removal and disposal	87
A.6.14.1 — General	87
A.6.14.2 — Structural releases	87
A.6.14.3 — Lifting appurtenances	87
A.6.14.4 — Heavy lift and set-down operations	87
A.7 — Guidance on actions and analysis methods	87
A.7.1 — General	87
A.7.2 — In-place actions	88
Table A.1 — Typical minimum local actions for topsides structure	88
A.7.3 — Action factors	89
A.7.3.1 Design actions for operational design/assessment situations in still water	89
A.7.3.2 Design actions for operational design/assessment situations with operating environmental actions	89
A.7.3.3 Design actions for extreme design/assessment situations	89
A.7.4 — Vortex-induced vibrations	89

A.7.5 Indirect actions and resulting forces (action effects).....	90
A.7.6 Metocean and ice actions.....	90
A.7.6.1 Wave, current and ice actions.....	90
A.7.6.1.1 General.....	90
A.7.6.1.2 Fixed platform.....	90
A.7.6.1.3 Floating facilities.....	90
A.7.6.2 Wind actions.....	90
A.7.6.3 Cold region effects.....	90
A.7.7 Seismic actions.....	90
A.7.7.1 General.....	90
A.7.7.2 Minimum lateral acceleration.....	91
A.7.7.3 Equipment and appurtenances.....	91
A.7.8 Actions during fabrication, loadout, transportation and installation.....	92
A.7.9 Actions due to accidental hazards.....	92
A.7.9.1 General.....	92
Figure A.1 ISD and barrier steps for risk-based design.....	93
A.7.9.1.1 Accidental hazards.....	94
A.7.9.1.2 Design for accidental events.....	94
A.7.9.1.3 Intensity of hazardous event.....	94
A.7.9.2 Structural design for fire hazards.....	94
A.7.9.2.1 Fire design situations.....	94
A.7.9.2.2 Fire actions.....	95
Table A.2 Yield strength reduction factors for steel at elevated temperatures (ASTM A36/A36M ⁽⁴⁵⁾ and ASTM A633/A633M ⁽⁴⁶⁾ Grades C and D).....	96
A.7.9.2.3 Transient heat transfer analysis.....	96
A.7.9.2.4 Creep.....	96
A.7.9.2.5 Nonlinear finite element analysis for response to fire actions.....	97
A.7.9.2.5.1 General.....	97
A.7.9.2.5.2 Material modelling of carbon steels.....	97
A.7.9.2.5.3 Initial out-of-straightness.....	97
A.7.9.2.5.4 Local cross-sectional buckling.....	98
A.7.9.2.5.5 Strain limits.....	98
A.7.9.2.5.6 Accuracy of fire thermal and response analyses.....	98
A.7.9.2.6 Fire mitigation.....	99
Table A.3 Summary of fire ratings and performance for fire walls.....	99
A.7.9.3 Structural design for explosion hazard.....	100

ISO/FDIS 19901-3:2023(E)

A.7.9.3.1	General	100
A.7.9.3.2	Explosion actions	100
A.7.9.3.3	Overpressure time history	101
A.7.9.3.4	Structural response analysis	101
A.7.9.3.4.1	General	101
A.7.9.3.4.2	Dynamic analysis	102
A.7.9.3.4.3	Nonlinear finite element analysis	102
A.7.9.3.4.4	Strength limit	103
A.7.9.3.4.5	Deformation limit	103
A.7.9.3.4.6	Strain limit	104
A.7.9.3.5	Simplified design methods	104
A.7.9.3.5.1	Design of structural components	105
A.7.9.3.5.2	Ductile deflection limits and local buckling	106
A.7.9.3.5.3	Supports reactions, beam releases and non-fixed connections	106
A.7.9.3.5.4	Material properties for design	106
A.7.9.3.6	Explosion mitigation	107
A.7.9.4	Explosion and fire interaction	107
A.7.9.4.1	General	107
A.7.9.4.2	Deck plating	108
A.7.9.4.3	Blast walls and fire walls	108
A.7.9.4.4	Beams	108
A.7.9.4.5	Slender structural components	108
A.7.9.4.6	Pipe and vessel supports	108
A.7.9.5	Cryogenic spill	109
A.7.9.6	Actions due to vessel collision	109
A.7.9.7	Actions due to dropped and swinging objects and projectiles	110
A.7.9.8	Actions due to loss of buoyancy	110
A.7.9.9	Actions due to topsides acceleration	110
A.7.10	Other actions	111
A.8	Guidance on strength and stability of structural components	111
A.8.1	Correspondence factor K_c	111
A.8.1.1	K_c determined by equivalent reliability	111
A.8.1.2	K_c determined by utilisation ratio	113
A.8.2	Design of cylindrical tubular sections	114
A.8.3	Design of non-cylindrical sections	114

A.8.3.1 Rolled and welded non-circular prismatic members	114
A.8.3.2 Plate girder	114
A.8.3.3 Box girder	114
A.8.3.4 Stiffened plate components and stressed skin structures	114
A.8.4 Connections	114
A.8.4.1 General	114
A.8.4.2 Restraint and shrinkage	114
A.8.4.3 Bolted connections	114
A.8.4.3.1 Design and installation requirements	114
A.8.4.3.2 Connections classes	114
A.8.4.3.3 Corrosion protection	115
A.8.5 Castings and forgings	115
A.8.6 Design for structural stability	115
A.8.6.1 General	115
A.8.6.2 Braced and unbraced frames	115
Figure A.2 Braced topsides	116
Figure A.3 Unbraced portal frame between lowest deck and jacket	117
Figure A.4 Unbraced portal frame at intermediate deck level	118
Figure A.5 Unbraced portal frame between main legs	119
Figure A.6 Unbraced portal frame associated with float over deck configuration	120
A.8.6.3 $P-\Delta$ and $P-\delta$ second order effects frames	120
Figure A.7 $P-\Delta$ and $P-\delta$ second order effects	121
A.8.6.4 Specific requirements of ANSI/AISC 360-22 ^[12] and EN 1993-1-1 ^[13] stability analysis methods	121
Table A.4 Description and comparison of ANSI/AISC 360-22 ^[12] stability analysis methods	121
Table A.5 Description and comparison of EN 1993-1-1 ^[13] stability analysis methods	123
Figure A.8 Example platform	125
Table A.6 Buckling eigenvalues α_{cr} and corresponding B_2	125
Figure A.9 Example results	126
A.9 Guidance on limit state verification	126
A.9.1 Limit state verification approach	126
A.9.2 Limit state verification for fire and explosion events	126
A.9.3 Approaches for limit state verification for fire and explosion events	126
A.9.3.1 Semi-probabilistic approach for limit state verification	126
A.9.3.2 Reliability-based approach for limit state verification	126
A.9.3.3 Risk-informed approach for limit state verification	127

ISO/FDIS 19901-3:2023(E)

Figure A.10 — Example risk calculation	131
A.9.4 — Risk and risk targets	131
A.9.5 — Limit state verification for fire and explosion events by semi-probabilistic approach	132
A.10 — Guidance on structural systems	132
A.10.1 — Topsides design	132
A.10.2 — Topsides structural design models	132
A.10.2.1 — General	132
A.10.2.2 — Substructure model for topsides design	132
A.10.2.3 — Topsides model for topsides design	133
A.10.2.4 — Modelling for design of equipment and piping supports	133
A.10.3 — Substructure interface	133
A.10.4 — Flare towers, booms, vents, and similar structures	133
A.10.5 — Helicopter landing facilities (helidecks)	133
A.10.5.1 — General	133
A.10.5.2 — Construction	134
A.10.5.3 — Helideck design verification	134
A.10.5.3.1 — Design/assessment situations	134
A.10.5.3.2 — Specific design requirements	134
A.10.5.3.3 — Actions for helicopter landings	134
A.10.5.3.4 — Actions for helicopter at rest	135
A.10.5.3.5 — Actions for empty helideck	135
A.10.5.3.6 — Actions for short duration (post-damage) situations	135
A.10.5.3.7 — Combinations of actions	135
A.10.5.3.8 — Strength and resistance of structural components	135
A.10.5.3.9 — Safety-net arms and framings	135
A.10.5.3.10 — Helicopter tie-down points	135
A.10.5.4 — Reassessment of existing helidecks	135
A.10.6 — Crane support structure and crane boom rest	135
A.10.6.1 — General	135
A.10.6.2 — Design requirements	135
A.10.6.3 — Static design	136
A.10.6.3.1 — Design action types	136
A.10.6.3.2 — Design assessment situations and actions	136
A.10.6.3.3 — In-place operating conditions	136
A.10.6.3.4 — In-place out-of-service conditions	136

ISO/FDIS 19901-3:2023(E)

A.10.6.3.5	Accidental design/assessment situations — Gross overload condition/Crane collapse failure condition	136
A.10.6.4	Fatigue design	136
A.10.6.5	Seismic/Earthquake design	136
A.10.6.6	Dynamic design	136
A.10.6.7	Fabrication	136
A.10.6.8	Crane boom rest design	137
A.10.7	Derrick equipment set	137
A.10.8	Bridges	137
A.10.9	Bridge bearings	137
A.10.10	Anti-vibration mountings for modules and major equipment skids	137
A.10.11	System interface assumptions	137
A.10.12	Fire protection systems	138
A.10.13	Penetrations	138
A.10.14	Difficult-to-inspect areas	138
A.10.15	Drainage	138
A.10.16	Strength reduction due to heat	138
A.10.17	Walkways, laydown areas and equipment maintenance	138
A.10.18	Muster areas and lifeboat stations	138
A.11	Guidance on materials	138
A.11.1	General	138
A.11.2	Carbon steel	138
A.11.3	Stainless steel	139
A.11.4	Aluminium alloys	139
A.11.5	Fibre-reinforced polymers (FRP)	139
A.11.6	Timber	140
A.12	Guidance on fabrication, quality control, quality assurance and documentation	140
A.12.1	Assembly	140
A.12.2	Welding	140
A.12.3	Fabrication inspection	140
A.12.4	Quality control, quality assurance and documentation	141
A.12.5	Corrosion protection	141
A.12.6	In-service inspection, monitoring and maintenance of corrosion control	141
A.13	Guidance on loadout, transportation, and installation	141
A.14	Guidance on in-service inspection and structural integrity management	142
A.14.1	General	142

ISO/FDIS 19901-3:2023(E)

A.14.2 Requirements applying to topsides structures	142
A.14.2.1 Corrosion protection systems	142
A.14.2.2 Critical structures	142
A.14.2.3 Control of hot work (e.g. welding and cutting)	142
A.14.2.4 Accidental events and incidents	142
A.14.2.5 Change control	142
Annex B (informative) Example calculation of correspondence factor	143
B.1 General	143
Table B.1 Data used for example calculation	143
B.2 Design and utilizations to ISO 19902	143
B.2.1 Tension case	143
Table B.2 Design and utilizations to ISO 19902 Tension case	144
B.2.2 Compression case	144
Table B.3 Design and utilizations to ISO 19902 Compression case	144
B.2.3 Bending case	144
Table B.4 Design and utilizations to ISO 19902 Bending case	144
B.2.4 Combined compression and bending	145
Table B.5 Design and utilizations to ISO 19902 Combined compression and bending	145
B.3 Design and utilizations to ANSI/AISC 360-22^(1,2)	145
B.3.1 Tension case	145
Table B.6 Design and utilizations to ANSI/AISC 360-22^(1,2) Tension case	145
B.3.2 Compression case	145
Table B.7 Design and utilizations to ANSI/AISC 360-22^(1,2) Compression case	146
B.3.3 Bending case	146
Table B.8 Design and utilizations to ANSI/AISC 360-22^(1,2) Bending case	146
B.3.4 Combined compression and bending	147
Table B.9 Design and utilizations to ANSI/AISC 360-22^(1,2) Combined compression and bending	147
B.3.5 Derivation of correspondence factor	147
Table B.10 Derivation of correspondence factor	147
Bibliography	148
Foreword	29
Introduction	32
1 Scope	1
2 Normative references	2

3	Terms and definitions	3
4	Symbols and abbreviated terms	5
4.1	Symbols	5
4.2	Abbreviated terms	6
5	Overall requirements	7
5.1	Conceptual design	7
5.2	Codes and standards	7
5.2.1	Limit states and allowable stress philosophies	7
5.2.2	Use of national building standards	8
5.3	Deck elevation	8
5.4	Exposure level	9
5.5	Operational requirements	9
5.5.1	Functional requirements	9
5.5.2	Spillage and containment	9
5.6	Design physical environmental conditions	9
5.7	Critical structure	9
5.8	Assessment of existing topsides structure	10
5.9	Reuse of topsides structure	10
5.10	Repairs, modifications and refurbishment	11
6	Design requirements	11
6.1	General	11
6.2	Design/assessment situations	11
6.3	Material selection	11
6.4	Structural interfaces	11
6.5	Design for serviceability	12
6.5.1	Serviceability limits	12
6.5.2	Vibrations	12
6.5.3	Deflections	13
Table 1 — Serviceability limits for vertical deflections		13
6.6	Design for strength	14
6.7	Design for fatigue	14
Table 2 — Partial damage design factors for topsides structure, γ_{FD}		14
6.8	Robustness	15
6.8.1	General	15
6.8.2	Ductility	15
6.9	Confirmation of execution of design requirements	16
6.10	Corrosion control	16
6.11	Design for fabrication and inspection	17
6.12	Design for loadout, transportation and installation	17
6.13	Design for structural integrity management	17
6.14	Design for decommissioning, removal and disposal	18
6.14.1	General	18
6.14.2	Structural releases	18
6.14.3	Lifting appurtenances	18
6.14.4	Heavy lift and set-down operations	18
7	Actions and analysis methods	18
7.1	General	18
7.2	In-service actions	19
7.3	Action factors	21
7.3.1	Design actions for operational design/assessment situations in still water	21

ISO/FDIS 19901-3:2023(E)

7.3.2	Design actions for operational design/assessment situations with operating environmental actions	21
7.3.3	Design actions for extreme design/assessment situations	22
7.4	Vortex-induced vibrations	22
7.5	Indirect actions and resulting forces (action effects)	22
7.6	Metocean and ice actions	23
7.6.1	Wave, current and ice actions	23
7.6.2	Wind actions	24
7.6.3	Cold regions effects	24
7.7	Seismic actions	25
7.7.1	General	25
7.7.2	Minimum lateral acceleration	25
7.7.3	Equipment and appurtenances	25
7.8	Actions during fabrication, loadout, transportation, and installation	26
7.9	Actions arising from accidental events	26
7.9.1	General	26
Figure 1	— Example hazard curves	28
7.9.2	Structural design for fire hazard	29
7.9.3	Structural design for explosion hazard	29
Table 3	— Drag coefficients for component shapes (1=Flow)	30
Figure 2	— Overpressure time history	32
Figure 3	— Variability in pulse duration versus peak overpressure	33
Figure 4	— Structural interaction between roof, wall, and floor	34
7.9.4	Explosion and fire interaction	35
7.9.5	Cryogenic spill	35
7.9.6	Actions due to vessel collision	35
7.9.7	Actions due to dropped and swinging objects and projectiles	35
7.9.8	Actions due to loss of buoyancy	36
7.9.9	Actions due to topsides acceleration	36
7.10	Other actions	36
7.10.1	Drilling	36
7.10.2	Conductors	38
7.10.3	Risers	38
7.10.4	Caissons	38
7.10.5	Maintenance, mechanical handling and lifting aids	38
7.10.6	Bridge supports	39
8	Strength and resistance of structural components	39
8.1	Correspondence factor K_c	39
Table 4	— Values of correspondence factor K_c	39
8.2	Design of cylindrical tubular sections	40
8.3	Design of non-cylindrical sections	40
8.3.1	Rolled and welded non-circular prismatic members	40
8.3.2	Plate girder	40
8.3.3	Box girder	41
8.3.4	Stiffened plate components and stressed skin structures	41
8.4	Connections	41
8.4.1	General	41
8.4.2	Restraint and shrinkage	41
8.4.3	Bolted connections	41

Table 5 — Connection class - CC	42
Table 6 — Nominal clearance for bolts and pins (allowable additional hole diameter)	43
8.5 Castings and forgings	46
8.6 Design for structural stability	46
9 Limit state verification	47
9.1 Limit state verification approach	47
9.2 Limit state verification for fire and explosion events	48
9.3 Approaches for limit state verification for fire and explosion events	48
9.4 Risk and risk targets	49
Figure 5 — Example risk matrix and example risk curve (based on UK HSE terminology and limits)	52
9.5 Limit state verification for fire and explosion events by semi-probabilistic approach	52
9.5.1 DL limit state verification	52
9.5.2 NC limit state verification	53
9.5.3 Representative values of accidental actions	53
10 Structural systems	53
10.1 Topsides design	53
10.1.1 General	53
10.1.2 Topsides on concrete substructures	54
10.1.3 Topsides on floating structures	54
10.1.4 Equipment supports	54
10.2 Topsides structure design models	54
10.2.1 General	54
10.2.2 Substructure model for topsides design	55
10.2.3 Topsides model for topsides design	56
10.2.4 Modelling for design of equipment and piping supports	56
10.3 Substructure interface	56
10.3.1 Responsibility	56
10.3.2 Strength design	56
10.3.3 Fatigue design	57
10.4 Flare towers, booms, vents and similar structure	57
10.5 Helicopter landing facilities (helidecks)	58
10.5.1 General	58
10.5.2 Construction	58
10.5.3 Helideck design verification	58
Table 7 — Combinations of actions	62
10.5.4 Reassessment of existing helidecks	63
10.6 Crane support structure and crane boom rest	63
10.6.1 General	63
10.6.2 Design requirements	63
10.6.3 Static design	64
10.6.4 Fatigue design	67
10.6.5 Seismic/Earthquake design	68
10.6.6 Dynamic design	68
10.6.7 Fabrication	68
10.6.8 Crane boom rest design	69
10.7 Derrick equipment set	69
10.8 Bridges	70
10.9 Bridge bearings	70
10.10 Anti-vibration mountings for modules and major equipment skids	71