

---

---

**Textile slings — Lifting slings for  
general purpose lifting operations  
made from fibre ropes — High  
modulus polyethylene (HMPE)**

*Élingues textiles — Élingues de levage pour opérations de levage pour  
usage général en cordages en fibres — Polyéthylène à haut module  
(HMPE)*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 18264:2022

<https://standards.iteh.ai/catalog/standards/sist/d1e66f8b-e0cd-42c4-989e-88d230acaf4e/iso-18264-2022>



iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 18264:2022

<https://standards.iteh.ai/catalog/standards/sist/d1e66f8b-e0cd-42c4-989e-88d230acaf4e/iso-18264-2022>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|  |           |
|--|-----------|
| <b>Foreword</b>  | <b>v</b>  |
| <b>Introduction</b>  | <b>vi</b> |
| <b>1 Scope</b>   | <b>1</b>  |
| <b>2 Normative references</b>  | <b>1</b>  |
| <b>3 Terms and definitions</b>   | <b>1</b>  |
| <b>4 Hazards</b>   | <b>8</b>  |
| <b>5 Sling materials and components</b>  | <b>9</b>  |
| 5.1 Fibre ropes  | 9         |
| 5.2 Coatings   | 10        |
| 5.3 Cover (sleeves, jackets)   | 10        |
| 5.4 Mechanical components  | 10        |
| 5.5 Other materials and components   | 10        |
| <b>6 Sling constructions, fabrication and lifting configurations</b>   | <b>11</b> |
| 6.1 Sling constructions  | 11        |
| 6.2 Fabrication  | 11        |
| 6.2.1 Splicing   | 11        |
| 6.2.2 Considerations for connecting hardware and fittings  | 12        |
| 6.2.3 Other requirements for mechanical components   | 13        |
| 6.3 Lifting configurations   | 13        |
| 6.4 Design factor  | 15        |
| 6.5 Working load limit (WLL)   | 16        |
| 6.5.1 Calculation of the working load limit (WLL) of a lifting configuration   | 16        |
| 6.5.2 Calculation of the working load limit (WLL) of a lifting configuration as a consequence of bending losses  | 17        |
| 6.6 Effective work length  | 19        |
| 6.7 Traceability code  | 20        |
| <b>7 Sling verification</b>  | <b>20</b> |
| 7.1 General  | 20        |
| 7.2 Qualification of personnel   | 20        |
| 7.3 Type test of sling constructions   | 20        |
| 7.3.1 General  | 20        |
| 7.3.2 Methodology for testing of MBS   | 21        |
| 7.3.3 Type test to verify the interaction of a sling construction with fittings  | 21        |
| 7.4 Manufacturing tests  | 21        |
| 7.4.1 Visual examination   | 21        |
| 7.4.2 Determination of the effective work length of sling legs   | 21        |
| 7.4.3 Proof testing requirements   | 22        |
| 7.4.4 Breaking force tests   | 22        |
| 7.5 Visual examination   | 23        |
| <b>8 Sling marking</b>   | <b>23</b> |
| 8.1 General  | 23        |
| 8.2 Labelling  | 23        |
| 8.2.1 Information  | 23        |
| 8.2.2 Label colour   | 24        |
| <b>9 Manufacturer's certificate</b>  | <b>24</b> |
| <b>10 Instructions for selection, use, inspection and maintenance</b>  | <b>24</b> |
| <b>Annex A (normative) Instructions for selection, use, inspection and maintenance to be provided by the sling manufacturer or its authorized representative with the HMPE fibre rope slings</b> | <b>25</b> |

|   |           |
|---|-----------|
| <b>Annex B (informative) Suggested content of information to be provided by the manufacturer or its authorized representative with the HMPE fibre rope sling assembly .....</b> | <b>26</b> |
| <b>Bibliography .....</b>   | <b>31</b> |

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 18264:2022  
<https://standards.iteh.ai/catalog/standards/sist/d1e66f8b-e0cd-42c4-989e-88d230acaf4e/iso-18264-2022>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 38, *Textiles*.

This second edition cancels and replaces the first edition (ISO 18264:2016), which has been technically revised.

The main changes are as follows:

- the Scope has been made more concise;
- the Normative references have been updated; some references have been moved to the Bibliography;
- the Terms and definitions have been updated;
- the formulae in [Table 4](#) have been corrected;
- figures and designations have been changed in accordance with ISO/IEC Directives Part 2:2021;
- subclauses [7.3.2](#) and [7.3.3](#) have been rewritten and simplified. References are given to ISO 2377 and ISO 9554 instead of repeating the texts in those standards.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This document has been prepared to be a standard providing one means of complying with the essential safety requirements.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 18264:2022  
<https://standards.iteh.ai/catalog/standards/sist/d1e66f8b-e0cd-42c4-989e-88d230acaf4e/iso-18264-2022>

# Textile slings — Lifting slings for general purpose lifting operations made from fibre ropes — High modulus polyethylene (HMPE)

## 1 Scope

This document specifies the requirements related to safety, including methods of rating and testing sling constructions made from fibre ropes. It is applicable to ropes made of high modulus polyethylene (HMPE) fibre having a minimum reference number of 12 and a maximum reference number of 72.

The fibre rope slings covered by this document are intended for general-purpose lifting operations only, i.e. when used for lifting objects, materials or goods which require no deviations from the requirements, design factors, or work load limits specified.

This document does not cover slings used for the lifting of persons, potentially dangerous materials such as molten metal and acids, glass sheets, fissile materials, nuclear reactors and special (non-routine and engineered) lifting operations. This document can be used as a reference for lifting slings made with HMPE fibres to be used in special lifting operations.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1968, *Fibre ropes and cordage — Vocabulary*

ISO 2262, *General purpose thimbles for use with steel wire ropes — Specification*

ISO 2307, *Fibre ropes — Determination of certain physical and mechanical properties*

ISO 2415, *Forged shackles for general lifting purposes — Dee shackles and bow shackles*

ISO 7500-1, *Metallic materials — Calibration and verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Calibration and verification of the force-measuring system*

ISO 7597, *Forged steel lifting hooks with latch, grade 8*

ISO 8539, *Forged steel lifting components for use with Grade 8 chain*

ISO 9554:2019, *Fibre ropes — General specifications*

ISO 10325, *Fibre ropes — High modulus polyethylene — 8-strand braided ropes, 12-strand braided ropes and covered ropes*

ISO 12100:2010, *Safety of machinery — General principles for design — Risk assessment and risk reduction*

ISO 16798, *Links of Grade 8 for use with slings*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1968 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1

#### **abrasion**

mechanical wearing of a surface resulting from frictional contact with other materials and objects


### 3.2

#### **angle of choke**

$\alpha_{CH}$

angle formed in a sling body as it passes through the choking eye or fittings

Note 1 to entry: See 3.9, Figure 1 and Figure 4.



**Figure 1 — Example of angle of choke**

### 3.3


#### **angle of loading**

$\alpha$

horizontal angle

Note 1 to entry:  $\beta$  vertical angle. See Figure 2.



**Key**

- $\beta$  vertical angle  
 $\alpha$  horizontal angle

**Figure 2 — Example of angle of loading**

<https://standards.iteh.ai/catalog/standards/sist/d1e66f8b-e0cd-42c4-989e-88d230acaf4e/iso-18264-2022>

**3.4****competent person**

designated person, suitably trained and qualified by knowledge and practical experience, and with the necessary instructions to enable the required tests and operations as well as examinations to be carried out

**3.5****design factor**

factor by which the nominal breaking strength of *sling construction* (3.25) is divided to determine its working load limit in straight pull

Note 1 to entry: Also referred to as safety factor (SF).

Note 2 to entry: This term has the same meaning as the term “working coefficient” used in the EU Machinery Directive.

Note 3 to entry: Fittings may have different design factors from that of the fibre ropes to which they are connected.

**3.6****effective work length****EWL**

actual finished length of the fibre rope sling construction, inclusive fittings, from bearing point to bearing point while being loaded to a reference load to be determined and documented by the manufacturer

Note 1 to entry: See *nominal length* (3.19) as well as Figure 6 and Figure 7.

### 3.7

#### **general-purpose lifting operation**

operation identified and described as the one which<sup>[8]</sup> is a repetitive lift covered by a previously prepared JRA and LP, carried out by lifting team trained in the use of specific lifting operation/device and competent to complete the entire operation


Note 1 to entry: Also referred to as routine lifts or lifting operation, and is the opposite of special (non-routine or engineered) lifting operation.

### 3.8

#### **basket hitch**

method of rigging a sling in which the sling is passed around the load and both loop eyes and end fittings are attached to the lifting device

Note 1 to entry: See [Figure 3](#).



**Figure 3 — Example of basket hitch**

### 3.9

#### **choker hitch**

method of rigging a sling in which the sling is passed around the load, then through one loop eye, end fitting, or other piece of hardware, with the other loop eye or end fitting attached to the lifting device

Note 1 to entry: This *hitch* ([3.10](#)) can be done with a sliding choker hook or similar device (see [Figure 4](#)).



Figure 4 — Example of choker hitch

### 3.10 hitch

method of rigging (attaching) one or several slings temporarily to a load, or object, for the purpose of lifting

### 3.11 vertical hitch

method of rigging a sling in which the load is attached to the loop eye or end fitting at one end of the sling and the loop eye or end fitting at the other end is attached to the lifting device

Note 1 to entry: Any *hitch* (3.10) less than 5° from the vertical ( $\beta$  in Figure 2) may be considered a vertical hitch (see Figure 5).



Figure 5 — Example of vertical hitch

### 3.12

#### **intermediate master link**

link used to connect one or two legs of a sling to a *master link* (3.16)

Note 1 to entry: Intermediate links can be assembled with a master link to form a permanent master link.

### 3.13

#### **job risk assessment**

##### **JRA**

process where

- health and safety hazards are identified,
- risks associated with the hazards are analysed and evaluated, and
- appropriate ways to eliminate or control these hazards are determined

Note 1 to entry: In practical terms, a risk assessment is a thorough look at your workplace to identify those things, situations, processes, etc. that can cause harm, particularly to people. After identification is made, the user of the slings evaluates how likely and severe the risk is, and then decides what measures should be in place to effectively prevent or control the harm from happening. The result of this process is documented by the user of the slings in the form of a job risk assessment (JRA).

### 3.14

#### **lifting configuration**

arrangement characterized by the number of sling legs in the lifting assembly, the *angle of loading* (3.3) under which they spread and in which the sling assembly is connecting the suspended load and the lifting mechanism

Note 1 to entry: The lifting configuration is characterized by the number of sling legs in the lifting assembly, the angle of loading under which they spread and in which the sling assembly is connected to the suspended load. As part of the arrangement additional hardware, such as e.g. (intermediate) master links, shackles and spreader bars may be used".

### 3.15

#### **lift plan**

##### **LP**

documented plan of the proposed lifting operation

Note 1 to entry: Lift plan covers aspects such as the following:

- characterization of the load in terms of dimensions, weight and centre of gravity;
- characterization of the task in terms of lifting, rotation, speeds and travel directions;
- evaluation of the hazards to determine consequences resulting from collision, upset or dropping of the suspended load;
- determination of how to rig the load using good rigging practices and ensuring the use of proper rigging techniques during the lift;
- ensuring that the attachment points and suspended load can withstand the forces created by the rigging gear attachment;
- selecting equipment and rigging based on the type, category of lift and minimum capacity of lifting equipment (hoist, crane, slings, lifting fixture, etc.) and on the identified load, task and hazards;
- ensuring that sling angles are considered when determining forces on rigging equipment and the suspended load.

### 3.16

#### **master link**

link forming the upper terminal of a sling or *intermediate master link* (3.12) by means of which the sling is attached to the hook of a crane or other lifting device