



© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: + 41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Space After: 0 pt, Line spacing: single

Formatted: Left: 1.9 cm, Right: 1.9 cm, Bottom: 1 cm, Gutter: 0 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Commented [eXtyles1]: The reference is to a withdrawn standard which has been replaced

ISO 20344, Personal protective equipment — Test methods for footwear

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Indent: Left: 0 cm, Right: 0 cm, Space Before: 0 pt, No page break before, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: French (Switzerland)

Formatted: French (Switzerland)

Formatted: French (Switzerland)

# iTeh Standards (<https://standards.iteh.ai>) Document Preview

ISO/PRF 9211-1

<https://standards.iteh.ai/catalog/standards/sist/670e4cd4-f1f9-41ad-abf0-0eebdf80ee3f/iso-prf-9211-1>

Formatted: FooterPageRomanNumber

Contents

Foreword .....v

Introduction.....vi

Part 1: Vocabulary .....1

1 Scope .....1

2 Normative references .....1

3 Terms and definitions.....1

3.1 Basic terms and definitions .....2

3.1.1 General terms .....2

3.1.2 Terms for optical properties of a coated surface.....2

3.1.3 Terms for polarization .....5

3.1.4 Phase related terms .....7

3.2 Designations of coatings by principal function .....8

3.2.1 Reflecting function.....8

3.2.2 Antireflecting function .....8

3.2.3 Beam splitting function.....8

3.2.4 Attenuating function .....8

3.2.5 Bandpass or band rejection filtering function.....8

3.2.6 Selecting or combining function .....9

3.2.7 Polarizing function .....9

3.2.8 Phase changing function.....9

3.2.9 Absorbing function .....9

3.2.10 Supplementary function .....10

3.3 Terms related to common coating imperfections .....11

3.3.1 Point-like imperfections.....11

3.3.2 Line-like imperfections.....11

3.3.3 Area-like imperfections .....12

3.3.4 Volume-like imperfections .....12

Annex A (informative) Micrographs of common types of coating imperfections .....14

Bibliography .....23

Foreword — 4

Introduction — 5

1 — Scope — 1

2 — Normative references — 1

3 — Terms and definitions — 1

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

**ISO/PRF 9211-1:2023(E)**

3.1 Basic terms and definitions 1  
3.1.1 General terms 1  
3.1.2 Terms for optical properties of a coated surface 2  
3.1.3 Terms for polarization 5  
3.1.4 Phase related terms 6  
3.2 Designations of coatings by principal function 7  
3.2.1 Reflecting function 7  
3.2.2 Antireflecting function 7  
3.2.3 Beam splitting function 7  
3.2.4 Attenuating function 7  
3.2.5 Bandpass or band rejection filtering function 7  
3.2.6 Selecting or combining function 8  
3.2.7 Polarizing function 8  
3.2.8 Phase changing function 8  
3.2.9 Absorbing function 8  
3.2.10 Supplementary function 8  
3.3 Terms related to common coating imperfections 10  
3.3.1 Point like imperfections 10  
3.3.2 Line like imperfections 10  
3.3.3 Area like imperfections 11  
3.3.4 Volume like imperfections 11  
Annex A (informative) Micrographs of common types of coating imperfections 12  
Bibliography 14

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Space After: 0 pt, Line spacing: single

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO/PRF 9211-1

<https://standards.iteh.ai/catalog/standards/sist/670e4cd4-f1f9-41ad-abf0-0cebdf80ee3f/iso-prf-9211-1>

Formatted: FooterPageRomanNumber

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 172, *Optics and photonic*, Subcommittee SC 3, *Optical materials and components*.

This fourth edition cancels and replaces the third edition (ISO 9211-1:2018), which has been technically revised.

The main changes are as follows:

- — addition of the definition of spectral optical density;
- — explanations of subscript for spectral average;
- — explanations of average transmittance, reflectance, absorptance, and optical density over wavelength or wave number.

A list of all parts in the ISO 9211 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font - 1

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Commented [eXtyles2]: Invalid reference: "ISO 9211 series"

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

## Introduction

The optical properties of a coated surface are characterized by spectrophotometric values. These values relate to the energy transported by electromagnetic waves (radiant or luminous) and they vary as a function of the wavelength, the angle of incidence, and the state of polarization. Additional influences can be caused by scattering.

NOTE 1 The functional spectral dependency is generally indicated by including the wavelength,  $(\lambda)$ , in parentheses as part of the symbol.

NOTE 2 The wavelength ( $\lambda$ ) can be replaced by the wavenumber ( $\sigma$ ) or the photon energy ( $h\nu$ ).  $h$  = Planck constant;  $\nu$  = frequency. The units recommended are the nanometre (nm) or the micrometre ( $\mu\text{m}$ ) for the wavelength, the reciprocal centimetre ( $\text{cm}^{-1}$ ) for the wavenumber and the electron volt (eV) for the photon energy.

When a coating is used at an angle of incidence different from zero, its characteristics depend upon the state of polarization of the incident radiation and it can influence the polarization state of the emergent radiation. It might then be necessary to indicate the orientation of the electric field vector in relation to the plane of incidence.

The coatings are defined according to their function, i.e. according to the nature of the principal modification to the surface properties that they realize. A coating intended to realize a principal function as defined in Table 1 can also include one or more secondary functions. Their relative importance with regard to the principal function may be indicated.

A surface for visual applications can be characterized by colorimetric parameters. These depend on the reference illumination source, the reference observer, and the optical properties of the surface. Colorimetric parameters are not part of this standard.

Examples of coating imperfections are given in Annex A. Test methods for the surface imperfections are described in ISO 14997.

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Space After: 0 pt, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: FooterPageRomanNumber

# Optics and photonics — Optical coatings

## Part 1 Vocabulary

**WARNING** — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

### 1 Scope

This document defines terms relevant to optical coatings. These terms are grouped in four classes: Terms and definitions, definition of coatings by function, definitions of common coating imperfections and other definitions.

This document identifies surface treatments of components and substrates excluding ophthalmic optics (spectacles) by the application of optical coatings and gives a standard form for their specification. It defines the general characteristics and the test and measurement methods whenever necessary, but is not intended to define the process method.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

<std>ISO 11145, Optics and photonics — Lasers and laser-related equipment — Vocabulary and symbols</std>

<std>ISO 80000-7, Quantities and units — Part 7: Light and radiation</std>

ISO 80000-7, Quantities and units — Part 7: Light and radiation

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11145 and ISO 80000-7 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

Formatted: Left: 1.9 cm, Right: 1.9 cm, Bottom: 1 cm, Gutter: 0 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Formatted: Main Title 2, Space After: 0 pt, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

### 3.1 Basic terms and definitions

#### 3.1.1 General terms

##### 3.1.1.1

##### surface treatment of components and substrates

application of a coating of material(s) intended to modify the optical, physical or chemical characteristics originally possessed by the surface of a component

Note\_1-to\_entry: The substrates are considered to be geometrically perfect and optically homogeneous. In reality, an assembly made up of a substrate and a coating is identified and measured experimentally as an entity.

##### 3.1.1.2

##### incident medium

medium from which the electromagnetic radiation enters a coating

##### 3.1.1.3

##### emergent medium

medium into which the electromagnetic radiation exits a coating

Note\_1-to\_entry: Besides acting as mechanical support, the substrate carrying the coating physically can constitute the incident medium and/or the emergent medium.

##### 3.1.1.4

##### clear aperture

##### effective aperture

surface area to meet specifications

##### 3.1.1.5

##### rim

surface area outside of the clear aperture

##### 3.1.1.6

##### witness sample

sample that represents the actual coated component used for spectral and environmental testing

Note\_1-to\_entry: The details of witness samples and measurements (e.g. material, surface texture, dimensions, number per batch, position in the coating chamber, etc.) is subject to agreement between manufacturer and customer.

#### 3.1.2 Terms for optical properties of a coated surface

##### 3.1.2.1

##### spectral transmittance

##### $\tau(\lambda)$

ratio of the spectral radiant or luminous flux transmitted to that of the incident radiant or luminous flux

Note\_1-to\_entry: Spectral transmittance is related to spectral optical density  $D(\lambda)$  by the formula:  $\tau(\lambda) = 10^{-D(\lambda)}$ .

Note\_2-to\_entry: Wherever the Greek letter  $\tau$  is mistakable  $T(\lambda)$  may be used.

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Space After: 0 pt, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Regular Italic, Font: Bold, Not Italic

Formatted: Regular, Font: Bold

Formatted: Regular Italic, Font: Bold, Not Italic

Formatted: Regular, Font: Bold

Formatted: Superscript, Not Raised by / Lowered by

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: FooterPageRomanNumber



3.1.2.2

average spectral transmittance over wavelength

$$\tau_{ave}(\lambda_1 \text{ to } \lambda_2)$$

$$\tau_{ave}(\lambda_1 \text{ to } \lambda_2)$$

average of the spectral transmittance over a specified wavelength range

$$\tau_{ave}(\lambda_1 \text{ to } \lambda_2) = \frac{\int_{\lambda_1}^{\lambda_2} \tau(\lambda) d\lambda}{\lambda_2 - \lambda_1} \approx \frac{\sum_{i=1}^m \tau(\lambda_i) \Delta\lambda}{\lambda_2 - \lambda_1} = \frac{\sum_{i=1}^m \tau(\lambda_i)}{m}$$

$$\tau_{ave}(\lambda_1 \text{ to } \lambda_2) = \frac{\int_{\lambda_1}^{\lambda_2} \tau(\lambda) d\lambda}{\lambda_2 - \lambda_1} \approx \frac{\sum_{i=1}^m \tau(\lambda_i) \Delta\lambda}{\lambda_2 - \lambda_1} = \frac{\sum_{i=1}^m \tau(\lambda_i)}{m}$$

where

$$\Delta\lambda = \frac{\lambda_2 - \lambda_1}{m}$$

$$\Delta\lambda = \frac{\lambda_2 - \lambda_1}{m}$$

Note\_1\_to\_entry: The average spectral transmittance over wavelength has a different value than the average transmittance over wavenumber even if the range of wavelength is equivalent to the range of wavenumber.

Note\_2\_to\_entry: The range of wavelength and units ( $\lambda_1$  to  $\lambda_2$ ) ( $\lambda_1$  to  $\lambda_2$ ) may be given.

Note\_3\_to\_entry: The index "avg" may be used instead of "ave".

3.1.2.3

average spectral transmittance over wavenumber

$$\tau_{ave}(\sigma_1 \text{ to } \sigma_2)$$

$$\tau_{ave}(\sigma_1 \text{ to } \sigma_2)$$

average of the spectral transmittance over a specified wavenumber range

$$\tau_{ave}(\sigma_1 \text{ to } \sigma_2) = \frac{\int_{\sigma_1}^{\sigma_2} \tau(\sigma) d\sigma}{\sigma_2 - \sigma_1} \approx \frac{\sum_{i=1}^m \tau(\sigma_i) \Delta\sigma}{\sigma_2 - \sigma_1} = \frac{\sum_{i=1}^m \tau(\sigma_i)}{m}$$

$$\tau_{ave}(\sigma_1 \text{ to } \sigma_2) = \frac{\int_{\sigma_1}^{\sigma_2} \tau(\sigma) d\sigma}{\sigma_2 - \sigma_1} \approx \frac{\sum_{i=1}^m \tau(\sigma_i) \Delta\sigma}{\sigma_2 - \sigma_1} = \frac{\sum_{i=1}^m \tau(\sigma_i)}{m}$$

where

$$\Delta\sigma = \frac{\sigma_2 - \sigma_1}{m}$$

$$\Delta\sigma = \frac{\sigma_2 - \sigma_1}{m}$$

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

Note\_1\_to entry: The average spectral transmittance over wavelength has a different value than the average transmittance over wavenumber even if the range of wavelength is equivalent to the range of wavenumber.

Note\_2\_to entry: The average spectral transmittance over wavenumber is used mainly for large ranges, i.e. broadband filters in the Infrared.

Note\_3\_to entry: The range of wavenumber and units ( $\sigma_1$  to  $\sigma_2$ ) ( $\sigma_1$  to  $\sigma_2$ ) may be given.

Note\_4\_to entry: The index "avg" may be used instead of "ave".

### 3.1.2.4 spectral reflectance

$\rho(\lambda)$   
ratio of the spectral radiant or luminous flux reflected to that of the incident radiant or luminous flux

Note\_1\_to entry: Wherever the Greek letter  $\rho$  is mistakable  $R(\lambda)$  may be used.

Note\_2\_to entry: Average spectral reflectance over wavenumber or over wavelength can be calculated in the same manner as that shown for spectral transmittance.

### 3.1.2.5 spectral absorbance

$\alpha(\lambda)$   
ratio of the spectral radiant or luminous flux absorbed to that of the incident radiant or luminous flux

Note\_1\_to entry: Wherever the Greek letter  $\alpha$  is mistakable  $A(\lambda)$  may be used.

Note\_2\_to entry: The quantities defined in 3.1.2.1, 3.1.2.4, 3.1.2.1, 3.1.2.4 and 3.1.2.5, 3.1.2.5 are interrelated as follows:

$$1 = \tau(\lambda) + \rho(\lambda) + \alpha(\lambda)$$

$$1 = \tau(\lambda) + \rho(\lambda) + \alpha(\lambda)$$

with <https://standards.iteh.ai/catalog/standards/sist/670e4cd4-f1f9-41ad-abf0-...>

$$\tau(\lambda) = \tau_r(\lambda) + \tau_d(\lambda)$$

$$\rho(\lambda) = \rho_r(\lambda) + \rho_d(\lambda)$$

$$\tau(\lambda) = \tau_r(\lambda) + \tau_d(\lambda)$$

$$\rho(\lambda) = \rho_r(\lambda) + \rho_d(\lambda)$$

where

$\tau_r(\lambda)$  is the specular spectral transmittance (regular);

$\rho_r(\lambda)$  is the specular spectral reflectance (regular);

$\tau_d(\lambda)$  is the diffuse spectral transmittance (scattered);

$\rho_d(\lambda)$  is the diffuse spectral reflectance (scattered).

Formatted: Font: 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Space After: 0 pt, Line spacing: single

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Regular Italic, Font: Bold, Not Italic

Formatted: Regular, Font: Bold

Formatted: Regular Italic, Font: Bold, Not Italic

Formatted: Regular, Font: Bold

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Regular Italic, Font: Bold, Not Italic

Formatted: Regular, Font: Bold

Formatted: Regular Italic, Font: Bold, Not Italic

Formatted: Regular, Font: Bold

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Default Paragraph Font

Formatted

Formatted

Formatted: Subscript, Not Raised by / Lowered by

Formatted

Formatted Table

Formatted: Subscript, Not Raised by / Lowered by

Formatted

Formatted: Subscript, Not Raised by / Lowered by

Formatted

Formatted: Subscript, Not Raised by / Lowered by

Formatted

Formatted: FooterPageRomanNumber