
INTERNATIONAL STANDARD



3149

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Radiators, convectors and similar appliances — Determination of thermal output — Test method using liquid-cooled closed booth

Radiateurs, convecteurs et appareils similaires — Détermination de la puissance thermique — Méthode d'essai en chambre fermée à refroidissement par liquide

First edition — 1975-07-01

[ISO 3149:1975](https://standards.iteh.ai/catalog/standards/sist/0d81e072-14f3-4f16-b79c-289063044438/iso-3149-1975)

<https://standards.iteh.ai/catalog/standards/sist/0d81e072-14f3-4f16-b79c-289063044438/iso-3149-1975>



UDC 697.358

Ref. No. ISO 3149-1975 (E)

Descriptors : heaters, heat radiators, tests, measurement, thermal output, liquid cooling.

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3149 was drawn up by Technical Committee ISO/TC 116, *Space-heating appliances*, and circulated to the Member Bodies in September 1973.

It has been approved by the Member Bodies of the following countries :

Australia	France	South Africa, Rep. of
Belgium	Germany	Thailand
Bulgaria	Ireland	Turkey
Canada	Italy	United Kingdom
Czechoslovakia	Netherlands	Yugoslavia
Denmark	Norway	
Egypt, Arab Rep. of	Romania	

No Member Body expressed disapproval of the document.

Radiators, convectors and similar appliances — Determination of thermal output — Test method using liquid-cooled closed booth

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies a method for the determination of the thermal output of radiators, convectors and similar appliances, using a closed booth with walls, ceiling and floor cooled by water or another liquid.

Radiators are heating bodies which emit heat partly by radiation. Convectors, on the contrary, emit heat almost wholly by natural convection.

2 REFERENCES

ISO 3147, *Heat exchangers — Verification of thermal balance of water-fed or steam-fed primary circuits — Principles and test requirements.*

ISO 3150, *Radiators, convectors and similar appliances — Calculation of thermal output and presentation of results.*

<https://standards.iteh.ai/catalog/standards/sist/0d81e072-14f3-4f16-b79c-289063044438/iso-3149-1975>

3 TEST INSTALLATION

The tests shall be carried out in an installation containing the following equipment :

- a test booth, the walls, ceiling and floor of which can be cooled by circulating water or possibly another liquid;
- apparatus for cooling the water or other liquid circulating in the walls, ceiling and floor;
- a primary heating fluid circuit feeding the appliance under test (see ISO 3147);
- measuring and checking instruments.

3.1 Test booth

3.1.1 Dimensions

The test booth shall have the following internal dimensions :

floor : $4 \pm 0,2$ m X $4 \pm 0,2$ m

height : $2,8 \pm 0,2$ m

However, the following dimensions are permitted for existing booths :

floor : 3,5 to 4,2 m X 3,9 to 5 m

height : 2,6 to 3 m

3.1.2 Construction

The walls, ceiling and floor of the test booth shall be cooled with water or another liquid in such a way that the inner surface temperature is reasonably uniform (for example, by means of panels having multi-pass or single-pass water tubes).

The inner surfaces of the test booth shall be covered with paint without metallic pigment.

The inner surface of the wall against which the heating appliance under test is placed shall be covered over its entire width and up to a height of 1,25 m above the floor with an insulating panel having a heat resistance of not less than $0,05 \text{ m}^2 \cdot \text{K/W} \pm 10 \%$ from the outer surface of the panel to the corresponding water-cooled wall. The thickness of the insulating panel is to be approximately 6 mm. If the outer surface of the panel is painted, paint without metallic pigment shall be used.

To ensure the reasonably uniform cooling of the surfaces, as specified above, it is advisable to establish a total flow of cooling water for all the surfaces corresponding to a heat transfer of at least 6 900 W for a temperature rise of 1°C .

The water flow in each single wall shall be controllable.

3.1.3 Calibration

To facilitate the initial setting of the temperature of the liquid at the inlet of the cooling pipe system, a definitive calibration shall be made before the booth is used permanently for testing. The results of the calibration shall show the value of the temperature of the inlet liquid as a function of appliance heat output. The calibration shall be made in such a way that an air temperature of 20°C at the reference point of the booth is obtained.

3.2 Measurements in the booth

3.2.1 Air temperature measurement

Temperatures shall be measured as indicated below, to within $\pm 0,2^\circ \text{C}$ (with the exception of that of the reference position, which shall be measured to within $\pm 0,1^\circ \text{C}$).

3.2.1.1 On the vertical axis of the booth

- at the reference point 0,75 m from the floor;

- b) at four points :
- 0,05 m from the floor;
 - 0,50 m from the floor;
 - 1,50 m from the floor;
 - 0,05 m from the ceiling.

3.2.1.2 On four verticals at 1 m from each of two adjoining walls

At eight points (two on each vertical) :

- 0,75 m from the floor;
- 1,50 m from the floor.

3.2.2 *Temperature measurements on the internal faces*

The temperatures shall be measured to within $\pm 0,2^\circ\text{C}$:

- a) at six points, at the centres of the six inner faces of the enclosure;
- b) at a point on the vertical centre line of the inner face of the wall against which the appliance under test is placed :
- 0,30 m from the floor.

3.2.3 *Other measurements*

- a) Relative humidity of the air within the test booth.
- b) Temperature of the liquid entering the cooling circuit, to within $\pm 0,2^\circ\text{C}$.
- c) Barometric pressure, to within $\pm 0,1\text{ kPa}$ ($\pm 1\text{ mbar}$).

4 PROCEDURE

The tests shall be carried out in the closed booth with six cooled surfaces, steady-state conditions being recorded by the logging of temperatures as indicated below.

4.1 *Preparation and installation of appliances*

Tests may be carried out only on appliances with characteristics lying within the following ranges :

- a) an output per unit volume of the test booth of less than 87 W/m^3 ;
- b) a total output of not less than 700 W ;
- c) a length of not less than $0,5\text{ m}$;
- d) in the case of a sectional appliance, the number of sections in the unit tested is, if possible, not less than 10.

Unless other conditions are specified by the maker, the appliance shall be installed in the following reference conditions :

- e) the appliance shall be placed parallel to, and symmetrically about the centre line of, one of the walls of the booth;

f) the gap between the rear of the nearest heat-emitting surface of the appliance and the wall against which it is placed shall be $0,05 \pm 0,005\text{ m}$;

g) the gap between the floor and the bottom of the appliance shall be between $0,10\text{ m}$ and $0,12\text{ m}$;

h) the appliance under test shall be connected with the flow connection at the top of one end and the return connection at the bottom of the opposite end, except when otherwise specified by the manufacturer;

j) a uniform coating of paint shall be applied to all external surfaces; paints with metallic pigments are not to be used.

NOTE – Requirement j) does not apply to convectors.

The appliance shall be supported and fixed in the normal way with the components normally provided by the manufacturer. Alternatively, fixings are to be such that they will not affect the output of the appliance.

Connecting pipes shall be fixed with a slope of $0,5\%$ and suitable air vents shall be provided in the primary fluid circuit to ensure a normal circulation without air locks.

4.2 *Steady-state conditions*

Steady-state conditions shall be maintained throughout the duration of the test and shall have been established before the start of the test, so far as both the primary fluid circuit and the ambient conditions in the test booth are concerned.

Steady-state conditions are deemed to have been established and maintained throughout the duration of the test (as defined in 4.4.1 and 4.4.2) when the values of the temperatures measured at not less than six equal intervals during the test do not exceed the limits specified in 4.2.1 and 4.2.2.

4.2.1 *Primary circuit*

See ISO 3147.

4.2.2 *Test booth*

Temperatures measured	Maximum deviation from mean value $^\circ\text{C}$
Temperatures at the centres of the inner faces	$\pm 0,3$
Temperature on the inner surface of the wall against which the appliance is placed	$\pm 0,5$
Air temperature at the reference point	$\pm 0,1$

4.3 *Preparation for test*

The appliance having been placed in position (see 4.1), the test rig shall be preheated and adjusted to give the test conditions required.

During this preparatory period, temperatures shall be recorded and the setting of the heating and cooling rates shall be adjusted until steady-state conditions have been established in both the primary heating circuit and the test booth, as defined in 4.2.

4.4 Performance of tests

See ISO 3147.

For each test, temperatures shall be recorded, to confirm that stable conditions exist.

4.4.1 Tests with low pressure hot water or superheated water

Carry out at least three tests with any three successive values of the following mean temperatures of the primary fluid in the appliance :

$50 \pm 5^\circ\text{C}$

$65 \pm 5^\circ\text{C}$

$80 \pm 3^\circ\text{C}$

$100 \pm 10^\circ\text{C}$

$140 \pm 15^\circ\text{C}$

The tests shall be carried out with the same flow of water, to within $\pm 2\%$, such that the temperature drop lies in the range $20 \pm 2^\circ\text{C}$ for radiators and $10 \pm 2^\circ\text{C}$ for convectors and skirting heating units, when the mean water temperature is approximately 80°C .

When so required by the manufacturer, convectors and skirting heating units can be tested at the same mean temperature but at higher primary fluid flows, such as

250 to 300 kg/h, or

500 to 600 kg/h

Each test, lasting not less than 1 h, shall consist of the recording, at equal intervals not exceeding 10 min, of all the required measurements for the primary and secondary circuits : temperatures, pressures and flow or energy input.

After confirmation of the validity of the tests (maintenance of steady-state conditions), the mean values shall be used for calculation of the thermal balance and the presentation of the test results, as laid down in ISO 3147 and ISO 3150.

4.4.2 Tests with steam

Carry out one or three tests for one or three successive pressures from the range:

5 kPa (0,05 bar)

20 kPa (0,2 bar)

100 kPa (1 bar)

400 kPa (4 bar)

800 kPa (8 bar)

within limits of $\pm 10\%$ of the absolute pressure used.

Each test, lasting not less than 1 h, shall consist of the recording, at equal intervals not exceeding 10 min, of all the required measurements of the primary and secondary circuits : temperatures, pressures and flow or energy input.

After confirmation of the validity of the tests (maintenance of steady-state conditions), the mean values shall be used for calculation of the thermal balance and the presentation of the test results as laid down in ISO 3147 and ISO 3150.

5 PRESENTATION OF TEST RESULTS

See ISO 3150.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

ISO 3149:1975

<https://standards.iteh.ai/catalog/standards/sist/0d81e072-14f3-4f16-b79c-289063044438/iso-3149-1975>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

ISO 3149:1975

<https://standards.iteh.ai/catalog/standards/sist/0d81e072-14f3-4f16-b79c-289063044438/iso-3149-1975>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

ISO 3149:1975

<https://standards.iteh.ai/catalog/standards/sist/0d81e072-14f3-4f16-b79c-289063044438/iso-3149-1975>