ISO/FDIS 12625-16:2023(E)

ISO/TC 6/SC 2

Secretariat:-SIS

Date: 2023-12-022024-xx

Tissue paper and tissue products —

Part-16:

Determination of optical properties — Opacity (paper backing) — Diffuse reflectance method for opacity (paper backing)

Papier tissue et produits tissue —

Partie 16: Détermination des propriétés optiques — Méthode par réflectance diffuse de l'opacité sur fond papier

(https://standards.iteh Document Preview

ps://standards.itch.eFDIS.stage4db4-dacd-4bef-963a

Style Definition	
Style Definition	

Style Definition
Style Definition
Style Definition

ISO/FDIS 12625-16:2023(E2024(en))

© ISO 20232024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11 EmailE-mail; copyright@iso.org

Website: www.iso.orgwww.iso.org

Published in Switzerland

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Right: 1.5 cm, Bottom: 1 cm, Gutter: 0 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Commented [eXtyles1]: The reference is to a withdrawn standard which has been replaced

ISO 20344, Personal protective equipment — Test methods for footwear

Formatted: Default Paragraph Font

Formatted: French (France)

Formatted: French (France)

Formatted: French (France)

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 12625-16

https://standards.iteh.ai/catalog/standards/iso/08d04db4-daed-4bet-963a-e5ca958c174t/iso-tdis-12625-16

© ISO 2023 All rights reserved

/

Formatted: FooterPageRomanNumber

Formatted: Font: 11 pt, Bold Formatted: Font: Bold **Contents** Formatted: HeaderCentered, Left Foreword..... Introduction..... Normative references..... Terms and definitions Apparatus..... 5.1 Reflectometer..... 5.2 Reference standards..... 5.3 Working standards..... 5.4 Black cavity 6 Sampling..... Conditioning..... Preparation of test pieces Procedure 10 Calculation..... Annex A (informative) Spectral characteristics of reflectometers for measuring luminous factor Annex B (normative) Precision..... Bibliography Foreword 3 Introduction 1/4 tandards.iteh.ai/catalog/standards/iso/08d04db4-daed-4bef-963a-ef-ca958c174f/iso-fdis-12625-16 Scope 4 Normative references 4 Terms and definitions 5 Principle 6 5 Apparatus 6 5.1 Reflectometer 6 5.2 Reference standards 6 5.3 Working standards 7 5.4 Black cavity 7 6 Sampling 7 Conditioning 7 —Preparation of test pieces Formatted: FooterPageRomanNumber © ISO 2023 All rights reserved iii

Formatted: Font: 11 pt, Bold

ISO/FDIS 12625-16:2023(E2024(en))

© ISO 2024 – All rights reserved
iii

ISO/FDIS 12625-16:2023(E2024(en))

 9
 Procedure
 7

 10
 Calculation
 8

 11
 Test report
 8

Annex A (normative) Spectral characteristics of reflectometers for measuring luminous factor 10

Annex B (informative) Precision 14

Bibliography 16

i₩

Formatted: Font: 11 pt, Bold
Formatted: Font: 11 pt, Bold
Formatted: Font: Bold
Formatted: HeaderCentered

Formatted: FooterPageRomanNumber

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 12625-16

https://standards.iteh.ai/catalog/standards/iso/08d04db4-daed-4bet-963a-e5ca958c174t/iso-tdis-12625-16

© ISO 2023 All rights reserved

© ISO 2024 - All rights reserved

iv

ISO/FDIS 12625-16:2023(E2024(en))

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents.www.iso.org/patents.. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 6, *Paper, board and pulps*, Subcommittee SC 2, *Test methods and quality specifications for paper and board,* in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 172, *Pulp, paper and board,* in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 12625-16:2015), which has been technically revised.

The main changes are as follows:

—Information has been added to Annex Annex Annex Information for instruments with bandpass correction;
 Table A.2 Table A.2 provides weighting functions needed for calculations related to instruments with bandpass correction.

A list of all parts in the ISO 12625 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. complete listing of these bodies can be found at www.iso.org/members.html.

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered, Left

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: English (United Kingdom)

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Commented [eXtyles2]: Invalid reference: "ISO 12625

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

© ISO 2023 – All rights reserved

© ISO 2024 - All rights reserved

v

JSO/FDIS 12625-16:2023(E2024(en)

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold
Formatted: HeaderCentered

Introduction

Optical measurements are affected by the geometry of the instruments used and by the texture of the material.

The optical properties are related to the visual appearance of the material. Although optical properties are intrinsic properties of tissue paper, they are not functional properties.

The opacity value depends on the principle used for its evaluation, and a method should be chosen which most closely relates to the interpretation to be placed upon the results. The method described in this document is applicable when it is desired to measure that property of a tissue paper or tissue product which governs the extent to which one sheet visually obscures print on underlying sheets. It should not be confused with methods based on the reduction in a standard contrast by interposition of the paper opacity (white backing), formerly known as contrast ratio, nor with the assessment of the amount and condition of light penetrating a sheet (transparency or translucency).

The calculation of opacity requires luminance-factor data obtained by measurement under specified conditions. The luminance factor depends on the conditions of measurement, and particularly on the spectral and geometric characteristics of the instrument used for its determination.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 12625-16

https://standards.iteh.ai/catalog/standards/iso/08d04db4-daed-4bet-963a-e5ca958c1/4t/iso-tdis-12625-16

s reserved

Formatted: FooterPageRomanNumber

νi

© ISO 2024 – All rights reserved

Tissue paper and tissue products — Part 16: Determination of optical properties — Opacity (paper backing) — Diffuse reflectance method

<u> Part 16:</u>

<u>Determination of optical properties — Diffuse reflectance method for opacity (paper backing)</u>

1 Scope

This document specifies the testing procedures for the instrumental determination of the opacity of tissue paper or tissue products by diffuse reflectance using a paper backing.

This document contains specific instructions for the preparation of test pieces of single-ply and multi-ply products, where special preparation/procedures might be necessary.

It can be used to determine the opacity of tissue paper and tissue products containing fluorescent whitening agents, provided the UV content of the radiation incident on the test piece has been adjusted to conform to that in the CIE illuminant C using a fluorescent reference standard provided by an authorized laboratory as described in ISO 2470-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

<std>ISO 186, Paper and board Sampling to determine average quality</std>

<std>ISO 186, Paper and board — Sampling to determine average quality

JSO_187, Paper, board and pulps — Standard atmosphere for conditioning and testing and procedure for monitoring the atmosphere and conditioning of samples </std>

<std>ISO 2469, Paper, board and pulps Measurement of diffuse radiance factor (diffuse reflectance factor)</sd>

<std>ISO 2470-ISO 2469, Paper, board and pulps — Measurement of diffuse radiance factor (diffuse reflectance factor)

ISO 2470-1, Paper, board and pulps — Measurement of diffuse blue reflectance factor — Part 1: Indoor daylight conditions (ISO brightness)</br>

<std>ISO 4094, Paper, board and pulps — General requirements for the competence of laboratories authorized for the issue of optical reference transfer standards of level 3

<std>ISO/CIE 11664-1, Colorimetry — Part 1: CIE standard colorimetric observers</std>

<std>ISO/CIE 11664 2, Colorimetry Part 2: CIE standard illuminants</std>

Formatted: Right: 1.5 cm, Bottom: 1 cm, Gutter: 0 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font
Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Commented [eXtyles3]: ISO 2469: current stage is 50.00

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Commented [eXtyles4]: eXtyles Inline Standards Citation Match reports that the normative reference "ISO/CIE 11664-2" is not cited in the text.

ISO/FDIS 12625-16: 2023(E2024(en)		

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ——ISO Online browsing platform: available at https://www.iso.org/obp
- ——IEC Electropedia: available at https://www.electropedia.org/

3.1

reflectance factor

ratio of the radiation reflected by a surface element of a body in the direction delimited by a given cone with its apex at the surface element to that reflected by the perfect reflecting diffuser under the same conditions of illumination

Note 1-to entry:-The ratio is often expressed as a percentage.

Note 2-to entry:-This term may be used only when it is known that the test material exhibits no luminescence (fluorescence).

[SOURCE: ISO 2469:2014, 3.4]

Note 3_to entry:_The reflectance factor is influenced by the backing if the body is translucent.

[SOURCE: ISO 5631-1:2022, 2469:—, 3.4, modified — Note 3] to entry deleted.]

3.2

luminance factor (C)

luminous reflectance factor

Y(C/2°)-value

reflectance factor (3.1)(3.1) or radiance factor defined with reference to the CIE illuminant C and the visual efficiency function $V(\lambda)$

Note 1-to entry:-The visual efficiency function describes the sensitivity of the eye to light, so that the luminance factor (C) corresponds to the attribute of visual perception of the reflecting surface.

Note 2-to entry:-For computational purposes, the function is identical with the CIE 1931 colour-matching function $\frac{-}{y}$ $\{\bar{y}(\lambda).$

[SOURCE: ISO 2471:2008, 3.2]

Formatted Formatted **Formatted Formatted Formatted Formatted** [... **Formatted** Formatted **Formatted Formatted Formatted Formatted** <u>...</u> **Formatted Formatted** [... **Formatted** Commented [eXtyles5]: The term "luminous reflectance"... **Formatted Formatted** Commented [eXtyles6]: The term "Y(C/2°)-value" has r ... **Formatted Formatted** Formatted <u>...</u> **Formatted** Formatted **Formatted Formatted Formatted** Commented [eXtyles7]: The term "Ry" has not been use ... **Formatted** Formatted **Formatted** Formatted Formatted Formatted Formatted Formatted **Formatted Formatted**

Formatted Formatted Formatted

Formatted

© ISO 2023 All rights reserved

2

JSO/FDIS 12625-16: 2023(E 2024(en))	1	Formatted: Font: 11 pt, Bold		
		Formatted		
3.3		Formatted: HeaderCentered, Left		
single-sheet luminance factor (C)		Commented [eXtyles8]: The term "single-she factor (C)" is used only in terms and definitions s		
luminance factor (C) (3.2)(3.2) of a single sheet of paper with a black cavity as backing	-	Formatted		
[SOURCE: ISO 2471;2008, 3.3, modified — The symbol has been changed.]		Formatted: Line spacing: At least 11.5 pt, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 1.7 cm		
intrinsic luminance factor (C)		Formatted		
$R\mathbf{y}_{\mathbf{x}^{\omega}}$ luminance factor-(C) (3.2)(3.2) of a layer or pad of material thick enough to be opaque, i.e. such that increasing the thickness of the pad by doubling the number of sheets results in no change in the measured reflectance.		Formatted: Adjust space between Latin and Adjust space between Asian text and numbe		
factor (3.1)(3.1)		Commented [eXtyles9]: The term "intrinsic la factor (C)" is used only in terms and definitions s		
[SOURCE: JSO 2471;2008, 3.4, modified — The symbol has been changed.]	`	Formatted		
2.5		Formatted		
3.5 opacity <paper backing=""> ratio of the single-sheet luminance factor (C) (3.3), (3.3),</paper>		Commented [eXtyles10]: The term "opacity backing>" has not been used anywhere in this Formatted: Adjust space between Latin and	document	
Note 1-to-entry:-Opacity is expressed as a percentage.	_	Adjust space between Asian text and number	rs	
[SOURCE: JSO 2471;2008, 3.5] 4 Principle		Formatted: Adjust space between Latin and Adjust space between Asian text and numbe stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm	rs, Tab 2.8 cm +	
T Timespie		Formatted		
The luminance factor of a single sheet of the tissue paper or tissue product over a black cavity and the intrinsic luminance factor of the tissue paper or tissue product are determined. The opacity is calculated as the ratio of these two luminance factor values.		Formatted: Adjust space between Latin and Adjust space between Asian text and numbe		
5 Apparatus <u>ISO/FDIS 12625-16</u>		F 4 F 40 F		
https://standards.iteh.ai/catalog/standards/iso/08d04db4-daed-4bef-963a-e:	3995	Formatted 0-fd - 12625-16		
		Commented [eXtyles11]: ISO 2469: current s	tage is 50.00	
5.1.1 Reflectometer, having the geometric, spectral and photometric characteristics described in ISO 2469 calibrated in accordance with ISO 2469 and equipped for the measurement of luminance factor (C).	\checkmark	Formatted		
	1	Formatted Comments of LeVision 121, 150, 2460	. 50.00	
The materials to be measured can contain fluorescent whitening agents. The reflectometer shall therefore be	1/	Commented [eXtyles12]: ISO 2469: current s	tage is 50.00	
equipped with a radiation source adjusted to correspond to the CIE illuminant C described in ISO-11664.2 This should be achieved through the use of a fluorescent reference standard (5.2.2)(5.2.2) as described in	1/			
ISO 24701.	_ //	Formatted		
5.1.2 Filter reflectometer, having a filter which, in conjunction with the optical characteristics of the basic	۱ / ۲	Commented [eXtyles13]: The reference is to		
instrument, gives an overall response equivalent to the CIE tristimulus value <i>Y</i> , described in ISO/CIE-11664	¬ / /	Formatted		
1, of the CIE 1931 standard colorimetric system of the test piece evaluated for the CIE illuminant C.	-///	Formatted		
5.1.3 Abridged spectrophotometer whose function permits the calculation of the		Formatted	[.	
CIE tristimulus value Y, described in ISO/CIE 11664-1, of the CIE 1931 standard colorimetric system of the test piece graduated for the CIE illuminant C using the weighting functions given in Append Append		Formatted	<u>.</u>	
test piece, evaluated for the CIE illuminant C using the weighting functions given in Annex A. Annex A.				
	/	Formatted: FooterPageRomanNumber		
© ISO 2023 All rights reserved				

ISO/FDIS 12625-16:2023(E2024(en))

5.2 Reference standards

The reference standards for calibrating the instrument and the working standards should be used with sufficient regularity to ensure satisfactory performance.

5.2.1 Non-fluorescent reference standard, for photometric calibration, issued by an <u>ISO 4094 authorized</u> laboratory in accordance with ISO 2469.

5.2.2 Fluorescent reference standard, for use in adjusting the UV content of the radiation incident upon the sample in order to adjust the UV setting of the instrument to conform to UV(C) conditions, as described in ISO 2470-1.

5.3 Working standards

5.3.1 Two plates, of flat opal glass, ceramic, or other suitable material, cleaned and calibrated as described in JSO 2469.

NOTE In some instruments, the function of the primary working standard can be fulfilled by a built-in internal standard.

5.4 Black cavity

The black cavity should have a reflectance factor which does not differ from its nominal value by more than 0,2 %, at all wavelengths. The black cavity should be stored upside down in a dust-free environment or with a protective cover.

NOTE 1 The condition of the black cavity can be checked by reference to the instrument manufacturer.

NOTE 2 The nominal value is given by the manufacturer.

6 Sampling

If the tests are being made to evaluate a lot, the sample shall be selected in accordance with ISO 186. If the tests are made on another type of sample, the test pieces taken shall be representative of the sample received.

When sampling finished roll products, eliminate at least the first six layers and the last six layers because of the possible presence of adhesive or mechanical damage.

On finished products, one single sheet can be made of several plies. Do not try to separate the constituting plies.

7 Conditioning

Mark the samples for identification and make sure that the two sides of the paper or of the product can be distinguished.

Condition the samples according to <u>ISO 187</u> and keep them in the standard atmosphere throughout the test. Preconditioning with elevated temperatures should not be applied since it might change the optical properties.

Formatted: Font: 11 pt, Bold

Formatted: Font: 11 pt, Bold

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Commented [eXtyles14]: ISO 2469: current stage is 50.00

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Commented [eXtyles15]: ISO 2469: current stage is 50.00

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted

Formatted

Formatted

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

Formatted: Default Paragraph Font

 $\textbf{Formatted:} \ \mathsf{FooterPageRomanNumber}$

© ISO 2023 All rights reserved