#### ISO/FDIS 14968:2021

ISO TC 6/SC 2

Date: 2021-08-17

Paper and board — Cut-size office paper — Measurement of curl in a pack of sheets

Papier et carton — Papier en format à usage de bureau — Mesurage du tuilage dans un paquet de feuilles

### iTeh STANDARD PREVIEW

### FDIS stage

ISO 14968:2022

#### Warning for WDs and CDs

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

@ ISO #### – All rights reserved

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14968:2022



# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14968:2022

#### © ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva

Phone: +41 22 749 01 11

Email: copyright@iso.org

Website: www.iso.orgwww.iso.org

Published in Switzerland

## iTeh STANDARD PREVIEW

(standards.iteh.ai)

#### ISO 14968:2022

https://standards.iteh.ai/catalog/standards/sist/0ff47182-c2eb-4e28-b870-33d54b3437c6/iso-14968-2022

© ISO #### – All rights reserved

#### **CONTENT**

Forewordiv	
Introductionv	
1	Scope1
2	Normative references1
3	Terms and definitions1
4	Principle2
5	Apparatus2
6	Test atmosphere
7	Sampling3
8	Procedure3
	Expression of results4
10	Precision4
	Test report4
Annex A (informative) Types of curl5	
Annex B (informative) Curl gauge construction	

ISO 14968:2022

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part-1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part-2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC-6 Paper, board and pulps, Subcommittee SC-2. Test methods and quality specifications for paper and board.

This second edition cancels and replaces the first edition (ISO-14968:1999), of which it constitutes a minor revision.

#### minor revision.

The main changes compared to the previous edition are as follows:

- Updating of the normative references in Clause\_2-have been updated;
- Updated ISO template.
- editorial corrections have been applied.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

Field Code Changed

© ISO #### - All rights reserved

#### Introduction

Curl in cut-size office papers plays an important part in the performance of these papers in copying processes. Frequently, cut-size papers are used on copier and other printing devices, operating at high speeds. Curl which exists in the ream before the paper enters the imaging process, and curl developed during the imaging process, can affect office paper performance, especially if two-sided printing or collating is involved. Common problems experienced include jamming and misregistration.

The experience used in developing this test method was limited to uncoated papers in the commonly used cut sizes. The technique is basic and <u>couldcan</u> be used with coated papers as well as paperboard to identify the type and magnitude of curl.

The test method identifies the type and degree of curl in a pack of sheets but does not address variations that might be present in individual sheets. The method of ISO-\_11556 can be used to measure curl in individual sheets.

It should be recognized that the curl occurring after processing in a copier or a printing device may bear no relation to the curl of the paper as received.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14968:2022

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14968:2022

#### Paper and board — Cut-size office paper — Measurement of curl in a pack of sheets

#### 1 Scope

This International Standard document specifies a method for the measurement of curl in cut-size office papers. The test method wouldis typically be-used in evaluating papers of the type described in ISO-210

This method is limited to papers with a maximum dimension of 300-mm in both directions.

The measurement maycan be made on papers as received, after conditioning, or after processing in copier or printing device.

#### **Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO-186:2002, Paper and Board of Sampling to determine average quality

ISO 187 Paper, board and pulps Standard atmosphere for conditioning and testing and procedure for monitoring the atmosphere and conditioning of samples

ISO 216, Writing paper and certain classes of printed indication of machine direction

#### **53** Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- \_\_\_ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at <a href="https://www.electropedia.org/">httphttps://www.electropedia.org/</a>

#### 3.1 curl

deviation from a flat surface which has three major components: magnitude, direction of curl axis and the side towards which the paper curls

#### 3.1.1

#### curl magnitude

quantitative measure of the deviation of a paper test piece from a flat surface

Note-1 to entry: It is expressed as the reciprocal of the radius of curvature, R, of the curled test piece with units of reciprocal metres (m-1).

© ISO 2021 - All rights reserved

**Field Code Changed** 

Note-2 to entry. The radius of curvature for the curled test piece is the distance from the arc to the centre of a circle, of which the arc forms a part. The reciprocal radius  $(R^{-1})$  has a value of zero for a flat sheet.

Note\_3 to entry: Curl characteristics of paper and board are time-dependent and the magnitude of any curl may be transient.

#### 3.1.2

#### curl axis direction

direction of the curl axis of paper and board, characterized as follows:

- \_\_\_curl axis which is perpendicular to the paper's machine direction
- \_\_\_curl axis which is parallel to the paper's machine direction
- \_\_\_curl axis which is neither parallel nor perpendicular to the paper's machine direction

Note 1 to entry: See figures Figures A.1 to A.3, respectively.

### iTeh STANDARD PREVIEW

#### 3.1.3

#### concave side

side towards which the paper or board curls

Note 1 to entry: See also annex Annex A.

ISO 14968:2022

https://standards.iteh.ai/catalog/standards/sist/0ff47182-c2eb-4e28-b870-33d54b3437c6/iso-

### 3.2 double curl

form of curl which tends to alternate between the two sides, when the sheet is manipulated lightly

Note  $\underline{1}$  to entry: This tendency is a phenomenon which may be described as two curl patterns that are finely balanced within the same sheet of paper.

#### 3.3

#### cut-size office papers

papers in the range 60-g/m $^2$  to 150-g/m $^2$  which are used for writing and/or in various printing and copying devices

#### 3.4

#### reference side

for a non-imaged paper that side indicated by arrows on the end labels of a sealed ream, that side facing the top of a box of unwrapped sheets or, if arrows, or other instructions, are not present, that side facing the wrapper seam

© ISO #### – All rights reserved

#### 64 Principle

A pack of approximately 10 to 15-sheets is taken from the sample to be tested and the magnitude of the curl is measured, noting the curl axis direction and the side towards which the paper curls.

#### **75** Apparatus

#### 7.15.1 Curl guagegauge

Consisting of a straight line 210-\_mm long and companion arcs at least 210-\_mm long of radii such that their curl magnitude varies between 1,00-\_m-1 and 10,00-\_m-1. The construction of such a gauge is shown in Annex-B.

Note 1—Copies of the curl gauge made on a toner-imaging device should not be used because such device frequently has a built-in enlargement which would change the dimensions of the arcs.

Note 2—It maycan be convenient to use a set of templates with their edges corresponding to the curl o magnitudes given in annexAnnex B. Each template should be labelled with its curl magnitude.

**Commented [CM1]:** Changed to regular text because recommendations are not permitted inside notes

**Commented [CM2]:** Changed to regular text because recommendations are not permitted inside notes

#### **86** Test atmosphere

The purpose of this method is usually to test the inherent curl of the paper at the moisture content that it has immediately following its removal from a ream, or after processing in a copier or other printing device

In this case, the paper shall not be conditioned in a standard atmosphere. The actual testing may be carried out either in the standard atmosphere described in ISO-187, or under the measured ambient conditions of the area surrounding the imaging device.

https://standards.iteh.ai/catalog/standards/sist/0ff47182-c2eb-4e28-b870-33d54b3437c6/iso-

#### 97 Sampling

- **7.1–** If tests are being made to evaluate a lot, the sample shall be selected in accordance with ISO 186:2002 clause 5.1.
- **7.2** —For the purposes of this  $\frac{International Standard document}{International Standard document}$ , a test piece is understood to be a pack of 10 to 15 consecutive sheets.
- **7.3–** When taking paper from unopened packages, open the package, pull out 10 to 15 consecutive sheets and make the measurement, in accordance with the procedure (elause see Clause 8). To ensure that only samples which have experienced minimum exposure to the atmosphere are selected, do not pull sheets from near the top or bottom of the pack.
- **7.4** When taking paper from stacks that are not wrapped, pull 10 to 15 sheets from some distance down the stack so as to avoid paper that has been exposed to the atmosphere. Make the measurement, in accordance with the procedure (elause see Clause 8) without delay.
- **7.5** Identify the machine direction and referenced side of the paper.

Note 1 The referenced side is the side that should be imaged first.

**Commented [CM3]:** Changed to regular text because recommendations are not permitted inside notes

© ISO #### – All rights reserved

© ISO 2021 - All rights reserved