FINAL DRAFT

INTERNATIONAL STANDARD

ISO/FDIS 19901-8

ISO/TC 67/SC 7

Secretariat: **BSI**

Voting begins on: 2023-06-19

Voting terminates on: **2023-08-14**

Petroleum and natural gas industries — Specific requirements for offshore structures —

Part 8: Marine soil investigations

Industries du pétrole et du gaz naturel — Exigences spécifiques relatives aux structures en mer — Startie 8: Investigations des sols en mer

ISO 19901-8 https://standards.iteh.ai/catalog/standards/sist/cc99daa6-861b-463b-b929-070bf8211adb/iso-19901-8

ISO/CEN PARALLEL PROCESSING

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNO-LOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STAN-DARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number ISO/FDIS 19901-8:2023(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19901-8

https://standards.iteh.ai/catalog/standards/sist/cc99daa6-861b-463b-b929-070bf8211adb/iso-19901-8



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword					
Introduction					
1	Scope				
2	Normative references				
3	Terms and definitions				
4	Symbols, units and abbreviated terms				
-	4.1 Symbols	6			
	4.2 Units				
_	4.3 Abbreviated terms				
5	Objectives, planning and requirements 5.1 Objectives				
	5.2 Planning				
	5.2.1 Sequence of activities				
	5.2.2 Integrated geoscience studies				
	5.3 Scope of work and development of project specifications				
	5.4 Health, safety and environmental requirements for marine operations				
	5.4.1 General5.4.2 Investigation vessel				
	5.4.2 Investigation vessel 5.4.3 Hazardous substances and acoustic noise	18 10			
	5.4.4 Shallow gas				
	5.5 Other requirements				
	5.5.1 Operational requirements				
	5.5.2 Quality requirements				
	5.5.3 Specific considerations for unconventional soils				
6	Deployment of investigation equipment				
	6.1 Non-drilling mode deployment				
	6.2 Drilling mode deployment.				
	6.2.1 General				
	6.2.2 Vessel drilling				
	6.2.3 Seafloor drilling				
	6.3 Uncertainty of vertical depth measurements6.3.1 General				
	6.3.2 Factors affecting the uncertainty of vertical depth measurements				
	6.3.3 Depth uncertainty classes				
	6.4 Horizontal positioning				
	6.5 Interaction of investigation equipment with the upper seabed				
7	Drilling and logging				
	7.1 General				
	7.2 Project-specific drilling requirements				
	7.3 Drilling objectives and selection of drilling equipment and procedures				
	 7.4 Drilling operations plan 7.5 Recording of drilling parameters 				
	7.5 Recording of drilling parameters7.6 Borehole geophysical logging				
	7.6 General				
	7.6.2 Reporting of results				
8	In situ testing				
-	8.1 General				
	8.2 General requirements for the reporting of in situ tests				
	8.3 Cone penetration test				
	8.3.1 General				
	8.3.2 Equipment				

		8.3.3 Test procedures				
		8.3.4 Procedures for testing offshore				
		8.3.5 Presentation of test results				
	8.4	Pore pressure dissipation test				
		8.4.1 General				
		8.4.2 Equipment				
		8.4.3 Test procedure				
		8.4.4 Presentation of results				
	8.5	Ball and T-bar penetration tests				
		8.5.1 General				
		8.5.2 Equipment				
		8.5.3 Calibration and verification of ball and T-bar penetrometers				
		8.5.4 Procedures for testing offshore				
		8.5.5 Presentation of results				
	8.6	Seismic cone penetration test				
		8.6.1 General				
		8.6.2 Equipment				
		8.6.3 Procedures for testing offshore				
	~ -	8.6.4 Presentation of results				
	8.7	Other in situ tests				
		8.7.1 General				
9	Samp	ling				
	9.1	Purpose and objectives of sampling	46			
	9.2	Sampling systems				
	9.3	Selection of samplers				
		9.3.1 General				
		9.3.2 Drilling mode samplers				
		9.3.3 Non-drilling mode samplers				
	9.4	Sample recovery considerations				
	9.5	Handling, transport and storage of samples				
		9.5.1 ttpGeneral ards iteh ai/catalog/standards/sist/cc99daa6-861b-463b-b929-				
		9.5.2 Offshore sample handling 211adb/iso-19901-8				
		9.5.3 Offshore storage				
		9.5.4 Onshore transport, handling and storage				
10	Labor	ratory testing	52			
	10.1	General				
	10.2	Project specifications				
	10.3	Presentation of laboratory test results				
	10.4	Instrumentation, calibration and data acquisition				
	10.5	Preparation of soil specimens for testing.				
		10.5.1 Minimum sample size and specimen dimensions				
		10.5.2 Preparation of disturbed samples and soil batching				
		10.5.3 Preparation of intact specimens (fine soils)				
		10.5.4 Laboratory-prepared compacted and reconstituted specimens				
		10.5.5 Preparation of remoulded samples				
	10.6	Evaluation of intact sample quality				
11	Dono	rting				
11	11.1	Reporting requirements				
	11.1	Presentation of field operations and factual data				
	11.2	Data interpretation and soil parameters				
Annex A (informative) Additional information and guidance 61						
Annex	x B (inf	Formative) Laboratory testing				
		y				
011010	Sraph	J	J.T.J			

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 67, *Oil and gas industries including lower carbon energy*, Subcommittee SC 7, *Offshore structures*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 12, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 19901-8:2014), which has been technically revised.

The main changes are as follows:

- application classes for in situ testing tools are removed and replaced by an assessment of documented calibration results and uncertainty analyses;
 - new procedures for calibration and verification of cone penetrometers are introduced with reference to the latest edition of ISO 22476-1.
 - references to project specifications for technical details have been reduced where possible and roles and responsibilities have been further clarified.
 - title and scope change adopted as per Technical Management Board Resolution 53/2022.

A list of all parts in the ISO 19901 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

The International Standards on offshore structures prepared by TC 67/SC 7 (ISO 19900, the ISO 19901 series, ISO 19902, ISO 19903, ISO 19904, ISO 19905 series and ISO 19906) constitutes a common basis covering those aspects that address design requirements and assessments of all offshore structures used by the petroleum and natural gas industries worldwide. Through their application, the intention is to achieve reliability levels appropriate for manned and unmanned offshore structures, whatever the nature or combination of the materials used. Application specific requirements for different energy industries are referencing relevant overarching standards. For example, for the offshore wind industry the IEC standards IEC 61400-1 and IEC 61400-3-1 outline the normative design requirements (e.g. return periods) for offshore turbine support structures.

Structural integrity is a concept comprising models for describing actions, structural analyses, design rules, safety elements, workmanship, quality control procedures and national requirements, all of which are mutually dependent. The modification of one aspect of design in isolation can disturb the balance of reliability inherent in the overall concept of structural integrity (see ISO 19900). The implications involved in modifications, therefore, should be considered in relation to the overall reliability of all offshore structural systems.

A marine soil investigation is only one of many possible marine site investigations as illustrated in <u>Figure 1</u>. The scope of a marine soil investigation, such as field programme, equipment to be used, laboratory testing programme, soil parameters to be established and reporting, is usually defined in project specifications based on important factors, such as type of structures involved, type of soil conditions expected, regional or site-specific investigation, preliminary or final soil investigations. The reporting can comprise anything from field data only to reporting of soil parameter values.



Figure 1 — Marine soil investigations shown as one of many types of marine site investigations.

Use of this document is based on the following assumptions:

- communication takes place between geophysical and geotechnical specialists for defining the scope of the marine soil investigation based on the results of a geophysical investigation (see ISO 19901-10);
- communication takes place between geotechnical personnel involved in marine soil investigations and the personnel responsible for foundation design, for construction and for installation of the offshore structures;
- soil data are collected, documented and interpreted by trained personnel;
- the project-specific scope of work for marine soil investigations is defined by one or more project specifications.

The detailed requirements for equipment and methods given in this document are only applicable if relevant for the scope of work defined in the project specifications.

This document is intended to provide flexibility in the choice of marine soil investigation techniques without hindering innovation.

In this document, the following verbal forms are used:

— "shall" indicates a requirement;

- "should" indicates a recommendation;
- "can" indicates a possibility or a capability;
- "may" indicates a permission.

Information marked as "NOTE" is intended to assist the understanding or use of the document. "Notes to entry" used in <u>Clause 3</u> provide additional information that supplements the terminological data and can contain requirements relating to the use of a term.

<u>Annex A</u> gives additional information intended to assist the understanding or use of this document. The clause numbers in <u>Annex A</u> correspond to the normative main text to facilitate easy cross-referencing. <u>Annex B</u> covers conduct of laboratory tests as part of marine soil investigations.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19901-8</u> https://standards.iteh.ai/catalog/standards/sist/cc99daa6-861b-463b-b929-070bf8211adb/iso-19901-8

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19901-8</u> https://standards.iteh.ai/catalog/standards/sist/cc99daa6-861b-463b-b929-070bf8211adb/iso-19901-8

Petroleum and natural gas industries — Specific requirements for offshore structures —

Part 8: Marine soil investigations

1 Scope

This document specifies requirements and provides recommendations and guidelines for marine soil investigations regarding:

- a) objectives, planning and execution of marine soil investigations;
- b) deployment of investigation equipment;
- c) drilling and logging;
- d) in situ testing;
- e) sampling;
- f) laboratory testing;
- g) reporting.

Although this document focuses on investigations of soil, it also provides guidance, with less detail, for investigations of chalk, calcareous soils, cemented soils and weak rock. **b**-463b-b929-

Foundation design is not covered by this document.

NOTE 1 ISO 19901-4 and the respective design standards covering foundation design for the specific types of offshore structures to meet the requirements of application specific standards are given on the ISO website.

The results from marine geophysical investigations are, when available and where appropriate, used for planning, optimization and interpretation of marine soil investigations.

This document neither covers the planning, execution and interpretation of marine geophysical investigations nor the planning and scope of geohazard assessment studies, only the corresponding marine soil investigations aspects thereof.

NOTE 2 ISO 19901-10 covers the planning, execution and interpretation of marine geophysical investigations.

This document specifies requirements and provides guidance for obtaining measured values and derived values. This document excludes requirements for determination of design values and representative values. Limited guidance is provided in <u>11.3</u> related to data interpretation.

This document is intended for clients, soil investigation contractors, designers, installation contractors, geotechnical laboratories and public and regulatory authorities concerned with marine soil investigations for any type of offshore structures, or geohazard assessment studies.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/FDIS 19901-8:2023(E)

ISO 14688-1, Geotechnical investigation and testing — Identification and classification of soil — Part 1: Identification and description

ISO 14688-2, Geotechnical investigation and testing — Identification and classification of soil — Part 2: Principles for a classification

ISO 14689, Geotechnical investigation and testing — Identification, description and classification of rock

ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories

ISO 19900, Petroleum and natural gas industries — General requirements for offshore structures

ISO 22476-1, Geotechnical investigation and testing — Field testing — Part 1: Electrical cone and piezocone penetration test

ISO/IEC Guide 99, International vocabulary of metrology — Basic and general concepts and associated terms (VIM)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 14688-1, ISO 14688-2, ISO 14689 and the following apply:

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at <u>https://www.electropedia.org/</u>

3.1

accuracy

closeness of agreement between a measured quantity value and a true quantity value of a measurand [SOURCE: ISO/IEC Guide 99:2007, 2.13]

3.2

borehole geophysical logging

measurement of physical properties of a borehole and/or the surrounding soil, obtained by one or more logging probes deployed in the borehole

3.3

client

party or person with overall responsibility for the marine soil investigation, including preparation of project specifications

3.4

coordinate reference system

coordinate system that is related to an object by a datum

Note 1 to entry: Geodetic and vertical datums are referred to as reference frames.

3.5

contractor

party or person responsible for an assigned scope of work described in project specifications

3.6

derived value

value of a geotechnical parameter obtained from test results by theory, correlation or empiricism

design value

value derived from the representative value for use in the design verification

[SOURCE: ISO 19900:2019, 3.14]

3.8

disturbed sample

sample whose soil structure, water content and/or constituents have changed as a result of sampling and handling

3.9

drained condition

condition whereby the applied stresses and stress changes are supported entirely by the soil skeleton and do not cause a change in pore pressure

3.10 drilling mud

drilling fluid

fluid pumped down a rotary drilled borehole to facilitate the drilling process

Note 1 to entry: The hardware associated with handling drilling fluids is commonly prefixed 'mud' (e.g. mud tank, mud pump, mud valve). Drilling parameters associated with drilling fluids are similarly prefixed (mud pressure, mud flow, etc.).

3.11

geohazard

geological condition that has the potential to have adverse effects on persons, operations, offshore structures or the environment

3.12

ground model

ISO 19901-8

2- or 3-dimensional representation of the seafloor (bathymetry) and, where applicable, the sub-seafloor conditions, at a given time, that is specific to the offshore structure(s) considered

3.13

ground truthing

integration of seafloor or sub-seafloor geophysical data with data acquired by marine soil investigation and other data

3.14

in-pipe logging

borehole geophysical logging (3.2) in a section of the borehole with drill pipe between the tool and the borehole wall

Note 1 to entry: The number of parameters that can be usefully measured in these circumstances is restricted.

3.15

inclination

the angular deviation of the cone penetrometer from the vertical.

3.16

intact sample

sample that was collected with intention to preserve its in situ characteristics

3.17

integrated geoscience study

combination of geophysical data, a model for geological processes and geotechnical data for development of a *ground model* (<u>3.12</u>)

marine geophysical investigation

type of marine site investigation of seafloor or sub-seafloor that uses non-destructive methods requiring marine deployment of geophysical tools

Note 1 to entry: See Figure 1.

3.19

marine site investigation

type of investigation at an offshore or nearshore site

EXAMPLE Marine soil investigation, marine geophysical investigation, marine biological investigation, metocean investigation. See <u>Figure 1</u>.

3.20

marine soil investigation

type of *marine site investigation* (3.19) whose primary objective is to obtain reliable and representative soil data for characterization of the seabed soil conditions to facilitate the design of offshore structures and/or for *geohazard* (3.11) evaluation

Note 1 to entry: See <u>Figure 1</u> and ISO 19901-10.

3.21

measured value

value that is measured in a test

3.22

nominal value

value assigned to a variable specified or determined on a non-statistical basis, typically acquired experience or physical conditions, or as published in a recognized code or standard

3.23

<u>ISO 19901-8</u>

open-hole logging *borehole geophysical logging* (3.2) in a section of the borehole without, for example, casing or drill pipe between the tool and the borehole wall

3.24

project specification

scope of work for marine soil investigations (3.20) assigned by the client (3.3) to a contractor (3.5)

3.25

rat hole

additional depth drilled at the end of the borehole (beyond the last zone of interest) to ensure that the zone of interest for *borehole geophysical logging* (3.2) can be fully evaluated

Note 1 to entry: The rat hole allows tools at the top of the logging string to reach and measure the deepest zone of interest.

3.26

reconstituted specimen

laboratory specimen prepared by mixing a soil sample to specified state using a specified procedure

3.27

remoulded sample

remoulded specimen

laboratory specimen that is thoroughly reworked mechanically at a constant water content

3.28

remoulded shear strength shear strength of remoulded soil

representative value

value assigned to a basic variable for verification of a limit state in a design/assessment situation

[SOURCE: ISO 19900:2019, 3.40]

3.30

residual shear strength

shear strength at large strains where shear stress versus strain levels off to a constant value

3.31

sample

portion of soil or rock recovered from the seabed by sampling techniques

3.32

sample quality

classification of soil *samples* (3.31) and specimens based on qualitative or quantitative techniques for assessment of the degree of inevitable disturbance induced by the sampling, transportation, handling and storage processes

Note 1 to entry: Sample quality criteria for low to medium OCR clays, where the sample quality is based on measured volume change from laboratory consolidation tests, are given in <u>Table 9</u>.

3.33

seabed

materials below the seafloor

Note 1 to entry: Sub-seafloor can also be used as an equivalent term (See ISO 19901-10).

3.34

seafloor

interface between the sea and the seabed (3.33) 901-8

3.35 https://standards.iteh.ai/catalog/standards/sist/cc99daa6-861b-463b-b929-

settlement 070bf8211adb/iso-19901

elastic or permanent downward movement of a structure as a result of its own weight and other actions

3.36

site

defined investigation area, including vertical extent.

3.37

soil parameter

soil property that can be quantified by a descriptor or a value

Note 1 to entry: Cone resistance and undrained shear strength are examples of soil parameters; low strength and very dense are examples of descriptors; nominal value, measured value and derived value are examples of types of values that can be determined for a soil parameter.

3.38

specimen

part of a *sample* (3.31) used for a laboratory test

3.39

strength index test

test that yields an indication of the shear strength

swelling

expansion due to reduction of effective stress, resulting from either reduction of total stress or absorption of (in general) water at constant total stress

Note 1 to entry: Swelling includes the reverse of both compression and consolidation.

Note 2 to entry: Exsolution of dissolved gas due to stress relief during sampling can cause significant swelling in samples.

3.41

taper angle

rate, in degrees, at which the outside diameter of the sampler cutting shoe reduces

3.42

uncertainty

non-negative parameter that characterizes the dispersion of the quantity values that are being attributed to a measurand

[SOURCE: ISO/IEC Guide 99:2007, 2.26]

3.43

undisturbed sample

sample (3.31) in which no change of practical significance has occurred in the soil characteristics

3.44

undrained condition

condition whereby the applied stresses and stress changes are supported by both the soil skeleton and the pore fluid and do not cause a change in volume **CONTROL CONTROL**

3.45

undrained shear strength

<u>ISO 19901-8</u>

maximum shear stress at yielding or at a specified maximum strain in an *undrained condition* (3.43)

Note 1 to entry: Yielding is the condition of a material in which a large plastic strain occurs at little or no stress increase.

4 Symbols, units and abbreviated terms

4.1 Symbols

- *A* projected area of the miniature cone, T-bar or ball penetrometer
- *A*_c nominal cross-sectional area of a cone penetrometer
- $A_{\rm n}$ area of the load cell or shaft on which pore pressure can act
- $A_{\rm p}$ projected area of the penetrometer in a plane normal to the shaft
- *A*_s surface area of the friction sleeve
- $A_{\rm sb}$ cross-sectional area of the bottom of the friction sleeve
- *A*_{sp} cross-sectional area of the ball or T-bar penetrometer connecting shaft
- *A*_{st} cross sectional area of the top of the friction sleeve
- *a* net area ratio of a cone penetrometer, ball or T-bar penetrometer
- *B* Skempton's pore pressure parameter

Bq	pore pressure ratio
b	net area ratio of the friction sleeve
C _A	area ratio of sampling tube
C _i	inside clearance ratio
C _c	compression index
C _v	coefficient of consolidation
с'	effective stress cohesion intercept
d_{w}	water depth
D	diameter of miniature penetrometer
D _i	inner diameter of sampling tube
D _o	outer diameter of sampling tube
D_1	diameter of miniature penetrometer in earlier test, for calculation of edge-to-edge test spacing
<i>D</i> ₂	diameter of miniature penetrometer in later test, for calculation of edge-to-edge test spacing
е	void ratio h STANDARD PREVIEW
e_{\min}	minimum void ratio tandards.iteh.ai)
e _{max}	maximum void ratio
e_0	hinitial void ratio https://standards/sist/cc99daa6-861b-463b-b929-
F	measured axial force on the ball or T-bar relative to zero at seafloor
$f_{\rm S}$	sleeve friction
F _r	friction ratio (= f_s/q_{net})
F_{thrust}	applied thrust to push rod
G	shear modulus
G _{max}	initial (small strain) shear modulus
G _s	specific gravity of solid particles
g	acceleration due to gravity (= $9,81 \text{ m/s}^2$),
Н	specimen height
h _e	height of the cylindrical extension
h _s	height of drill pipe above main deck level
h _d	height of main deck level above the sea level
$h_{\rm sf}$	height of reference point above seafloor
i	inclination of the cone penetrometer