

FINAL  
DRAFT

INTERNATIONAL  
STANDARD

ISO/IEC  
FDIS  
**23009-1**

ISO/IEC JTC 1/SC 29

Secretariat: JISC

Voting begins on:  
**2022-04-25**

Voting terminates on:  
**2022-06-20**

---

---

## Information technology — Dynamic adaptive streaming over HTTP (DASH) —

### Part 1: Media presentation description and segment formats

iTeh STANDARD REVIEW

(sta) *Technologies de l'information — Diffusion en flux adaptatif dynamique sur HTTP (DASH) —*

*Partie 1: Description de la présentation et formats de remise des médias* [ISO/IEC FDIS 23009-1](#)

<https://standards.iteh.ai/catalog/standards/sist/68e73f12-442e-4d43-84c9-7753705527a6/iso-iec-fdis-23009-1>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number  
ISO/IEC FDIS 23009-1:2022(E)

© ISO/IEC 2022

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC FDIS 23009-1](#)

<https://standards.iteh.ai/catalog/standards/sist/68e73f12-442e-4d43-84c9-7753705527a6/iso-iec-fdis-23009-1>



## COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

<b>Foreword.....</b>	<b>vii</b>
<b>Introduction.....</b>	<b>viii</b>
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms, definitions, symbols and abbreviated terms .....</b>	<b>2</b>
<b>3.1 Terms and definitions.....</b>	<b>2</b>
<b>3.2 Symbols and abbreviated terms.....</b>	<b>7</b>
<b>3.3 Conventions .....</b>	<b>9</b>
<b>4 Overview .....</b>	<b>10</b>
<b>4.1 System description .....</b>	<b>10</b>
<b>4.2 DASH Client model.....</b>	<b>11</b>
<b>4.3 DASH data model overview .....</b>	<b>12</b>
<b>4.4 Protocols .....</b>	<b>15</b>
<b>4.5 Media stream and Representation properties .....</b>	<b>16</b>
<b>4.5.1 Switching and Random Access Support.....</b>	<b>16</b>
<b>4.5.2 Media stream access points .....</b>	<b>16</b>
<b>4.5.3 Non-overlapping Segments and Subsegments.....</b>	<b>17</b>
<b>4.5.4 Conforming Segment track.....</b>	<b>18</b>
<b>4.6 Brands.....</b>	<b>18</b>
<b>4.7 Schemes.....</b>	<b>19</b>
<b>5 Media Presentation.....</b>	<b>22</b>
<b>5.1 General.....</b>	<b>22</b>
<b>5.2 Media Presentation Description.....</b>	<b>22</b>
<b>5.2.1 General .....</b>	<b>22</b>
<b>5.2.2 Schema.....</b>	<b>23</b>
<b>5.2.3 Elements and Attributes added in revisions and amendments.....</b>	<b>24</b>
<b>5.3 Hierarchical data model.....</b>	<b>26</b>
<b>5.3.1 General .....</b>	<b>26</b>
<b>5.3.2 Period.....</b>	<b>33</b>
<b>5.3.3 Adaptation Sets.....</b>	<b>39</b>
<b>5.3.4 Media content component.....</b>	<b>50</b>
<b>5.3.5 Representation.....</b>	<b>51</b>
<b>5.3.6 Sub-Representation .....</b>	<b>62</b>
<b>5.3.7 Common attributes and elements .....</b>	<b>63</b>
<b>5.3.8 Subsets.....</b>	<b>70</b>
<b>5.3.9 Segments and Segment information .....</b>	<b>71</b>
<b>5.3.10 Label and Group Label .....</b>	<b>93</b>
<b>5.3.11 Preselection .....</b>	<b>95</b>
<b>5.3.12 Initialization Set, Group and Presentation.....</b>	<b>99</b>
<b>5.3.13 Resynchronization .....</b>	<b>103</b>
<b>5.4 Media Presentation Description updates.....</b>	<b>106</b>
<b>5.4.1 General .....</b>	<b>106</b>
<b>5.4.2 MPD Reset.....</b>	<b>108</b>
<b>5.5 MPD assembly .....</b>	<b>108</b>
<b>5.5.1 General .....</b>	<b>108</b>
<b>5.5.2 Syntax and semantics .....</b>	<b>108</b>
<b>5.5.3 Processing .....</b>	<b>109</b>
<b>5.6 Base URL Processing.....</b>	<b>110</b>

5.6.1 Overview .....	110
5.6.2 Semantics .....	111
5.6.3 XML syntax .....	112
5.6.4 Reference resolution .....	112
5.6.5 Alternative base URLs .....	113
5.7 Program information .....	113
5.7.1 Overview .....	113
5.7.2 Semantics .....	113
5.7.3 XML syntax .....	114
5.8 Descriptors .....	114
5.8.1 General .....	114
5.8.2 Semantics of generic descriptor .....	115
5.8.3 XML syntax of generic descriptor .....	115
5.8.4 Specific descriptors .....	116
5.8.5 Specific scheme definitions .....	122
5.9 DASH metrics descriptor .....	133
5.9.1 Overview .....	133
5.9.2 Semantics .....	133
5.9.3 XML syntax .....	134
5.9.4 Metric reporting .....	135
5.10 Events .....	135
5.10.1 Overview .....	135
5.10.2 MPD Events .....	135
5.10.3 Inband Event Signalling .....	139
5.10.4 DASH-specific events .....	142
5.11 MPD Chaining .....	146
5.11.1 General .....	146
5.11.2 Regular Chaining .....	146
5.11.3 Fallback Chaining .....	147
5.12 Producer Reference Time .....	148
5.12.1 General .....	148
5.12.2 Semantics .....	148
5.12.3 XML Syntax .....	150
5.13 Leap seconds .....	150
5.13.1 Overview .....	150
5.13.2 Semantics .....	151
5.13.3 XML-Syntax .....	151
5.13.4 Leap second information updates .....	152
5.14 Content Popularity Rate .....	152
5.14.1 General .....	152
5.14.2 Semantics .....	153
5.14.3 XML syntax .....	154
5.15 MPD patch framework .....	155
5.15.1 Overview .....	155
5.15.2 MPD Patch Location .....	155
5.15.3 MPD patch document .....	156
5.15.4 Processing Model .....	158
5.15.5 Recommended Client Operation .....	159
6 Segment formats .....	159
6.1 General .....	159
6.2 Segment types .....	160
6.2.1 General .....	160
6.2.2 Initialization Segment .....	160
6.2.3 Media Segment .....	160

6.2.4	Index Segment .....	162
6.2.5	Bitstream Switching Segment .....	162
6.2.6	Missing Content Segment.....	162
6.3	Segment formats for ISO base media file format.....	162
6.3.1	General .....	162
6.3.2	Preliminaries: Refinements of generic concepts .....	163
6.3.2.5	Resynchronization Point .....	163
6.3.3	Initialization Segment format .....	164
6.3.4	Media Segment types.....	164
6.3.5	Self-Initializing Media Segment formats .....	166
6.4	Segment formats for MPEG-2 transport streams .....	166
6.4.1	General .....	166
6.4.2	Preliminaries: Refinements of generic concepts .....	167
6.4.3	Initialization Segment types and formats.....	168
6.4.4	Media Segment types and formats .....	169
6.4.5	Bitstream Switching Segment .....	169
6.4.6	Index Segment .....	170
6.4.7	Boxes used with MPEG-2 TS Index Segments .....	172
7	Combined semantics of MPD and Segment formats .....	172
7.1	Overview .....	172
7.2	General.....	173
7.2.1	Media Presentation timeline .....	173
7.2.2	Segment Index .....	174
7.2.3	Segment alignment .....	174
7.2.4	Subsegment alignment .....	174
7.3	Media Presentation based on the ISO base media file format .....	174
7.3.1	General .....	174
7.3.2	Media presentation timeline .....	175
7.3.3	Authoring Rules for specific MPD attributes .....	175
7.3.4	Sub-Representations .....	176
7.3.5	Segment Timeline without Segment Index.....	176
7.4	Media Presentation based on MPEG-2 TS.....	176
7.4.1	General .....	176
7.4.2	Media presentation timeline .....	177
7.4.3	Authoring rules for specific MPD attributes.....	177
7.4.4	Sub-Representations .....	178
8	Profiles.....	178
8.1	Definition .....	178
8.2	Full profile .....	180
8.2.1	General .....	180
8.2.2	Media Presentation Description constraints.....	180
8.2.3	Segment format constraints .....	180
8.3	ISO Base media file format On Demand profile.....	180
8.3.1	General .....	180
8.3.2	Media Presentation Description constraints.....	181
8.3.3	Segment format constraints .....	182
8.4	ISO Base media file format live profile.....	182
8.4.1	General .....	182
8.4.2	Media Presentation Description constraints.....	182
8.4.3	Segment format constraints .....	183
8.5	ISO Base media file format main profile.....	183
8.5.1	General .....	183
8.5.2	Media Presentation Description constraints.....	184

8.5.3 Segment format constraints .....	184
8.6 MPEG-2 TS main profile .....	185
8.6.1 General.....	185
8.6.2 Media Presentation Description constraints .....	185
8.6.3 Segment format constraints .....	185
8.6.4 Comments and recommendations .....	185
8.7 MPEG-2 TS simple profile .....	186
8.7.1 General.....	186
8.7.2 Media Presentation Description constraints .....	186
8.7.3 Segment format constraints .....	186
8.7.4 Recommendations .....	187
8.8 ISO Base media file format extended live profile.....	187
8.8.1 General.....	187
8.8.2 Media Presentation Description constraints .....	187
8.8.3 Segment format constraints .....	188
8.8.4 Inband Events .....	188
8.9 ISO Base media file format extended On Demand profile .....	188
8.9.1 General.....	188
8.9.2 Media Presentation Description constraints .....	189
8.9.3 Segment format constraints .....	190
8.10 ISO Base media file format common profile.....	190
8.10.1 General.....	190
8.10.2 Media Presentation Description constraints .....	190
8.10.3 Segment format constraints .....	191
8.11 ISO Base media file format broadcast TV profile.....	191
8.11.1 General.....	191
8.11.2 Media Presentation Description constraints .....	191
8.11.3 Segment format constraints .....	193
8.11.4 MPD Updates and Inband Event Streams .....	193
8.12 DASH profile for CMAF content .....	194
8.12.1 General.....	194
8.12.2 CMAF content model for DASH profile definition .....	194
8.12.3 CMAF to DASH Mapping Principles .....	197
8.12.4 DASH profiles for CMAF content - Common constraints .....	200
8.12.5 DASH CMAF Core Profile .....	207
8.12.6 DASH CMAF Extended Profile .....	208
8.12.7 Conformance Checking Considerations .....	208
Annex A (informative) Example DASH Client behaviour .....	209
Annex B (normative) MPD schema .....	233
Annex C (normative) MIME type registration for MPD and other resources.....	234
Annex D (normative) DASH Metrics .....	241
Annex E (normative) Byte range requests with regular HTTP GET methods .....	250
Annex F (informative) Guidelines for extending DASH with other delivery formats.....	253
Annex G (informative) MPD Examples and MPD Usage.....	255
Annex H (normative) Spatial Relationship Description.....	283
Annex I (normative) Flexible Insertion of URL Parameters .....	292
Annex J (informative) Open GOP resolution change .....	306
Annex K (normative) DASH Service Description .....	307
Bibliography.....	318

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives) or [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)) or the IEC list of patent declarations received (see [patents.iec.ch](http://patents.iec.ch)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). In the IEC, see [www.iec.ch/understanding-standards](http://www.iec.ch/understanding-standards).

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This fifth edition cancels and replaces the fourth edition (ISO/IEC 23009-1:2020), which has been technically revised.

The main changes are as follows:

- DASH profile for using Common Media Application Format (CMAF) are added;
- The concept Resynchronization is added in order to identify stream access points in Segments;
- MPD patching is updated to support explicit MPD updates of smaller size, not only as inband messages;
- A client processing model for Event Streams and Timed Metadata tracks is introduced;
- Extensions are added to content protection for efficient signalling and to support robustness levels.
- A descriptor is added in order to describe the minimum required device output protection security;
- More flexible bandwidth signalling is provided to signal variable bitrate encoding.

A list of all parts in the ISO/IEC 23009 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html) and <https://www.iec.ch/national-committees>.

## **Introduction**

Dynamic adaptive streaming over HTTP (DASH) is intended to support a media-streaming model for delivery of media content in which control lies primarily with the client. Clients may request data using the HTTP protocol from standard web servers that have no DASH-specific capabilities. Consequently, this document focuses not on client or server procedures but on the data formats used to provide a DASH Media Presentation.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO and IEC take no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured ISO and IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO and IEC.

# **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[ISO/IEC FDIS 23009-1](#)

<https://standards.iteh.ai/catalog/standards/sist/68e73f12-442e-4d43-84c9-7753705527a6/iso-iec-fdis-23009-1>

# Information technology — Dynamic adaptive streaming over HTTP (DASH) —

## Part 1: Media presentation description and segment formats

### 1 Scope

This document primarily specifies formats for the Media Presentation Description and Segments for dynamic adaptive streaming delivery of MPEG media over HTTP. It is applicable to streaming services over the Internet.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 13818-1, *Information technology — Generic coding of moving pictures and associated audio information — Part 1: Systems*

ISO/IEC 14496-12, *Information technology — Coding of audio-visual objects — Part 12: ISO base media file format*

ISO/IEC 23000-19, *Information technology — Multimedia application format (MPEG-A) — Part 19: Common media application format (CMAF) for segmented media*

ISO/IEC 23091-2, *Information technology — Coding-independent code points — Part 2: Video*

ISO/IEC 23091-3, *Information technology — Coding-independent code points — Part 3: Audio*

IETF RFC 2397, *The “data” URL scheme*

IETF RFC 3629, *UTF-8, a transformation format of ISO 10646*

IETF RFC 3986, *Uniform Resource Identifier (URI): Generic Syntax*

IETF RFC 4122, *A Universally Unique IDentifier (UUID) URN Namespace*

IETF RFC 4337, *MIME Type Registration for MPEG-4*

IETF RFC 4648, *The Base16, Base32, and Base64 Data Encodings*

IETF RFC 5234, *Augmented BNF for Syntax Specifications: ABNF*

IETF RFC 5261, *An Extensible Markup Language (XML) Patch Operations Framework Utilizing XML Path Language (XPath) Selectors*

IETF RFC 5646, *Tags for Identifying Languages*

IETF RFC 6381, *The ‘Codecs’ and ‘Profiles’ Parameters for “Bucket” Media Types*

IETF RFC 6838, *Media Type Specifications and Registration Procedures*

IETF RFC 7231, *Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content*

IETF RFC 7233, *Hypertext Transfer Protocol (HTTP/1.1): Range Requests*

IETF RFC 8141, *URN Syntax*

IETF RFC 8673, *HTTP Random Access and Live Content*

HTML 4.01 Specification, W3C Recommendation, 24 December 1999

W3C Canonical XML Version 1.1, W3C Recommendation, 2 May 2008

W3C Extensible Markup Language (XML) 1.0 (Fifth Edition), W3C Recommendation, 26 November 2008

W3C XLINK, XML Linking Language (XLink) Version 1.1, W3C Recommendation 06, May 2010

W3C Media Fragments URI 1.0 (basic), W3C Recommendation, 25 September 2012

### **3 Terms, definitions, symbols and abbreviated terms**

#### **3.1 Terms and definitions**

For the purposes of this document, the terms and definitions given in ISO/IEC 23000-19 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

##### **3.1.1**

##### **access unit**

unit of a *media stream* (3.1.29) with an assigned Media Presentation time

##### **3.1.2**

##### **accessibility**

degree to which a media content or certain *media content components* (3.1.22) are available to as many people as possible

##### **3.1.3**

##### **Adaptation Set**

set of interchangeable encoded versions of one or several *media content components* (3.1.22)

##### **3.1.4**

##### **asset**

content including media and metadata together with the rights to use the content by the content provider

**3.1.5****associated Representation**

*Representation* (3.1.38) which provides supplemental or descriptive information for at least one other *Representation*

**3.1.6****available Segment**

*Segment* (3.1.40) that is accessible at its assigned *HTTP-URL* (3.1.17) and a possibly assigned byte range that is the request with an HTTP GET results in a reply of the Segment and 2xx status code

**3.1.7****Bitstream Switching Segment**

*Segment* (3.1.40) that if present contains essential data to switch to the *Representation* (3.1.38) it is assigned to

**3.1.8****complementary Representation**

*Representation* (3.1.38) which complements at least one *dependent Representation* (3.1.12)

**3.1.9****continuous media**

media with an inherent notion of time

EXAMPLES      Speech, audio, video, timed text or timed metadata.

**3.1.10****DASH metric**

metric computed by the DASH Client and uniquely identified by a key

**3.1.11****data URL**

[ISO/IEC FDIS 23009-1](#)

URL with a fixed scheme "data"  
[http://www.iso.org/iso/iso\\_technical\\_committees/standards/sist/68e73f12-442e-4d43-84c9-7753705527a6/iso-iec-fdis-23009-1](http://www.iso.org/iso/iso_technical_committees/standards/sist/68e73f12-442e-4d43-84c9-7753705527a6/iso-iec-fdis-23009-1)

**3.1.12****dependent Representation**

*Representation* (3.1.38) for which *Segments* (3.1.40) from its *complementary Representations* (3.1.8) are necessary for presentation and/or decoding of the contained *media content components* (3.1.22)

**3.1.13****earliest presentation time**

smallest *presentation time* (3.1.36) of any *access unit* (3.1.1) of a *Media Segment* (3.1.28) Or *Subsegment* (3.1.50) for a *media stream* (3.1.29)

**3.1.14****event**

aperiodic sparse media-time related auxiliary information to the DASH Client or to an application

**3.1.15****event stream**

sequence of related *events* (3.1.14)

**3.1.16****group**

collection of *Adaptation Sets* (3.1.3) that are not expected to be presented simultaneously

**3.1.17**

**HTTP-URL**

URL with a fixed scheme of “http” or “https”

**3.1.18**

**Index Segment**

*Segment* (3.1.40) that primarily contains indexing information for *Media Segments* (3.1.28)

**3.1.19**

**Initialization Segment**

*Segment* (3.1.40) containing metadata that is necessary to present the *media streams* (3.1.29) encapsulated in *Media Segments* (3.1.28)

**3.1.20**

**Main Adaptation Set**

*Adaptation Set* (3.1.3) In A *Preselection* (3.1.35) that contains the *Initialization Segment* (3.1.19) for the complete experience

**3.1.21**

**media content**

single *media content period* (3.1.24) or contiguous sequence of media content periods

**3.1.22**

**media content component**

single continuous component of the *media content* (3.1.21) with an assigned *media content component type* (3.1.23)

(standards.iteh.ai)

**3.1.23**

**media content component type**

single type of *media content* (3.1.21)

[ISO/IEC FDIS 23009-1](#)

EXAMPLES https://standards.iteh.ai/catalog/standards/sist/68e73f12-442e-4d43-84c9-7753705527a6/iso-iec-fdis-23009-1

**3.1.24**

**media content period**

set of *media content components* (3.1.22) that have a common timeline as well as relationships on how they can be presented

**3.1.25**

**Media Presentation**

collection of data that establishes a bounded or unbounded presentation of *media content* (3.1.21)

**3.1.26**

**Media Presentation Description**

**MPD**

formalized description for a *Media Presentation* (3.1.25) for the purpose of providing a streaming service

**3.1.27**

**Media Presentation timeline**

concatenation of the timeline of all *Periods* (3.1.34) which itself is common to all *Representations* (3.1.38) in the Period

**3.1.28****Media Segment**

*Segment* (3.1.40) that complies with media format in use and enables playback when combined with zero or more preceding Segments and an *Initialization Segment* (3.1.19) (if any)

**3.1.29****media stream**

encoded version of a *media content component* (3.1.22)

**3.1.30****Media Subsegment**

*Subsegment* (3.1.50) that only contains media data but no *Segment Index* (3.1.44)

**3.1.31****message**

part of an *event* (3.1.14) containing information that is exclusively handled by the event handler

**3.1.32****MPD start time**

approximate presentation start time of a *Media Segment* (3.1.28) signalled in *MPD* (3.1.26)

**3.1.33****MPD duration**

approximate presentation duration of a *Media Segment* (3.1.28) signalled in *MPD* (3.1.26)

**3.1.34****Period**

interval of the *Media Presentation* (3.1.24), where a contiguous sequence of all Periods constitutes the Media Presentation

[ISO/IEC FDIS 23009-1](#)

**3.1.35****Preselection**

set of *media content components* (3.1.22) that are intended to be consumed jointly

**3.1.36****presentation time**

time associated to an *access unit* (3.1.1) that maps it to the *Media Presentation timeline* (3.1.27)

**3.1.37****remote element entity**

entity that contains one or more elements and is referenced in the *MPD* (3.1.26) with an *HTTP-URL* (3.1.17) contained in an @xlink:href attribute, referred to as "remote resource" by XLink

**3.1.38****Representation**

collection and encapsulation of one or more *media streams* (3.1.29) in a delivery format and associated with descriptive metadata

**3.1.39****Resynchronization Point**

point within a Segment from which it is possible to start processing the Representation

**3.1.40**

**Segment**

unit of data associated with an *HTTP-URL* (3.1.17) and optionally a byte range that are specified by an *MPD* (3.1.26), or with a *data URL* (3.1.11)

**3.1.41**

**Segment availability start time**

latest time instant in *wall-clock time* (3.1.53) at which a *Segment* (3.1.40) becomes an *available Segment* (3.1.6)

**3.1.42**

**adjusted Segment availability start time**

time instant in *wall-clock time* (3.1.53) at which a *Segment* (3.1.40) becomes an *available Segment* (3.1.6)

**3.1.43**

**Segment availability end time**

time instant in *wall-clock time* (3.1.53) at which a *Segment* (3.1.40) ceases to be an *available Segment* (3.1.6)

**3.1.44**

**Segment Index**

compact index of the time range to byte range mapping within a *Media Segment* (3.1.28) separately from the *MPD* (3.1.26)

iTeh STANDARD PREVIEW

**3.1.45**

**Segment Sequence**

sequence of *Segments* (3.1.40) that are sharing a common address prefix

**3.1.46**

[ISO/IEC FDIS 23009-1](#)

**Segment Track**

concatenation of *Segments* (3.1.40) forming a track with potential conformance properties

**3.1.47**

**spatial object**

*media content component* (3.1.22) corresponding to a region in a coordinate system associated to this media content component

**3.1.48**

**stream access point**

**SAP**

position in a *Representation* (3.1.38) enabling playback of a *media stream* (3.1.29) to be started using only the information contained in Representation data starting from that position onwards preceded by initializing data in the *Initialization Segment* (3.1.19), if any

**3.1.49**

**sub-asset**

*media content component* (3.1.22) (or part thereof) identified as corresponding to a part of an *asset* (3.1.4)

**3.1.50****Sub-Representation**

part of a *Representation* (3.1.38) described in the *MPD* (3.1.26) that is present in the entire *Period* (3.1.34)

**3.1.51****Subsegment**

unit within *Media Segments* (3.1.28) that is indexed by a *Segment Index* (3.1.44)

**3.1.52****valid Segment URL**

*HTTP-URL* (3.1.17) that is promised to reference a *Segment* (3.1.40) during its Segment availability period

**3.1.53****wall-clock time**

time as stated by UTC

## 3.2 Symbols and abbreviated terms

4CC	four character code
ABNF	augmented Backus-Naur form
ACK	acknowledgement message in TCP
AEMS	application event or metadata streams
API	application programming interface
AVC	advanced video coding
CAT	conditional access table
CDN	content delivery network
CMAF	common media application format
DASH	dynamic adaptive streaming over HTTP
DM	DASH metrics
DOM	document object model
DRM	digital rights management
ECM	entitlement control message
EIDR	entertainment identifier registry
EME	encrypted media extensions
EMIO	event/metadata internal object
EMM	entitlement management message
EPT	earliest presentation time
GAA	generic authentication architecture
GBA	generic bootstrapping architecture
GDR	gradual decoding refresh
GMT	Greenwich Mean Time