



Designation: C833 – 13

Standard Specification for Sintered (Uranium-Plutonium) Dioxide Pellets¹

This standard is issued under the fixed designation C833; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

INTRODUCTION

This specification is intended to provide the nuclear industry with a general standard for uranium-plutonium dioxide pellets for thermal reactor use. It recognizes the diversity of manufacturing methods by which uranium-plutonium dioxide pellets are produced and the many special requirements for chemical and physical characterization that may be imposed by the operating conditions to which the pellets will be subjected in specific reactor systems. It does not recognize the possible problems associated with the reprocessing of such pellets. It is, therefore, anticipated that the purchaser may supplement this specification with additional requirements for specific applications.

1. Scope

1.1 This specification covers finished sintered and ground (uranium-plutonium) dioxide pellets for use in thermal reactors. It applies to uranium-plutonium dioxide pellets containing plutonium additions up to 15 % weight (that is, 0.15 g Pu / g (U+Pu+Am)).

1.2 Pellets produced under this specification are available in four grades.

1.2.1 *Grade R*—²⁴⁰Pu content of (Pu+Am) (that is, g ²⁴⁰Pu / g (Pu+Am)) is at least 19 %.

1.2.2 *Grade F*—²⁴⁰Pu content of (Pu+Am) is at least 7 % and less than 19 %.

1.2.3 *Grade N1*—²⁴⁰Pu content of (Pu+Am) is less than 7 %.

1.2.4 *Grade N2*—²⁴⁰Pu / ²³⁹Pu does not exceed 0.10.

1.3 This specification does not include (1) provisions for preventing criticality accidents or (2) requirements for health and safety. Observance of this specification does not relieve the user of the obligation to be aware of and conform to all applicable international, federal, state, and local regulations pertaining to possessing, processing, shipping, or using source or special nuclear material. Examples of U.S. government documents are Code of Federal Regulations Title 10, Part 50—Domestic Licensing of Production and Utilization Facilities; Code of Federal Regulations Title 10, Part 71—Packaging and Transportation of Radioactive Material; and Code of

Federal Regulations Title 49, Part 173—General Requirements for Shipments and Packaging.

1.4 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.5 The following safety hazards caveat pertains only to the technical requirements portion, Section 4, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards*:²

[C698 Test Methods for Chemical, Mass Spectrometric, and Spectrochemical Analysis of Nuclear-Grade Mixed Oxides \(\(U, Pu\)O₂\)](#)

[C753 Specification for Nuclear-Grade, Sinterable Uranium Dioxide Powder](#)

[C757 Specification for Nuclear-Grade Plutonium Dioxide Powder, Sinterable](#)

[C859 Terminology Relating to Nuclear Materials](#)

[C1233 Practice for Determining Equivalent Boron Contents of Nuclear Materials](#)

[E105 Practice for Probability Sampling of Materials](#)

¹ This specification is under the jurisdiction of ASTM Committee C26 on Nuclear Fuel Cycle and is the direct responsibility of Subcommittee C26.02 on Fuel and Fertile Material Specifications.

Current edition approved Jan. 1, 2013. Published January 2013. Originally approved in 1976. Last previous edition approved in 2008 as C833 – 01(2008). DOI: 10.1520/C0833-13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

2.2 *ANSI Standard*.³

ANSI/ASME NQA-1 Quality Assurance Requirements for Nuclear Facility Applications

2.3 *U.S. Government Documents*.⁴

USNRC Regulatory Guide 1.126 An Acceptable Model and Related Statistical Methods for the Analysis of Fuel Densification

Code of Federal Regulations Title 10, Part 50 Domestic Licensing of Production and Utilization Facilities

Code of Federal Regulations Title 10, Part 71 Packaging and Transportation of Radioactive Material

Code of Federal Regulations Title 49, Part 173 General Requirements for Shipments and Packaging

3. Terminology

3.1 *Definitions*—Definitions shall be in accordance with Terminology C859.

4. Technical Requirements

4.1 *Chemical Requirements*—All chemical analyses shall be performed on portions of the representative sample prepared in accordance with Section 6. Analytical chemistry methods shall be as stated in Test Methods C698 (latest edition) or demonstrated equivalent as mutually agreed to between the buyer and the seller.

4.1.1 *Uranium and Plutonium Content*—Unless agreed upon by the buyer and seller, individual powders shall meet the requirements of Specifications C753 and C757. The uranium and plutonium contents combined shall be a minimum of 87.7 % weight on a dry weight basis compensated for the Am-241 content. (Dry weight is defined as the sample weight minus the moisture content). The plutonium content shall be that specified by the buyer, up to the limits covered in this specification (15 %).

4.1.2 *Impurity Content*—The impurity content shall not exceed the individual element limit specified in Table 1 based on the heavy metal content (uranium plus plutonium). The summation of the contribution of each of the impurity elements listed in Table 1 shall not exceed 1500 µg/g (U + Pu). If an element analysis is reported as “less than” a given concentration, this “less than” value shall be used in the determination of total impurities.

NOTE 1—Higher impurity limits should be acceptable for restricted burnups and linear power ratings if there is evidence to substantiate the relaxation. Higher impurity levels of 450 ppm aluminum, 250 ppm carbon, 250 ppm nitrogen, and 450 ppm silicon have been supported for

burnups of less than 35 000 MWd/t. The extension of the burnup limit may be determined by agreement between the buyer and seller as supporting data are accumulated.

4.1.3 *Stoichiometry*—The oxygen-to-heavy metal ratio of sintered fuel pellets shall be within the range from 1.98 to 2.02. The nominal value and allowable tolerance shall be agreed upon between the buyer and seller.

4.1.4 *Moisture Content*—The moisture content limit is included in the total hydrogen limit (see Table 1).

TABLE 1 Impurity Elements and Maximum Concentration Limits

Element	Maximum Concentration Limit (µg/g of U + Pu)
Aluminum	250
Carbon	100
Calcium + magnesium	200
Chlorine	25
Chromium	250
Cobalt	100
Fluorine	25
Hydrogen (total from all sources)	1.3
Iron	500
Nickel	250
Nitride/nitrogen	75
Silicon	250

4.1.5 *Gas Content*—The gas content, exclusive of moisture, shall not exceed, at Standard Temperature and Pressure (0°C and one atmosphere), 0.05 L/kg of the heavy metal content.

4.1.6 *Americium-241 Content*—The americium-241 content shall be measured by the seller and reported to the buyer. The americium-241 content or activity is important in the handling of UO₂-PuO₂ pellets and will vary with time. The maximum acceptable americium-241 content on a given date along with the date of analysis shall be agreed upon between the buyer and seller. The dates of separation of plutonium from this isotope and the analysis dates shall be considered; methods of reporting shall be agreed upon between the buyer and seller.

4.2 *Nuclear Requirements*:

4.2.1 *Isotopic Content*—The isotopic composition shall comply with the requirements of Table 2. The isotopic content of the americium, uranium, and plutonium in the (uranium-plutonium) dioxide pellets shall be determined and the date of the determination recorded. The ²³⁴U, ²³⁵U, ²³⁶U, and ²³⁸U content of the uranium shall be reported as a mass percentage with respect to total uranium, and the ²³⁸Pu, ²³⁹Pu, ²⁴⁰Pu, ²⁴¹Pu, and ²⁴²Pu content of the plutonium shall be reported on a Pu mass % or on (Pu + Am) mass % basis. The equivalent plutonium content based on uranium and plutonium isotopic concentrations shall be as agreed upon between the buyer and seller.

TABLE 2 Isotopic Requirements

Characteristic	Grade R	Grade F	Grade N1	Grade N2
²⁴⁰ Pu content, g ²⁴⁰ Pu/g (Pu+Am)	≥ 0.19	≥ 0.07 and < 0.19	< 0.07	...
²⁴⁰ Pu/ ²³⁹ Pu, g ²⁴⁰ Pu/g ²³⁹ Pu	≤ 0.10

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, http://www.ansi.org.

⁴ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http://www.access.gpo.gov.