



Designation: **D4615 – 06 D4615 – 12**

Standard Specification for *n*-Butyl Acetate (All Grades)¹

This standard is issued under the fixed designation D4615; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope*

- 1.1 This specification covers the various grades of *n*-butyl acetate suitable for use as solvents in paint and related coatings.
- 1.2 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.
- 1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.
- 1.4 For specific hazard information and guidance, see the supplier’s Material Safety Data Sheet for material listed in this specification.
- 1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

- D268 Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material
 - D891 Test Methods for Specific Gravity, Apparent, of Liquid Industrial Chemicals
 - D1078 Test Method for Distillation Range of Volatile Organic Liquids
 - D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)
 - D1296 Test Method for Odor of Volatile Solvents and Diluents
 - D1353 Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products
 - D1364 Test Method for Water in Volatile Solvents (Karl Fischer Reagent Titration Method)
 - D1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products
 - D3545 Test Method for Alcohol Content and Purity of Acetate Esters by Gas Chromatography
 - D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
 - D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry
 - E1 Specification for ASTM Liquid-in-Glass Thermometers
 - E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
 - E300 Practice for Sampling Industrial Chemicals
- #### 2.2 U.S. Federal Specification:
- PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of³

3. Properties

- 3.1 *n*-Butyl acetate shall conform to one of the requirements of one of the grades in Table 1.

¹ This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved June 1, 2006 Nov. 1, 2012. Published June 2006 January 2013. Originally approved in 1986. Last previous edition approved in 2004 2006 as D4615 – 95 (2001); D4615 – 06. DOI: 10.1520/D4615-06.10.1520/D4615-12.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard’s Document Summary page on the ASTM website.

³ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098.

*A Summary of Changes section appears at the end of this standard