

Pr-ISO-/FDIS 7581:2022(E)

ISO-/TC-330

Secretariat: AFNOR

Date: ~~2022-06-23~~2023-08-18

Evaluation of bactericidal activity of a non-porous antimicrobial surface used in a dry environment

iTeh STANDARD PREVIEW

FDIS stage

ISO/FDIS 7581

<https://standards.itih.ai/catalog/standards/sist/4da05ba8-b37d-4a55-b186-775b41dd9cee/iso-fdis-7581>

~~Edited DIS -
MUST BE USED
FOR FINAL
DRAFT~~

© ISO ~~2022~~2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
~~Email~~E-mail: copyright@iso.org
Website: ~~www.iso.org~~www.iso.org

Published in Switzerland

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 7581

<https://standards.iteh.ai/catalog/standards/sist/4da05ba8-b37d-4a55-b186-775b41dd9cee/iso-fdis-7581>

Contents—

Foreword	5
Introduction	6
1 Scope	1
2 Normative reference	1
3 Terms and definitions	1
4 Apparatus, reagents and materials	3
4.1 Test organisms	3
4.2 Culture media and reagents	3
4.3 Reference and test surfaces	5
4.3.1 General	5
4.3.2 Reference surfaces	5
4.3.3 Test surfaces	5
4.4 Apparatus and materials	6
5 Preparation of the test organism suspensions	8
5.1 Stock cultures of the test bacteria	8
5.2 Working culture of the test bacteria	8
5.3 Test suspensions	8
5.4 Quantifying of bacterial test suspensions	8
5.5 Calculation of the weighted mean bacteria concentration in the test suspensions	9
6 Evaluation method of the bactericidal activity of a non-porous surface and its efficacy	10
6.1 Obligatory experimental conditions	10
6.2 Test procedure	10
6.2.1 Sampling	10
6.2.2 Test (T_0 and T_{xh})	11
6.2.3 Reference surfaces (C_0 and C_{xh})	12
6.2.4 Validation (V_n)	12
7 Results	13
7.1 Determination of the number of viable bacteria	13
7.2 Verification of the methodology	14
7.3 Expression of results	14
7.3.1 Reduction	14
7.3.2 Conclusion: Bactericidal activity of non-porous surfaces	15
8 Test report	15
Annex A (normative) Corresponding obligatory reference strains	17
Annex B (informative) Standard test report of the measurement of the bactericidal activity of non-porous surfaces	18

<u>Annex C (informative) Examples of surface preparation protocols</u>	<u>21</u>
<u>Annex D (informative) Neutralizers</u>	<u>22</u>
<u>Annex E (informative) Technical guide to depositing the inoculum</u>	<u>24</u>
<u>Bibliography</u>	<u>27</u>

Foreword	4
Introduction	5
1 Scope	1
2 Normative reference	1
3 Terms and definitions	1
4 Apparatus, reagents and materials	3
4.1 Test organisms	3
4.2 Culture media and reagents	3
4.3 Reference and test surfaces	4
4.4 Apparatus and materials	6
5 Preparation of the test organism suspensions	7
5.1 Stock cultures of the test bacteria	7
5.2 Working culture of the test bacteria	7
5.3 Test suspensions	7
5.4 CFU Counting from bacterial test suspensions	8
5.5 Calculation of the weighted mean bacteria concentration in the test suspensions	8
6 Evaluation method of the bactericidal activity of a non-porous surface and its efficacy	9
6.1 Obligatory experimental conditions	9
6.2 Test procedure	10
7 Results	12
7.1 Determination of the number of viable bacteria	12
7.2 Verification of the methodology	13
7.3 Expression of results	13
8 Test report	14
Annex A (normative) Corresponding obligatory reference strains	16
Annex B (informative) Standard test report of the measurement of the bactericidal activity of non-porous surfaces	17
Annex C (informative) Examples of surface preparation protocols	20
Annex D (informative) Neutralizers	21
Annex E (informative) Technical guide to depositing the inoculum	23
Bibliography	25

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part_1. In particular, the different approval criteria needed for the different types of ISO ~~documents~~document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part_2 (see www.iso.org/directives).

~~Attention is drawn~~ISO draws attention to the possibility that ~~some of the~~ ~~elements~~implementation of this document may ~~be~~involve the ~~subject~~use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights, in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights. ~~Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).~~

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 330, *Surfaces with biocidal and antimicrobial properties*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Edited DIS -
MUST BE USED
FOR FINAL
DRAFT

Introduction

The surfaces in our environment can constitute significant reservoirs of bacteria and a risk to health that is essential to control.

In healthcare establishments, healthcare-associated infections (HAI) are a major cause of mortality and disability the world over. HAI affects 5 % to 15 % of hospital patients in developed countries and can affect 9 % to 37 % of patients admitted to intensive care units. Each year, about 1 in 25 U.S. hospital patients is diagnosed with at least one infection related to hospital care alone. At least five million HAI are estimated to occur in acute care hospitals in Europe, causing 135 000 deaths per year and approximately 25-million additional days spent in hospital, representing a financial cost of €13-billion to €24-billion.

In public transport, the risks of contamination between travellers are extremely high due to the frequency and number of contacts points. In establishments receiving the public, all common areas and collective spaces constitute a risk of the spread of pathogens microorganisms.

In the agri-food sector, microbial hazards are the highest risk amongst those that can impact consumer health, above malnutrition and chemical contaminants. In addition to the impact on health, the consequences of a case of contamination can be disastrous for the image and sustainability of a company. For instance:

- ~~Anan~~ estimated 600-million – almost 1 in 10-people in the world – fall ill after eating contaminated food and 420 000 die every year, resulting in the loss of 33-million healthy life years [disability-adjusted life years-].
- ~~US\$110-billion~~ is lost each year in productivity and medical expenses resulting from unsafe food in low- and middle-income countries.
- ~~Childrenchildren~~ under 5 years of age carry 40 % of the foodborne disease burden, with 125 000 deaths every year.
- ~~Diarrhoealdiarrhoeal~~ diseases are the most common illnesses resulting from the consumption of contaminated food, causing 550-million people to fall ill and 230 000 deaths every year.

The drive to control microbial risks extends to many other sectors (transport, pharmaceuticals, aeronautics, cosmetics, the phytosanitary sector, services, etc.), and even to the entire industrial manufacturing sector.

Pathogenic agents can be transmitted in a variety of ways, such as via food and water, via air (aerosols), via body contact with infected person and via surfaces contaminated by body secretions and fomites. Healthcare-associated infections, or infections acquired in healthcare settings are the most frequent adverse event in healthcare delivery worldwide. Hundreds of millions of patients are affected by ~~health-care~~healthcare-associated infections worldwide each year, leading to significant mortality and financial losses for health systems. Of every 100 hospitalized patients at any given time, 7 in developed and 10 in developing countries will acquire at least one healthcare-associated infection. Such infections annually account for 37 000 attributable deaths in Europe and potentially many more that can be related, and they account for 99 000 deaths in the USA. Amongst the available tools for reducing microbial risks, surfaces with biocidal properties can help to control cross-contaminations when used in combination with standard cleaning and disinfecting practice.

This document was written to address the need to demonstrate the biocidal efficacy of a surface under ambient conditions close to the conditions found in the field. The method described in this document simulates the contamination of a surface by a microdroplet. For example, this pathway of contamination is representative of a surface contamination following a sneeze (microdroplet post sneeze might have a mobility of several meters). The temperatures and humidity required for the test were defined in relation to conditions that are representative of the atmosphere in the healthcare facilities.

Numerous non-porous surfaces claim to perform a bactericidal function:

- ~~—~~surfaces of materials that have been treated with or include a biocidal product in order to give the material bactericidal properties, either temporarily or permanently.
- ~~—~~surfaces of materials, such as certain metals, that claim to have intrinsic bactericidal properties.

The method prescribes the representative basic strains to be tested. Additional strains may be tested, depending on the intended use. For a given use, further experiments including in use condition (soiling substances, ageing, adaption of environmental condition) are needed for demonstrating bactericidal activity of the tested surface as claimed.

This method will be revised in the near future to include interfering substances and to adapt strains/efficacy/contact time specifications to the needs of different sectors, in addition to the medical area. Ageing simulation testing will be produced soon by ISO/TC 330.

Surfaces with bactericidal properties supplement, but do not replace, the regular use of surface-treatment products, such as detergents, detergent-disinfectants and surface disinfectants which must be demonstrated to be compatible with maintaining the surface bactericidal activity.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 7581

<https://standards.iteh.ai/catalog/standards/sist/4da05ba8-b37d-4a55-b186-775b41dd9cee/iso-fdis-7581>

Edited DIS -
MUST BE USED
FOR FINAL
DRAFT

~~WARNING — Persons using this document shall have technical microbiological knowledge.~~

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 7581

<https://standards.iteh.ai/catalog/standards/sist/4da05ba8-b37d-4a55-b186-775b41dd9cee/iso-fdis-7581>

Evaluation of bactericidal activity of a non-porous antimicrobial surface used in a dry environment

WARNING — Persons using this document shall have technical microbiological knowledge.

1 Scope

This document specifies the test conditions and the levels of activity to determine the bactericidal activity of non-porous surfaces used in a dry environment. It defines a protocol to validate the bactericidal character of a surface and to measure its performance. It is not intended to be used to substantiate cleaning or disinfecting properties.

This document is applicable to surfaces claiming to have an activity against vegetative bacteria. The ~~obligatory~~ **obligatory** test conditions are defined in this document. It does not apply to porous surfaces.

It does not refer to methods for testing the toxicological and ecotoxicological properties of the surfaces. This document is used to measure bactericidal action, not bacteriostatic activity of a surface.

2 Normative reference

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12353, *Chemical disinfectants and antiseptics — Preservation of test organisms used for the determination of bactericidal (including Legionella), mycobactericidal, sporicidal, fungicidal and virucidal (including bacteriophages) activity* [775b41dd9cee/iso-fdis-7581](https://www.iso.org/obp/https://www.iso.org/obp/775b41dd9cee/iso-fdis-7581)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

bactericidal activity

capability of a surface to produce a reduction in the number of viable bacterial cells of representative *test organisms* (3.6)(3.6) under defined conditions without soil load, nor ageing test nor test conditions adaptation to a specific sector.

Note 1 to entry: Note to entry: At the moment this document does not include soiling or ageing condition.

3.2

bacteriostatic activity

capability of a surface to inhibit the growth of viable bacterial cells of representative *test organisms* (3.6)(3.6) under defined conditions

Note 1-to-entry: The term "bacteriostatic activity" cannot be used for claims according to this document.

3.3

additional condition

test conditions that are optional and not obligatory, that can be used for additional claims of *bactericidal activity* (3.1) regarding a surface

3.4

cleaning

all operations that achieve a level of cleanliness, appearance, comfort and hygiene

Note 1-to-entry: Such operations use, to varying degrees, the following combined factors: chemical action, mechanical action, temperature, duration of action

3.5

neutralizer

chemical agent or formulation that suppresses the residual microbicidal activity of a product or active substance from the surface to be tested for a specific test but does not inactivate or inhibit the *test organism* (3.6)(3.6)

3.6

test organism

strain of a microorganism selected to evaluate the antimicrobial activity of a surface for a standardized test

3.7

bactericidal surface

surface that irreversibly kill vegetative bacteria under defined conditions

Note 1-to-entry: The adjective "bactericidal" corresponds to the noun "bactericide".

3.8

reference surface

surface without any *bactericidal activity* (3.1) or properties, that is used to evaluate the quantity of culturable bacteria present at the moment when the bactericidal activity of the *test surface* (3.9)(3.9) is evaluated

3.9

test surface

surface claiming *bactericidal activity* (3.1)

Note 1-to entry: This method is suitable for testing any type of non-porous surfaces (~~Metals such as metals~~, plastic, glass, coated surfaces, etc.) as long as recovery of bacteria from the test surface shall not lose more than 1-log at T=0.

Note 2-to entry: Very hydrophobic surfaces, for which a drying time greater than 10 min (see 6.2.2)6.2.2) is necessary, cannot be tested according this method.

3.10

ambient light

light corresponding to a maximum value of ~~2000~~2 000 lux

Note 1-to-entry: Any specific light or light spectrum (e.g. strong light, UV, etc.) is not considered as ambient.

3.11

porous surface

surface permeable to water, air, or other fluids

4 Apparatus, reagents and materials

4.1 Test organisms

Bactericidal activity shall be evaluated using the following four strains:

- ~~—~~ *Pseudomonas aeruginosa* ATCC 15442 = CIP 103-467;
- ~~—~~ *Staphylococcus aureus* ATCC 6538 = CIP 4.83;
- ~~—~~ *Enterococcus hirae* ATCC 10541 = CIP 5855;
- ~~—~~ *Escherichia coli* ATCC 10536 = CIP 54127.

The reference strain numbers in other culture collections shall be in accordance with the strains specified in ~~Annex A.~~ Annex A.

The activity data can be completed with other strains using the experimental design described in this document, varying the conditions to meet the needs of the intended -practice application(s). If additional strains are used, they shall be incubated under optimum growth conditions (temperature, time, atmosphere) to be recorded in the test report.

Their suitability for supplying the inoculum and controls with a sufficient concentration shall be verified. If these additional test strains are not classified at a culture collection centre, their identification characteristics shall be stated. In addition, they shall be held by the testing laboratory or national culture collection under a reference for a five-year period.

NOTE ISO/TC 330 is currently adapting the method in terms of strains/efficacy levels/contact times/interfering substances according to different sectors' needs and to include not only the medical area.

4.2 Culture media and reagents

The reagents shall be of analytical grade and/or appropriate for microbiological purposes. They shall be free from substances that are toxic or inhibitory to the test organisms.

4.2.1 Water, which shall be free from any substances that are toxic or that inhibit the bacteria. It shall be freshly glass-distilled water or water for injection or possibly deionized or demineralized water.

Sterilize in the autoclave ~~(4.4.1).~~ (4.4.1).

NOTE If the water is sterilized during the sterilization of the reagents, this is not necessary.

4.2.2 Microbial suspension diluents

Tryptone-salt solution:

Tryptone, pancreatic digest of casein	1,0 g
Sodium chloride	8,5 g
Water (see <u>4.2.1</u>)	<u>4.2.1</u>	1,000 ml

Sterilize in the autoclave (see ~~4.4.1~~**4.4.1**). After sterilization, the pH of the medium shall be equivalent to $7,0 \pm 0,2$ when measured at 20 °C.

4.2.3 Liquid for bacteria recovery and for membrane rinsing

4.2.3.1 Composition:

Tryptone, pancreatic digest of casein _____ ~~1~~ **1,0**-g
 Sodium chloride _____
 8,5-g
 Polysorbate 80 _____
 5,0-g
 Water (see 4.2.1) _____ ~~1 000 ml~~

Water (see 4.2.1) _____ **1 000 ml**

4.2.3.2 Preparation:

- a) ~~a)~~ Dissolve the sodium chloride and tryptone in the water (see ~~4.2.2~~**4.2.2**). Add the Polysorbate 80, mix and complete up to ~~1 000~~ **1 000**-ml with water
- b) ~~b)~~ distribute into smaller adapted flasks. Sterilize in the autoclave.
- c) ~~c)~~ If necessary, add a neutralizer to the recovery liquid

The use of ~~ana~~ **ana** validated neutralizer of the respective antimicrobial is compulsory to warrant a correct test time for bacteria recovery and for membrane rinsing (see ~~4.2.3~~**4.2.3**): The functionality of the respective neutralizer shall be validated beforehand. The neutralizer:

- ~~—~~ shall be validated for the tested surface, as per ~~6.2.4.6.2.4~~ **6.2.4.6.2.4** and it shall be sterile;
- ~~—~~ shall be mentioned in the test report.

Examples of neutralizers are given in ~~Annex D~~ **Annex D**.

4.2.4 Agar for bacteria maintenance and counting (~~tryptone soya agar~~ **(TSA))**

Use agar to preserve the bacterial strains and count the viable bacteria.

Tryptone, pancreatic digest of casein _____ 15,0 g
 Soya peptone, papaic digest of soybean meal _____
 5,0 g
 Sodium chloride _____ 5,0 g
 Agar _____ 15,0 g
 Water (see ~~4.2.1~~ **4.2.1**) _____ ~~1 000 ml~~

Sterilize in the autoclave. After sterilization, the pH of the medium shall be equivalent to $7,2 \pm 0,2$ when measured at 20 °C. Pre pored plate TSA are acceptable if they meet the composition and ~~pH value describes~~ **pH value** ~~described~~ **described** in ~~4.2.4.4.2.4~~ **4.2.4.4.2.4**.