

Designation: D1141 - 98 (Reapproved 2013)

# Standard Practice for the Preparation of Substitute Ocean Water<sup>1</sup>

This standard is issued under the fixed designation D1141; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\varepsilon)$  indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

### 1. Scope

1.1 This practice covers the preparation of solutions containing inorganic salts in proportions and concentrations representative of ocean water.<sup>2</sup>

Note 1—Since the concentrations of ocean water varies with sampling location, the gross concentration employed herein is an average of many reliable individual analyses. Trace elements, occurring naturally in concentrations below  $0.005 \, \text{mg/L}$ , are not included.

- 1.2 This practice provides three stock solutions, each relatively concentrated but stable in storage. For preparation of substitute ocean water, aliquots of the first two stock solutions with added salt are combined in larger volume. An added refinement in adjustment of heavy metal concentration is provided by the addition of a small aliquot of the third stock solution to the previous solution.
- 1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.
- 1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

### 2. Referenced Documents

2.1 ASTM Standards:<sup>3</sup>

D1129 Terminology Relating to Water

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee D19 on Water and is the responsibility of Subcommittee D19.02 on Quality Systems, Specification, and Statistics.

Current edition approved Jan. 1, 2013. Published January 2013. Originally approved in 1950. Last previous edition approved in 2008 as D1141-98 (2008). DOI: 10.1520/D1141-98R13.

<sup>2</sup> This practice is based upon the following studies:

May and Black, "Synthetic Ocean Water," Naval Research Laboratory Report P-2909, August 1946.

May, T. P. and Alexander, A. L., "Spray Testing with Natural and Synthetic Sea Water, Part I–Corrosion Characteristics in the Testing of Metals," *Proceedings*, ASTM, Vol 50, 1950.

Alexander, A. L. and May, T. P., "Spray Testing with Natural and Synthetic Sea Water, Part II–A Study of Organic Coatings," *Proceedings*, ASTM, Vol 50, 1950.

<sup>3</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D1193 Specification for Reagent Water
E200 Practice for Preparation, Standardization, and Storage of Standard and Reagent Solutions for Chemical Analysis

## 3. Terminology

- 3.1 *Definitions*—For definitions of terms used in this practice, refer to Terminology D1129.
  - 3.2 Definitions of Terms Specific to This Standard:
- 3.2.1 *chlorinity*, , *n*—the weight of silver ion (g) required to completely precipitate the halides in 0.3285 kg of water (g/kg).

## 4. Significance and Use

- 4.1 This substitute ocean water may be used for laboratory testing where a reproducible solution simulating sea water is required. Examples are for tests on oil contamination, detergency evaluation, and corrosion testing.
- Note 2—The lack of organic matter, suspended matter, and marine life in this solution does not permit unqualified acceptance of test results as representing performance in actual ocean water. Where corrosion is involved, the results obtained from laboratory tests may not approximate those secured under natural testing conditions that differ greatly from those of the laboratory, and especially where effects of velocity, salt atmospheres, or organic constituents are involved. Also the rapid depletion of reacting elements present in low concentrations suggests caution in direct application of results.

#### 5. Reagents and Materials

- 5.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society.<sup>4</sup> Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.
- 5.2 *Purity of Water* Unless otherwise indicated, references to water shall be understood to mean reagent water conforming to Specification D1193, Type II.

<sup>&</sup>lt;sup>4</sup> Reagent Chemicals, American Chemical Society Specifications , American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see Analar Standards for Laboratory Chemicals, BDH Ltd., Poole, Dorset, U.K., and the United States Pharmacopeia and National Formulary, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD