INTERNATIONAL STANDARD

ISO/IEC 30193

Fourth edition 2021-12

Information technology — Digitally recorded media for information interchange and storage — 120 mm triple layer (100,0 Gbytes per disk) BD rewritable disk

Technologies de l'information — Supports enregistrés
Trumériquement pour échange et stockage d'information — Disques
BD réinscriptibles de 120 mm triple couche (100,0 Go par disque)
(Standards July 100,0 Go par disque)

ISO/IEC 30193:2021 https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-a5c536817c6f/iso-iec-30193-2021



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 30193:2021 https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-a5c536817c6f/iso-iec-30193-2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents			Page
Fore	eword		ix
Intr	oductio	n	X
1	Scope	e	1
2	-	1ative references	
3		is and definitions	
4		ools and abbreviated terms	
5		ormance	
	5.1 5.2	Optical diskGenerating system	
	5.3	Receiving system	
	5.4	Compatibility statement	
6	Conv	entions and notations	
U	6.1	Levels of grouping	
	6.2	Representation of numbers	
	6.3	Integer calculus	
7	Gene	ral description of disk	10
8		-	
O	8.1	ral requirements Environments STANDARD PREVIEW	11
	0.1	8.1.1 Test environment	11
		8.1.1 Test environment 8.1.2 Operating environment ds.iteh.ai	12
		8.1.3 Storage environment	13
		8.1.4 Transportation ISO/IEC 30193 2021	14
	8.2	Safety requirements ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-	14
	8.3	Flammability a5c536817c6ffiso-iec-30193-2021	
9	Reference drive		
	9.1	General	
	9.2 9.3	Measurement conditions Optical system	
	9.3 9.4	Optical beam	
	9.5	HF read channel	
	9.6	Radial PP read channel	17
	9.7	Disk clamping	17
	9.8	Rotation of disk and measurement velocity	
	9.9 9.10	Normalized servo transfer function Measurement velocities and reference servos for axial tracking	
	9.10	9.10.1 General	
		9.10.2 Reference servo for axial tracking for 1x measurement velocity	
		9.10.3 Reference servo for axial tracking for 2x measurement velocity	
	9.11	Measurement velocities and reference servos for radial tracking	21
		9.11.1 General	
		9.11.2 Reference servo for radial tracking for 1x measurement velocity	
		9.11.3 Reference servo for radial tracking for 2x measurement velocity	
10		ensional characteristics	
	10.1	General Pick of Control of Contro	
	10.2 10.3	Disk reference planes and reference axis Overall dimensions	
	10.3	First transition area	
	10.5	Protection ring	
	10.6	Clamping zone	26
	10.7	Second transition area	2.7

	10.8	Information area	27
		10.8.1 General	
		10.8.2 Subdivision of information zone on TL disk	
	10.9	Rim area	29
11	Mecha	anical characteristics	29
	11.1	Mass	29
	11.2	Moment of inertia	29
	11.3	Dynamic imbalance	
	11.4	Axial runout	
		11.4.1 General	
		11.4.2 Residual axial tracking error for 1x measurement velocity	
		11.4.3 Residual axial tracking error for 2x measurement velocity	
	11.5	Radial runout	
		11.5.1 General	
		11.5.2 Residual radial tracking error for 1x measurement velocity	
	11 (11.5.3 Residual radial tracking error for 2x measurement velocity	
	11.6	Durability of cover layer	
		11.6.2 Scratch resistance of cover layer	
		11.6.3 Repulsion of fingerprints by cover layer	
12		al characteristics in information area	
	12.1	General	
	12.2	Refractive index of transmission stacks (TS) Thickness of transmission stacks (TS) A.R.D. P.R.E.V.IE.VV	32
	12.3	Thickness of transmission stacks (TS) A.R. J. P.R. R. J. H. W. H. W. J. H.	32
	12.4	Example of target thickness of spacer layers for TL disks	33 25
	12.5 12.6	Reflectivity of recording (ayerindards.iteh.ai) Birefringence	35 26
	12.7	Angular deviation ISO/IEC 30193 2021	
13		format https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-	37
	13.1	General a5c536817c6f/iso-iec-30193-2021	
	13.2	Data frame	
	13.3	Error-detection code (EDC)	
	13.4 13.5	Scrambled data frame Data block	
	13.5	LDC block	
	13.7	LDC code words	
	13.7	LDC cluster	
	15.0	13.8.1 General	
		13.8.2 First interleaving step	
		13.8.3 Second interleaving step	
	13.9	Addressing and control data	
		13.9.1 General	
		13.9.2 Address units	45
		13.9.3 User control data	49
		13.9.4 Byte/Bit assignment for user control data	
		Access block	
		BIS block	
		BIS code words	
		BIS cluster	
		ECC cluster	
		Recording frames	
		Physical cluster	
	13.17	17PP modulation for recordable data	
		13.17.1 General	
		13.17.2Bit conversion rules 13.17.3dc-control procedure	
		13.17.4 Frame sync	
		13.17.71 ranic sync	00

	13.18	Modulation and NRZI conversion	62
14	Physi	ical data allocating and linking	62
	14.1	General	62
	14.2	Recording-unit block (RUB)	63
		14.2.1 General	
		14.2.2 Data run-in	
		14.2.3 Data run-out	
		14.2.4 Guard_3 field	
	14.3	Locating data relative to wobble addresses	66
		14.3.1 General	
		14.3.2 Start position shift (SPS)	66
15	Tracl	k format	68
	15.1	General	
	15.2	Track shape	68
		15.2.1 General	
		15.2.2 Groove geometry	
	15.3	Track path	
	15.4	Track pitch	
		15.4.1 Track pitch in BCA zone	
		15.4.2 Track pitch in embossed HFM areas	
		15.4.3 Track pitch in rewritable areas	
	455	15.4.4 Track pitch between embossed HFM area and rewritable area	70
	15.5	Track layout of HFM grooves 15.5.1 General STANDARD PREVIEW	70
		15.5.1 General	70
		15.5.2 Data format	/1
		15.5.3 Addressing and control data.iteh.ai)	72
	15 (15.5.4 Recording frames	
	15.6	Track layout of wobbled grooves _{30193,2021}	78 70
		15.6. https://dai.org/standards/sist/796dfe71-7c4e-44e8-b43e-	70
		15.6.2 Modulation of wobbles fire 30193-2021 15.6.3 Wobble polarity	
	15.7	ADIP information	
	13.7	15.7.1 General	
		15.7.2 ADIP unit types	
		15.7.3 ADIP word structure	
		15.7.4 ADIP data structure	
		15.7.5 ADIP error correction	
	15.8	Disk information (DI) in ADIP aux frame	
	20.0	15.8.1 General	
		15.8.2 Error protection for disk-information (DI) aux frames	
		15.8.3 Disk-Information (DI) data structure	
1.0	C		
16		ral description of information zone	
	16.1 16.2	General Format of information zone	
	_		
17	Layo	ut of rewritable area of information zone	
	17.1	General	
	17.2	Physical sector numbering	144
18	Innei	r zone	145
	18.1	General	
	18.2	Permanent information and control data (PIC) zone	
		18.2.1 General	
		18.2.2 Content of PIC zone	
		18.2.3 Emergency brake	
	18.3	Rewritable area of inner zone(s)	
		18.3.1 Protection zone 2	151
		18.3.2 Buffer	151

	18.3.3 INFO 2/Reserved 8	
	18.3.4 INFO 2/Reserved 7	
	18.3.5 INFO 2/Reserved 6	
	18.3.11 INFO 2/Control data 2	152
	18.3.12 OPC/Test zone	152
	18.3.13 Reserved	152
	18.3.14 INFO 1/Buffer 1	153
	18.3.15 INFO 1/Drive area (optional)	153
	·	
	iTeh STANDARD PREVIEW	154
	(standards.iteh.ai)	15/
	ISO/IFC 30193·2021	
	a5c536817c6f/iso-iec-30193-2021	
	18.3.22 INFO 1/Reserved	155
Outer	zone(s)	155
20.3	INFO 3/DMA 3	156
20.4		
20.4	INFO 3/Control data 3	
20.5	Angular buffer	156
20.5 20.6	Angular bufferINFO 4/DMA 4	156 156
20.5 20.6 20.7	Angular buffer	156 156 156
20.5 20.6 20.7 20.8	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4	156 156 156
20.5 20.6 20.7 20.8 20.9	Angular buffer. INFO 4/DMA 4. INFO 4/Control data 4. INFO 4/Buffer 4. DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone.	
20.5 20.6 20.7 20.8 20.9 20.10	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone Protection zone 3	
20.5 20.6 20.7 20.8 20.9 20.10 Physic	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3 cal-access control clusters	156 156 156 156 156 156
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1	Angular buffer. INFO 4/DMA 4. INFO 4/Control data 4. INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3 cal-access control clusters. General	156 156 156 156 156 156 156
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3 cal-access control clusters. General. Layout of PAC zones.	156 156 156 156 156 156 156 156
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2 21.3	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone Protection zone 3 cal-access control clusters. General Layout of PAC zones General structure of PAC clusters	156 156 156 156 156 156 156 156 157
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3 cal-access control clusters General Layout of PAC zones General structure of PAC clusters. Primary PAC cluster (mandatory)	156 156 156 156 156 156 156 157 157
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2 21.3 21.4	Angular buffer INFO 4/DMA 4 INFO 4/Control data 4 INFO 4/Buffer 4 DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone Protection zone 3 cal-access control clusters. General Layout of PAC zones General structure of PAC clusters	156 156 156 156 156 156 156 157 157 161
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2 21.3 21.4 21.5 21.6 Disk r	Angular buffer. INFO 4/DMA 4. INFO 4/Control data 4. INFO 4/Buffer 4. DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3. cal-access control clusters. General. Layout of PAC zones. General structure of PAC clusters. Primary PAC cluster (mandatory). Disk write-protect (DWP) PAC cluster (optional). IS1 and IS2 PAC clusters.	156 156 156 156 156 156 156 157 157 161 164 168
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2 21.3 21.4 21.5 21.6 Disk r 22.1	Angular buffer. INFO 4/DMA 4. INFO 4/Control data 4. INFO 4/Buffer 4. DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3. cal-access control clusters. General. Layout of PAC zones. General structure of PAC clusters. Primary PAC cluster (mandatory). Disk write-protect (DWP) PAC cluster (optional) IS1 and IS2 PAC clusters. management. General.	156 156 156 156 156 156 156 157 157 161 164 168 169
20.5 20.6 20.7 20.8 20.9 20.10 Physic 21.1 21.2 21.3 21.4 21.5 21.6 Disk r	Angular buffer. INFO 4/DMA 4. INFO 4/Control data 4. INFO 4/Buffer 4. DCZ 0/Test zone, DCZ 1/Test zone and DCZ 2/Test zone. Protection zone 3. cal-access control clusters. General. Layout of PAC zones. General structure of PAC clusters. Primary PAC cluster (mandatory). Disk write-protect (DWP) PAC cluster (optional). IS1 and IS2 PAC clusters.	156 156 156 156 156 156 156 156 157 157 161 164 168 169 170
	Outer 20.1 20.2	18.3.6 INFO 2/Reserved 5 18.3.7 INFO 2/PAC 2 18.3.8 INFO 2/Reserved 18.3.9 INFO 2/DMA 2 18.3.10 INFO 2/Buffer 2 18.3.11 INFO 2/Control data 2 18.3.12 OPC/Test zone 18.3.13 Reserved 18.3.14 INFO 1/Buffer 1 18.3.15 INFO 1/Drive area (optional) 18.3.16 INFO 1/Reserved 3 18.3.17 INFO 1/Reserved 2 18.3.18 INFO 1/Reserved 1

		22.2.2 Disk-definition structure (DDS) 22.2.3 Defect list (DFL)	
23	Assig	nment of logical-sector numbers (LSNs)	
24	_	acteristics of grooved areas	
25		180	
	25.1	General	180
	25.2	Environment	180
	25.3	Reference drive	
		25.3.1 General	
		25.3.2 Read power	
		25.3.3 Read channels	
		25.3.4 Tracking requirements	
	25.4	25.3.5 Scanning velocities Definition of signals	
	23.4	25.4.1 General	
		25.4.2 Push-pull signal	
		25.4.3 Wobble signal	
26	Signa	als from HFM grooves	
	26.1	Push-pull polarity	
	26.2	Push-pull signal	
	26.3	Wobble signal	183
	26.4	Jitter of HFM signal	183
27	Signa	Jitter of HFM signal	183
	27.1	Phase depth Push-pull signal (standards.iteh.ai)	183
	27.2		
	27.3	Wobble signal	184
		27.3.1 General <u>ISO/IEC 30193:2021</u>	184
		27.3.2 ^{tt} Measurement of I _{NWS} /standards/sist/796dfe71-7c4e-44e8-b43e- 27.3.3 Measurement of the wobble CNRl 23-2021	184
		27.3.4 Measurement of harmonic distortion of wobble	
28	Chara	acteristics of recording layer	
29		od of testing for recording layer	
49	29.1		
		Environment	
	29.3	Reference drive	
		29.3.1 General	185
		29.3.2 Read power	
		29.3.3 Read channels	
		29.3.4 Tracking requirements	
	20.4	29.3.5 Scanning velocities	
	29.4	Write conditions 29.4.1 Write-pulse waveform	
		29.4.2 Write powers	
		29.4.3 Average power	
		29.4.4 Write conditions for i-MLSE measurement	
		29.4.5 Write conditions for cross-erase measurements	
	29.5	Definition of signals	187
30	Signa	ıls from recorded areas	188
	30.1	HF signals	188
	30.2	Modulated amplitude	
	30.3	Reflectivity-modulation product	
	30.4	Asymmetry	
	30.5	i-MLSE@DOW(n)	
	30.6	Cross-erase @ DOW(n) _{XE}	190

	30.7	Read stability	190
31	Local	defects	191
32	Chara	acteristics of user data	191
33	Method of testing for user data 33.1 General		191
	33.2	Environment	
	33.3	Reference drive 33.3.1 General	
		33.3.2 Read power	
		33.3.3 Read channels	
		33.3.4 Error correction	
		33.3.5 Tracking requirements	
	00.4	33.3.6 Scanning velocities	
	33.4	Error signals	
		33.4.1 Byte error	
		33.4.3 Symbol error rate (SER)	
		33.4.4 Random symbol error rate (RSER)	
34	Minimum quality of recorded information		194
	34.1	General	
	34.2	Random symbol error rate (RSER)	
	34.3	Maximum burst errors	194
	34.4	User-written data ch STANDARD PREVIEW	
35	Burst	t-cutting area (BCA) (standards.iteh.ai) rmative) Thickness of transmission stacks (TSs) in case of multiple layers	194
Anne	x B (no	rmative) Measurement of reflectivity C 30193-2021	199
		rmative) Measurement of scratch resistance of cover layer	
Anne	x D (no	rmative) Measurement of repulsion of grime of cover layer	207
Anne	x E (no	rmative) Measurement of wobble amplitude	210
Anne	x F (no	rmative) Write-pulse waveform for testing	215
	-	rmative) Optimum power control (OPC) procedure for disk	
Anne	x H (1	normative) HF signal pre-processing for integrated-maximum likelihood ence error estimation (i-MLSE) measurements	225
Anne	x I (nor	mative) Measurement procedures	237
Anne	x J (info	ormative) Measurement of birefringence	249
Anne	x K (inf	Formative) Measurement of thickness of cover layer and spacer layer	251
Anne	x L (inf	ormative) Measurement of impact resistance of cover layer	254
Anne	x M (in	formative) Groove deviation and wobble amplitude	256
Anne	x N (inf	Formative) Guidelines for write pulse adjustment using L-SEAT edge-shift	258
Biblic	graph	y	267

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document is in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html (Standards.iteh.ai)

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digitally recorded media for information interchange and storage*.

This fourth edition cancels and replaces the third edition (ISO/IEC 30193:2020), which has been technically revised.

The main changes are as follows:

— The missing condition of pulse width regarding residual errors has been added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

In March 2002, the Blu-ray Disc Founders (BDF) came together to create optical-disk formats with large capacity and high-speed transfer rates that would be needed for recording and reproducing high-definition video content. This joint effort turned out to be fruitful and the first version of its Blu-ray $\operatorname{Disc}^{\mathsf{rm1}}$ Rewritable format Part 1 version 1.0, with cartridge, was issued in June 2002.

The Blu-ray Disc Association (BDA) issued version 2.1 of the Blu-ray Disc™ Rewritable format Part 1 in October 2005 and version 3.0, without cartridge, in June 2010.

To maintain compatibility of the removable medium in the market, a standard alone is not enough. It is necessary to check that the disks and devices can satisfy the specifications. The BDA also conducts verification activities for both disks and devices and has established more than 10 testing centers in Asia, Europe and the USA.

Blu-ray[™] disks, players, recorders and PC drives/software based on BDA standards became popular all over the world. The BDA gave consumer applications the highest priority in the first few years. But it was known, of course, that international standardization would be required before many government entities and their contractors would be allowed to use Blu-ray Disc™. In January and February 2011, the chairs of ISO/IEC JTC 1/SC 23 and JIIMA (Japan Image and information Management Association) formally requested the BDA to consider international standardization. The reason for this was to enable the inclusion of writable BDs along with DVDs and CDs in an international standard specifying the test methods for the estimation of a lifetime of optical storage media for long-term data storage. In October 2011, the President of the BDA responded that the organization had decided to pursue international standardization for the basic physical formats for the recordable and rewritable Blu-ray™ Formats.

In December 2011, the BDA sent project proposals for international standardization of four formats to ISO/IEC JTC 1/SC 23 via the Japanese national body. They are 120 mm single layer (25,0 Gbytes per disk) and dual layer (50,0 Gbytes per disk) BD recordable disks, 120 mm single layer (25,0 Gbytes per disk) and dual layer (50,0 Gbytes per disk) BD rewritable disks, 120 mm triple layer (100,0 Gbytes per disk) and quadruple layer (128,0 Gbytes per disk) BD recordable disks and 120 mm triple layer (100,0 Gbytes per disk) BD rewritable disk.

This document specifies the mechanical, physical and optical characteristics of a 120 mm rewritable optical disk with a capacity of 100,0 Gbytes.

A few additional specifications are required in order to write and read video-recording applications, such as BDAV format which had been specified by the BDA for use on BD rewritable disks. These specifications, which are related to the BD application (BDAP), the file system or the content-protection system, are required for the disk, the generating system and the receiving system. For more information about the BDAP, the content-protection system and the additional requirements for the Blu-ray $^{\text{M}}$ Format specifications, see http://www.blu-raydisc.info.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this document may involve the use of a patent.

ISO and IEC take no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured ISO and IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO and IEC. information may be obtained from the patent database available at www.iso.org/patents.

X

¹⁾ Blu-ray $^{\text{TM}}$ and Blu-ray Disc $^{\text{TM}}$ are the trademark of products supplied by Blu-ray Disc Association. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO or IEC of the product named.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those in the patent database. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 30193:2021 https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-a5c536817c6f/iso-iec-30193-2021

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 30193:2021

https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-a5c536817c6f/iso-iec-30193-2021

Information technology — Digitally recorded media for information interchange and storage — 120 mm triple layer (100,0 Gbytes per disk) BD rewritable disk

1 Scope

This document specifies the mechanical, physical and optical characteristics of a 120 mm rewritable optical disk with a capacity of 100,0 Gbytes. It specifies the quality of the recorded and unrecorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. User data can be written, read and overwritten many times using a reversible method. This disk is identified as a BD rewritable disk.

This document specifies the following:

- the one disk type;
- the conditions for conformance;
- the environments in which the disk is to be operated and stored;
- the mechanical and physical characteristics of the disk, in order to provide mechanical interchange between data processing systems;
 standards.iteh.ai
- the format of the information on the disk, including the physical disposition of the tracks and sectors;
- the error-correcting codes and the coding method used; https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-
- the characteristics of the signals recorded on the disk? enabling data processing systems to read data from the disk.

This document provides for interchange of disks between disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 646, Information technology — ISO 7-bit coded character set for information interchange

ISO 9352, Plastics — Determination of resistance to wear by abrasive wheels

IEC 60068-2-2, Environmental testing — Part 2-2: Tests — Test B: Dry heat

IEC 60068-2-30, Environmental testing — Part 2-30: Tests — Test Db: Damp heat, cyclic (12 h + 12 h cycle)

IEC 60950-1, Information technology equipment — Safety — Part 1: General requirements

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1

BD

disk having a *cover layer* (3.4) around 0,1 mm thick and a *substrate* (3.43) around 1,1 mm thick on which data is read or recorded by an optical pick-up unit (OPU) using 405 nm laser diode and numerical aperture, NA = 0,85 lens

Note 1 to entry: User data recorded on a disk is formatted using 17PP modulation and an LDC+BIS Code.

3.2

BD application

BDAP

contents standard specified for a BD (3.1), e.g. a video application, which requires area for a content-protection system and for its own defect-management system on the disk

3.3

channel bit

cbs

element by which the binary value ZERO or ONE is represented by *pits* (3.27), *marks* (3.19) and *spaces* (3.42) on a disk

3.4

iTeh STANDARD PREVIEW

cover layer transparent layer with precisely controlled optical properties that covers the *recording layer* (3.33) closest to the *entrance surface* (3.10) of a disk

ISO/IEC 30193:2021

3.5 data zone *n*

https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-

a5c536817c6f/iso-jec-30193-2021

area between the inner zone and the outer zone on *layer Ln* (3.17)

3.6

defective cluster

cluster in a *user-data area* (3.47) that has been registered in a defect list as unreliable or uncorrectable

3.7

DSV

digital-sum value

arithmetic sum obtained from a bit stream by assigning the decimal value +1 to channel bits (3.3) set to ONE and the decimal value -1 to channel bits set to ZERO

3.8

disk reference plane

plane defined by the perfect flat annular surface of an ideal spindle, onto which the clamping zone of a disk is clamped, that is normal to the axis of rotation

3.9

embossed HFM area

area on a disk where information has been stored by means of an HFM groove (3.13) during manufacturing of the disk

3.10

entrance surface

surface of a disk onto which the optical beam first impinges

3.11

erased groove

blank *groove* (3.12) on a disk that has been erased by irradiating the track (3.44) using only erase power level, P_{EO} , as determined by the OPC algorithm

3.12

groove

trench-like feature of a disk connected to a recording layer (3.33)

Note 1 to entry: In case of triple-layer disk, one groove can be carried by the *substrate* (3.43) and other grooves can be carried by the *spacer layer* (3.41) or the *cover layer* (3.4) (see Figure 1) grooves are used to define the *track* (3.44) locations.

In the BD rewritable system, there are 3 types of grooves:

- wobbled groove (3.49) in rewritable area containing address information;
- *HFM groove* (3.13) in *embossed HFM area* (3.9) containing permanent information and control data;
- straight groove without any modulation in the BCA zone.

3.13

HFM groove

high-frequency modulated groove

groove (3.12) modulated in the radial direction with a rather high bandwidth signal

Note 1 to entry: HFM groove creates a data channel with sufficient capacity and data rate for replicated information.

3.14

(standards.iteh.ai)

information area

area on a disk in which information can be recorded 2021

3.15

https://standards.iteh.ai/catalog/standards/sist/796dfe71-7c4e-44e8-b43e-a5c536817c6f/iso-iec-30193-2021

nformation zono

information zone

recorded part of the information area (3.14)

3.16

land

surface of a recording layer (3.33) between successive windings of a groove (3.12)

3.17

laver Ln

one recording layer (3.33) of a disk identified by n

Note 1 to entry: layer L(n+1) is closer to the *entrance surface* (3.10) of a disk than layer Ln.

3.18

laver type

identification of a disk using the number of layer(s)

Note 1 to entry: In case of triple-layer disk, the layer type is TL (see <u>Clause 7</u>).

3.19

mark

feature of a *recording layer* (3.33), which can take the form of an amorphous domain in the crystalline recording stack due to recording, that can be sensed by an optical read-out system

Note 1 to entry: The pattern of marks and *spaces* (3.42) represents the data on a disk.

3.20

mark polarity

polarity of reflectivity change when marks (3.19) are recorded