



International
Standard

ISO 10882-1

Health and safety in welding and
allied processes — Sampling of
airborne particles and gases in the
operator's breathing zone —

Part 1:
Sampling of airborne particles

*Hygiène et sécurité en soudage et techniques connexes —
Échantillonnage des particules en suspension et des gaz dans la
zone respiratoire des opérateurs —*

Partie 1: Échantillonnage des particules en suspension

Third edition

PROOF/ÉPREUVE

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/PRF 10882-1](#)

<https://standards.iteh.ai/catalog/standards/iso/417477f9-5b17-42f8-b566-75366192a511/iso-prf-10882-1>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

PROOF/ÉPREUVE

© ISO 2024 – All rights reserved

Contents

| | Page |
|--|-----------|
| Foreword | v |
| Introduction | vi |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 3.1 General definitions..... | 2 |
| 3.2 Sampling definitions..... | 3 |
| 3.3 Welding terms..... | 5 |
| 3.4 Statistical terms..... | 6 |
| 4 Principle | 6 |
| 5 Requirement | 7 |
| 6 Equipment | 7 |
| 6.1 Sampling equipment..... | 7 |
| 6.2 Weighing equipment, if required..... | 8 |
| 7 Assessment strategy | 9 |
| 8 Measurement strategy | 9 |
| 8.1 General..... | 9 |
| 8.2 Personal exposure measurement..... | 9 |
| 8.3 Fixed-point measurements..... | 9 |
| 8.4 Selection of measurement conditions and measurement pattern..... | 10 |
| 8.4.1 General..... | 10 |
| 8.4.2 Screening measurements of time-weighted average concentration and worst-case measurements..... | 10 |
| 8.4.3 Measurements for comparison with limit values and periodic measurements..... | 10 |
| 9 Procedure | 11 |
| 9.1 Preliminary considerations..... | 11 |
| 9.1.1 Selection of exposure metric(s)..... | 11 |
| 9.1.2 Selection and use of samplers..... | 11 |
| 9.1.3 Selection of sampling period..... | 11 |
| 9.1.4 Consideration of temperature and pressure effects..... | 12 |
| 9.2 Preparation for sampling..... | 12 |
| 9.2.1 Cleaning of samplers..... | 12 |
| 9.2.2 Loading collection substrates into samplers..... | 12 |
| 9.2.3 Setting of flow rate..... | 12 |
| 9.3 Sampling position..... | 13 |
| 9.3.1 Personal sampling position..... | 13 |
| 9.3.2 Fixed-point sampling position..... | 13 |
| 9.4 Sampling..... | 13 |
| 9.5 Transportation..... | 14 |
| 9.6 Analysis..... | 14 |
| 9.6.1 Gravimetric analysis of samples..... | 14 |
| 9.6.2 Chemical analysis of samples..... | 14 |
| 9.7 Expression of results..... | 15 |
| 9.7.1 Concentration of airborne particles and/or chemical agent(s) of interest..... | 15 |
| 9.7.2 Calculation of the time-weighted average concentration..... | 15 |
| 9.7.3 Temperature and pressure correction for the indicated sampling flow rate..... | 15 |
| 10 Exposure assessment | 16 |
| 11 Recording of sampling data and presentation of results | 16 |
| Annex A (normative) Gravimetric analysis | 17 |

ISO 10882-1:2024(en)

| | |
|--|-----------|
| Annex B (informative) Examples of arrangements for mounting samplers | 19 |
| Annex C (informative) An example of a report | 28 |
| Annex D (informative) Blank report form | 31 |
| Bibliography | 34 |

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO/PRF 10882-1](https://standards.iteh.ai/catalog/standards/iso/417477f9-5b17-42f8-b566-75366192a511/iso-prf-10882-1)

<https://standards.iteh.ai/catalog/standards/iso/417477f9-5b17-42f8-b566-75366192a511/iso-prf-10882-1>

PROOF/ÉPREUVE

© ISO 2024 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 44, *Welding and allied processes*, Subcommittee SC 9, *Health and safety*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 121, *Welding and allied processes*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 10882-1:2011), which has been technically revised.

<https://standards.iteh.ai/catalog/standards/iso/417477f9-5b17-42f8-b566-75366192a511/iso-prf-10882-1>

The main changes are as follows:

- references to other documents have been updated;
- in [8.2](#) and [9.3.1.1](#), alternative personal sampling position(s) for air-fed welder's helmets and sampling methods with more than one collection device have been added.

A list of all parts in the ISO 10882 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html. Official interpretations of ISO/TC 44 documents, where they exist, are available from this page: <https://committee.iso.org/sites/tc44/home/interpretation.html>.

Introduction

The health of workers in many industries is at risk through exposure by inhalation to airborne particles generated by welding and allied processes (welding fumes) and other airborne particles generated by welding-related operations, such as grinding. Industrial hygienists and other public health professionals need to determine the effectiveness of measures taken to control workers' exposure to these harmful substances and this is generally achieved by making personal exposure measurements.

This document is intended to be of benefit to agencies concerned with health and safety at work, industrial hygienists and other public health professionals, industrial users of welding and allied processes and their workers, and analytical laboratories.

It has been assumed in the drafting of this document that the execution of its provisions, and the interpretation of the results obtained, is entrusted to appropriately qualified and experienced people.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO/PRF 10882-1](https://standards.iteh.ai/catalog/standards/iso/417477f9-5b17-42f8-b566-75366192a511/iso-prf-10882-1)

<https://standards.iteh.ai/catalog/standards/iso/417477f9-5b17-42f8-b566-75366192a511/iso-prf-10882-1>

Health and safety in welding and allied processes — Sampling of airborne particles and gases in the operator's breathing zone —

Part 1: Sampling of airborne particles

1 Scope

This document specifies a procedure for sampling airborne particles in the breathing zone of a person who performs welding and allied processes (the operator). It also provides details of relevant standards that specify required characteristics, performance requirements and test methods for workplace air measurement, and augments guidance provided in EN 689 on assessment strategy and measurement strategy.

This document also specifies a procedure for making gravimetric measurements of personal exposure to airborne particles generated by welding and allied processes (welding fumes) and other airborne particles generated by welding-related operations.

Additionally, it provides references to suitable methods of chemical analysis specified in other standards to determine personal exposure to specific chemical agents present in welding fumes and other airborne particles generated by welding-related operations.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7708:1995, *Air quality — Particle size fraction definitions for health-related sampling*

ISO 15767, *Workplace atmospheres — Controlling and characterizing uncertainty in weighing collected aerosols*

ISO 18158, *Workplace air — Terminology*

EN 482, *Workplace exposure — General requirements for the performance of procedures for the measurement of chemical agents*

EN 13205-1, *Workplace exposure — Assessment of sampler performance for measurement of airborne particle concentrations — Part 1: General requirements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 7708 and in ISO 18158 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 General definitions

3.1.1

chemical agent

chemical element or compound, on its own or admixed, as it occurs in the natural state or as produced, used or released, including release as waste, by any work activity, whether or not produced intentionally and whether or not placed on the market

[SOURCE: Council Directive 98/24/EC, Art. 2 a)]

3.1.2

breathing zone

space around the nose and mouth from which breath is taken

Note 1 to entry: Technically, the breathing zone corresponds to a hemisphere (generally accepted to be 30 cm in radius) extending in front of the human face, centred on the midpoint of a line joining the ears. The base of the hemisphere is a plane through this line, the top of the head and the larynx. This technical description is not applicable when respiratory protective equipment is used.

[SOURCE: ISO 18158:2016, 2.1.5.5]

3.1.3

exposure

<inhalation> situation in which a *chemical agent* (3.1.1) or biological agent is present in the air that is inhaled by a person

[SOURCE: ISO 18158:2016, 2.1.5.1]

3.1.4

occupational exposure limit value

OELV

limit of the time-weighted average of the concentration of a *chemical agent* (3.1.1) in the air within the *breathing zone* (3.1.2) of a worker in relation to a specified reference period

Note 1 to entry: Limit values are mostly set for reference periods of 8 h, but can also be set for shorter periods or concentration excursions. Limit values for gases and vapours are stated in terms independent of temperature and air pressure variables in millilitres per cubic metre, and in terms dependent on those variables in milligrams per cubic metre, for a temperature of 20 °C and a pressure of 101,3 kPa. Limit values for airborne particles, as well as mixtures of particles and vapours, are given in milligrams per cubic metre or multiples of that unit for actual environmental conditions (temperature, pressure) at the workplace. Limit values of fibres are given in number of fibres per cubic metre or number of fibres per cubic centimetre for actual environmental conditions (temperature, pressure) at the workplace.

[SOURCE: Council Directive 98/24/EC, Art. 2 d), modified — Note 1 to entry added.]

3.1.5

reference period

specified period of time for which the *occupational exposure limit value* (3.1.4) of a *chemical agent* (3.1.1) or biological agent applies

Note 1 to entry: The reference period is usually 8 h for long-term measurements and 15 min for short-term measurements.

[SOURCE: ISO 18158:2016, 2.1.5.7]

3.1.6

time-weighted average concentration

TWA concentration

concentration of a *chemical agent* (3.1.1) in the atmosphere, averaged over a reference period

[SOURCE: ISO 25901-2:2022, 3.3.10, modified — “<occupational health>” deleted as the domain for the definition.]

3.1.7

total airborne particles

all particles surrounded by air in a given volume of air

Note 1 to entry: Because all measuring instruments are size selective to some extent, it is often impossible to measure the total airborne particle concentration.

[SOURCE: ISO 7708:1995, 2.13]

3.1.8

workplace

designated area or areas in which the work activities are carried out

[SOURCE: ISO 18158:2016, 2.1.6.2]

3.2 Sampling definitions

3.2.1

sample

air sample

product of the process of (air) *sampling* (3.2.2)

Note 1 to entry: An air sample is frequently considered to include the collection substrate(s) as well as the collected *chemical agents* (3.1.1) and/or biological agents; or sometimes it is considered to be the fractional part of a larger volume of air.

[SOURCE: ISO 18158:2016, 2.2.1.1, modified — “<workplace air quality>” deleted as the domain for the definition.]

3.2.2

sampling

air sampling

process consisting of the separation of *chemical agents* (3.1.1) and/or biological agents from air or the withdrawal or isolation of a fractional part of a larger volume of air

[SOURCE: ISO 18158:2016, 2.2.3.1, modified — “<workplace air quality>” deleted as the domain for the definition.]

3.2.3

collection substrate

sampling substrate

collection medium

sampling medium

medium on which airborne *chemical agents* (3.1.1) and/or biological agents are collected for subsequent analysis

Note 1 to entry: Filters, polyurethane foams and sampling cassettes are examples of collection substrates for airborne particles.

[SOURCE: ISO 18158:2016, 2.2.3.7, modified — Note 2 and Note 3 to entry were deleted]

3.2.4

inhalable fraction

mass fraction of *total airborne particles* (3.1.7) which are capable of being inhaled through the nose and mouth

Note 1 to entry: The inhalable fraction depends on the speed and direction of the air movement, the rate of breathing and other factors.

[SOURCE: ISO 7708:1995, 2.3, modified — Definition revised.]

3.2.5

inhalable sampler

aerosol sampler that is used to collect the *inhalable fraction* (3.2.4) of airborne particles from the surrounding air

[SOURCE: ISO 18158:2016, 2.2.2.1.6.1]

3.2.6

key component of welding fume

component of *welding fume* (3.3.9) that has the greatest occupational hygienic significance and therefore requires the most stringent control measures to ensure that a welder is not exposed to an excessive level of the substance concerned, i.e. it is the component whose limit value is exceeded at the lowest *welding fume* (3.3.9) concentration

[SOURCE: ISO 15011-4:2017, 3.3]

3.2.7

personal sample

product of the process of using a *sampler* (3.2.12), attached to a person, to collect gases, vapours and/or airborne particles in the breathing zone for the purpose of measuring exposure to *chemical agents* (3.1.1) and/or biological agents

[SOURCE: ISO 18158:2016, 2.2.1.3]

3.2.8

personal sampler

sampler (3.2.12), attached to a person, that collects gases, vapours or airborne particles in the *breathing zone* (3.1.2) for the purpose of measuring exposure to *chemical agents* (3.1.1) and/or biological agents

[SOURCE: ISO 18158:2016, 2.2.2.2]

3.2.9

personal sampling

process of using a *sampler* (3.2.12), attached to a person, to collect gases, vapours or airborne particles in the *breathing zone* (3.1.2) for the purpose of measuring exposure to *chemical agents* (3.1.1) and/or biological agents, representative of the exposure being evaluated

[SOURCE: ISO 18158:2016, 2.2.3.3, modified — Definition revised.]

3.2.10

respirable fraction

mass fraction of inhaled particles capable of penetration to the unciliated airways

[SOURCE: ISO 7708:1995, 2.11, modified — Definition revised.]

3.2.11

respirable sampler

aerosol sampler that is used to collect the respirable fraction of airborne particles from the surrounding air

[SOURCE: ISO 18158:2016, 2.2.2.1.6.3]

3.2.12

sampler

air sampler

device for separating and/or collecting *chemical agents* (3.1.1) and/or biological agents from the surrounding air

Note 1 to entry: (Air) samplers are generally designed for a particular purpose, for example for sampling gases and vapours or for sampling airborne particles.

[SOURCE: ISO 18158:2016, 2.2.2.1, modified — “<workplace air quality>” deleted as domain.]

3.2.13

screening measurements of time-weighted average concentration

measurements performed to obtain basic information on the exposure level in order to decide whether an exposure problem exists and, if so, to further investigate it

Note 1 to entry: Screening measurements of time-weighted average concentration can also be used to determine if exposure is well below or well above the limit value. For more information see EN 482.

3.2.14

worst-case measurements

screening measurements of time-weighted average concentration made to identify work activity during which highest exposure occurs

3.3 Welding terms

3.3.1

filler material

welding consumable added during welding to form the weld

EXAMPLE Welding rods, wire, stick electrodes.

[SOURCE: ISO/TR 25901-1:2016, 2.1.10.4, modified — Examples added.]

3.3.2

harness

assembly that provides a means of maintaining a *welder's face shield* (3.3.6) in position on the head

[SOURCE: EN 175:1997, 3.7]

3.3.3

headband

part of the *harness* (3.3.2) to which the *welder's face shield* (3.3.6) is fixed and which surrounds the head, or that part of the *welder's goggles* (3.3.7) or *welder's spectacles* which secures the goggles or spectacles onto the head

[SOURCE: EN 175:1997, 3.8, modified — Definition revised.] 2-1

3.3.4

operator

welder

person who performs *welding and allied processes* (3.3.8)

3.3.5

operator's breathing zone

restricted *breathing zone* (3.1.2)

Note 1 to entry: It is essential to sample as near as possible to the operator's nose and mouth when measuring exposure to *welding fumes* (3.3.9) because of the very steep concentration gradients that occur in the immediate vicinity of the plume.

3.3.6

welder's face shield

welder's shield worn on the head and in front of the face, usually secured in position by a *harness* (3.3.2) to give protection to the eyes and face when fitted with the appropriate filter(s)

[SOURCE: EN 175:1997, 3.2]

3.3.7

welder's goggles

device, held in position usually by a *headband* (3.3.3), enclosing the orbital cavity, into which radiation arising from *welding and allied processes* (3.3.8) can penetrate only through filter(s) and, where provided, filter cover(s)

[SOURCE: EN 175:1997, 3.5]

3.3.8

welding and allied processes

surfacing or joining process, producing a continuity in the nature of the workpiece material(s) by means of heat or pressure or both, and with or without the use of *filler material* (3.3.1)

Note 1 to entry: Low-temperature processes such as soldering are excluded.

[SOURCE: ISO/TR 25901-1:2016, 2.1.1.1, modified — Term and definition revised, note 1 to entry replaced.]

3.3.9

welding fume

airborne particles generated during *welding and allied processes* (3.3.8)

[SOURCE: ISO 25901-2:2022, 3.1.8, modified — Definition revised and note to entry removed.]

3.3.10

welding-related operations

operations other than *welding and allied processes* (3.3.8) carried out by the operator

3.4 Statistical terms

3.4.1

measurand

quantity intended to be measured

[SOURCE: ISO/IEC Guide 99:2007, 2.3, modified — Notes to entry and examples deleted.]

3.4.2

measurement uncertainty

uncertainty of measurement

uncertainty

non-negative parameter characterizing the dispersion of the quantity values being attributed to a *measurand* (3.4.1), based on the information used

Note 1 to entry: The parameter can be, for example, a standard deviation called standard measurement uncertainty (or a specified multiple of it), or the half-width of an interval, having a stated coverage probability.

Note 2 to entry: Measurement uncertainty comprises, in general, many components. Some of these can be evaluated by Type A evaluation of measurement uncertainty from the statistical distribution of the quantity values from series of measurements and can be characterized by standard deviations. The other components, which can be evaluated by Type B evaluation of measurement uncertainty, can also be characterized by standard deviations, evaluated from probability density functions based on experience or other information.

[SOURCE: ISO/IEC Guide 99:2007, 2.26, modified — Notes 1 and 4 to entry deleted.]

4 Principle

Airborne particles are collected by drawing a known volume of air through a collection substrate, for example a filter, mounted in a sampler designed to collect the appropriate fraction of airborne particles. For personal sampling, the sampler is positioned in the operator's breathing zone. In such instances, it is necessary to use a mounting arrangement that enables the sampler to be maintained in position in the operator's breathing zone throughout the sampling period without impeding normal work activity. Exposure to airborne particles from welding and allied processes (welding fume) and airborne particles from welding-