



Designation: D7008 – 08 (Reapproved 2013)

Standard Specification for Geosynthetic Alternate Daily Covers¹

This standard is issued under the fixed designation D7008; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers the requirements for reusable and nonreusable geosynthetic alternate daily covers (ADCs) used on the working face of municipal solid waste landfills (MSWLF). Geosynthetic ADCs include a wide range of products including, but not limited to, reinforced film, unreinforced film, reinforced sheet, unreinforced sheet, coated geotextile and uncoated geotextile.

1.2 This standard addresses the base ADC materials and does not address grommets, straps or other fabricated parts.

1.3 The values stated in SI units are to be regarded as the standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

D882 Test Method for Tensile Properties of Thin Plastic Sheeting

D1004 Test Method for Tear Resistance (Graves Tear) of Plastic Film and Sheeting

D4355 Test Method for Deterioration of Geotextiles by Exposure to Light, Moisture and Heat in a Xenon Arc Type Apparatus

¹ This specification is under the jurisdiction of ASTM Committee D35 on Geosynthetics and is the direct responsibility of Subcommittee D35.06 on Geosynthetic Specifications.

Current edition approved Jan. 1, 2013. Published January 2013. Originally approved in 2003. Last previous edition approved in 2008 as D7008-08. DOI: 10.1520/D7008-08R13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D4439 Terminology for Geosynthetics

D4533 Test Method for Trapezoid Tearing Strength of Geotextiles

D4632 Test Method for Grab Breaking Load and Elongation of Geotextiles

D4833 Test Method for Index Puncture Resistance of Geomembranes and Related Products

E96/E96M Test Methods for Water Vapor Transmission of Materials

2.2 Other Standards:

National Fire Protection Association (NFPA) 701 Standard Methods of Fire Tests for Flame Propagation of Textiles
Geosynthetic Research Institute (GRI) Specification GM11 Accelerated Weathering of Geomembranes using a Fluorescent UVA-Condensation Exposure Device

3. Terminology

3.1 *Definitions*—For definitions of terms related to geosynthetics, refer to Terminology D4439.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *alternate daily cover, n*—an alternative to the traditional 15 cm (6 in.) soil cover required by the USEPA for landfill working faces to “control disease vectors, fires, odors, blowing litter, and scavenging, without presenting a threat to human health and the environment.”

3.2.2 *fire retardant, adj*—in geosynthetic ADCs, meeting the requirements of NFPA 701, Method 1, Standard Method of Fire Tests for Flame Propagation of Textiles and Films.

3.2.3 *nonreusable, adj*—in geosynthetics, a fabric or film intended to be placed once and then disposed of, discarded, or left in place.

3.2.4 *reusable, adj*—in geosynthetics, a fabric or membrane material intended to be retrieved and installed more than once to perform the cover function.

3.2.5 *working face, n*—the area of a landfill in which waste is actively being deposited.

4. Classification of Geosynthetic ADCs

4.1 *Nonreusable*—Nonreusable geosynthetic ADCs consist of disposable films or geotextiles, intended to be left in place without retrieval. Special equipment exists to facilitate the placement and anchoring of these materials to cover the working face of landfills. The cover may contain pro-degradant