

ISO/IEC ~~DIS PRF~~ 17823-2023(E)

ISO/IEC JTC 1/SC 28/~~AWG 5~~

Secretariat: JISC

Date: ~~2023-11-28~~2024-05-18

Information technology — Office equipment — ~~Colour terminology~~
Vocabulary for office colour equipment

FDIS stage

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/IEC PRF 17823

<https://standards.iteh.ai/catalog/standards/iso/14f7565e-8081-494a-b474-26b0a7e8e02b/iso-iec-prf-17823>

ISO/IEC PRF 17823:2024(en)

© ISO ~~2023~~/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: + 41 22 749 01 11
~~Email~~**E-mail**: copyright@iso.org
Website: www.iso.org

Published in Switzerland

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/IEC PRF 17823](#)

<https://standards.iteh.ai/catalog/standards/iso/14f7565e-8081-494a-b474-26b0a7e8e02b/iso-iec-prf-17823>

Contents

Foreword.....	iv
Introduction	v
1 Scope.....	1
2 Normative references	1
3 Terms and definitions.....	1
4 Classification and alphabetical index of terms	13
4.1 Classification of terms.....	13
4.2 Alphabetical index	13
Annex A (informative) Classification of terms	14
A.1 General.....	14
A.2 Colour terms list for office colour equipment	14
A.2.1 Terms that are not defined in previously published International Standards	14
A.2.2 Terms that have conflicting definitions in previously published International Standards.....	14
A.2.3 Terms with modified definitions for office equipment.....	15
A.2.4 Terms that have definitions in previously published International Standards that are appropriate for office equipment.....	15
Annex B (informative) Primary colours and typical input in various devices versus market segments	16
Bibliography	21
Index	23

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

<https://standards.iteh.ai>
ISO/IEC PRF 17823

<https://standards.iteh.ai/catalog/standards/iso/14f7565e-8081-494a-b474-26b0a7e8e02b/iso-iec-prf-17823>

ISO/IEC PRF 17823:2024(en)

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Field Code Changed

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

Field Code Changed

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 28, *Office equipment*.

This second edition cancels and replaces the first edition (ISO/IEC 17823:2015), which has been technically revised.

The main changes are as follows:

- ~~some~~ new terms and ~~their~~ definitions have been added;
- ~~the citation of the~~ references ~~has~~ have been updated.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

ISO/IEC PRF 17823:2024(en)

Introduction

Technical colour terms have been published in various fields of standards such as colour photography, graphic technology printing and computer graphics. However, no standard colour terms have been published for office equipment.

As a result, misunderstandings between users and colour office equipment providers may occur when terms are interpreted differently.

The purpose of this document is to provide terminology for use by office equipment providers to help customers use their colour equipment effectively.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/IEC PRF 17823](https://standards.iteh.ai/catalog/standards/iso/14f7565e-8081-494a-b474-26b0a7e8e02b/iso-iec-prf-17823)

<https://standards.iteh.ai/catalog/standards/iso/14f7565e-8081-494a-b474-26b0a7e8e02b/iso-iec-prf-17823>

Information technology — Office equipment — ~~Colour terminology~~ — Vocabulary for office colour equipment

1 Scope

This document provides definitions for colour terms used with office equipment, in particular for use with colour scanning and printing devices that have digital imaging capabilities, including multi-function devices.

This document is not intended to replace terms and definitions published in documents or user interfaces issued or created by manufacturers.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

~~For the purposes of this document, the following terms and definitions apply.~~

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ~~ISO~~ Online browsing platform: available at <https://www.iso.org/obp>
- ~~IEC~~ Electropedia: available at <https://www.electropedia.org/>

3.1

colour balance

adjustment of colour channel gains or processing

3.1.1

grey balance

set of tone values for cyan, magenta and yellow that are expected to appear as an achromatic grey under specified *viewing conditions* (~~3.12.11(3.12.11)~~) when printed using the specified printing conditions

Note 1 to entry: There are three practical definitions and one theoretical definition for grey:

a) ~~a)~~—practical definitions:

- 1) ~~1)~~ — colour having the same CIELAB a^* and b^* values as the print substrate;
- 2) ~~2)~~ — colour that has the same CIELAB a^* and b^* values as a half-tone *tint* (~~3.16.2(3.16.2)~~) of similar L^* value printed with black ink;
- 3) ~~3)~~ — functional (linear or nonlinear) combination of both.

b) ~~b)~~—theoretical definition:

- 1) ~~1)~~ — colour that the CIELAB a^* and b^* values both equal to 0.

[SOURCE: ISO/TS 10128:2009/2023, 3.34, modified — Note 1 to entry has been modified.]

3.2

black

ISO/IEC PRF 17823:2024(en)

3.2.1

composite black

black printed with multiple *colourants* [\(3.9\(3.9\)\)](#)

3.2.2

pure black

black generated only in black *colourant* [\(3.9\(3.9\)\)](#) in a printing device

3.2.3

rich black

black generated by a mixture of black *colourant* [\(3.9\(3.9\)\)](#) and other colourants in a printing device

3.3

calibration

set of operations that establish, under specified conditions, the relationship between values of quantities indicated by a measuring instrument or measuring system, or values represented by a material measure or a reference material, and the corresponding values realized by standards

[SOURCE: ISO 14807:2001, 3.11]

3.4

colour appearance

aspect of visual perception through which an object is perceived to have a colour with certain attributes

[SOURCE: CIE S 017/E:2020, 17-22-058]

3.4.1

brightness

attribute of a visual perception according to which an area appears to emit, transmit or reflect, more or less light

[SOURCE: CIE S 017/E: 2020, 17-22-059]

3.4.2

colourfulness

attribute of a visual perception according to which the perceived colour of an area appears to be more or less chromatic

[SOURCE: IEC 60050-845:2020, 845-22-072, modified — Notes to entry have been removed.]

3.4.3

highlight colour

adjustment of colour channel gains or processing

3.4.4

metamerism

phenomenon perceived when two specimens have the same colour under the lighting of an illuminant, but different spectral reflection and transmission curves

[SOURCE: ISO 4618: ~~2024~~2023, 3.154]

3.4.5

vividness

attribute of colour used to indicate the degree of departure of the colour from a neutral black colour

ISO/IEC PRF 17823:2024(en)

3.5 colour difference

~~perceived colour difference~~ perceived dissimilarity between two colour stimuli

[SOURCE: CIE S 017/E: 2020, 17-22-041]

3.6 colour encoding

3.6.1 colour palette

fixed set or range of available colours that can be selected

3.6.2 full colour

representation of colours with 3-channel or more, and each channel has 8-bit or more information

Note 1 to entry: Each channel may have 12-bit or 16-bit. In "commercial printing", there are multi-channel colour ~~reproduction~~ reproductions such as "Cyan(C), Magenta(M), Yellow(Y), black(K), Orange(O) and Green(G)".

3.6.3 indexed colour

palette colour

colour selection scheme in which the colour index is used to retrieve colour values from a colour table

[SOURCE: ISO/IEC 8632-1:1999, 4.1.62, modified — The term "palette colour" has been added.]

3.6.4 metallic colour

colour associated with polished metal, ~~whose~~ the brightness (3.4.1(3.4.1)) of which varies with the angle of the incident light and the viewing angle

Note 1 to entry: Typically, metallic colour cannot be reproduced well by mixture of device process colours (3.6.7(3.6.7)).

3.6.5 multi colour

multi-colour

additional colour(s) other than device process colours (3.6.7(3.6.7)), used in printing process that enhance(s) colour image quality

Note 1 to entry: Typically, complementary colours of process colours such as red, green, violet are used to expand colour gamut (3.7.2(3.7.2)).

Note 2 to entry: Sometimes light colourants (3.9(3.9)) such as light cyan, light magenta, light black or grey are used to improve image granularity and colour gamut in highlight.

3.6.6 named colour

colour with associated colour expression specification

3.6.7 process colour

colour that is the outcome of a colour separation operation

Note 1 to entry: A process colour typically requires one or more printing units and process inks to be reproduced.

ISO/IEC PRF 17823:2024(en)

Note 2 to entry: It is typically cyan, magenta, yellow, black for four-colour printing.

[SOURCE: ISO/TS 19303-1:2020, 3.10, modified — Note 2 to entry has been added.]

3.6.8 special colour

specific colour of single *colourant* (3.9(3.9)), designated, that cannot be reproduced by mixture of device *process colours* (3.6.7(3.6.7)).

3.6.9 spot colour

colour of single *colourant* (3.9(3.9)), identified by name, ~~whose~~ the printing tone-values of which are specified independently from the colour values specified in a colour coordinate system

[SOURCE: ISO 12639:2004, 4.1.10, modified — ~~a key~~ the word “colour” is added.]

3.7 colour management

communication of the associated data required for unambiguous interpretation of colour content data, and application of colour data conversions, as required, to produce the intended reproductions

[SOURCE: ISO 15076-1:2010, 3.1.11, modified — Notes to entry have been removed.]

3.7.1 characterization

process of relating device-dependent colour values to device-independent colour values

Note 1 to entry: Adapted from ISO 12637-2:2008, 2.7.

3.7.2 colour gamut

volume, area or solid in a *colour space* (3.8(3.8)), consisting of all those colours that are either one of the following:

- a) ~~a)~~ present in a specific scene, artwork, photograph, photomechanical, or other reproduction, ~~or~~
- b) ~~b)~~ capable of being created using a particular output device and/or medium

Note 1 to entry: In reproduction and media applications, only the volume or solid in colour space is regarded as colour gamut. In applications such as signal lighting, the colour gamut is an area.

[SOURCE: CIE S 017/E: 2020, 17-32-007]

3.7.3 colour gamut boundary

surface determined by a *colour gamut's* (3.7.2(3.7.2)) extremes

[SOURCE: ISO/IEC TR 29186:2012, 3.3]

3.7.4 gamut boundary descriptor

GBD
overall way of approximately describing a *colour gamut boundary* (3.7.3(3.7.3))

[SOURCE: ISO/IEC TR 29186:2012, 3.4]

ISO/IEC PRF 17823:2024(en)

3.7.5

gamut mapping

mapping of the *colour space* [\(3.8\(3.9\)\)](#) coordinates of the elements of a source image to colour space coordinates of the elements of a reproduction to compensate for differences in the source and output medium *colour gamut* [\(3.7.2\(3.7.2\)\)](#) capability

Note 1 to entry: The term "gamut mapping" is somewhat more restrictive than the term "colour rendering" because gamut mapping is performed on colourimetry that has already been adjusted to compensate for viewing condition differences and viewer preferences, although these processing operations are frequently combined in reproduction and preferred reproduction models.

[SOURCE: ISO 22028-2:2013, 3.14]

3.7.6

ICC

International Color Consortium

industry association formed to develop standardized mechanisms for *colour management* [\(3.7\(3.7\)\)](#)

[SOURCE: ISO 15930-3:2002, 3.9]

3.7.7

ICC profile

file format of the International Color Consortium [\(3.7.6Consortium's \(3.7.6\) file format\)](#), used to store transforms from one colour encoding to another

[SOURCE: ISO 22028-1:2016, 3.24, modified — Example part has been removed from the definition.]

3.7.8

print settings profile

digital file that is or contains an *International Color Consortium* [\(3.7.6\(ICC\) \(3.7.6\)\)](#) output profile along with *colourant settings* [\(3.21.1\(3.21.1\)\)](#) and optional additional metadata

[SOURCE: ISO/IEC 22954:2022, 3.10]

<https://standards.iteh.ai/catalog/standards/iso/14f7565e-8081-494a-b474-26b0a7e8e02b/iso-iec-prf-17823>

3.7.9

rendering intent

style of mapping colour values from one image description to another

[SOURCE: ISO 15076-1:2010, 3.1.27, modified — Note 1 to entry has been removed.]

3.8

colour space

geometric representation of colours in space

Note 1 to entry: A colour space is usually of three dimensions.

[SOURCE: IEC 60050-845:2020, 845-23-041]

3.8.1

colour space encoding

digital encoding of a *colour space* [\(3.8\(3.8\)\)](#), including the specification of a digital encoding method, and a colour space value range

Note 1 to entry: Multiple colour space encodings may be defined based on a single colour space where the different colour space encodings have different digital encoding methods and/or colour space value ranges. (For example, 8-bit sRGB and 10-bit bg-sRGB are different colour space encodings based on a particular additive RGB colour space.)