



International
Standard

ISO 24021-2

Light gauge metal containers —
Vocabulary and classification —

Part 2:
General cans

Réipients métalliques légers — Vocabulaire et classification —

Partie 2: Boîtes à usage général

First edition

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 24021-2](#)

<https://standards.itih.ai/catalog/standards/iso/b13ce6d4-19d5-4b1d8-b4f7-630e025a269e/iso-24021-2>

PROOF/ÉPREUVE

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 24021-2](https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2)

<https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

PROOF/ÉPREUVE

© ISO 2024 – All rights reserved

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Terms related to raw and processed materials.....	1
3.2 Terms related to manufacturing technique.....	2
3.3 Terms related to quality.....	3
3.4 Terms related to classification.....	8
Annex A (informative) Classification	17

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 24021-2](https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2)

<https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 52, *Light gauge metal containers*.

A list of all parts in the ISO 24021 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

[ISO 24021-2](https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2)

<https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2>

Introduction

The terms and classification of open-top cans and ends are specified in ISO 24021-1. This document is a continuation of ISO 24021-1, and aims to specify relevant terminology and classification on general cans according to industries situation, and to promote the technical communication and international trade for stakeholders in this field.

Similar to open-top cans and ends, some terminology of general cans currently in use has developed through common usage and is not always logical. There are occasional conflicts between tradition and logic, and some definitions inevitably represent a compromise. The same situation exists with classification, the method by which classifiers are defined depends upon the application area. In addition, the classifiers used within a particular application area will not always be adequate for all situations.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 24021-2](https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2)

<https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2>

Light gauge metal containers — Vocabulary and classification —

Part 2: General cans

1 Scope

This document defines terms and establishes a classification (see [Annex A](#)) for general cans.

This document is applicable to general cans used in food, chemical, gift and other fields made of tinplate or chrome plated steel, stainless steel plate and laminated steel plate with a nominal material thickness no more than 0,49 mm.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 Terms related to raw and processed materials

3.1.1

plain plate

ETP or TFS plate with bare surface

Note 1 to entry: ETP is the abbreviation for tinplate or electrolytic tinplate.

Note 2 to entry: TFS is the abbreviation for tin free steel, another name for electrolytic chromium or chromium oxide-coated steel.

3.1.2

stainless steel

steel with no rust, corrosion resistance, and chromium content of at least 10,5 %, and the maximum carbon content of not more than 1,2 %

3.1.3

coated tinplate or tin free steel

plain plate (3.1.1) coated with lacquer and cured at high temperature to form a film on its surface

3.1.4

laminated steel

composite material with dual properties of organic polymer material and metal material formed by laminating a layer of polymer film on the surface of *plain plate* (3.1.1) through the melting method

3.2 Terms related to manufacturing technique

3.2.1

cutting angle

notch

right angles or certain degree angles cut symmetrically on the four corners of the flat metal sheet used for can body forming

3.2.2

pre bending

action of making the edge of the can to form an inward or outward curve

3.2.3

bending

action of making the body blank bent according to the desired length of the finished can

3.2.4

forming

cylinder formed from the body blank by the rounding device

3.2.5

flanging

upper or lower edge of the can that is flared out at right angles to the vertical axis of the can

3.2.6

lock seam

seaming formed by the two edges of a can body shaped like hooks and compressed to form four layers of plate

3.2.7

necking

die or spinning method for reducing the diameter of the open top of a cylinder blank

3.2.8

expanding

punching method for enlarging the diameter of the open top of a cylinder blank

3.2.9

embossing

printing process that uses a concave and convexity mould to form printed material deformation under a certain pressure to form a pattern on the surface

3.2.10

bottom locking

process that allows the body and bottom of the can to be locked together

3.2.11

curling

adding of a circular roll to the edge of the sheet

3.2.12

welding

joining of two vertical edges of the body cylinder by using heat at high temperature

3.2.13

punching

making of a hole on metal plate by die

3.2.14

riveting

use of mechanical fastener, composed of head and tail, to fasten attachment with can body or end

3.2.15

drawing

processing method that uses the extensibility of metal materials by drawing die to put a blank or semi-finished product of a certain shape into a mould to form an open hollow can

3.2.16

seam

sealing structure formed by rollers to make the flange of the can body and the hook of the cover (bottom) overlap each other and press tightly

3.2.17

ink-jet printing

process of marking product information on can ends or labels with a printer

3.2.18

seaming roll

main part on a can seamer with two small round wheels with different curvatures around that forms the double-seam structure, in which the first roller is to roll the can cover hook under the can body flange and roll them together, and the second roller is to press the first roller tightly, so that the curling is tightly combined with each other, and the sealant is filled inside the forming gap between the can body and the cover hook

3.2.19

seaming rail

sealing accessory part of the high-speed sealing machine, which replaces the roller, forms a double seam and meets the sealing requirements

3.2.20

base plate

part that lifts the can lid and the can body upward when the can sealing machine is running, so that the pressure head is embedded in the can lids, and the can body is stabilized to avoid sliding, so as to facilitate the formation of double curling and meet the sealing requirements

3.2.21

seaming chuck

part of the can sealing machine that can be embedded in the countersunk part of the can cover and support the combined part of the can cover and the can body with the peripheral side to resist the pressure of the sealing roller

3.2.22

double seam

sealing structure formed by the operation of the first roller and the second roller to make the flanging of the can body and the hook of the cover (bottom) overlap each other and press tightly, which is composed of three layers of top (bottom) cover thickness and two layers of can body thickness

3.2.23

compound

sealing material formulated with latex or rubber, filler and tackifier

3.2.24

handle

metal or other material installed on the can body or lid for lifting the can

3.3 Terms related to quality

3.3.1

body hook

BH

folding over of the body flange into an interlocking hook

3.3.2

cover hook

CH

hook formed from the cover curl extending from the radius to an opposite (180°) radius

3.3.3

seam thickness

maximum external dimension measured across or perpendicular to the body and cover hook

3.3.4

seam width

seam length

seam height

maximum dimension measured parallel to folds in the seam

3.3.5

seam gap

place between the top of the body hook radius and the underside of the seaming panel

3.3.6

length of overlap

actual overlap

measurement of how much the *body hook* (3.3.1) overlaps the *cover hook* (3.3.2)

3.3.7

rate of overlap

% OL

percentage of overlap

ratio of the *length of overlap* (3.3.6) relative to the internal seam length, expressed as a per cent

3.3.8

wrinkles rating

WR

degree of waviness occurring in the *cover hook* (3.3.2) from which the degree of double seam tightness is determined

[ISO 24021-2](https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2)

<https://standards.iteh.ai/catalog/standards/iso/b13ce6d4-19d5-4bd8-b4f7-630e025a269e/iso-24021-2>

tightness rating

TR

measure of the degree of wrinkle left on the end hook on the completed double seam

3.3.10

cover hook butting

CHB

percentage of the can *cover hook* (3.3.2) at the overlap of the seam to the theoretical *cover hook* (3.3.2) length

3.3.11

body hook butting

BHB

percentage of the can *body hook* (3.3.1) at the overlap of the seam to the theoretical *body hook* (3.3.1) length

3.3.12

countersink depth

distance from the top radius of the double seam to the bottom of the countersink radius

3.3.13

pressure ridge

clearly visible impression formed by seaming roll pressure around the inside of the can body against the cover countersink wall by stripping the double seam for inspection