INTERNATIONAL STANDARD

ISO 11382

Second edition

Optics and photonics — Optical materials and components — Characterization of optical materials used in the infrared spectral range from 0,78 µm to 25 µm

Optique et photonique — Matériaux et composants optiques — Caractérisation des matériaux optiques utilisés dans la bande spectrale infrarouge de 0,78 µm à 25 µm

ISO/PRF 11382

https://standards.iteh.ai/catalog/standards/sist/b0e34c8f-b581-40b6-a2fb 159db2941d86/iso-prf-11382

PROOF/ÉPREUVE



Reference number ISO 11382:2022(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/PRF 11382 https://standards.iteh.ai/catalog/standards/sist/b0e34c8f-b581-40b6-a2fb 159db2941d86/iso-prf-11382



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents			Page
For	eword		iv
Intr	oductio	on	v
1	Scor	oe	1
2	-	mative references	
3		ns and definitions	
4	Symbols and units		2
5	Nomenclature		
	5.1	General	
	5.2	Name	
	5.3 5.4	Manufacturer reference	
	5. 4 5.5	Material structure	
	5.6	Form of nomenclature	
_			
6		cal properties	
	6.1 6.2	General Transmittance	
	0.2	6.2.1 Specification to be provided	
		6.2.2 Temperature dependence	
	6.3	Absorption coefficient	
		6.3.1 General	
		6.3.2 Specification to be provided (to be consistent with <u>6.5.2</u>)	
	6.4	Transmittance uniformity	6
		6.4.1 General	
		6.4.2 Bubbles and inclusions PRE 11382	
	, t	6.4.3 Local variation of the manufacturing process	
	6.5	Refractive index	
		6.5.1 General 6.5.2 Specification reports to be provided	
	6.6	Refractive index variation	
	6.7	Dependence of the refractive index on temperature	
	6.8	Optical homogeneity (homogeneity of refractive index)	
	6.9	Birefringence	
		6.9.1 Materials with natural birefringence	
		6.9.2 Stress birefringence	
	6.10	Photoelastic constant	
	6.11	Dispersion	9
7	Othe	er properties	9
	7.1	General	
	7.2	Specific gravity	
	7.3	Molecular mass	
	7.4	Thermal properties	
		7.4.1 Thermal conductivity	
		7.4.2 Thermal expansion 7.4.3 Specific heat.	
		7.4.4 Melting temperature and softening temperature	
	7.5	Hardness	
	7.6	Elastic modulus	
	7.7	Maximum dimensions	
Bihl	iogran	hy	11
		-,	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 172, *Optics and photonics*, Subcommittee SC 3, *Optical materials and components*.

This second edition cancels and replaces the first edition (ISO 11382:2010), which has been technically revised. 159db2941d86/iso-prf-11382

The main changes are as follows:

- update of <u>Clause 2</u> and Bibliography;
- update of <u>Table 1</u> and <u>Table 2</u>.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Many standards for optical glass exist that are primarily used for the visible range, however, it is not easy to apply these standards directly to infrared materials.

Often, the properties of infrared materials are known with less certainty than those used in the visible range because the methods of measurements are different, incomplete or inaccurate.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/PRF 11382 https://standards.iteh.ai/catalog/standards/sist/b0e34c8f-b581-40b6-a2fb 159db2941d86/iso-prf-11382

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/PRF 11382

https://standards.iteh.ai/catalog/standards/sist/b0e34c8f-b581-40b6-a2fb-159db2941d86/iso-prf-11382

1

Optics and photonics — Optical materials and components — Characterization of optical materials used in the infrared spectral range from 0,78 μ m to 25 μ m

1 Scope

This document provides guidelines for the description of data sheets for infrared materials. It specifies the nomenclature and the properties of infrared materials which are reported on such data sheets. These data sheets do not necessarily contain information on every property identified in this document.

This document also specifies the parameters needed to characterize optical materials intended for use in the infrared spectral range from 0,78 μm to 25 μm and provides various methods to be used for measuring these parameters.

This document is applicable only to materials used in the manufacture of passive optical components. The properties of materials used in active applications (e.g. optoelectronics) are not taken into account.

Materials specified in this document can also transmit in other spectral domains (microwaves, visible or ultraviolet).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10110-18, Optics and photonics — Preparation of drawings for optical elements and systems — Part 18: Stress birefringence, bubbles and inclusions, homogeneity, and striae

ISO 12123:2018, Optics and photonics — Specification of raw optical glass

ISO 15368, Optics and photonics — Measurement of reflectance of plane surfaces and transmittance of plane parallel elements

ISO 80000-7, Quantities and units — Part 7: Light and radiation

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12123, ISO 80000-7 and the following apply¹⁾.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1

regular transmittance

ratio of the regularly transmitted part of the (whole) transmitted flux to the incident flux

© ISO 2022 – All rights reserved PROOF/ÉPREUVE

¹⁾ These terms and definitions are consistent with those given in IEC 60050-845 and ISO/IEC Guide 98-3.

ISO 11382:2022(E)

3.2

regular reflectance

specular reflectance

ratio of the regularly reflected part of the (whole) reflected flux to the incident flux

3.3

absorptance

ratio of the absorbed radiant flux to the incident flux

3.4

scatter

scatterance

ratio of the scattered radiant flux to the incident flux

3.5

standard uncertainty

uncertainty of the result of a measurement expressed as a standard deviation

3.6

expanded uncertainty

quantity defining an interval about the result of a measurement that may be expected to encompass a large fraction of the distribution of values that could reasonably be attributed to the measurand

4 Symbols and units

For the purposes of this document, the following symbols and units apply.

- d thickness of the sample, expressed in millimetres
- α absorptance
- δ scatter https://standards.iteh.ai/catalog/standards/sist/b0e34c8f-b581-40b6-a2fb-
- λ wavelength, expressed in micrometres
- o reflectance
- τ transmittance

5 Nomenclature

5.1 General

The optical materials covered by this document shall be identified as follows:

- a) the name (see 5.2);
- b) the manufacturer reference (see <u>5.3</u>);
- c) the material structure (optional) (see <u>5.4</u>);
- d) the manufacturing process (see 5.5);
- e) a reference to this document, i.e. ISO 11382:—.

5.2 Name

Either the trademark or the generic name (e.g. germanium or sapphire), followed by reference to the method of manufacture, shall be given in the nomenclature.

5.3 Manufacturer reference

A reference to the manufacturer shall be given in the nomenclature.

5.4 Material structure

If known, the type of the material structure shall be given, i.e. the following:

- amorphous material (e.g. glasses and some plastics);
- polycrystalline material;
- crystal (natural or synthetic);
- ceramics, etc.

5.5 Manufacturing process

The manufacturing process shall be given in the nomenclature; this description may be simplified (e.g. CVD instead of chemical vapour deposition). If a change in the manufacturing process modifies one or several properties of the material, another reference shall be used.

NOTE A great number of materials which transmit in the infrared spectral range exist in nature. However, due to their scarcity, small size, or impurity levels, the optical materials are usually manufactured or refined by industrial processes.

5.6 Form of nomenclature

The nomenclature shall be expressed in sequence, separated by dashes, as shown in the following examples.

```
EXAMPLE 1 Germanium – Manufacturer A – Monocrystalline n type – Zone fusion – ISO 11382:—
```

EXAMPLE 2 ZnS - Manufacturer B - Polycrystalline - Hot isostatic pressed - ISO 11382:—


6 Optical properties

6.1 General

The methods for obtaining data should be reported. If the data are quoted from a reference, the reference document and publication data date shall be reported.

The material is assumed to be in the form of a plane-parallel element with optically polished surfaces 1 and 2, as shown in Figure 1.

ISO 11382:2022(E)



Key

- 1, 2 optically polished surfaces
- 3 incident light beam
- 4 reflected part
- 5 transmitted part
- 6 scattered part

Figure 1 — Schematic of the light propagation through an element

The light beam incident on the schema given in Figure 1 is divided into

- a reflected part,
- a transmitted part,
- a scattered part, and
- an absorbed part.

(standards.iteh.ai)

talog/standards/sist/b0e34c8f-b581-40b6-a2fb-

If m donates a surface number, the light beam incident can be described by Formulae (1) to (3), as follows:

$$\tau_m + \rho_m + \alpha_m + \delta_m = 1 \tag{1}$$

$$\tau_{t} = \frac{\tau_{1}\tau_{i}\tau_{2}}{1 - \tau_{i}^{2}\rho_{1}\rho_{2}} \text{ or } \tau_{t} = \frac{\tau_{s}^{2}\tau_{i}}{1 - \tau_{i}^{2}\rho_{s}^{2}}$$
 (2) and (3)

where

 τ_{t} is the transmittance of the element;

 τ_m is the regular transmittance of the surface, m;

 τ_1 is the regular transmittance of surface 1;

 au_2 is the regular transmittance of surface 2;

 $\tau_{\rm s}$ is the regular transmittance of the surface, m, when surfaces 1 and 2 are

identical;

 $\tau_{\mathrm{d}m}$ is the scattered transmittance of the surface, m;

 au_{i} is the internal transmittance of the element;