

INTERNATIONAL
STANDARD

ISO
3185

First edition
1993-12-15

Aerospace — Bolts, normal bihexagonal head, normal shank, short or medium length MJ threads, metallic material, coated or uncoated, strength classes less than or equal to 1 100 MPa — Dimensions

ITEH Standard
<https://standards.iteh.ai>

Document Preview

Aéronautique et espace — Vis à tête bihexagonale normale, avec tige normale et filetage MJ court ou de longueur moyenne, en matériau métallique, revêtues ou non revêtues, des classes de résistance inférieures ou égales à 1 100 MPa — Dimensions

<https://standards.iteh.ai/catalog/standards/iso/1d7fb650-d5cb-4c59-b86e-75151daa2697/iso-3185-1993>



Reference number
ISO 3185:1993(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 3185 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Sub-Committee SC 4, *Aerospace fastener systems*.

ISO 3185:1993

<https://standards.iteh.ai/catalog/standards/iso/1d7fb650-d5cb-4c59-b86e-75151daa2697/iso-3185-1993>

© ISO 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland
Printed in Switzerland

Aerospace — Bolts, normal bihexagonal head, normal shank, short or medium length MJ threads, metallic material, coated or uncoated, strength classes less than or equal to 1 100 MPa — Dimensions

1 Scope

This International Standard specifies the dimensions of normal bihexagonal head bolts, with close or large tolerance normal shank, and short or medium length MJ threads, in metallic material, coated or uncoated, with strength classes less than or equal to 1 100 MPa.

It is intended for the drawing up of aerospace product standards.

<https://standards.iteh.ai/catalog/standards/iso/1d7fb650-d5cb>

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 286-2:1988, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts*.

ISO 3353:1992, *Aerospace — Rolled threads for bolts — Lead and runout requirements*.


ISO 4095:1978, *Fasteners for aerospace construction — Bi-hexagonal wrenching configuration*.

ISO 5855-2:1988, *Aerospace — MJ threads — Part 2: Limit dimensions for bolts and nuts*.


3 Configuration and dimensions

See figure 1 and table 1. Dimensions and tolerances are expressed in millimetres. They are applicable after any surface coating, but before the application of any lubricant.

Break sharp edges 0,1 to 0,4



<https://standards.iteh.ai/catalog/standards/iso/1d7fb650-d5cb-4c59-b86e-75151daa2697/iso-3185-1993>



1) Rounded or chamfered in this area.

Figure 1