

ISO/FDIS 293:2022(E)

~~2022-11-05~~

ISO TC 61/SC 9/WG 18

~~2022-11-11~~

Secretariat: KATS

Plastics

Compression moulding of test specimens of thermoplastic materials

Plastiques — Moulage par compression des éprouvettes en matières thermoplastiques

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 293

<https://standards.iteh.ai/catalog/standards/sist/dca44653-7bf4-3bbbd3a6bed1/iso-fdis-293>

Style Definition: List Number 1: Tab stops: Not at 19.85 pt + 39.7 pt + 59.55 pt + 79.4 pt + 99.25 pt + 119.05 pt + 138.9 pt + 158.75 pt + 178.6 pt + 198.45 pt

Style Definition: List Bullet 4: Indent: Left: 42.45 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 60.45 pt, List tab

Style Definition: List Number: Indent: Left: 0 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 18 pt, List tab

Style Definition: List Bullet: Indent: Left: 0 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 18 pt, List tab

Style Definition: List Bullet 3: Indent: Left: 28.3 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 46.3 pt, List tab

Style Definition: List Bullet 2: Indent: Left: 14.15 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 32.15 pt, List tab

Style Definition: List Bullet 5: Indent: Left: 56.6 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 74.6 pt, List tab

Style Definition: Body Text Indent 2

Style Definition: Footer

Style Definition: Header

Style Definition: List Number 5: Indent: Left: 56.6 pt, Hanging: 18 pt, No bullets or numbering, Tab stops: 74.6 pt, List tab

Style Definition: Body Text Indent 3

Style Definition: a2: Tab stops: 18 pt, List tab

Style Definition: a3: Tab stops: 36 pt, List tab

Style Definition: a4: Tab stops: 54 pt, List tab

Style Definition: a5: Tab stops: 54 pt, List tab

Style Definition: a6: Tab stops: 72 pt, List tab

Style Definition: AMEND Terms Heading: Pattern: 15%

Style Definition: AMEND Heading 1 Unnumbered: Pattern: 15%

Style Definition: 해시태그1

Style Definition: 멘션1

Style Definition: 스마트 하이퍼링크1

Style Definition: 확인되지 않은 멘션1

Formatted: Different first page header

Formatted: Font: Not Bold

Formatted: Font: Not Bold, Italic

© ISO 2022, Published in Switzerland

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva

Phone: +41 22 749 01 11

Email: copyright@iso.org

Website: www.iso.orgwww.iso.org

Formatted: Font: 11.5 pt, Bold

Formatted: Font: 12 pt

Formatted: Normal

Formatted: Font: 11.5 pt, Bold

Formatted

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 293

<https://standards.iteh.ai/catalog/standards/sist/dca44653-7bf4-4ade-9c4e-3bbbd3a6bed1/iso-fdis-293>

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

ii © ISO 2022 – All rights reserved

ii © ISO 2022 – All rights reserved

Formatted: Font: 11.5 pt, Bold

Formatted: Normal

Formatted: Font: 11.5 pt, Bold

Contents

Foreword.....iv

Introduction.....vi

1 Scope.....1

2 Normative references.....1

3 Terms and definitions.....1

4 Apparatus.....2

5 Procedure.....5

6 Inspection of the moulded specimens or sheets.....7

7 Specimen preparation report.....7

Bibliography.....8

Foreword.....iv

Introduction.....vi

1 Scope.....1

2 Normative references.....1

3 Terms and definitions.....1

4 Apparatus.....2

4.1 Moulding press.....2

4.2 Moulds.....3

4.2.1 General.....3

4.2.2 Fabrication.....4

4.2.3 Types.....4

5 Procedure.....5

5.1 Preparation of moulding material.....5

5.1.1 Drying of granular material.....5

5.1.2 Preparation of preforms.....5

5.2 Moulding.....5

5.3 Cooling.....6

5.3.1 General.....6

5.3.2 Cooling methods.....6

6 Inspection of the moulded specimens or sheets.....7

7 Specimen preparation report.....7

Bibliography.....8

~~Edited DIS -~~
MUST BE USED
~~FOR FINAL~~
DRAFT

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

Formatted: Font: 11.5 pt, Bold

Formatted: Font: 12 pt

Formatted: Normal

Formatted: Font: 11.5 pt, Bold

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 9, *Thermoplastic materials*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 249, *Plastics*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This fourth edition cancels and replaces the third edition (ISO 293:2004), which has been technically revised.

The main changes are as follows:

- ~~“Cooling”~~ the definition for “cooling rate” has been revised ~~in terms and definitions~~ (see [Clause 3.6](#));
- ~~The~~ requirements regarding the biggest clamping force and the highest platens temperature ~~has~~ been ~~revised~~ changed (see 4.1);
- ~~The~~ the description of common specifications of positive mould has been given (see 4.2.3.3);
- ~~The~~ the conditions for the use of vacuum oven while material drying ~~has~~ been ~~given~~ added (see 5.1.1);

Formatted: No underline

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

ISO/FDIS-293:2022(E)

Formatted: Font: 11.5 pt, Bold

Formatted: Normal

Formatted: Font: 11.5 pt, Bold

Formatted: No underline

Formatted: No underline

— ~~The~~ methods of cooling rate have been revised (see Table_1);

— ~~The~~ bibliography has been ~~given~~added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 293

<https://standards.iteh.ai/catalog/standards/sist/dca44653-7bf4-4ade-9c4e-3bbbd3a6bed1/iso-fdis-293>

~~Edited DIS -
MUST BE USED
FOR FINAL
DRAFT~~

© ISO 2022 – All rights reserved

© ISO 2022 – All rights reserved

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

Formatted: Font: 11.5 pt, Bold

Formatted: Font: 12 pt

Formatted: Normal

Formatted: Font: 11.5 pt, Bold

Introduction

For reproducible test results, specimens with a specified state are required. In contrast to injection moulding, the aim of compression moulding is to produce test specimens and sheets for machining or stamping of test specimens that are homogeneous and isotropic.

In the process of compression moulding, mixing of material takes place on a negligible scale. Granules and powders fuse only at their surfaces and preforms (milled sheets) are only partially softened.

Isotropic and homogeneous specimens can, therefore, only be obtained when the moulding material is itself homogeneous and isotropic. This has to be considered when processing multiphase materials, such as ABS, which retain their internal structure.

The cooling rate in the crystallization stage has a great influence on the properties of semi-crystalline or crystalline polymer (such as PB, PE, PP, etc.), so it is necessary to control the cooling rate more strictly at the cooling stage.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 293

<https://standards.iteh.ai/catalog/standards/sist/dca44653-7bf4-4ade-9c4e-3bbbd3a6bed1/iso-fdis-293>

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

Plastics — Compression moulding of test specimens of thermoplastic materials

Formatted: Section start: New page, Different first page header

1 Scope

This document specifies the general principles and the procedures to be followed with thermoplastics in the preparation of compression-moulded test specimens, and sheets from which test specimens may be machined or stamped.

NOTE In order to obtain mouldings in a reproducible state, the main steps of the procedure, including eight different cooling methods, are standardized. For each material, the required moulding temperature and cooling methods are as specified given in the appropriate International Standard for the material or as agreed between the interested parties.

Formatted: Tab stops: 19.85 pt, Left + 39.7 pt, Left + 59.55 pt, Left + 79.4 pt, Left + 99.25 pt, Left + 119.05 pt, Left + 138.9 pt, Left + 158.75 pt, Left + 178.6 pt, Left + 198.45 pt, Left

This document is not applicable to reinforced thermoplastics.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <http://www.electropedia.org/>

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: English (United States)

Formatted: English (United States)

Formatted: Font: Times New Roman, 12 pt, English (United States)

Formatted: English (United States)

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 19.85 pt + 39.7 pt + 59.55 pt + 79.4 pt + 99.25 pt + 119.05 pt + 138.9 pt + 158.75 pt + 178.6 pt + 198.45 pt

Formatted: Hyperlink, English (United States)

3.1 moulding temperature

temperature of the mould or the press platens during the preheating and moulding time, measured in the nearest vicinity to the moulded material

Note 1 to entry: The moulding temperature is usually expressed in Degrees Celsius.

3.2 demoulding temperature

temperature of the mould or the press platens at the end of the cooling time, measured in the nearest vicinity to the moulded material

ISO/FDIS 293:2022(E)

Formatted: Normal, Space After: 36 pt, Line spacing: Exactly 12 pt

Formatted: Font: 12 pt

Note 1 to entry: -The demoulding temperature is usually expressed in Degreesdegrees Celsius.

3.3 preheating time

time required to heat the material in the mould up to the *moulding temperature* (3.1) while maintaining the contact pressure

Formatted: cite_sec

Note 1 to entry: -The preheating time is usually expressed in Minuteminute.

3.4 moulding time

time during which full pressure is applied while maintaining the *moulding temperature* (3.1)

Formatted: cite_sec

Note 1 to entry: -The moulding time is usually expressed in Minuteminute.

3.5 average cooling rate

<non-linear>rate of cooling by a constant flow of the cooling fluid, calculated by dividing the difference between *moulding temperature* (3.1) and *demoulding temperature* (3.2) by the time required to cool the mould to the *demoulding temperature* (3.2)

Formatted: cite_sec

Formatted: cite_sec

Formatted: cite_sec

Note 1 to entry: -The average cooling rate is usually expressed in degrees Celsius per minute.

3.6 cooling rate controlled cooling rate

<linear>constant rate of cooling in a specified temperature range obtained by controlling the flow of the cooling fluid in such a way that over each specified time interval the deviation from this specified cooling rate does not exceed the specified tolerance

Note 1 to entry: The cooling rate is usually expressed in degrees Celsius per minute.

Note 2 to entry: -The specified time interval-controlled cooling rate is based on the system design of moulding press. Usually the shorter time interval used, the more accurate controlled cooling rate can be gained.

4 Apparatus

4.1 Moulding press

The press shall have a clamping force capable of applying a pressure (conventionally given as the ratio of the clamping force to the area of the mould cavity) of at least 12-MPa.

The pressure shall be maintained to within 10-% of the specified pressure during the moulding cycle.

The platens shall be capable of:

- a) being heated to at least 320-°C;
- b) being cooled at a rate given in Table-1.

Formatted: Tab stops: 19.85 pt, Left + 39.7 pt, Left + 59.55 pt, Left + 79.4 pt, Left + 99.25 pt, Left + 119.05 pt, Left + 138.9 pt, Left + 158.75 pt, Left + 178.6 pt, Left + 198.45 pt, Left

Formatted: No underline

Formatted: No underline

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

The difference between the temperatures of any points of the mould surfaces shall not vary by more than ±2-°C during heating and ±4-°C during cooling.

2 © ISO 2022 – All rights reserved

2 © ISO 2022 – All rights reserved

Formatted: Normal, Right, Space After: 36 pt, Line spacing: Exactly 12 pt

Formatted: Font: 12 pt

When the heating and cooling system is incorporated in the mould, it shall comply with the same conditions.

The platens or mould shall be heated either by high-pressure steam, by a heat-conducting fluid in an appropriate channel system, or by using electric heating elements. The platens or mould are cooled by a heat-conducting fluid (usually cold water) in a channel system.

For quench cooling (see method C in Table_1), two presses shall be used, one for heating during moulding and the other for cooling.

For a specified cooling method, the flow rate of the heat-conducting fluid shall be predetermined in a test without any material in the mould.

The temperature may be continuously controlled in the centre between the upper and lower platen of the press.


4.2 Moulds

4.2.1 General


The characteristics of the test specimens prepared by using different types of moulds are not the same. In particular, the mechanical properties depend on the pressure applied to the material during cooling.

In general, two types of moulds, “flash mould (picture frame mould)” (see Figure-1) and “positive mould” (see Figure-2), are used for compression moulding test specimens of thermoplastics.

Formatted: Tab stops: 36 pt, Left



Figure_1 — Schematic diagram of flash mould (picture frame mould)



Figure_2 — Schematic diagram of positive mould

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

ISO/FDIS 293:2022(E)

Formatted: Normal, Space After: 36 pt, Line spacing: Exactly 12 pt

Formatted: Font: 12 pt

Flash mould permits excess moulding material to be squeezed out and do not exert moulding pressure on the moulding material during cooling. They are particularly convenient for preparing test specimens or panels of similar thickness or comparable levels of low internal stress.

With positive moulds, the full moulding pressure, neglecting friction, is exerted on the material during cooling. The thickness, stress and density of the resulting mouldings depend on mould construction, size of material charge and the moulding and cooling conditions. This type of mould produces consolidated test specimens with moulded surfaces and is therefore particularly suitable for obtaining flat surfaces or suppressing the formation of voids within test specimens.

4.2.2 Fabrication

Formatted: Tab stops: 36 pt, Left

The moulds shall be made of materials capable of withstanding the moulding temperature and pressure. The surfaces in contact with the material shall be polished to obtain good surface conditions on the specimens (recommended surface roughness 0,16 Ra 16 Ra, see ISO 21920-2). Specimen removal can be made easier by chromium plating these surfaces. For specimens of small dimensions, a 2° taper is strongly recommended.

Blind holes may be drilled in the mould so that temperature can be measured in the vicinity of the moulded material by using thermocouples.

Depending on the performance of the press (see 4.1), the moulds may have built-in heating and/or cooling devices similar to those described for the press platens.

An alloy steel, resistant to mechanical shock and heat-treated to provide a tensile strength of 2-200 MPa, will generally be satisfactory for the moulds. However, in the special case of PVC moulding materials, the use of martensite stainless steel treated to provide a tensile strength of 1-050 MPa is recommended.

4.2.3 Types

Formatted: Tab stops: 36 pt, Left

4.2.3.1 General

Formatted: Tab stops: 36 pt, Left + 54 pt, Left

The type of mould used shall be capable of producing test specimens of the types and states specified in the appropriate International Standard for the material or shall be agreed upon between the interested parties.

4.2.3.2 Flash mould (picture frame mould)

Formatted: Tab stops: 36 pt, Left + 54 pt, Left

With this type of mould, the excess material is squeezed out and the moulding pressure during cooling is only exerted on the frame and not on the material. The thickness in the centre of the mouldings is slightly less than at the edges due to the shrinkage during cooling. Directly moulded test bars may also have sink marks or voids if the shrinkage is hindered by sticking of the plastic material to the mould.

To overcome these disadvantages, stamping or machining of test specimens from the central part of compression-moulded sheets is preferred.

For moulding sheets, simple and economical flash moulds can be used, consisting of a frame covered with two plates (see Figure-1). The lower and upper plates, having a thickness of about 4 mm to 5 mm, can be made from polished steel or chromium-plated brass to aid release. To avoid the plastic material sticking to the plates, they can be covered by a flexible foil, for example of aluminium or polyester.

Use of a release agent is not allowed.

The thickness of the chase shall be appropriate to the moulded sheet thickness.

The size of the moulding frame shall be such that the main test area of the specimens can be cut or machined without using the outer 20 mm perimeter of the sheet.

Formatted: Font: 11 pt

Formatted: Space After: 0 pt, Line spacing: single

4 © ISO 2022 – All rights reserved

4 © ISO 2022 – All rights reserved