

---

**INTERNATIONAL STANDARD**



**3195**

---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

---

## **Sodium hydroxide for industrial use — Sampling — Test sample — Preparation of the main solution for carrying out certain determinations**

*Hydroxyde de sodium à usage industriel — Prélèvement — Échantillon pour essai — Préparation de la solution principale pour l'exécution de certains dosages*

**First edition — 1975-03-15**

**(standards.iteh.ai)**

ISO 3195:1975

<https://standards.iteh.ai/catalog/standards/sist/3f9a1012-97e5-4889-933b-aa891a953c4e/iso-3195-1975>

---

**UDC 661.322.1 : 54.05**

**Ref. No. ISO 3195-1975 (E)**

**Descriptors :** sodium hydroxide, sampling, test specimens.

Price based on 1 page

## FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3195 was drawn up by Technical Committee ISO/TC 47, *Chemistry*, and circulated to the Member Bodies in October 1973.

**STANDARD PREVIEW**  
**(standards.iteh.ai)**

It has been approved by the Member Bodies of the following countries :

Australia	Hungary	<u>ISO 3195:1975</u>
Austria	India	<a href="https://standards.iteh.ai/catalog/standards/siv/3195-1975">https://standards.iteh.ai/catalog/standards/siv/3195-1975</a>
Belgium	Israel	South Africa, Rep. of
Bulgaria	Italy	Spain
Chile	Netherlands	Switzerland
Czechoslovakia	New Zealand	Thailand
Egypt, Arab Rep. of	Poland	Turkey
France	Portugal	United Kingdom
Germany	Romania	U.S.S.R.
		Yugoslavia

No Member Body expressed disapproval of the document.

This International Standard cancels and replaces ISO Recommendations R 977-1969 and R 978-1969.

# Sodium hydroxide for industrial use – Sampling – Test sample – Preparation of the main solution for carrying out certain determinations

## 1 SCOPE AND FIELD OF APPLICATION

This International Standard gives instructions relating to the sampling of consignments of sodium hydroxide, indicates the conditions under which the test sample shall be prepared, and specifies a method for the preparation of the main solution which will be used for carrying out certain determinations.

## 2 LABORATORY SAMPLE

2.1 The properties of sodium hydroxide make particular precautions essential: its hygroscopic characteristics, its ability to absorb carbon dioxide and its corrosive action on containers. These properties make it necessary that:

- samples shall be taken rapidly in a dry atmosphere;
- the laboratory sample shall be stored in an airtight bottle, protected from contact with the atmosphere;
- the bottle shall be made of a material which does not contaminate the sample with the elements to be determined (for example, a silica-free material such as polyethylene, if the determination of silica content is intended).

2.2 For the methods of sampling, and the number of portions to be drawn from a given quantity, see ISO . . . 1)

## 3 TEST SAMPLE

3.1 The laboratory sample shall be protected from the atmosphere and handled in such a way that no appreciable absorption of water or carbon dioxide is possible during the operations.

Crushing or grinding in a mortar, if necessary, shall be carried out as rapidly as possible in an atmosphere of maximum dryness.

It is recommended that these operations should be carried out in a glove box from which moisture and carbon dioxide have been removed by the introduction, at least 1 h before the sample is treated, of flat dishes, one containing phosphorus(V) oxide and another potassium hydroxide pellets.

3.2 Take about 300 g of the laboratory sample and, in the case of a solid product, grind it, if necessary, to ensure that

the greatest dimension of the particles does not exceed about 6 mm. Place the sample in an airtight container made of a material which will not contaminate the sample with the elements to be determined, and which is of such a capacity that it is almost completely filled.

The container shall bear a label, with a protective coating, indicating:

- the origin and identification of the test sample;
- the date on which it was placed in the container.

## 4 PREPARATION OF THE MAIN SOLUTION FOR CARRYING OUT CERTAIN DETERMINATIONS (SOLUTION A)

### 4.1 Test portion

In a glass weighing bottle fitted with a ground lid, weigh, to the nearest 0,01 g, a mass of the solid or liquid test sample corresponding to a little less than 40 g of NaOH.

### 4.2 Reagent

Distilled carbonate-free water, or water of equivalent purity, shall be used.

### 4.3 Procedure (Preparation of the main solution (A))

#### 4.3.1 Solid products

Dissolve the test portion (4.1) in about 200 ml of water. Cool to room temperature and transfer the solution quantitatively to a 1 000 ml one-mark volumetric flask, dilute almost to the mark, cool again to room temperature, complete the dilution to the mark, and mix.

#### 4.3.2 Liquid products

Transfer the test portion (4.1) directly and quantitatively to a 1 000 ml one-mark volumetric flask, dilute almost to the mark, cool again to room temperature, complete the dilution to the mark and mix.

NOTE – If the silica content is to be determined, dissolve the test portion in a container made of silica-free material (for example, polyethylene or silver). In the case of a polyethylene container, cool the outer walls with running water in order to prevent softening. After the dilution to the mark in a 1 000 ml one-mark volumetric flask, transfer the solution to a dry polyethylene bottle with an airtight closure.

1) In preparation.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

This page intentionally left blank

[ISO 3195:1975](#)

<https://standards.iteh.ai/catalog/standards/sist/3f9a1012-97e5-4889-933b-aa891a953c4e/iso-3195-1975>