ISO/DTS-11899-1:2023(E)

ISO-<u>/</u>TC-<u>281</u>/WG 3

Secretariat: JISC

Date: 2023-06-1507-21

Fine-bubble technology— — Transportation and dispensing systems for agro- and aqua-cultural applications— —

Part-1:

Ultrafine bubble concentration loss in ultrafine bubble water passing through long-distance plastic pipes

(standards.iteh.ai)

<u>ISO/DTS 11899-1</u> https://standards.iteh.ai/catalog/standards/sist/d5c1286c-2484-45d3-a5a2cd66c75acfd1/iso-dts-11899-1

DTSFDIS stage

Warning for WDs and CDs

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

A model manuscript of a draft International Standard (known as "The Rice Model") is available at <u>https://www.iso.org/iso/model_document-rice_model.pdf</u>

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DTS 11899-1 https://standards.iteh.ai/catalog/standards/sist/d5c1286c-2484-45d3-a5a2cd66c75acfd1/iso-dts-11899-1

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/DTS 11899-1</u> https://standards.iteh.ai/catalog/standards/sist/d5c1286c-2484-45d3-a5a2cd66c75acfd1/iso-dts-11899-1

ISO/DTS-11899-1:2023(:(E)

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +_41 22 749 01 11 <u>EmailE-mail</u>: copyright@iso.org Website: <u>www.iso.orgwww.iso.org</u>

Published in Switzerland

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DTS 11899-1 https://standards.iteh.ai/catalog/standards/sist/d5c1286c-2484-45d3-a5a2cd66c75acfd1/iso-dts-11899-1

_v

Contents

<u>Forew</u>	vord	<u></u> vii
Introd	duction	viii
<u>Part 1</u> plastic	L: Ultrafine bubble concentration loss in ultrafine bubble water passing through lo	<u>ng-distance</u> 1
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
<u>4</u>	Testing method and data analysis	2
<u>4.1</u>	Basic testing method	2
<u>4.2</u>	Equipment and environment	<u></u> 3
<u>4.2.1</u>	Reservoir	4
<u>4.2.2</u>	Ultrafine bubble water	<u></u> 4
<u>4.2.3</u>	Pumping	<u></u> 4
<u>4.2.4</u>	Long winding pipe	<u></u> 4
<u>4.2.5</u>	Flow meter	4
<u>4.2.6</u>	Measuring instrument of number concentration index of ultrafine bubble	<u></u> 4
<u>4.2.7</u>	Sampling pipet and glass bottle	<u></u> 5
<u>4.2.8</u>	Thermometer	<u></u> 5
<u>4.2.9</u>	Stop watch	<u></u> 5
<u>4.3</u>	<u>Test procedure</u>	<u></u> 5
<u>4.4</u>	Data analysis	6
<u>5</u>	Test report	<u></u> 7
Annex	x A (informative) Example of test and data analysis	8
<u>A.1</u>	System settings	8
<u>A.1.1</u>	Measuring instrument	8
<u>A.1.2</u>	Reservoir	8
<u>A.1.3</u>	Gear pump	<u></u> 8
<u>A.1.4</u>	Pressure gauge 1	8
<u>A.1.5</u>	Pressure gauge 2	8
<u>A.1.6</u>	<u>Flowmeter</u>	<u></u> 8
<u>A.1.7</u>	Sampling pipet	<u> </u>
<u>A.1.8</u>	Pipe	<u></u> 9
<u>A.1.9</u>	Plastic bobbin	<u></u> 9
<u>A.2</u>	Procedure of the operation	<u></u> 11
<u>A.3</u>	Data analysis	<u></u> 13
<u>A.3.1</u>	Initial check	<u></u> 13
<u>A.3.2</u>	Results of the test	<u></u> 13
<u>A.4</u>	Some elements of the report	<u></u> 16

ISO/DTS-11899-1:2023(:(E)

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Testing method and data analysis 2

4.1—Basic of testing method 2

4.2—Equipment and environment 3

4.3 Test procedure4

4.4 Data analysis 4

5 Test report 5

Annex A (informative) Example of test and data analysis 7

A.1 System settings 7

A.2 Procedure of Operation 9

A.3 Data analysis 10 h STANDARD PREVIEW

A.4 Some elements of the report 11 Bibliography 12

Bibliography 13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part-1. In particular, the different approval criteria needed for the different types of ISO <u>documentsdocument</u> should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part-___2 (see <u>www.iso.org/directiveswww.iso.org/directives</u>).

Attention is drawnISO draws attention to the possibility that some of the elementsimplementation of this document may beinvolve the subjectuse of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights- in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

<u>SO/DTS 11899-</u>

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <u>www.iso.org/iso/foreword.html</u>.

This document was prepared by Technical Committee ISO/TC 281, *Fine bubble technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

Fine bubbles are applied to agro- and aqua-culture in their uses for supplying water, nutrition and chemicals for facilitation of growth, sterilization and cleaning. Ultrafine bubbles are known to exhibit great stability in water, provided that they are used appropriately within their intended application.

However, since their farms are spatially broad and remotely located, water needs to be transported by pipe lines to meet the huge amounts required. Furthermore, in order to see the benefit of applying ultrafine bubbles, the transportation line should maintain consistent fine bubble water characteristics, including its number concentration index of ultrafine bubbles. <u>One can show many Many</u> mechanisms <u>can be shown</u> for removal of ultrafine bubbles due to mechanical, chemical and thermodynamical effect to imagine the change in the number concentration index loss due to flow in the pipe. When designing the farming system, a reliable prediction on the removal of ultrafine bubbles in the water on the site is required<u>needed</u>.

However, there is no useful test method for data or relevant experiment to evaluate how long ultrafine bubbles can practically survive after long transportation.

This technical specification<u>document</u> provides the test method on experimental evaluation on a long transfer plastic pipe system in terms of reduction in the ultrafine bubble concentration index due to the flow in pipes. The system, consisting of a reservoir for ultrafine bubble water and a winding pipe, through which the water is circulated periodically from the reservoir, allows description of concentration loss by empirical equation. Systematic analysis of the data output from the practical test process can benefit users for planning and improving a similar system. An example of deduced formula optimized to reproducing observed data is given in an informative annex. Annex A.

This document is not to cannot be used for any conformity assessment activities on relevant test.

ISO/DTS 11899-1 https://standards.iteh.ai/catalog/standards/sist/d5c1286c-2484-45d3-a5a2cd66c75acfd1/iso-dts-11899-1

Part-1:

Ultrafine bubble concentration loss in ultrafine bubble water passing through long—_distance plastic pipes

1 Scope

This document specifies a test procedure, equipment and environment for evaluating the concentration loss of ultrafine bubbles (UFB) due to long-_distance transfer of ultrafine bubble water in a plastic pipe. The test results are analysed and expressed in terms of a formula with the flow parameters, pipe length, flow velocity and number of circulations through the pipe. –The formula is intended to be used for designing long-distance transport system for industrial applications including agro- and aqua- farming.

<u>32</u>Normative references

There are no normative references in this document.

43_Terms and definitions(standards.iteh.ai)

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>https://www.iso.org/obp

— IEC Electropedia: available at <u>https://www.electropedia.org/</u>https://www.electropedia.org/

3.1 surviving rate

Φ

ratio of number concentration index of ultrafine bubbles [1]^[1] at the entrance of a pipe to that at the end of the pipe

Note 1-_to-_entry:-_The number concentration index of ultrafine bubbles in the water decreases during the flow through the pump and the winding pipe. -The rate is evaluated for a sample taken from a reservoir. The vessel is open to room air and the water level is kept over the inlet and the outlet.

3.2

reservoir

vessel for ultrafine bubble water staying almost at rest during the water circulation filled with the water returning back from pipe at its inlet and fed to the gear pump at its outlet, intended to sample ultrafine bubble water for measurement

3.3

sampling

sampling of ultrafine bubble water from the reservoir using a pipet and sampling bottle for the measurement of a size index and a number concentration index $[3]^{[3]}$

3.4

long winding pipe

long plastic pipe with small inner diameter winding on the bobbin to simulate the behaviour of the longdistance plastic pipe for practical use

3.5

number of circulation-np

<u>n</u>p

number of ultrafine bubble water circulation passing through the transport system

Note 1-to-entry:-The number is defined by the ratio of the product of flow rate in the long winding pipe with elapsed time of an experiment to volume of long winding pipe.

3.6

flow velocity-#d

<u>*U*</u><u>d</u>

fluid velocity of ultrafine bubble water in the long winding pipe

3.7

loss factor

k

coefficient relating the time derivative of <u>the</u> surviving rate to the surviving rate itself

Note-_1-_to-_entry:-_In the analysis of the report, the relationship is assumed to be linear and the loss factor, k_* is its proportional coefficient. See the Formula (1). Formula (1).

54 Testing method and data analysis rds.iteh.ai)

5.14.1 Basic testing method

<u>ISO/DTS 11899-1</u>

The behaviour of extended long-distance plastic pipe is simulated by a pipe winding by many turns measuring long distance in the testing room. The ultrafine bubble water in a reservoir is pushed in by a pump from one end of the pipe and released back to the reservoir after the water completely passes through the long winding pipe.

The decrease in number concentration index of ultrafine bubbles after the passing is measured by particle tracking analysis method.

The process is operated continuously by feeding the water from the outlet of the pipe to the inlet through a reservoir and the pressurizing pump. The pushing pressure is kept constant throughout an experiment $\frac{1}{2}$.

The measurement sample is taken from the reservoir several times synchronous with the period of the circulation. The systematic decrease of number concentration index and elapsed time are recorded for an experiment with selected parameters on inner diameter, *d*, length of pipe, L_{\star} and flow velocity, $v_{d,\tau_{\star}}$

The experiments are conducted for various different values of the parameters and all accumulated output data are analysed for deducing an empirical formula applicable to the condition within the parameter setting.

In Figure 1, Figure 1, a loop indicates one turn of pipe around the bobbin as a part of long winding pipe.





<u>Key</u>

- <u>1</u> <u>reservoir</u>
- <u>2</u> rotor flow meter
- <u>3</u> <u>needle valve</u>
- 4 gear pump
- 5 pressure gauge 1
- <u>6</u> pressure gauge 2
- <u>7</u> pipeline



5.34.2 Equipment and environment

The environment for the test operation should be conducted at ambient temperature and air pressure and water should be less exposed to the room air in order not to introduce solid contaminant to the water.

The following equipment should be applied for the test system.