

FINAL DRAFT International Standard

ISO/FDIS 8745

ISO/TC 2

Secretariat: DIN

Voting begins on: 2024-12-05

Voting terminates on: 2025-01-30

Document Preview

ISO/FDIS 8745

https://standards.iteh.ai/catalog/standards/iso/301b1dc6-6fed-43c1-8d1f-4e9a67c10e08/iso-fdis-8745

ISO/CEN PARALLEL PROCESSING

Fasteners — Taper grooved pins —

Half-length progressive grooves

Fixations — Goupilles cannelées progressives — Cannelures

progressives sur la moitié de la longueur

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNO-LOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 8745

https://standards.iteh.ai/catalog/standards/iso/301b1dc6-6fed-43c1-8d1f-4e9a67c10e08/iso-fdis-8745



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org Published in Switzerland

ISO/FDIS 8745:2024(en)

Contents

Forew	ordiv	
1	Scope 1	
2	Normative references 1	
3	Terms and definitions1	
4	Principles of grooved pins and assembly1	
5	Dimensions	
6	Requirements and reference International Standards	
7	Labelling on package	
8	Designation	
Bibliography		

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO/FDIS 8745</u>

https://standards.iteh.ai/catalog/standards/iso/301b1dc6-6fed-43c1-8d1f-4e9a67c10e08/iso-fdis-8745

ISO/FDIS 8745:2024(en)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 2, *Fasteners*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 185 *Fasteners*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 8745:1997) which has been technically revised.

<u>ISO/FDIS 8745</u>

The main changes are as follows: g/standards/iso/301b1dc6-6fed-43c1-8d1f-4e9a67c10e08/iso-fdis-8745

- terms and definitions, principles for grooved pins and assembly (including hole dimensions), control of the expanded diameter d_2 and pin straightness, mechanical and physical properties (including shear resistance and hardness) and inspection which are common for all grooved pins (product standards ISO 8739 to ISO 8747, ISO 13670 and ISO 13672) have been specified in the new reference standard ISO 13669;
- non-preferred diameters 1 mm, 3,5 mm, 7 mm, 9 mm, 14 mm and 18 mm have been added;
- values of expanded diameter d_2 for steel pins have been slightly increased for the shortest length range, and have been added for stainless steel pins;
- tolerances for the rounded end and values for the chamfered end have been added;
- tolerances for the length of the grooves have been added;
- stainless steel grades A2, A4, C1 and F1 have been added;
- other materials (such as hardened steels, brass, aluminium) are by agreement (see <u>Table 3</u>);
- specifications for labelling have been added as <u>Clause 8</u>.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Fasteners — Taper grooved pins — Half-length progressive grooves

1 Scope

This document specifies the characteristics of taper grooved pins with half-length progressive grooves (with close-end at the insertion side), in steel and stainless steel, and with nominal diameter 1 mm to 25 mm.

These grooved pins are designed to fulfil the main following functions:

— positioning or guiding, and

relative rotation of the assembled parts,

with an easy installation (due to its shape) and a medium level of pull-out resistance (due to the elastic fit behaviour of the pin).

NOTE The general requirements (including functional principles for grooved pins and assembly) are specified in ISO 13669.

2 Normative references

iTeh Standards

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1891-4, Fasteners — Vocabulary — Part 4: Control, inspection, delivery, acceptance and quality

ISO 3269, Fasteners — Acceptance inspection ISO/FDIS 8745

ISO 3506-6, Fasteners — Mechanical properties of corrosion-resistant stainless steel fasteners — Part 6: General rules for the selection of stainless steels and nickel alloys for fasteners

ISO 4042, Fasteners — Electroplated coating systems

ISO 9717, Metallic and other inorganic coatings — Phosphate conversion coating of metals

ISO 10683, Fasteners — Non-electrolytically applied zinc flake coating systems

ISO 13669, Fasteners — Grooved pins — General requirements

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13669 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at <u>https://www.electropedia.org/</u>

4 Principles of grooved pins and assembly


The principles of grooved pins and assembly specified in ISO 13669 shall apply.

5 Dimensions

Dimensions shall be in accordance with Figure 1 and with Tables 1 and 2. The control of the expanded diameter d_2 and the pin axial straightness *t* shall be as specified in ISO 13669.

For coated pins, dimensions and tolerances shall apply prior to coating.

Unless otherwise agreed at the time of the order, the pins are manufactured with rounded ends.



b) Option: pin with chamfered ends (CH)

Кеу

- 1 insertion side
- ^a The pin diameter d_1 is only applicable in areas where grooves are not present.
- ^b The angle of 120° between two grooves shall apply with a tolerance of $\pm 20^{\circ}$.
- ^c The groove angle of 70° is a reference dimension, see ISO 13669.

Figure 1 — Taper grooved pins with half-length progressive grooves

In accordance with Figure 1, the length of the grooves shall be equal to l/2 with the following tolerance:

- $l \le 10 \text{ mm} \qquad l/2 \pm 0.3 \text{ mm}$
- $10 \text{ mm} < l \le 50 \text{ mm}$ $l/2 \pm 0.6 \text{ mm}$
- $50 \text{ mm} < l \le 100 \text{ mm}$ $l/2 \pm 1,0 \text{ mm}$
- $100 \text{ mm} < l \le 200 \text{ mm}$ $l/2 \pm 1,5 \text{ mm}$

The three grooves shall be open at the end opposite to the insertion side.