

SLOVENSKI STANDARD SIST ISO 3212:1995

01-november-1995

Polipropilenske cevi - Zahteve preskušanja odpornosti na notranji tlak

Polypropylene pipes -- Burst test requirements

Tubes en polypropylène -- Spécifications pour les essais de résistance à l'écartement

Ta slovenski standard je istoveten z: ISO 3212:1975

SIST ISO 3212:1995

https://standards.iteh.ai/catalog/standards/sist/0a93f8a0-b054-48cd-90ae-9ef1f6b9d047/sist-iso-3212-1995

<u>ICS:</u>

23.040.20 Cevi iz polimernih materialov Plastics pipes

SIST ISO 3212:1995

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 3212:1995</u> https://standards.iteh.ai/catalog/standards/sist/0a93f8a0-b054-48cd-90ae-9ef1 f6b9d047/sist-iso-3212-1995



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION METALYHAPOLHAR OPFAHUSALUR DO CTAHLAPTUSALUU.ORGANISATION INTERNATIONALE DE NORMALISATION

Polypropylene pipes – Burst test requirements

Tubes en polypropylène - Spécifications pour les essais de résistance à l'éclatement

First edition – 1975-09-01Teh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 3212:1995</u> https://standards.iteh.ai/catalog/standards/sist/0a93f8a0-b054-48cd-90ae-9ef1f6b9d047/sist-iso-3212-1995

UDC 621.643

Ref. No. ISO 3212-1975 (E)

Descriptors : plastic pipes, polypropylene, tests, burst tests, high pressure tests, testing conditions.

3212

SIST ISO 3212:1995

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3212 was edrawn up by Technical Committee VIEW ISO/TC 138, *Plastic pipes, fittings and valves for the transport of fluids, and* circulated to the Member Bodies in September 1973. **Cancel Science** 1973.

It has been approved by the Member Bodies of the following countries 2:1995

Belgium	https://standards.iteh.ai/catalog/standards/sistflep3fla0-b054-48cd-90ae-		
Bulgaria	Ireland	9ef1f6b9sWe7eist-iso-3212-1995	
Czechoslovakia	Israel	Switzerland	
Denmark	Netherlands	Thailand	
Egypt, Arab Rep. of	Norway	Turkey	
Finland	Poland	U.S.A.	
France	Portugal	U.S.S.R.	
Germany	Romania		
	•		

No Member Body expressed disapproval of the document.

◎ International Organization for Standardization, 1975 ●

Printed in Switzerland

Polypropylene pipes – Burst test requirements

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies the conditions (temperature, time and stress) in which the burst tests of polypropylene pipes (homopolymer and copolymer) shall be carried out.

2 CONDITIONS

The conditions in which the burst tests shall be carried out are given in the following table.

Material	Temperature	Time	Tangential stress
	°c	h	N/mm ²
Homopolymer	h STANDARD	PREVIEW	23
	(stan@ards.it	eh.ai) 1 000 1)	2,3
	(95)1)	(1 000) ¹⁾	(3,5)
	ards.iteh.ai/catalog/standards/sist	/0a93f8a0-b0345498cd-90ae-	1,6
Copolymer	9ef1f6b2d047/sist-iso-3	212-1995 ₁	18
	120 ¹⁾	1 000 ¹⁾	1,9
	(95) ¹⁾	(1 000) ¹⁾	(2,5)
	120 ²⁾	2 500	1,6

1) It is recommended to carry out the test at 120 °C, 1 000 h - which is the reference test - rather than the test at 95 °C.

2) The test at 120 °C, 2 500 h, is for the establishment of the quality of pipes when they are made with a new resin or composition.

NOTES

1 The values in brackets are to be avoided as far as possible.

2 During an interim period, tests at 95 $^{\circ}$ C are permitted in place of tests at 120 $^{\circ}$ C, 2 500 h. These tests shall be carried out in the following conditions :

Homopolymer : $95 \degree C - 8 \ 000 \ h - 2.5 \ N/mm^2$;

Copolymer : $95 \degree C - 4 000 h - 2,0 N/mm^2$.

3 The burst tests at 20 °C and 95 °C shall be carried out with water in the pipes, and water or air around them. The burst tests at 120 °C shall be carried out with water in the pipes, and air around them.