



Designation: F2965 – 13

Standard Guide for Selection of Walkway Surfaces and Treatments When Considering Aggressive Contaminant Conditions in Commercial and Industrial (Not Including Construction) Environments¹

This standard is issued under the fixed designation F2965; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide is intended to assist in the selection of walking surfaces and treatments where the foreseeable presence of aggressive contaminants produces the danger of a slip and fall injury events in commercial and industrial (not including construction) environments, for persons wearing appropriate footwear.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

F1646 Terminology Relating to Safety and Traction for Footwear

3. Terminology

3.1 For general definitions of terms, refer to the Terminology F1646.

3.2 *Definitions:*

3.2.1 *aggressive contaminants, n*—substances that create a gross separation between the footwear bottom and the walkway surface.

3.2.2 *self-cleaning, adj*—property of a walkway surface or treatment where foot pressure breaks up or displaces, or both, a contaminant on a walkway surface in a manner that restores direct contact between the walkway surface and the footwear bottom in contaminated conditions.

¹ This test method is under the jurisdiction of ASTM Committee F13 on Pedestrian/Walkway Safety and Footwear and is the direct responsibility of Subcommittee F13.50 on Walkway Surfaces.

Current edition approved March 1, 2013. Published April 2013. DOI: 10.1520/F2965-13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

4. Summary of Guide

4.1 Slip and fall injury events are often caused by contaminants on a walkway surface. Slips that occur because of the presence of contaminants result from the additional interface between the footwear bottom and the walkway surface. The interface between the footwear bottom and the walkway surface is replaced by an interface between the footwear bottom and the contaminant, and another interface between the contaminant and the walkway surface.

4.2 Aggressive contaminants create a gross separation between the footwear bottom and the walkway surface, where the least dimension of solid contaminants or the depth of highly viscous liquid contaminants is greater than the height of the walkway surface protrusions or asperities, and/or greater than the depth of texturing or tread of footwear. Aggressive contaminants are exemplified by high viscosity liquids or semi-liquids such as juicy fruits and vegetables, rounded objects that act as roller bearings such as rounded stones and gravel on hard smooth surfaces, manufacturing scraps and byproducts on the walkway surface, snow, ice, mud, and other similar contaminants.

4.3 Primary control of contaminants should be to eliminate or contain contaminants at the source to prevent contamination. Secondary control of contaminants, if needed, should be to establish methodologies and procedures to promptly remove contaminants when introduced onto a walkway surface. Walkway surface safety enhancement is recommended where the presence of aggressive contaminants cannot be practicably and reliably removed from or otherwise controlled on a walkway surface to acceptable levels as determined by a competent safety analysis.

4.4 The primary enhancement method is to increase the slip-resistance of the walkway surface. Walkway surfaces with prominent projections of sufficient height or sharpness, or both, may be of benefit. Walkway surfaces that are self-cleaning as they are used by pedestrians may be of benefit. Self-cleaning, as a property of a walkway surface or treatment, is where foot pressure breaks up the contaminant on the walkway surface or otherwise forces the contaminant into voids between openings,