

ISO/DTR 10300-30:2023(E)

ISO TC 60/SC 2/WG 13

Date: 2023-09-26 11:29

Calculation of load capacity of bevel gears — Part 30: ISO rating system for bevel and hypoid gears — Sample calculations

DTR stage

ISO/DTR 10300-30

<https://standards.iteh.ai/catalog/standards/sist/65844b6d-8d24-487c-9ff5-f7b9065dd6ba/iso-dtr-10300-30>

ISO/DTR 10300-30:2023(E)

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO/DTR 10300-30](https://standards.iteh.ai/catalog/standards/sist/65844b6d-8d24-487c-9ff5-f7b9065dd6ba/iso-dtr-10300-30)

<https://standards.iteh.ai/catalog/standards/sist/65844b6d-8d24-487c-9ff5-f7b9065dd6ba/iso-dtr-10300-30>

ii ————— © ISO 2023 – All rights reserved

ii ————— © ISO 2023 – All rights reserved

Contents

Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 Application	10
5.1 General.....	10
5.2 Structure of calculation methods.....	11
Annex A (informative) Sample 1: Rating of a spiral bevel gear pair without hypoid offset according to Method B1 and Method B2	14
A.1 Initial data.....	14
A.2 Calculation of Sample 1 according to Method B1.....	18
A.3 Calculation of Sample 1 according to Method B2.....	58
A.4 Calculation of Sample 1 according to local calculation method for surface durability—Method B1 localised.....	100
Annex B (informative) Sample 2: Rating of a hypoid gear set according to Method B1 and Method B2	186
B.1 Initial data.....	186
B.2 Calculation of Sample 2 according to Method B1.....	193
B.3 Calculation of Sample 2 according to Method B2.....	228
B.4 Calculation of Sample 2 according to local calculation method for surface durability—Method B1 localised.....	275
Annex C (informative) Sample 3: Rating of a hypoid gear set according to Method B1 and Method B2	317
C.1 Initial data.....	317
C.2 Calculation of Sample 3 according to Method B1.....	322
C.3 Calculation of Sample 3 according to Method B2.....	356
C.4 Calculation of Sample 3 according to local calculation method for surface durability—Method B1 localised.....	398
Annex D (informative) Sample 4: Rating of a hypoid gear set according to Method B1 and Method B2	439
D.1 Initial data.....	439
D.2 Calculation of Sample 4 according to Method B1.....	444
D.3 Calculation of Sample 4 according to Method B2.....	473

D.4 Calculation of Sample 4 according to local calculation method for surface durability – Method B1 localised	518
Annex E (informative) Graphical representation of the calculation results for Sample 1 to Sample 4	605
Bibliography	612
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 Application	10
5.1 General	10
5.2 Structure of calculation methods	11
Annex A (informative) Sample 1: Rating of a spiral bevel gear pair without hypoid offset according to Method B1 and Method B2	14
A.1 Initial data	14
A.2 Calculation of Sample 1 according to Method B1	18
A.3 Calculation of Sample 1 according to Method B2	58
A.4 Calculation of Sample 1 according to local calculation method for surface durability – Method B1 localised	100
Annex B (informative) Sample 2: Rating of a hypoid gear set according to Method B1 and Method B2	186
B.1 Initial data	186
B.2 Calculation of Sample 2 according to Method B1	193
B.3 Calculation of Sample 2 according to Method B2	228
B.4 Calculation of Sample 2 according to local calculation method for surface durability – Method B1 localised	275
Annex C (informative) Sample 3: Rating of a hypoid gear set according to Method B1 and Method B2	317
C.1 Initial data	317
C.2 Calculation of Sample 3 according to Method B1	322
C.3 Calculation of Sample 3 according to Method B2	356
C.4 Calculation of Sample 3 according to local calculation method for surface durability – Method B1 localised	398
Annex D (informative) Sample 4: Rating of a hypoid gear set according to Method B1 and Method B2	439
D.1 Initial data	439

D.2 Calculation of Sample 4 according to Method B1	444
D.3 Calculation of Sample 4 according to Method B2	473
D.4 Calculation of Sample 4 according to local calculation method for surface durability - Method B1 localised.....	518
Annex E (informative) Graphical representation of the calculation results for Sample 1 to Sample 4	605
Bibliography	612

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/DTR 10300-30](#)

<https://standards.iteh.ai/catalog/standards/sist/65844b6d-8d24-487c-9ff5-f7b9065dd6ba/iso-dtr-10300-30>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of patents. ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of patents which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This second edition cancels and replaces the first edition (ISO/TR 10300-30:2017), which has been technically revised.

The main changes are as follows:

- all sample calculations ~~apply~~ **have been revised according to ISO-10300-1:2023, ISO-10300-2:2023 and ISO-10300-3:2023;**
- all sample calculations include localised calculation method for Method B1.

A list of all parts in the ISO 10300 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 10300 series consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of bevel gears* (see Table 1).

- International Standards contain calculation methods that are based on widely accepted practices and — have been validated.
- TS contain calculation methods that are still subject to further development.
- TR contain data that is informative, such as example calculations.

The procedures specified in ISO 10300-1 to ISO 10300-19 cover fatigue analyses for gear rating. The procedures described in ISO 10300-20 to ISO 10300-29 are predominantly related to the tribological behaviour of the lubricated flank surface contact. ISO 10300-30 to ISO 10300-39 include example calculations. The ISO 10300 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting standardized calculations according to [the ISO 10300 series](#) without referring to specific parts requires the use of only those parts that are currently designated as International Standards (see Table 1 for listing). When requesting further calculations, the relevant part or parts of ISO 10300 need to be specified. [Use](#) [The use](#) of a Technical Specification as acceptance criteria for a specific design [need/needs](#) to be agreed in advance between manufacturer and purchaser.

Table 1 — Overview of [the ISO 10300 series](#)

Calculation of load capacity of bevel gears	International Standard	Technical Specification	Technical Report
Part 1: Introduction and general influence factors	X		
Part 2: Calculation of surface durability (macropitting)	X		
Part 3: Calculation of tooth root strength	X		
Part 4 to 19: to be assigned			
Part 20: Calculation of scuffing load capacity – Flash temperature method		X	
Part 21 to 29: to be assigned			
Part 30: ISO rating system for bevel and hypoid gears — Sample calculations			X
Part 32: ISO rating system for bevel and hypoid gears — Sample calculation for scuffing load capacity			X
NOTE At the time of publication of this document, some of the parts listed here were under development. Consult the ISO website.			

This document was prepared with sample calculations for different bevel gear designs. They are intended for users of the ISO 10300 series to follow a whole calculation procedure formula by formula. Practical experience has shown that this way, to get into a complex subject, is very helpful.

On the other hand, this document is not intended for use by the average engineer. Rather, it is aimed at the well-versed engineer capable of selecting reasonable values for the parameters and factors in these formulae based on knowledge of similar designs and on awareness of the effects behind these formulae.

Calculation of load capacity of bevel gears —

Part 30: ISO rating system for bevel and hypoid gears — Sample calculations

1 Scope

This document provides sample calculations for the load capacity of different bevel gear designs, ~~how the load capacity is numerically~~ determined according to the methods and formulae of the ISO_10300_series. The initial geometric gear data necessary for these calculations ~~in accordance with~~ are according to ISO 23509.

The term “bevel gear” is used to mean straight, helical (skew), spiral bevel, zerol and hypoid gear designs. Where this document pertains to one or more, but not all, the specific forms are identified.

The manufacturing process of forming the desired tooth form is not intended to imply any specific process, but rather to be general in nature and applicable to all calculation methods of the ISO 10300 series. The fact that there are bevel gear designs with tapered teeth and others where the tooth depth remains constant along the facewidth (uniform depth) does not ~~demand~~ require to apply Method B2 for the first and Method B1 for the second tooth configuration.

The rating system of the ISO 10300 series is based on virtual cylindrical gears and restricted to bevel gears whose virtual cylindrical gears have transverse contact ratios of $\epsilon_{va} < 2$. Additionally, the given relations are valid for bevel gears of which the sum of profile shift coefficients of pinion and wheel is zero (see ISO 23509).

WARNING— The user is cautioned that when the formulae are used for large average mean spiral angles, $(\beta_{m1} + \beta_{m2})/2 > 45^\circ$, for effective pressure angles, $\alpha_e > 30^\circ$ and/or for large facewidths, $b > 13 m_{mn}$, to confirm the calculated results of the ISO 10300 series by experience.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10300-1:2023, *Calculation of load capacity of bevel gears — Part 1: Introduction and general influence factors*

ISO 10300-2:2023, *Calculation of load capacity of bevel gears — Part 2: Calculation of surface durability (macropitting)*

ISO 10300-3:2023, *Calculation of load capacity of bevel gears — Part 3: Calculation of tooth root strength*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 10300-1, ISO 10300-2 and ISO 10300-3 apply.

ISO/DTR 10300-30:2023(E)

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

4 Symbols and abbreviated terms

For the purposes of this document, the symbols and units given in ISO 10300-1:2023, Table 1 and Table 2, ISO 10300-2:2023, Table 1 and Table 2, ISO 10300-3:2023, Table 1 and Table 2 as well as the abbreviated terms given in ISO 10300-2:2023, Table 3, and ISO 10300-3:2023, Table 3, apply.

Table 2 — Symbols and units used in ISO 10300 (all parts)

Symbol	Description or term	Unit
A	Auxiliary factor for calculating the dynamic factor $K_v - c$	—
A^*	Related area for calculating the load sharing factor Z_{LS}	mm
A_{sne}	Outer tooth thickness allowance	mm
a	Hypoid offset	mm
a_{rel}	Relative hypoid offset	—
a_v	Centre distance of virtual cylindrical gear pair	mm
a_{vn}	Centre distance of virtual cylindrical gear pair in normal section	mm
B	Accuracy grade according to ISO 17485	—
b	Facewidth	mm
b_b	Related base facewidth	—
b_{ce}	Calculated effective facewidth	mm
b_{eff}	Effective facewidth (e.g. measured length of contact pattern)	mm
b_v	Facewidth of virtual cylindrical gears	mm
$b_{v,eff}$	Effective facewidth of virtual cylindrical gears	mm
C_F	Correction factor of tooth stiffness for non-average conditions	—
C_{lb}	Correction factor for the length of contact lines	—
C_{ZL}, C_{ZR}, C_{ZV}	Constants for determining lubricant film factors	—
c_{ham}	Mean addendum factor of wheel	—
c_v	Empirical parameter to determine the dynamic factor	—
c_γ	Mean value of mesh stiffness per unit facewidth	N/(mm · μ m)
$c_{\gamma 0}$	Mesh stiffness for average conditions	N/(mm · μ m)
c'	Single stiffness	N/(mm · μ m)
$c_{0'}$	Single stiffness for average conditions	N/(mm · μ m)
d_e	Outer pitch diameter	mm
d_m	Mean pitch diameter	mm

Symbol	Description or term	Unit
d_T	Tolerance diameter according to ISO 17485	mm
d_v	Reference diameter of virtual cylindrical gear	mm
d_{va}	Tip diameter of virtual cylindrical gear	mm
d_{van}	Tip diameter of virtual cylindrical gear in normal section	mm
d_{vb}	Base diameter of virtual cylindrical gear	mm
d_{vbn}	Base diameter of virtual cylindrical gear in normal section	mm
d_{vf}	Root diameter of virtual cylindrical gear	mm
d_{vn}	Reference diameter of virtual cylindrical gear in normal section	mm
E	Modulus of elasticity, Young's modulus	N/mm ²
E, G, H	Auxiliary variables for tooth form factor (Method B1)	—
e_{LS}	Exponent for the distribution of the load peaks along the lines of contact	—
F	Auxiliary variable for mid-zone factor	—
F_{mt}	Nominal tangential force at mid facewidth of the reference cone	N
F_{mth}	Determinant tangential force at mid facewidth of the reference cone	N
F_n	Nominal normal force	N
F_{vmt}	Nominal tangential force of virtual cylindrical gears	N
f	Distance from the centre of the zone of action to a contact line	mm
f_{max}	Maximum distance to middle contact line	mm
f_{maxB}	Maximum distance to middle contact line at right side of the contact pattern	mm
f_{max0}	Maximum distance to middle contact line at left side of the contact pattern	mm
f_{pt}	Single pitch deviation	μm
$f_{p\text{ eff}}$	Effective pitch deviation	μm
f_{alim}	Influence factor of limit pressure angle	
g_c	Length of contact line (Method B2)	mm
g_{va}	Length of path of contact of virtual cylindrical gear in transverse section	mm
g_{van}	Related length of action in normal section	—
g_l	Length of action from mean point to point of load application (Method B2)	mm
g_n	Relative length of action within the contact ellipse	mm
HB	Brinell hardness	—
h_{am}	Mean addendum	mm
h_{a0}	Tool addendum	mm

ISO/DTR 10300-30:2023(E)

Symbol	Description or term	Unit
h_{Fa}	Bending moment arm for tooth root stress (load application at tooth tip)	mm
h_{fm}	Mean dedendum	mm
h_{fp}	Dedendum of the basic rack profile	mm
h_m	Mean whole depth used for bevel spiral angle factor	mm
h_{vfm}	Relative mean virtual dedendum	—
h_N	Load height from critical section (Method B2)	mm
j_{en}	Outer normal backlash	mm
K	Constant; factor for calculating the dynamic factor K_{v-B}	—
K_A	Application factor	—
K_{F0}	Lengthwise curvature factor for bending stress	—
$K_{F\alpha}$	Transverse load factor for bending stress	—
$K_{F\alpha}^*$	Preliminary transverse load factor for bending stress for non-hypoid gears	—
$K_{F\beta}$	Face load factor for bending stress	—
$K_{H\alpha}$	Transverse load factor for contact stress	—
$K_{H\alpha}^*$	Preliminary transverse load factor for contact stress for non-hypoid gears	—
$K_{H\beta}$	Face load factor for contact stress	—
$K_{H\beta-be}$	Mounting factor	—
K_v	Dynamic factor	—
K_v^*	Preliminary dynamic factor for non-hypoid gears	—
k'	Contact shift factor	—
k_c	Clearance factor	—
k_d	Depth factor	—
k_{hap}	Basic crown gear addendum factor (related to m_{mn})	—
k_{hfp}	Basic crown gear dedendum factor (related to m_{mn})	—
k_t	Circular thickness factor	—
l_b	Length of contact line (Method B1)	mm
l_{b0}	Theoretical length of contact line	mm
l_{bm}	Theoretical length of middle contact line	mm
m_{et}	Outer transverse module	mm
m_{mn}	Mean normal module	mm
m_{mt}	Mean transverse module	mm
m_{red}	Mass per unit facewidth reduced to the line of action of dynamically equivalent cylindrical gears	kg/mm
m^*	Related individual gear mass per unit facewidth referred to the line of action	kg/mm

Symbol	Description or term	Unit
N	Reference speed related to resonance speed n_{E1}	—
N_L	Number of load cycles	—
n	Rotational speed	min ⁻¹
n_{E1}	Resonance speed of pinion	min ⁻¹
P	Nominal power	kW
p	Peak load	N/mm
p_{et}	Transverse base pitch (Method B2)	mm
p_{max}	Maximum peak load	N/mm
p^*	Related peak load for calculating the load sharing factor (Method B1)	—
p_{mn}	Relative mean normal pitch	—
p_{nb}	Relative mean normal base pitch	—
p_{vet}	Transverse base pitch of virtual cylindrical gear (Method B1)	mm
q	Exponent in the formula for lengthwise curvature factor	—
q_s	Notch parameter	—
q_s	Notch parameter (Method B2)	—
R_a	= CLA = AA arithmetic average roughness	µm
R_e	Outer cone distance	mm
R_m	Mean cone distance	mm
R_{mpt}	Relative mean back cone distance	—
R_z	Mean roughness	µm
R_{Z10}	Mean roughness for gear pairs with relative curvature radius $\rho_{rel} = 10$ mm	µm
r_{c0}	Cutter radius	mm
r_{mf}	Tooth fillet radius at the root in mean section	mm
r_{mpt}	Mean pitch radius	mm
r_{my0}	Mean transverse radius to point of load application (Method B2)	mm
r_{va}	Relative mean virtual tip radius	—
r_{vn}	Relative mean virtual pitch radius	—
S_F	Safety factor for bending stress (against breakage)	—
S_{Fmin}	Minimum safety factor for bending stress	—
S_H	Safety factor for contact stress (against macropitting)	—
S_{Hmin}	Minimum safety factor for contact stress	—
S_{Fn}	Tooth root chord in calculation section	mm
s_{mn}	Mean normal circular thickness	mm
s_N	One-half tooth thickness at critical section (Method B2)	mm

ISO/DTR 10300-30:2023(E)

Symbol	Description or term	Unit
s_{pr}	Amount of protuberance at the tool	mm
$T_{1,2}$	Nominal torque of pinion and wheel	Nm
u	Gear ratio of bevel gear	—
u_v	Gear ratio of virtual cylindrical gear	—
v_{et}	Tangential speed at outer end (heel) of the reference cone	m/s
$v_{et\ max}$	Maximum pitch line velocity at operating pitch diameter	m/s
v_g	Sliding velocity in the mean point P	m/s
$v_{g\ par}$	Sliding velocity parallel to the contact line	m/s
$v_{g\ vert}$	Sliding velocity vertical to the contact line	m/s
v_{mt}	Tangential speed at mid facewidth of the reference cone	m/s
v_{Σ}	Sum of velocities in the mean point P	m/s
$v_{\Sigma h}$	Sum of velocities in profile direction	m/s
$v_{\Sigma l}$	Sum of velocities in lengthwise direction	m/s
$v_{\Sigma\ vert}$	Sum of velocities vertical to the contact line	m/s
W_{m2}	Wheel mean slot width	mm
w	Angle of contact line relative to the root cone	°
x_{hm}	Profile shift coefficient	—
x_{sm}	Thickness modification coefficient (backlash included)	—
x_{smn}	Thickness modification coefficient (theoretical)	—
x_N	Tooth strength factor (Method B2)	mm
x_{oo}	Distance from mean section to point of load application	mm
Y_A	Root stress adjustment factor (Method B2)	—
Y_{BS}	Bevel spiral angle factor	—
Y_{Fa}	Tooth form factor for load application at the tooth tip (Method B1)	—
Y_{FS}	Combined tooth form factor for generated gears	—
Y_f	Stress concentration and stress correction factor (Method B2)	—
Y_i	Inertia factor (bending)	—
Y_j	Bending strength geometry factor (Method B2)	—
Y_{LS}	Load sharing factor (bending)	—
Y_{NT}	Life factor (bending)	—
$Y_{R\ rel\ T}$	Relative surface condition factor	—
Y_{Sa}	Stress correction factor for load application at the tooth tip	—
Y_{ST}	Stress correction factor for dimensions of the standard test gear	—
Y_X	Size factor for tooth root stress	—