
**Road vehicles — Diagnostic
communication over Controller Area
Network (DoCAN) —**

**Part 5:
Specification for an in-vehicle network
connected to the diagnostic link
connector**

*Véhicules routiers — Communication de diagnostic sur gestionnaire
de réseau de communication (DoCAN) —*

*Partie 5: spécification pour un réseau véhicule connecté sur la prise
de diagnostic*

[ISO 15765-5:2023](https://standards.iteh.ai/catalog/standards/sist/7f475d24-7fdf-42a1-b21c-fb889592ef79/iso-15765-5-2023)

<https://standards.iteh.ai/catalog/standards/sist/7f475d24-7fdf-42a1-b21c-fb889592ef79/iso-15765-5-2023>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 15765-5:2023](https://standards.iteh.ai/catalog/standards/sist/7f475d24-7fdf-42a1-b21c-fb889592ef79/iso-15765-5-2023)

<https://standards.iteh.ai/catalog/standards/sist/7f475d24-7fdf-42a1-b21c-fb889592ef79/iso-15765-5-2023>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
4.1 Symbols.....	2
4.2 Abbreviated terms.....	2
5 Conventions	4
6 In-vehicle network to external test equipment connection	4
6.1 Connectivity scenarios between external test equipment and vehicle.....	4
6.2 Technical requirements overview.....	4
6.3 ASP — Data.req, Data.ind and Data.conf service interface.....	5
6.4 ASP — Parameter mapping and configuration of OSI layers.....	5
6.5 Transport layer (TL).....	6
6.5.1 TL – Data interface primitive parameter mapping.....	6
6.5.2 TL – Message segmentation.....	6
6.5.3 TL – ISO 15765-2 segment flow control.....	6
6.6 Network layer (NL).....	6
6.6.1 NL – Data interface primitive parameter mapping.....	6
6.6.2 NL – ISO 15765-2 network layer services.....	7
6.6.3 NL – ISO 15765-2 network layer timing parameters.....	7
6.6.4 NL – ISO 15765-2 uniqueness of node diagnostic address.....	7
6.6.5 NL – ISO 15765-2 supported addressing formats.....	7
6.7 Data link layer (DLL).....	8
6.7.1 DLL – Data interface primitive parameter mapping.....	8
6.7.2 DLL – Service interface parameter requirements.....	9
6.7.3 DLL – Device acceptance of CAN identifier.....	10
6.8 Physical layer (PHY).....	10
6.8.1 PHY – Classical CAN.....	10
6.8.2 PHY – CAN FD.....	12
6.8.3 PHY – Physical media attachment (PMA) requirements.....	14
6.8.4 PHY – Physical media dependent (PMD) sub-layer requirements.....	15
Annex A (informative) Compatibility between test equipment and in-vehicle network connected to diagnostic link connector	17
Bibliography	18

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

This second edition cancels and replaces the first edition (ISO 15765-5:2021), which has been technically revised.

The main changes are as follows:

- clarification on network address translation between OSI-layers;
- editorial corrections.

A list of all parts in the ISO 15765 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The ISO 15765 series defines common requirements for vehicle diagnostic systems using the controller area network (CAN), as specified in the ISO 11898 series.

The ISO 15765 series presumes the use of external test equipment for inspection, diagnostics, repair and other possible use cases connected to the vehicle.

This document defines the requirements to enable the in-vehicle CAN network to successfully establish, maintain and terminate communication with the devices externally connected to the diagnostic link connector.

This document has been structured according to the open systems interconnection (OSI) basic reference model, in accordance with ISO/IEC 7498-1 and ISO/IEC 10731, which structures communication systems into seven layers. When mapped on this model, the OSI layer 4 to OSI layer 1 framework requirements specified or referenced in the ISO 15765 series are structured according to [Figure 1](#), which shows the related documents of OSI layer 4 to OSI layer 1.




Figure 1 — CAN documents reference according to OSI model

The documents include the following content:

- transport layer (TL) -related requirements with reference to ISO 15765-2;
- network layer (NL) -related requirements with reference to ISO 15765-2;
- data link layer (DLL) -related requirements with reference to ISO 11898-1, which are composed of:
 - DLL protocol entity requirements;
 - DLL device interface requirements;
 - DLL network system requirements;
- physical layer (PHY) -related requirements with reference to ISO 11898-2, which are composed of:
 - physical coding sub-layer (PCS) requirements, which are composed of:
 - PCS entity requirements;

- PCS interface requirements;
- PCS network system requirements;
- physical media attachment (PMA) requirements, which are composed of:
 - PMA protocol entity requirements;
 - PMA device interface requirements;
- physical media dependent (PMD) requirements, which are composed of:
 - PMD entity requirements;
 - PMD device interface requirements;
 - PMD network system requirements.

The PCS is implemented in the CAN protocol controller. The PMA sub-layer is implemented normally in the CAN transceiver or the system base chip (SBC). Optionally it can comprise also additional protection circuitry. The media-dependent sub-layer comprises the connectors and the cabling.

Figure 2 shows an implementation example of the data link and physical layers block diagram.




Figure 2 — Implementation example of lower OSI layers block diagram

The above structure is chosen to provide the following implementers with relevant requirements:

- transceiver developers;
- device (e.g. electronic control unit) developers;
- system network developers.

All requirements are numbered and headlined uniquely, so that each implementer can reference them.

Annex A provides a description of the compatibility between test equipment and in-vehicle network connected to the diagnostic link connector.

Road vehicles — Diagnostic communication over Controller Area Network (DoCAN) —

Part 5: Specification for an in-vehicle network connected to the diagnostic link connector

1 Scope

This document specifies the OSI layers 4 to 1 (transport layer, network layer, data link layer and physical layer) requirements related to the connection between the external test equipment externally connected to the diagnostic link connector and the in-vehicle CAN network to successfully establish and maintain communication utilizing the communication parameters (communication profile) specified in (application-type) standards referencing this document.

The SIC (signal improvement capability) transceiver options, as specified in ISO 11898-2, are out of scope in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11898 (all parts), *Road vehicles — Controller area network (CAN)*

ISO 15031-3, *Road vehicles — Communication between vehicle and external equipment for emissions-related diagnostics — Part 3: Diagnostic connector and related electrical circuits: Specification and use*

ISO 15765-2, *Road vehicles — Diagnostic communication over Controller Area Network (DoCAN) — Part 2: Transport protocol and network layer services*

ISO 15765-4, *Road vehicles — Diagnostic communication over Controller Area Network (DoCAN) — Part 4: Requirements for emissions-related systems*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in the ISO 11898 series, ISO 15765-2, ISO 15765-4 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

segment

TL_PDU which consists of the TL_PCI and TL_DATA

3.2 application-type standard

standard which specifies application-related use cases, requirements and communication profile parameter values of the protocol stack

4 Symbols and abbreviated terms

4.1 Symbols

–	empty table cell or feature undefined
Δf	oscillator tolerance
f_{Ba}	nominal arbitration bit rate
f_{Bd}	data bit rate
l_{CABLE}	cable length between in-vehicle CAN node and diagnostic link connector
t_{Ba}	arbitration bit time
t_{Bd}	data bit time
t_{BIT}	bit time
t_{BIT_RX}	receive bit time
t_{BIT_TX}	transmit bit time
t_{Qa}	nominal arbitration bit time quantum length
t_{Qd}	nominal data bit time quantum length
t_{SJWa}	arbitration bit synchronisation jump width
t_{SJWd}	data bit synchronisation jump width
t_Q	time quantum
t_{SPa}	nominal arbitration bit sample point position
t_{SPd}	nominal data bit sample point position
X	table cell selected or feature defined

4.2 Abbreviated terms

AE	address extension
AL	application layer
ASP	abstract service primitive
CAN	controller area network
CAN FD	controller area network flexible data-rate
CBFF	classical base frame format

CEFF	classical extended frame format
DCC	diagnostic communication channel
DiagNormAddr	diagnostic message with normal addressing
DiagNormFixAddr	diagnostic message with normal fixed addressing
DiagExtAddr	diagnostic message with extended addressing
DLL	data link layer
DoCAN	diagnostic communication over controller area network
Ftype	frame type
FBFF	FD base frame format
FEFF	FD extended frame format
L_	data link
MSb	most significant bit
Mtype	message type
N_	network
NL	network layer
N_PDU	network protocol data unit
OSI	open system interconnection
PDU	protocol data unit
PCS	physical coding sub-layer
PHY	physical layer
PMA	physical media attachment
PMD	physical media dependent
Ptype	packet type
RDiagMixAddr	remote diagnostic message with mixed addressing
SA	source address
SIC	signal improvement capability
SJW	synchronisation jump width
SP	sample point
T_Data	T_Data interface
TA	target address
TAtype	target address type

TL transport layer
 T_PDU transport protocol data unit

5 Conventions

This document is based on OSI service conventions as specified in ISO/IEC 10731.

6 In-vehicle network to external test equipment connection

6.1 Connectivity scenarios between external test equipment and vehicle

This document specifies the requirements for the diagnostic link connector providing access to CAN FD network. A backward compatibility to classical CAN is described in [Annex A](#).

6.2 Technical requirements overview

[Table 1](#) provides an overview of the technical requirements and associated requirement numbers.

Table 1 — Technical requirements overview

REQ #	Technical requirement title
OSI4	Transport layer (TL)
OSI4.1	TL – ISO 15765-2 T_Data interface primitive parameter mapping
OSI4.2	TL – ISO 15765-2 TX_DL = 8
OSI4.3	TL – ISO 15765-2 TX_DL > 8
OSI3	Network layer (NL)
OSI3.1	NL – ISO 15765-2 N_Data interface primitive parameter mapping
OSI3.2	NL – ISO 15765-2 network layer services
OSI3.3	NL – ISO 15765-2 network layer timing parameters
OSI3.4	NL – ISO 15765-2 uniqueness of node diagnostic address
OSI3.5	NL – ISO 15765-2 supported addressing formats
OSI3.6	NL – ISO 15765-2 functional addressing
OSI3.7	NL – ISO 15765-2 reception of N_PDU
OSI2	Data link layer (DLL)
OSI2.1	DLL – Data interface primitive parameter mapping – Mapping of upper OSI layer service interface parameters
OSI2.2	DLL – Data interface primitive parameter mapping – ISO 11898-1
OSI2.3	DLL – Mapping of N_AI into the 11-bit CAN identifier
OSI2.4	DLL – Mapping of N_AI into the 29-bit CAN identifier
OSI2.5	DLL – Device acceptance of CAN identifier
OSI1	Physical layer (PHY)
OSI1.1	PHY – PCS entity requirements – ISO 11898-1 conformance
OSI1.2	PHY – PCS interface requirements – Classical CAN bit timing parameters
OSI1.3	PHY – PCS interface requirements – CAN FD sampling method
OSI1.4	PHY – PCS interface requirements – CAN FD bit timing parameters
OSI1.5	PHY – PCS interface requirements – CAN FD transmitter delay compensation
OSI1.6	PHY – PCS interface requirements – Termination resistance
OSI1.7	PHY – PMA entity requirements – ISO 11898-2 conformance