
INTERNATIONAL STANDARD



Second edition 2023-02

Electrically propelled road vehicles — Test specification for electric propulsion components —

Part 1: General test conditions and definitions

Véhicules routiers à propulsion électrique — Spécification d'essai pour les composants de propulsion électrique —

Partie 1: Conditions générales et définitions ISO 21782-1:2023

https://standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33-9b40a3723a08/iso-21782-1-2023



Reference number ISO 21782-1:2023(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 21782-1:2023

https://standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33-9b40a3723a08/iso-21782-1-2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Contents

Fore	eword	iv
Intro	roduction	
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Abbreviated terms	
5	General test conditions	
	5.1 Operating points	
	5.1.1 Operating points for motor, inverter and i	
	5.1.2 Operating points for DC/DC converter	
	5.2 Methods for determining the rank for operating	load test
	5.2.1 Target rank verification method 5.2.2 Rank search method	
	5.2.2 Rank search method	
	5.3 Provision for current, voltage and power measur	rement
	5.4 DC input voltage	
	5.5 Temperature and humidity	
	5.6 Measurement accuracy	
	nex A (informative) Formula of power	
Bibli	liography 1100 STANDARD PR	<u>EVIEW</u> 18

(standards.iteh.ai)

ISO 21782-1:2023

https://standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33-9b40a3723a08/iso-21782-1-2023

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 37, *Electrically propelled vehicles*.

This second edition cancels and replaces the first edition (ISO 21782-1:2019), which has been technically revised. 9b40a3723a08/iso-21782-1-2023

The main changes are as follows:

- addition of ISO 21782-4, ISO 21782-5 and ISO 21782-7 general specifications and requirements to this document;
- correction of the subclause numbers cited in the Terms and definitions clause.

A list of all parts in the ISO 21782 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

Until now, there was no international standardized test procedure for the motor system including motors, inverters DC/DC converters and their combinations for electric propulsion systems of electrically propelled road vehicles available. There are some International Standards for industrial use which consider the steady/constant running of motors and inverters but do not consider the dynamic operation (acceleration/deceleration).

The ISO 21782 series was prepared aiming at the reproducibility of test results which will enable to compare and evaluate fairly the performance and reliability of electric propulsion system components such as the motor system (the motor, inverter, DC/DC converter and their combinations).

The overview of the ISO 21782 series is in <u>Tables 1</u> to <u>7</u> shown below.

Item of this document	Description
Introduction	Background and purpose of the ISO 21782 series
Terms and definitions	Terms to use in the ISO 21782 series
Abbreviated terms	Abbreviated terms to use in the ISO 21782 series
iTeh STA	 Definition of general condition: operating point, methods for determining the rank for operating load test,
General test conditions	 current, voltage and power, DC input voltage, temperature and humidity, measurement accuracy.

Table 1 — Contents of this document: General test conditions and definitions

Table 2 — Contents of ISO 21782-2: Performance testing of the motor system

Item of ISO 21782-2	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
Measurement of total loss and total efficiency	This test measures total loss and total efficiency between the input power of inverter and the output power of the motor.				5.1	
Temperature rise test	This test investigates the temper- ature rise characteristics of each part of the motor system within the specified range.				5.2	
Torque characteristic test	This test measures the torque characteristics specified in the specifications of the motor system.				5.3	
Torque ripple test	This test measures the torque ripple of the motor.				5.4	

Item of ISO 21782-3	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
Measurement of	This test measures loss and efficien- cy between the input power and the output power.	5.1.1	5.2.1	5.3.1		
loss and efficiency	This test measures conversion rate between the input power and the output power.		5.2.1	5.3.1		
Temperature rise test	This test investigates the tempera- ture rise characteristics of each part of the component within the specified range.	5.1.2	5.2.2	5.3.2		
Torque characteristic test	This test measures the torque characteristics specified in the specifications of the motor.	5.1.3				
Cogging torque test	This test measures the cogging torque of the permanent magnetic motor.	5.1.4				

Table 4 — Contents of ISO 21782-4: Performance testing of the DC/DC converter

Item of ISO 21782-4	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
Measurement of loss and efficiency	This test measures loss and efficien- cy between the input power and the output power.	ds.it	eh.ai	i)		5.1
Temperature rise test	This test investigates the tempera- ture rise characteristics of each part of the DC/DC converter within the specified range.	<u>82-1:20</u> dards/si so-2178	<u>23</u> st/5acc0fe 2-1-2023	9-7259-45	ie6-be33	5.2

Table 5 — Contents of ISO 21782-5: Operating load testing of the motor system

Item of ISO 21782-5	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
Endurance test	Cyclic test of output torque pattern endurance including maximum torque and maximum speed				5.1	
Surge voltage measurement test	This test measures the surge voltage applied to the input terminals of the motor.				5.2	
Over speed test	The test verifies the no control failure according to the over speed and gives the corresponding rank.				5.3	

Table 6 — Contents of ISO 21782-6: Operating load testing of the motor and the inverter

Item of ISO 21782-6	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
	Cyclic test of high acceleration/ deceleration endurance	4.1.1				
Operation endurance tests of motor	Cyclic test of torque pattern endurance including maximum torque	4.1.2				
	Over speed test	4.1.3				

Table 6 (continued)

Item of ISO 21782-6	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
Operation endurance tests of inverter	Cyclic test of output current pattern endurance including maximum cur- rent		4.2.1			
Breakdown strength verification test	Contents of this test are mainly spin test, data acquisition of mechanical strength of the motor.	4.3.1				

Table 7 — Contents of ISO 21782-7: Operating load testing of the DC/DC converter

Item of ISO 21782-7	Description	Motor	Inverter	Chopper	Motor system	DC/DC converter
Operation endurance test	Cyclic test of output current pattern endurance including maximum current					5

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 21782-1:202</u>

https://standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33-9b40a3723a08/iso-21782-1-2023

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 21782-1:2023</u> https://standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33-9b40a3723a08/iso-21782-1-2023

Electrically propelled road vehicles — Test specification for electric propulsion components —

Part 1: General test conditions and definitions

1 Scope

This document specifies the test procedures for performance and operating load for voltage class B electric propulsion components (motor, inverter, DC/DC converter) and their combinations (motor system) of electrically propelled road vehicles.

This document specifies the terms and definitions used in the ISO 21782 series and general test conditions.

2 Normative references

There are no normative references in this document.

3 Terms and definitions tandards.iteh.ai)

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

— IEC Electropedia: available at <u>https://www.electropedia.org/</u>

3.1

chopper

DC electronic *power converter* (3.19) without an intermediate AC link giving a variable output voltage by varying the periods of conduction and non-conduction in an adjustable ratio

[SOURCE: IEC 60050-811:2017, 811-19-11, modified — The phrase "electronic power DC convertor" was modified to "DC electronic power converter".]

3.2

conversion rate

ratio of output base wave power or output DC power to input DC power

3.3

DC/DC converter

DC electric *power converter* (3.19) with an intermediate AC link transferring electric power between a voltage class B electric circuit and a voltage class A insulated electric circuit

3.4

DC link inductor

component boosted by the *chopper* (3.1) circuit, a magnetic energy storage and released in response to actuation of the switching element

3.5

efficiency

ratio of output power to input power

3.6

induction motor

IM

AC electric motor in which the electric rotor current needed to produce torque is obtained by electromagnetic induction from the magnetic field of the stator winding

EXAMPLE Asynchronous motor.

3.7

inverter

electric energy converter that changes direct electric current to single-phase or polyphase alternating currents

[SOURCE: IEC 60050-151:2001, 151-13-46]

3.8

maximum current for duration of t_0

 $I_{t=t0}$

maximum current defined for the time frame t_0 which can be constantly achieved for t_0 seconds starting from the steady-state condition of room temperature (RT) and the nominal cooling conditions until the *inverter* (3.7) and *chopper* (3.1) reach the defined maximum temperature limit

3.9

maximum operating speed

upper limit revolution speed for the torque-motor speed characteristics

3.10

maximum power for duration of t_0

<u>ISO 21782-1:2023</u>

 $P_{t=t0}$ https://standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33maximum power defined for the time frame t_0 which can be constantly achieved for t_0 seconds starting

from the steady-state condition of RT and the nominal cooling conditions until the motor, *inverter* (3.7) and *chopper* (3.1) reach the defined maximum temperature limit

3.11

maximum speed

n_m

highest defined speed which can maintain maximum power

Note 1 to entry: The maximum speed can be limited by control software or supplier's definitions.

3.12

motor system

electric propulsion system for an electrically propelled road vehicle comprising a combination of components such as motor, *inverter* ($\underline{3.7}$) and if necessary, *DC/DC converter* ($\underline{3.3}$)

3.13

maximum torque for duration of t_0

 $M_{t=t0}$

highest torque defined for the time frame t_0 which can be constantly achieved for t_0 seconds until the power limitation at higher speed starting from the steady-state condition of RT and the nominal cooling conditions until the motor reaches the defined maximum temperature limit

3.14

maximum voltage for unlimited operating capability

highest value of OS1

Note 1 to entry: See ISO 21498-1 about OS1.

3.15

minimum voltage for unlimited operating capability

lowest value of OS1

Note 1 to entry: See ISO 21498-1 about OS1.

3.16

no-load induced electromotive force

 E_0

voltage generated in the armature when the motor is rotated at the *rated speed* (3.22) as a power generator while the terminal of the synchronous motor is opened

3.17

operating load test

test method that takes into account the deterioration due to the operation of the device itself

3.18

output frequency

frequency of the *inverter* (3.7) output current

3.19

power converter

device that converts electric energy from DC to AC or from AC to DC

EXAMPLE AC frequency conversion, DC power conversion, etc.

3.20

permanent magnet motor

ΡM

motor using permanent magnets for the field magnetic poles

3.21

<u>ISO 21/82-1:2023</u>

rated frequency/standards.iteh.ai/catalog/standards/sist/5acc0fe9-7259-45e6-be33-

 f_r <u>9b40a3723a08/iso-21782-1-2023</u> *output frequency* (<u>3.18</u>) at the operating point corresponding to the *rated speed* (<u>3.22</u>) of the combined motor

3.22

rated speed

n_r

intersection of the maximum torque for duration of t_0 (3.13) and iso-power line

3.23

rated voltage

*u*_r central value of OS1

Note 1 to entry: See ISO 21498-1 about OS1.

4 Abbreviated terms

- AC alternating current
- ACL 3-phase inductance equivalent to the leakage inductance of motor
- DC direct current
- DUT device under test
- EMF electromotive force