INTERNATIONAL STANDARD

ISO 19960

Third edition 2023-02

Cast steels and alloys with special physical properties

Aciers et alliages moulés avec caractéristiques physiques particulières

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19960:2023 /standards.iteh.ai/catalog/standards/sist/4ea0a6fc-14ca-450e-8541-9bf7e2ea0990/iso



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19960:2023

https://standards.iteh.ai/catalog/standards/sist/4ea0a6fc-14ca-450e-8541-9bf7e2ea0990/iso-19960-2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

| Cor | ontents | Page |
|-------|--|------|
| Fore | eword | iv |
| 1 | Scope | |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | |
| 4 | General conditions for delivery | |
| 5 | Chemical composition | 1 |
| 6 | Mechanical properties | 1 |
| 7 | Heat treatment | 2 |
| 8 | Welding | 2 |
| 9 | Verification of physical properties | 2 |
| 10 | Supplementary requirements | 2 |
| Anno | nex A (informative) UNS cast grades similar to ISO cast grades | 6 |
| Rihli | lingranhy | 7 |

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19960:2023

https://standards.iteh.ai/catalog/standards/sist/4ea0a6fc-14ca-450e-8541-9bf7e2ea0990/iso-19960-2023

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 17, *Steel*, Subcommittee SC 11, *Steel castings*.

This third edition cancels and replaces the second edition (ISO 19960:2015), of which it constitutes a minor revision. The changes are as follows:

- the unit of N/mm² in Table 2 was revised to MPa;
- GX5Ni36S in Table 4 was corrected to GX5NiS36.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Cast steels and alloys with special physical properties

1 Scope

This document specifies cast steel and alloy grades with special physical properties. The cast steel and alloy grades covered by this document are used in applications which require low linear thermal expansion, or low ferromagnetic responses, or low galling properties.

NOTE Annex A gives information on ISO grade designation and available UNS numbers which are similar to the ISO grade designations.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4990, Steel castings — General technical delivery requirements

ISO 11970, Specification and qualification of welding procedures for production welding of steel castings

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1 galling

damage or breaking of the surface by friction or abrasion

4 General conditions for delivery

Materials furnished according to this document shall conform to the applicable requirements of ISO 4990 including the supplementary requirements that are indicated on the enquiry and purchase order.

5 Chemical composition

The cast steel and alloy grades shall conform to the requirements for chemical composition specified in Table 1.

6 Mechanical properties

Cast steel and alloy grades shall conform to the mechanical property requirements given in $\underline{\text{Table 2}}$ up to the maximum ruling thickness. Verification of impact properties is not required except when indicated by the customer. Test blocks used to verify the mechanical properties shall not have a thickness exceeding 100 mm. For blocks taken from castings, the test bar location and the mechanical properties required shall be agreed between the manufacturer and purchaser.

ISO 19960:2023(E)

For grades GX3NiCo32, GX3NiCo29-17, and G-NiCr13SnBiMo, no mechanical properties are specified.

7 Heat treatment

Castings shall be heat treated in accordance with the requirements of <u>Table 3</u>.

8 Welding

Castings shall be welded in accordance with the procedures described in ISO 11970.

9 Verification of physical properties

When physical properties are specified, the method of measurement and acceptance requirements shall be the subject of an agreement between the manufacturer and purchaser. Typical values for some physical properties are given in Table 4.

10 Supplementary requirements

A list of standardized supplementary requirements for use at the option of the purchaser is included in ISO 4990. The subclauses of ISO 4990 which are ordinarily considered suitable for use with this document are given in Annex A. Other supplementary requirements, whether or not in ISO 4990, may be used with this document upon agreement by the manufacturer and purchaser.

(standards.iteh.ai)

ISO 19960:2023

https://standards.iteh.ai/catalog/standards/sist/4ea0a6fc-14ca-450e-8541-9bf7e2ea0990/iso-19960-2023

Table 1 — Chemical composition, mass fraction in $\%^{
m d}$

| | | | | | | | | • | | | | |
|--|---------------|------------|---------------|---------------------------|-------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-------------------------------------|
| Grade designation | ı | ر | :5 | M | ps: | 3 | | Mo | :IN | N | ره | 0.04+0 |
| Name | Number | ر | 31 | IIII | //st | c | 5 | OM | INI | 2 | 00 | Official |
| GX12CrNi18-11ª | 1.3955 | 0,15 | 1,00 | 2,0 | o,045 audar | 0:030 | 16,5 to 18,5 | 0,75 | 10,0 to 12,0 | | | |
| GX2CrNiN18-13a | 1.3940 | 0,030 | 1,00 | 2,0 | ds.ite 0'032 | 0,020 | 16,5 to 18,5 | ı | 12,0 to 14,0 | 0,10 to 0,20 | | |
| GX2CrNiMoN18-14 ^a | 1.3960 | 0,030 | 1,00 | 2,0 | n.ai/c 0'032 | 0,020 | 16,5 to 18,5 | 2,5 to 3,0 | 13,0 to 15,0 | 0,15 to 0,25 | | |
| GX2CrNiN19-11ª | 1.3939 | 0,030 | 1,5 | 2,0 | atalog | 0,020 | 18,0 to 20,0 | 1,0 | 10,0 to 12,0 | 0,10 to 0,20 | | |
| GX3CrNiMnSi17-9-8a | 1.3975 | 0,05 | 3,5 to 4,5 | 7,0 to 9,0 | /stan | 0,030 | 16,0 to 18,0 | 1,0 | 8,0 to 9,0 | 0,08 to 0,18 | | |
| GX4CrNiMnN22-12-5 ^a | 1.3956 | 90'0 | 1,0 | 4,0 to 6,0 | 0,040 0,040 | 0,030 | 20,5 to 23,5 | 1,50 to 3,00 | 11,5 to 13,5 | 0,20 to 0,40 | | Nb: 0,10 to 0,30 V: 0,10 to 0,30 |
| GX2CrNiMnMoNNb21-16-5-3a 1.3967 | 1.3967 | 0,030 | 1,0 | 4,0 to 6,0 | 0,025 0,025 0,025 | 0,010 | 20,0 to 21,5 | 3,0 to 3,5 | 15,0 to 17,0 | 0,20 to 0,35 | | Nb: 0,25 |
| GX3NiCo32 ^b | 1.3983 | 0,05 | 09'0 | 9'0 | a0a61 0.0000 | 2023 | 0,25 | 1,0 | 30,5 to 33,5 | | 4,0 to 6,5 | Al: 0,10 |
| GX1NiCo29-17 ^b | 1.3988 | 0,05 | 09'0 | 0,5 | 0000 | 0,02 | 0,25 | 1,0 | 28,0 to 30,0 | | 16,0 to 18,0 | |
| GX3Ni36 ^b | 1.3961 | 0,05 | 0,5 | 0,5 | a-450 080'0 | 0,02 | 0,25 | 1,0 | 35,0 to 37,0 | | | |
| GX5NiS36 ^b | 1.3963 | 0,05 | 0,5 | 0,5 | 0,030 % | 0,10 to 0,20 | 0,25 | 1,0 | 35,0 to 37,0 | | | |
| G-NiCr13SnBiMo ^c | 2.4712 | 0,05 | 0,5 | 1,5 | 41-9bf7 080'0 | 0,030 | 11,0 to 14,0 | 2,0 to 3,5 | balance | | | Fe: 2,0 Bi: 3,0 to 5,0 |
| | | | | | e2 | | | | | | | Sn: 3,0 to 5,0 |
| a Low ferromagnetic response grades with magnetic permeability, $\mu_{\rm r} \le 1,01$. | e grades with | ı magnetic | permeabi | lity, $\mu_{\rm r} \le 1$ | .01 (a0 | | | | | | | |

For low linear-expansion grades see <u>Table 4</u>.

Single value indicates maximum.

Low galling grade.

³

Table 2 — Mechanical properties at room temperature

| Grade designation | | $R_{p0,2}$ | R _m | A | K |
|--------------------------|--------|------------|----------------|------|------|
| Name | Number | min. | МРа | min. | min. |
| Name | Number | МРа | | % | J |
| GX12CrNi18-11a | 1.3955 | 195 | 440 to 590 | 20 | 80 |
| GX2CrNiN18-13a | 1.3940 | 210 | 440 to 640 | 30 | 115 |
| GX2CrNiMoN18-14a | 1.3960 | 240 | 490 to 690 | 30 | 80 |
| GX2CrNiN19-11a | 1.3939 | 180 | ≥440 | 30 | |
| GX3CrNiMnSi17-9-8a | 1.3975 | 290 | ≥580 | 24 | |
| GX4CrNiMnN22-12-5a | 1.3956 | 290 | ≥580 | 24 | |
| GX2CrNiMnMoNNb21-16-5-3a | 1.3967 | 315 | 570 to 800 | 20 | 65 |
| GX3Ni36 ^b | 1.3961 | 275 | ≥395 | 28 | |
| GX5NiS36 ^b | 1.3963 | 275 | ≥395 | 25 | |

Low ferromagnetic response grades with magnetic permeability, $\mu_{\rm r} \le 1{,}01$.

Table 3 — Heat treatment

| Grade designation | | Tuo at mont? | |
|---------------------------|-----------|--|--|
| Name | Number | Treatment ^a | |
| GX12CrNi18-11 b | 1.3955 | Solution anneal 1 050 °C to 1 150 °C; quench | |
| GX2CrNiN18-13 b | 1.3940 | Solution anneal 1 050 °C to 1 150 °C; quench | |
| GX2CrNiMoN18-14 b | 1.3960 | Solution anneal 1 050 °C to 1 150 °C; quench | |
| GX2CrNiN19-11 b | 1.3939 | Solution anneal 1 050 °C min; quench | |
| GX3CrNiMnSi17-9-8 b | 1.3975 | Solution anneal 1 050 °C min; quench | |
| GX4CrNiMnN22-12-5 b | 1.3956 19 | Solution anneal 1 065 °C min; quench | |
| GX2CrNiMnMoNNb21-16-5-3 b | 1.3967 | Solution anneal 1 080 °C to 1180 °C; quench | |
| GX3NiCo32 ^c | 1.3983 | 820 °C to 850 °C/quench + 300 to 350 °C/air | |
| GX1NiCo29-17 ^c | 1.3988 | 820 °C to 850 °C/quench + 300 to 350 °C/air | |
| GX3Ni36 ^c | 1.3961 | 820 °C to 850 °C/quench + 300 to 350 °C/air | |
| GX5NiS36 ^c | 1.3963 | 820 °C to 850 °C/quench + 300 to 350 °C/air | |
| G-NiCr13SnBiMo d | 2.4712 | As cast | |

^a Temperatures are for information only.

For low linear-expansion grades, see <u>Table 4</u>.

Low ferromagnetic response grades with magnetic permeability, $\mu_{\rm r} \le 1{,}01$.

^c For low linear-expansion grades see <u>Table 4</u>.

d Low galling grade.

Table 4 — Typical values for physical properties

| Grade designation | | Coefficient of expansion (mm/mm) | | | | | |
|-------------------|--------|---|---|---|---|---|--|
| | | | | $(10^{-6}K^{-1})$ | | | |
| Name | Number | 20 °C to 100 °C | 20 °C to 200 °C | 20 °C to 300 °C | 20 °C to 500 °C | 20 °C to 800 °C | |
| GX3NiCo32 | 1.3983 | 0,63 | _ | _ | _ | _ | |
| GX1NiCo29-17 | 1.3988 | 5,9 | 5,2 | 5,1 | 6,1 | 10,3 | |
| GX3Ni36 | 1.3961 | 1,3 | 2,1 | 4,2 | _ | _ | |
| GX5NiS36 | 1.3963 | 1,6 | 3,0 | 5,9 | _ | _ | |

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19960:2023

https://standards.iteh.ai/catalog/standards/sist/4ea0a6fc-14ca-450e-8541-9bf7e2ea0990/iso-19960-2023

Annex A

(informative)

UNS cast grades similar to ISO cast grades

Table A.1 — UNS cast grades similar to ISO cast grades

| Grade designation | UNS Numbers | |
|-------------------------|-------------|------------------------------|
| Name | Number | (similar grade) ^a |
| GX12CrNi18-11 | 1.3955 | - |
| GX2CrNiN18-13 | 1.3940 | J92500 |
| GX2CrNiMoN18-14 | 1.3960 | - |
| GX2CrNiN19-11 | 1.3939 | - |
| GX3CrNiMnSi17-9-8 | 1.3975 | J92972 |
| GX4CrNiMnN22-12-5 | 1.3956 | J93790 |
| GX2CrNiMnMoNNb21-16-5-3 | 1.3967 | - |
| GX3NiCo32 | 1.3983 | - |
| GX1NiCo29-17 | 1.3988 | |
| GX3Ni36 | 1.3961 | - |
| GX5NiS36 | 1.3963 | h.ai) |
| G-NiCr13SnBiMo | 2.4712 | N26055 |

NOTE The grade designations including the names and the numbers follow the rules of EN 10027-1 and EN 10027-2.

 $^{^{\}rm a}$ $\,$ The similar UNS (Unified Numbering System) grades may not be equivalent to the grades in this document.