

Designation: D3984 - 08 D3984 - 13

Standard Specification for Ethane Thermophysical Property Tables¹

This standard is issued under the fixed designation D3984; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (\$\epsilon\$) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 The thermophysical property tables for ethane are for use in the calculation of the pressure-volume-temperature (PVT), thermodynamic, and transport properties of ethane for process design and operations. Tables are provided for gaseous and liquid ethane at temperatures between 92 and 600 K at pressures to 20 MPa. One table provides Two tables provide properties at the conditions of liquid-vapor equilibrium (saturation properties). The other A third table provides properties at selected *T,p* points for the equilibrium phase at those conditions. The tables were developed by the National Institute of Standards and Technology from a Standard Reference Database product REFPROP, version 8.0.9.0.
 - 1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

2. Applicability

2.1 These tables apply directly only to pure gaseous ethane. However, it is expected that they may find substantial use in mathematical models and tables for the thermophysical properties of mixtures containing ethane.

iTeh Standards (https://standards.iteh.ai) Document Preview

ASTM D3984-13

https://standards.iteh.ai/catalog/standards/sist/3c9a29ad-a21e-4f38-9179-df6c76d0a9aa/astm-d3984-13

¹ This specification is under the jurisdiction of ASTM Committee D03 on Gaseous Fuels and is the direct responsibility of Subcommittee D03.08 on Thermophysical Properties.

Current edition approved Dec. 1, 2008May 1, 2013. Published January 2009May 2013. Originally approved in 1982. Last previous edition approved in 20032008 as D3984 – 93 (2003):D3984 – 08. DOI: 10.1520/D3984-08.10.1520/D3984-13.

3. Tables

- 3.1 These tables were produced by equations from a computer package, "NIST Standard Reference Database 23; Reference Fluid Thermodynamic and Transport Properties Database (REFPROP): Version 9.0." A wide selection of units (SI units, engineering units, chemical units) and additional properties are available with this program.²
 - 3.2 These thermophysical property tables are:
- 3.2.1 Thermophysical Properties of Coexisting Gaseous and Liquid Ethane, Ethane Liquid at Vapor-Liquid Equilibrium, in SI units. See Table 1.
 - 3.2.2 Thermophysical Properties of Ethane Along Isobars, Vapor at Vapor-Liquid Equilibrium, in SI units. See Table 2.
 - 3.2.3 Thermophysical Properties of Ethane Along Isobars, in SI units. See Table 3.
 - 3.3 The symbols are:
 - T, temperature (K)
 - ρ, molar density (mol·l⁻¹)
 - H, molar enthalpy (J·mol⁻¹)
 - S, molar entropy $(J \cdot K^{-1} \cdot mol^{-1})$
 - C_{v} , constant volume molar heat capacity (J·K⁻¹·mol⁻¹)
 - C_p , constant pressure molar heat capacity $(J \cdot K^{-1} \cdot mol^{-1})$
 - \underline{c} , speed of sound (m·s⁻¹)
 - η, viscosity (μPa·s)
 - λ , thermal conductivity (mW·m⁻¹·K⁻¹)
 - 3.4 The tabulated thermophysical properties are:
 - ρ, molar density (mol·l⁻¹)
 - H, molar enthalpy (J·mol⁻¹)
 - S, molar entropy $(J \cdot K^{-1} \cdot mol^{-1})$

 - C_{ν} , constant volume molar heat capacity (J·K⁻¹·mol⁻¹) C_{p} , constant pressure molar heat capacity (J·K⁻¹·mol⁻¹)
 - c, speed of sound ($m \cdot s^{-1}$)
 - η, viscosity (μPa·s)
 - λ , thermal conductivity (mW·m⁻¹·K⁻¹)
- 3.3 These tables were produced by equations from a computer package, "NIST Standard Reference Database 23; Reference Fluid Thermodynamic and Transport Properties Database (REFPROP): Version =8.0" A wide selection of units (SI units, engineering units, chemical units) is available with this program.²

4. Additional Information

4.1 Reference state properties are required to calculate certain of the thermodynamic properties (enthalpy, entropy, etc.) from an equation of state formulation. The reference state properties used to generate the tables in this specification are: enthalpy, H, and entropy, S, at 298.15 K and 0.101325 MPa the Normal Boiling Point; 184.57K and 0.10133MPa (H=11874.2=14716 J/mol and S = 221.116 J/(mol K) = 79.731 J/(mol K). The molar mass of ethane is 30.069 g/mol.

5. Keywords

5.1 ethane gas tables; natural gas; thermodynamic properties of ethane; transport properties of ethane

² Available from Standard Reference Data, National Institute of Standards and Technology (NIST), 100 Bureau Drive, Stop 3460, Gaithersburg, MD 20899.

∰ D3984 – 13

TABLE 1 Thermophysical Properties of Coexisting Gaseous and Liquid Ethane

TABLE 1 Inermophysical Properties of Goexisting Gaseous and Liquid Ethane										
<i>T</i> K	<i>p</i> MPa	ρ mol·l ⁻¹	<i>H</i> J⋅mol ⁻¹	<i>S</i> J⋅mol ⁻¹ ⋅K ⁻¹	C_{ν} J·mol ⁻¹ ·K ⁻¹	C_p J·mol ⁻¹ ·K ⁻¹	<i>c</i> m⋅s ⁻¹	η μPa⋅s	λ mW·m⁻¹·K⁻	
90.4	1.15E-06	21.667	-14794	69.195	48.26	69.93	2008.5	255.6	1279	
90.4	1.15E-06	1.53E-06	3089.2	267.02	26.81	35.13	180.97	2.910	3.044	
92	1.74E-06	21.608	-14682	70.419	47.85	69.60	1996.7	254.3	1193	
92	1.74E-06	2.28E-06	3145.5	264.2	26.90	35.22	182.48	3.000	3.089	
0.4	0.005.00	04 505	14540	74.040	47.00	00.07	1000.1	050.0	1007	
94 94	2.86E-06 2.86E-06	21.535 3.65E-06	-14543 3216	71.912 260.84	47.39 27.02	69.27 35.34	1982.1 184.36	252.8 3.113	1097 3.145	
J-1	2.00L-00	3.03L-00	3210	200.04	27.02	00.04	104.50	5.115	3.143	
96	4.58E-06	21.462	-14405	73.368	46.99	69.01	1967.5	251.1	1013	
96	4.58E-06	5.74E-06	3286.8	257.66	27.14	35.46	186.22	3.227	3.202	
98	7.2E-06	21.389	-14267	74.788	46.64	68.80	1952.9	249.5	939.1	
9 8	7.2E-06	8.83E-06	3357.8	254.64	27.26	35.58	188.05	3.341	3.259	
-00	1.11E-05	21.316	-14130	76.176	4 6.32	68.64	1938.4	247.8	873.2	
'UU	1.11E-05	1.33E-05	3429.1	251.77	27.38	35.70	189.86	3.456	3.316	
102	1.68E-05	21.243	-13993	77.534	46.04	68.52	1924	246.1	814.5	
02	1.68E-05	1.98E-05	3500.6	249.04	27.50	35.82	191.65	3.572	3.373	
04	2.49E-05	21.17	-13856	78.864	45.79	68.44	1909.5	244.4	761.9	
04 04	2.49E-05 2.49E-05	21.17 2.88E-05	-13856 3572.3	78.864 246.44	45.79 27.63	58.44 35.94	1909.5 193.42	244.4 3.689	761.9 3.430	
	202 00	2.002 00	0072.0	2.0	27.00	00.0	.002	0.000	000	
06	3.64E-05	21.097	-13719	80.167	45.56	68.38	1895.1	242.7	714.6	
06	3.64E-05	4.13E-05	3644.2	243.97	27.75	36.07	195.17	3.807	3.488	
08	5.24E-05	21.024	-13582	81.445	45.36	68.36	1880.8	240.9	672.0	
08	5.24E-05	5.83E-05	3716.4	241.62	27.87	36.19	196.9	3.925	3.545	
	_		1	Tell 2	tallua	lrus				
10 10	7.43E-05 7.43E-05	20.951 8.12E-05	-13446 3788.7	82.699 239.37	45.17 28.00	68.35 36.32	1866.4 198.61	239.1 4.045	633.4 3.603	
10	7.452-05	0.121-03	3700.7	253.57	n / 9 i / 1	30.52	130.01	4.043	5.005	
12	0.000104	20.878	-13309	83.931	45.00	68.36	1852	237.3	598.3	
12	0.000104	0.000112	3861.3	237.24	28.12	36.45	200.3	4.165	3.662	
14	0.000144	20.805	-13172	85.141 E	44.85	68.39	1837.6	235.5	566.3	
14	0.000111	0.000152	3934.1	235.2	28.25	36.58	201.98	4.286	3.720	
16 16	0.000196 0.000196	20.731 0.000203	-13035 4007.0	86.331 233.25	1D 44.71 13 28.38	68.43 36.71	1823.2 203.63	233.6 4.409	537.1 3.778	
ht	tne://standa	rds iteh ai/ca	talog/stands	200.20 arde/ejet/2 e 0 e	20.50 2024_221e.	_/1f3	df6c76d0a0)22/25tm_d3	308/1_13	
18	0.000264	20.658	-12898	87.501	44.57	68.48	1808.8	231.8	510.4	
18	0.000264	0.000269	4080.2	231.39	28.52	36.85	205.27	4.532	3.837	
20	0.000352	20.584	-12761	88.653	44.45	68.54	1794.4	229.9	485.8	
20	0.000352	0.000353	4153.5	229.61	28.65	36.99	206.89	4.657	3.896	
22	0.000465	20.511 0.000459	-12624	89.786	44.34	68.61	1780	228.0	463.1	
22	0.000465	0.000455	4227.0	227.91	28.79	37.14	208.49	4.782	3.955	
24	0.000608	20.437	-12487	90.903	44.24	68.69	1765.5	226.1	442.2	
24	0.000608	0.00059	4300.6	226.29	28.93	37.29	210.07	4.909	4.015	
26	0.000787	20.363	-12349	92.002	44.14	68.78	1751	224.2	422.8	
26	0.000787	0.000752	4374.4	224.73	29.08	37.45	211.63	5.037	4.074	
28	0.001009	20.289	-12212	93.086	44.05	68.86 27.61	1736.5	222.3 5.166	404.9	
28	0.001009	0.000949	4448.3	223.24	29.23	37.61	213.17	5.166	4.134	
30	0.001284	20.214	-12074	94.154	43.96	68.96	1722	220.4	388.2	
30	0.001284	0.001189	4522.3	221.82	29.38	37.77	214.69	5.296	4.194	
32	0.00162	20.14	-11936	95.208	43.88	69.06	1707.5	218.4	372.6	
32 32	0.00162 0.00162	20.14 0.001478	-11936 4596.4	95.208 220.45	43.88 29.53	59.06 37.94	1707.5 216.19	218.4 5.427	372.6 4.254	
		2.30 / 0			20.00	30		J,	0 r	
34	0.002028	20.065	-11798	96.247	43.81	69.16	1692.9	216.4	358.1	
34	0.002028	0.001824	4670.6	219.14	29.69	38.11	217.68	5.560	4.314	
36	0.002521	19.991	-11659	97.273	43.74	69.27	1678.3	214.5	344.5	
36	0.002521	0.002234	4744.8	217.89	29.84	38.28	219.14	5.694	4.374	
38	0.003111	19.916	-11520	98.285	43.67	69.38	1663.7	212.5	331.8	




TABLE 1 Continued

				.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	. i Commuca				
T K	<i>p</i> MPa	ρ mol·l ⁻¹	<i>H</i> J⋅mol ⁻¹	<i>S</i> J⋅mol ⁻¹ ⋅K ⁻¹	C_{ν} J·mol ⁻¹ ·K ⁻¹	C_p J·mol ⁻¹ ·K ⁻¹	c m⋅s⁻¹	η μPa⋅s	λ mW·m ⁻¹ ·K ⁻¹
138	0.003111	0.002718	4819.2	216.69	30.00	38.45	220.58	5.829	4.435
140 140	0.003814 0.003814	19.84 0.003286	-11382 4893.6	99.284 215.53	43.61 30.15	69.50 38.62	1649.1 222.01	210.6 5.966	319.8 4.496
140	0.003614	0.003280	4090.0	210.00	30.13	30.02	222.01	3.900	4.430
142	0.004645	19.765	-11242	100.27	43.55	69.62	1634.4	208.6	308.5
142	0.004645	0.003947	4968.0	214.43	30.31	38.79	223.42	6.104	4.556
144	0.005623	19.689	-11103	101.24	43.49	69.74	1619.7	206.6	297.9
144	0.005623	0.004714	5042.4	213.37	30.45	38.96	224.80	6.244	4.617
146	0.006766	19.613	-10963	102.21	43.44	69.87	1605.0	204.7	287.9
146	0.006766	0.005599	5116.8	212.35	30.60	39.13	226.17	6.385	207.9 4.678
148	0.008097 0.008097	19.537	-10823 5191.2	103.16	43.40 30.74	70.00	1590.3 227.51	202.7	278.5 4.740
148	0.000097	0.006614	3191.2	211.37	30.74	39.29	227.91	6.528	4.740
150	0.009638	19.461	-10683	104.1	43.35	70.14	1575.5	200.7	269.6
150	0.009638	0.007773	5265.6	210.42	30.88	39.45	228.84	6.672	4.801
152	0.011413	19.384	-10543	105.03	43.31	70.28	1560.7	198.7	261.1
152	0.011413	0.009091	5339.8	209.52	31.01	39.61	230.14	6.819	4.863
454	0.040440	10.007	10400	105.05	40.07	70.40	4545.0	100.0	050.0
154 154	0.013448 0.013448	19.307 0.010582	-10402 5414.0	105.95 208.65	43.27 31.14	70.42 39.76	1545.9 231.42	196.8 6.967	253.0 4.924
156	0.015772	19.23	-10261	106.86	43.24	70.57	1531.1	194.8	245.4
156	0.015772	0.012264	5488.1	207.81	31.26	39.92	232.68	7.116	4.986
158	0.018414	19.152	-10120	107.76	43.21	70.73	1516.2	192.8	238.1
158	0.018414	0.014151	5561.9	207.01	31.39	40.08	233.91	7.268	5.048
160	0.021405	19.074	-9977.8	108.65	43.18	70.89	1501.3	190.8	231.2
160	0.021405	0.016263	5635.6	206.23	31.51	40.24	235.12	7.422	5.110
100	0.004770	10.000	0005.0	100.50	40.10	71.05	1400.0	100.0	004.5
162 162	0.024779 0.024779	18.996 0.018617	-9835.8 5709.0	109.53 205.48	43.16 31.64	71.05 40.40	1486.3 236.3	188.9 7.577	224.5 5.172
164 164	0.02857 0.02857	18.918 0.021232	-9693.3 5782.2	110.4 204.76	43.14 31.76	71.22 40.57	1471.4 237.45	186.9 7.735	218.2 5.234
T 0 T	0.02037	0.021202	5702.2	204.70	51.70	40.57	207.40	7.705	5.204
166	0.032814	18.839	-9550.6	111.27	43.12	71.40	1456.4	184.9	212.2
166 ht	tp 0.032814 da	rds ^{0.024127} /ca	talo 5855.0 nda	ards 204.07 c9 a	129a 31.90 21e-	-4ß 40.75 79-	df6 238.57 0a9	aa/ 2.895 -d3	3984 5.297
168	0.037551	18.759	-9407.4	112.12	43.11	71.58	1441.4	183.0	206.4
168	0.037551	0.027324	5927.6	203.4	32.03	40.94	239.67	8.057	5.360
170	0.042819	18.68	-9263.9	112.97	43.10	71.77	1426.3	181.0	200.8
170	0.042819	0.030843	5999.7	202.75	32.17	41.14	240.73	8.221	5.422
170	0.04000	10.0	0100.0	440.04	40.00	74.00	4444.0	170 1	105.5
172 172	0.04866 0.04866	18.6 0.034706	-9120.0 6071.4	113.81 202.13	43.09 32.32	71.96 41.35	1411.2 241.76	179.1 8.388	195.5 5.485
174 174	0.055118 0.055118	18.519 0.038935	-8975.6 6142.7	114.64 201.53	43.09	72.16	1396.1	177.1 8.557	190.4 5.548
174	0.055116	0.030933	0142.7	201.00	32.48	41.58	242.76	0.557	3.340
176	0.062235	18.438	-8830.9	115.47	43.09	72.37	1380.9	175.2	185.5
176	0.062235	0.043553	6213.5	200.95	32.65	41.83	243.72	8.728	5.612
178	0.07006	18.357	-8685.7	116.28	43.10	72.59	1365.7	173.3	180.7
178	0.07006	0.048584	6283.7	200.38	32.83	42.09	244.65	8.902	5.675
100	0.070600	10.075	0540.0	4474	40.11	70.01	10E0 E	171.0	176.0
180 180	0.078638 0.078638	18.275 0.054053	-8540.0 6353.4	117.1 199.84	43.11 33.02	72.81 42.38	1350.5 245.54	171.3 9.079	176.2 5.739
182	0.088019	18.193	-8393.8	117.9	43.12	73.04	1335.2	169.4	171.8
182	0.088019	0.059985	6422.6	199.31	33.21	42.68	246.39	9.258	5.803
184	0.098253	18.11	-8247.2	118.7	43.14	73.28	1319.9	167.5	167.6
184	0.098253	0.066405	6491.2	198.8	33.42	43.00	247.2	9.441	5.867
186	0.10939	18.026	-8100.0	119.49	43.16	73.53	1304.5	165.6	163.5
186	0.10939	0.07334	6559.1	198.3	33.65	43.34	247.98	9.626	5.931



TABLE 1 Continued

				171222					
<i>T</i> K	р MPa	ρ mol·l ⁻¹	<i>H</i> J⋅mol ⁻¹	<i>S</i> J⋅mol ⁻¹ ⋅K ⁻¹	C_{ν} J·mol ⁻¹ ·K ⁻¹	C_p J·mol ⁻¹ ·K ⁻¹	<i>c</i> m⋅s ⁻¹	η μPa⋅s	λ mW⋅m⁻¹⋅K⁻¹
188	0.12149	17.942	-7952.3	120.28	43.18	73.79	1289.2	163.7	159.5
188	0.12149	0.080817	6626.4	197.82	33.88	43.69	248.71	9.814	5.996
190	0.13459	17.858	-7804.1	121.06	43.21	74.06	1273.7	161.8	155.7
190	0.13459	0.088865	6693.0	197.36	34.12	44.07	249.41	10.00	6.061
192	0.14876	17.773	-7655.2	121.83	43.24	74.33	1258.3	156.0	152.0
192	0.14876	0.097512	6758.9	196.91	34.37	44.46	250.06	10.20	6.126
194	0.16405	17.687	-7505.8	122.6	43.28	74.62	1242.8	158.1	148.4
194	0.16405	0.10679	6824.1	196.47	34.63	44.89	250.67	10.40	6.192
196	0.18052	17.601	-7355.8	123.37	43.32	74.92	1227.2	156.2	144.9
196	0.18052	0.11672	6888.6	196.04	34.90	45.31	251.24	10.60	6.258
198	0.19823	17.514	-7205.1	124.13	43.36	75.23	1211.7	154.4	141.5
198	0.19823	0.12735	6952.3	195.63	35.18	45.76	251.77	10.80	6.324
200	0.21723	17.426	-7053.8	124.88	43.41	75.55	1196.0	152.6	138.3
200	0.21723	0.1387	7015.2	195.23	35.46	4 6.22	252.26	11.01	6.391
202	0.23759	17.337	-6901.8	125.63	43.46	75.88	1180.4	150.7	135.1
202	0.23759	0.1508	7077.3	194.84	35.74	46.70	252.70	11.22	6.458
204	0.25936	17.248	-6749.1	126.38	43.52	76.23	1164.7	148.9	132.0
204	0.25936	0.1637	7138.6	194.45	36.04	47.19	253.10	11.44	6.526
206	0.28261	17.158	-6595.7	127.12	43.58	76.58	1148.9	147.1	129.0
206	0.28261	0.17742	7199.0	194.08	36.33	47.70	253.45	11.66	6.594
208	0.3074	17.068	-6441.5	127.86	43.65	76.96	1133.1	145.3	126.1
208	0.3074	0.192	7258.5	193.72	36.63	48.23	253.76	11.88	6.663
210 210	0.3338 0.3338	16.976 0.20749	-6286.6 7317.1	128.59 193.37	43.72 36.94	77.34 48.77	1117.3 254.02	143.5 12.11	123.2 6.732
212 212	0.36185 0.36185	16.884 0.22392	-6130.8 7374.8	129.32 193.03	43.79 37.24	77.75 49.33	1101.4 254.24	141.7 12.34	120.5 6.802
014	0.00164	16.70	5074.0	120.05	40.07	70.17	1005.4	100.0	117.0
214 214	0.39164 0.39164	16.79 0.24133	-5974.2 7431.5	130.05 192.69	43.87 37.55	78.17 49.90	1085.4 254.41	139.9 12.58	117.8 6.872
				<u>A511</u> V	1 D3964-13				
216 216	0.42323 0.42323	rds 16.696 0.25976	talo 5816.7 nda 7487.1	ards 130.77 192.36	a29a <mark>43.95</mark> 21e-	-413 78.60 79 -	d 1069.5 254.54)aa/a <mark>138.1</mark> -d3	3984_ 115.1 6.944
040	0.45007	10.001	5050.0	101.10	44.04	70.00	1050.4	100.4	440.0
218 218	0.45667 0.45667	16.601 0.27927	-5658.3 7541.7	131.49 192.04	44.04 38.17	79.06 51.09	1053.4 254.62	136.4 13.07	112.6 7.016
		16 504		120.01					110.0
220 220	0.49205 0.49205	16.504 0.29989	-5498.9 7595.2	132.21 191.73	44.13 38.49	79.53 51.72	1037.3 254.65	134.6 13.32	110.0 7.089
222	0.52941	16.407	-5338.6	132.93	44.23	80.02	1021.2	132.8	107.6
222	0.52941	0.32168	7647.6	191.42	38.80	52.36	254.63	13.58	7.163
224	0.56884	16.309	-5177.3	133.64	44.33	80.54	1005.0	131.1	105.2
224	0.56884	0.34468	7698.8	191.12	39.12	53.03	254.56	13.84	7.238
226	0.6104	16.209	-5015.0	134.35	44.44	81.07	988.76	129.4	102.9
226	0.6104	0.36896	7748.7	190.83	39.43	53.72	254.44	14.11	7.313
228	0.65416	16.108	-4851.5	135.06	44.54	81.64	972.46	127.7	100.6
228	0.65416	0.39457	7797.4	190.53	39.76	54.43	254.27	14.38	7.390
230	0.70018	16.006	-4687.0	135.76	44.66	82.22	956.09	126.0	98.34
230	0.70018	0.42157	7844.7	190.25	40.08	55.18	254.05	14.66	7.469
232	0.74854	15.903	-4521.2	136.47	44.78	82.84	939.66	124.2	96.15
232	0.74854	0.45003	7890.6	189.97	40.40	55.95	253.78	14.95	7.548
236	0.85256	15.692	-4186.0	137.87	45.04	84.16	906.6	120.9	91.89
236	0.85256	0.51158	7977.9	189.41	41.06	57.60	253.07	15.55	7.712
238	0.90836	15.584	-4016.5	138.57	45.17	84.86	889.97	119.2	89.82
238	0.90836	0.54482	8019.2	189.14	41.40	58.49	252.64	15.86	7.796



TABLE 1 Continued

	TABLE 1 Continued										
T K	р MPa	ρ mol·l ⁻¹	<i>H</i> J⋅mol ⁻¹	<i>S</i> J⋅mol ⁻¹ ⋅K ⁻¹	C_{ν} J·mol ⁻¹ ·K ⁻¹	C_p J·mol ⁻¹ ·K ⁻¹	<i>c</i> m⋅s ⁻¹	η μPa⋅s	λ mW⋅m⁻¹⋅K⁻¹		
240	0.96679	15.475	-3845.6	139.27	45.31	85.61	873.25	117.5	87.80		
240	0.96679	0.57983	8058.7	188.87	41.74	59.42	252.14	16.18	7.881		
242	1.0279	15.364	-3673.2	139.97	45.46	86.40	856.45	115.8	85.81		
242	1.0279	0.61668	8096.6	188.61	42.09	60.40	251.59	16.51	7.969		
244	1.0918	15.251	-3499.3	140.67	45.61	87.23	839.57	114.2	83.86		
244	1.0918	0.65547	8132.5	188.34	42.44	61.44	250.98	16.85	8.059		
246	1.1585	15.136	-3323.9	141.37	45.77	88.11	822.59	112.6	81.94		
246	1.1585	0.6963	8166.5	188.08	42.80	62.54	250.31	17.20	8.151		
248	1.2282	15.019	-3146.8	142.06	45.94	89.04	805.51	110.9	80.05		
248	1.2282	0.73929	8198.5	187.81	43.17	63.71	249.58	17.56	8.245		
250	1.3008	14.901	-2968.0	142.76	46.11	90.02	788.33	109.3	78.19		
250	1.3008	0.78456	8228.2	187.55	43.55	64.96	248.79	17.93	8.342		
252	1.3766	14.779	-2787.4	143.46	4 6.29	91.08	771.03	107.7	76.36		
252	1.3766	0.83224	8255.7	187.28	4 3.93	66.29	247.93	18.32	8.442		
254	1.4555	14.656	-2604.9	144.16	4 6.47	92.20	753.60	106.0	74.56		
254	1.4555	0.88247	8280.8	187.02	44.33	67.72	247.00	18.72	8.545		
256	1.5376	14.53	-2420.3	144.86	4 6.66	93.39	736.05	104.4	72.78		
256	1.5376	0.93543	8303.3	186.75	44.74	69.26	246.01	19.14	8.652		
258	1.623	14.401	-2233.7	145.57	46.87	94.68	718.36	102.8	71.03		
258	1.623	0.99127	8323.0		45.16	70.91	244.95	19.57	8.762		
260	1.7118	14.27	-2044.8	146.27	47.08	96.06	700.52	101.2	69.30		
260 262	1.7118 1.8041	1.0502 14.135	8339.9 -1853.6	186.21 146.98	45.59 1 0 47.29	72.71 97.55	243.81 682.53	20.02 99.64	8.876 67.60		
262	1.8041	1.1124	8353.6	185.94	46.03	74.67	242.61	20.50	8.995		
264	1.9	13.997	-1659.8	147.69	47.52	99.17	664.38	98.05	65.91		
264	1.9	1.1782	8364.0	185.66	46.49	76.80	241.33	21.00	9.119		
266 266	1.9996 1.9996 tps://standa	13.855 1.2478 rds iteh ai/ca	-1463.3 8370.9 talog/stand/	148.41 185.38	47.76 46.96	100.93 79.15	646.06 239.97	96.47 21.52	64.24 9.248		
268	2.1029	13.709	-1264	149.12	4 8.01	102.8	627.58	94.89	62.58		
268	2.1029	1.3215	8373.9	185.09	4 7.46	81.75	238.54	22.08	9.384		
270	2.21	13.559	-1061.5	149.85	48.27	105.0	608.92	93.31	60.94		
270	2.21	1.3998	8372.7	184.79	47.97	84.63	237.02	22.67	9.526		
272	2.321	13.405	- 855.75	150.58	48.54	107.3	590.08	91.73	59.30		
272	2.321	1.4829	8367.0	184.48	48.51	87.86	235.42	23.29	9.676		
274	2.4361	13.245	-646.35	151.31	48.82	109.9	571.04	90.16	57.68		
274	2.4361	1.5713	8356.4	184.17	49.08	91.51	233.73	23.97	9.834		
276	2.5554	13.079	-433.02	152.06	49.11	112.8	551.77	88.58	56.06		
276	2.5554	1.6657	8340.3	183.84	49.68	95.65	231.95	24.69	10.00		
278	2.6789	12.907	-215.36	152.81	49.42	116.1	532.23	87.01	54.45		
278	2.6789	1.7666	8318.2	183.5	50.31	100.4	230.07	25.47	10.18		
280	2.8067	12.728	7.0624	153.57	49.74	119.9	512.38	85.43	52.84		
280	2.8067	1.8748	8289.5	183.15	50.99	105.9	228.1	26.33	10.37		
282	2.9391	12.541	234.80	154.34	50.09	124.3	492.15	83.86	51.22		
282	2.9391	1.9913	8253.3	182.78	51.70	112.4	226.01	27.26	10.58		
284	3.076	12.345	4 68.51	155.13	50.47	129.4	471.46	82.28	49.60		
284	3.076	2.1172	8208.7	182.38	52.47	120.0	223.82	28.31	10.80		
286	3.2177	12.138	709.01	155.93	50.89	135.5	450.22	80.71	47.96		
286	3.2177	2.254	8154.3	181.96	53.30	129.3	221.51	29.47	11.05		
288	3.3643	11.918	957.38	156.75	51.37	142.9	428.34	79.14	46.30		