



Designation: ~~D1122~~—~~08~~ D1122 – 13

## Standard Test Method for Density or Relative Density of Engine Coolant Concentrates and Engine Coolants By The Hydrometer<sup>1</sup>

This standard is issued under the fixed designation D1122; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

### 1. Scope\*

- 1.1 This test method covers the determination of the relative density of engine coolant concentrates and engine coolants.
- 1.2 The values stated in SI units are to be regarded as standard. The values given in parentheses are for information only.
- 1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

[D1176 Practice for Sampling and Preparing Aqueous Solutions of Engine Coolants or Antirusts for Testing Purposes](#)

[E1 Specification for ASTM Liquid-in-Glass Thermometers](#)

[E100 Specification for ASTM Hydrometers](#)

[E230 Specification and Temperature-Electromotive Force \(EMF\) Tables for Standardized Thermocouples](#)

### 3. Terminology

3.1 *Definitions:*

3.1.1 *relative density, n*—the ratio of the density of a material at a stated temperature to the density of water at the same stated temperature.

### 4. Significance and Use

4.1 The relative density of an engine coolant may be used to determine the approximate percent glycol, freezing point, and boiling point, provided the glycol type is known.

4.2 The relative density of an engine coolant concentrate can be used as a production control test.

### 5. Apparatus

5.1 *Hydrometers*—Hydrometers shall be of glass, graduated in specific gravity range as listed in [Table 1](#), and shall conform to Specification [E100](#).

5.2 *Hydrometer Cylinder*—The hydrometer cylinder in which the sample for the relative density test is confined shall be made of clear glass and shall be cylindrical in shape. For convenience in pouring, it may have a lip on the rim. The inside diameter of the cylinder shall be at least 25.4 mm (1.0 in.) greater than the outside diameter of the hydrometer. The height of the cylinder shall be such that the length of the column of sample it contains is greater by at least 25.4 mm (1.0 in.) than the portion of the hydrometer which is immersed beneath the surface of the sample after a state of equilibrium has been reached.

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee [D15](#) on Engine Coolants and Related Fluids and is the direct responsibility of Subcommittee [D15.03](#) on Physical Properties.

Current edition approved ~~April 1, 2008~~ May 1, 2013. Published ~~April 2008~~ June 2013. Originally approved in 1950. Last previous edition approved in ~~2002~~ 2008 as ~~D1122-97a~~ [D1122-08](#), (~~2002~~): DOI: ~~10.1520/D1122-08~~ [10.1520/D1122-13](#).

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](#), or contact ASTM Customer Service at [service@astm.org](#). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard