



International
Standard

ISO 21771-1

**Cylindrical involute gears and
gear pairs —**

Part 1:

Concepts and geometry

Roues et engrenages cylindriques en développante de cercle —

Partie 1: Concepts et géométrie

**First edition
2024-10**

*iteh Standards
(<http://standards.iteh.ai>)
Document Preview*

[ISO 21771-1:2024](https://standards.iteh.ai/catalog/standards/iso/859abd99-aa53-4275-8ea0-bb8fe79bc285/iso-21771-1-2024)

<https://standards.iteh.ai/catalog/standards/iso/859abd99-aa53-4275-8ea0-bb8fe79bc285/iso-21771-1-2024>

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 21771-1:2024](https://standards.iteh.ai/catalog/standards/iso/859abd99-aa53-4275-8ea0-bb8fe79bc285/iso-21771-1-2024)

<https://standards.iteh.ai/catalog/standards/iso/859abd99-aa53-4275-8ea0-bb8fe79bc285/iso-21771-1-2024>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols, subscripts and units	1
3.1 Terms and definitions.....	1
3.2 Symbols.....	2
3.3 Subscripts.....	9
3.4 Units and conventions.....	10
3.4.1 Units.....	10
3.4.2 Conventions.....	10
4 Individual cylindrical gears	10
4.1 General.....	10
4.2 Concepts for an individual gear.....	11
4.2.1 Gear, cylindrical gear, external gear and internal gear.....	11
4.2.2 Tooth system, external teeth and internal teeth.....	11
4.2.3 Tooth and tooth space.....	11
4.2.4 Tooth system parameters.....	11
4.2.5 Number of teeth and sign of number of teeth.....	11
4.2.6 Tooth number.....	12
4.2.7 Top land and bottom land.....	12
4.2.8 Tooth flanks and flank sections.....	12
4.3 Reference surfaces, datum lines and reference quantities.....	13
4.3.1 Reference surface and datum face.....	13
4.3.2 Reference rack.....	13
4.3.3 Basic rack tooth profile for involute gear teeth.....	14
4.3.4 Reference cylinder, reference circle and reference diameter.....	15
4.3.5 Gear axis.....	15
4.3.6 Sections through a cylindrical gear.....	15
4.3.7 Module.....	16
4.3.8 Diametral pitch.....	16
4.3.9 Facewidth.....	16
4.3.10 Profile shift, profile shift coefficient and sign of profile shift.....	17
4.4 Involute helicoids.....	18
4.4.1 Generator of involute helicoids.....	18
4.4.2 Base cylinder, base circle and base diameter.....	19
4.4.3 Transverse pressure angle at a point and transverse pressure angle.....	19
4.4.4 Normal pressure angle at a point and normal pressure angle.....	20
4.4.5 Involute function.....	20
4.4.6 Lead.....	21
4.4.7 Helix angle and lead angle.....	21
4.4.8 Hand of helix.....	22
4.4.9 Roll angle of the involute.....	23
4.4.10 Radius of curvature of the involute and length of roll.....	23
4.4.11 Length of involute profile, L_{yt}	23
4.5 Angular pitch and pitches.....	23
4.5.1 Angular pitch.....	23
4.5.2 Pitches on the reference cylinder.....	23
4.5.3 Pitches on any cylinder.....	24
4.5.4 Axial pitch.....	25
4.5.5 Base pitch.....	25
4.6 Diameters of gear teeth.....	25
4.6.1 General.....	25
4.6.2 V-cylinder and V-circle diameter.....	26
4.6.3 y-cylinder and y-circle diameter.....	26

ISO 21771-1:2024(en)

4.6.4	Tip alteration coefficient.....	26
4.6.5	Tip cylinder, tip circle and tip diameter	26
4.6.6	Profile control diameter, d_{Cf}	26
4.6.7	Root cylinder, root circle and root diameter	26
4.7	Gear tooth depth.....	27
4.7.1	Tooth depth.....	27
4.7.2	Addendum, working addendum, dedendum and working dedendum.....	27
4.8	Tooth thickness and space width.....	27
4.8.1	General.....	27
4.8.2	Transverse tooth thickness	27
4.8.3	Transverse tooth thickness half angle.....	28
4.8.4	Transverse space width.....	29
4.8.5	Transverse space width half angle.....	29
4.8.6	Normal tooth thickness.....	29
4.8.7	Normal space width.....	29
4.9	Radii of curvature of the tooth flanks in different planes.....	30
4.10	Tilt angle of contact line.....	31
5	Parallel axis cylindrical gear pairs.....	32
5.1	General.....	32
5.2	Concepts for a gear pair.....	32
5.2.1	Mating gear and mating flank.....	32
5.2.2	Working flank and non-working flank.....	32
5.2.3	External gear pair.....	32
5.2.4	Internal gear pair.....	33
5.3	Mating quantities.....	33
5.3.1	Gear ratio.....	33
5.3.2	Driving gear, driven gear and transmission ratio.....	33
5.3.3	Line of centres and centre distance.....	33
5.3.4	Working transverse pressure angle.....	34
5.3.5	Working pitch point, pitch cylinders, pitch circles, pitch diameter and pitch axis.....	34
5.3.6	Working helix angles.....	36
5.3.7	Working depth.....	36
5.3.8	Tip clearance.....	36
5.3.9	Calculation of tip alteration coefficient k (for parallel axis gear).....	37
5.4	Calculation of the sum of the profile shift coefficients.....	38
5.5	Tooth engagement.....	38
5.5.1	General.....	38
5.5.2	Active area of the tooth flanks, start of active profile and active tip diameters.....	38
5.5.3	Plane of action, zone of action and contact line.....	40
5.5.4	Line of action, path of contact and point of contact.....	41
5.5.5	Form over dimension.....	41
5.5.6	Designations and values relating to the line of action.....	41
5.5.7	Radii of curvature of the tooth flanks in a transverse plane.....	42
5.5.8	Tooth interference.....	43
5.5.9	Mesh geometry parameters.....	45
5.5.10	Contact line and sum of the contact line lengths.....	47
5.6	Backlash.....	49
5.6.1	General.....	49
5.6.2	Transverse backlash.....	49
5.6.3	Circumferential backlash.....	49
5.6.4	Normal backlash.....	49
5.6.5	Radial backlash.....	50
5.6.6	Angular backlash.....	50
5.7	Velocities and sliding conditions at the tooth flanks.....	51
5.7.1	Angular velocity.....	51
5.7.2	Circumferential velocity.....	51
5.7.3	Normal velocity.....	51
5.7.4	Rolling velocity.....	52

ISO 21771-1:2024(en)

	5.7.5 Sliding velocity.....	52
	5.7.6 Sliding factor.....	53
	5.7.7 Specific sliding.....	54
6	Crossed axis cylindrical gear pairs.....	54
6.1	General.....	54
6.2	Concepts for a gear pair.....	55
6.3	Mating quantities.....	56
6.3.1	Gear ratio.....	56
6.3.2	Driving gear, driven gear and transmission ratio.....	56
6.3.3	Working pitch surfaces and working pitch point.....	56
6.3.4	Line of centres and working centre distance.....	56
6.3.5	Skew angle.....	57
6.3.6	Intermeshing racks at working pitch cylinders.....	57
6.3.7	Working transverse pressure angles.....	59
6.3.8	Working transverse tooth thicknesses.....	59
6.3.9	Basic rack profile to generate each part of the gear pair.....	60
6.3.10	Profile shift coefficients.....	60
6.3.11	Base space width half angle.....	61
6.3.12	Working conditions at minimum centre distance.....	61
6.3.13	Working conditions with backlash.....	62
6.3.14	Working depth.....	62
6.3.15	Tip clearance.....	62
6.3.16	Calculation of tip alteration coefficient k (for crossed axis gear).....	62
6.4	Tooth engagement.....	62
6.4.1	General.....	62
6.4.2	Line of action, path of contact and point of contact.....	63
6.4.3	Active area of the tooth flanks, start of active profile and active tip diameters.....	64
6.4.4	Form over dimension.....	65
6.4.5	Designations and values relating to the line of action.....	65
6.4.6	Tooth interference.....	66
6.4.7	Mesh geometry parameters.....	67
6.5	Backlash.....	67
6.5.1	General.....	67
6.5.2	Normal base backlash.....	68
6.5.3	Backlash angle and circumferential backlash.....	68
6.6	Sliding conditions at the tooth flanks.....	69
6.6.1	General.....	69
6.6.2	Angular velocities vectors.....	69
6.6.3	Velocity vectors of a point of contact along path of contact.....	70
6.6.4	Sliding velocity.....	71
7	Principal radii of curvature of the tooth flanks.....	71
7.1	General.....	71
7.2	Angle between the principal radius of curvature at point of contact.....	72
7.3	Particularities for crossed axis helical involute gear.....	73
7.4	Equivalent radii of curvature at point of contact.....	74
8	Tooth flank modifications.....	75
8.1	General.....	75
8.2	Tooth modifications which restrict the usable flank.....	75
8.2.1	Pre-finish flank undercut.....	75
8.2.2	Tip corner chamfering, tip corner rounding.....	75
8.3	Transverse profile modifications.....	77
8.3.1	General.....	77
8.3.2	Tip and root relief, $C_{\alpha a}$ $C_{\alpha f}$	77
8.3.3	Transverse profile slope modification, $C_{H\alpha}$	77
8.3.4	Profile crowning (barrelling), C_{α}	78
8.4	Flank line (helix) modifications.....	79
8.4.1	Flank line end relief, $C_{H\beta}$	79

ISO 21771-1:2024(en)

8.4.2	Helix angle modification, $C_{H\beta}$	79
8.4.3	Flank line (helix) crowning, C_{β}	80
8.5	Flank face modifications.....	80
8.5.1	Topographical modifications.....	80
8.5.2	Triangular end relief.....	81
8.5.3	Flank twist.....	82
8.6	Descriptions of modifications by functions.....	82
9	Geometrical limits	83
9.1	General.....	83
9.2	Counterpart rack tooth profile and rack tool profile.....	84
9.2.1	Counterpart rack tooth profile.....	84
9.2.2	Rack tool profile.....	87
9.3	Machining allowance.....	91
9.4	Limits of normal tooth thickness.....	91
9.5	Generating profile shift, generating profile shift coefficient.....	92
9.6	Generated root diameter.....	93
9.7	Usable area of the tooth flank, tip and root form diameter.....	93
9.8	Undercut.....	95
9.9	Overcut.....	96
9.10	Minimum tooth thickness at the tip circle of a gear.....	96
10	Start of involute for hob or rack type cutters	96
10.1	Formulae of involute and trochoid.....	96
10.2	Undercut conditions.....	98
10.3	Determination of start of involute.....	99
10.4	Determination of radius of curvature of trochoid.....	101
11	Start of involute calculation in case of pinion-type cutter	103
11.1	Geometry of pinion-type cutter.....	103
11.1.1	General.....	103
11.1.2	Pinon-type cutter without protuberance.....	105
11.1.3	Pinon-type cutter with protuberance.....	106
11.2	Undercut condition.....	107
11.3	Determination of start of involute when no undercut exists.....	108
11.4	Start of involute when there is undercut.....	108
11.4.1	Residual fillet undercut (transverse plane).....	108
11.4.2	Angle centre line of gear pair to centre point of tooth tip rounding:.....	108
11.4.3	Point Q (tangent point of cutter tip fillet and generated gear root fillet).....	109
11.4.4	Determination of start of involute.....	109
11.4.5	Determination of radius of curvature of trochoid.....	112
Annex A (informative)	Form diameters when a circular arc in a transverse plane is used for tooth tip corner radius or tooth root fillet radius	114
Annex B (informative)	Tip form radius when tooth tip corner radius is defined on normal surface with pinion type cutter	123
Annex C (informative)	Supplementary information for crossed axes cylindrical gears	131
Annex D (informative)	Geometry of surfaces in contact	138
Annex E (informative)	Projection of transverse profile of the tooth to other planes	148
Annex F (informative)	Interface for geometry of involute worms defined with ISO 10828	156
	Bibliography	159

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 1, *Nomenclature and wormgearing*.

This first edition of ISO 21771-1 cancels and replaces ISO 21771:2007, which has been technically revised.

The main changes are as follows:

- the sign convention for internal gears used in the ISO 6336 series^[8] has been adopted. The negative value for the number of teeth of an internal gear is applied to the diameters and centre distance, so these dimensions of internal gears have negative values;
- flank direction has been renamed as hand of helix and sign (+/-) of helix angle is used;
- a definition of normal surface has been added and this is used rather than normal plane;
- the annex on tooth thickness was removed because it is now addressed in ISO 21771-2.

Additional material has been added to cover:

- calculation of form diameters for tooth tip corner radius and tooth root fillet radius in the transverse plane for an involute cylindrical gear ([Clauses 10, 11](#) and [Annex B](#));
- calculation of the tooth tip corner radius for a specified form diameter and tip diameter of an involute cylindrical gear;
- calculation of a radius tangent to the involutes of adjacent teeth at root or tip diameter ([Annex A](#));
- generated tooth root fillet shape for individual involute cylindrical gears ([Annex B](#));
- concepts and parameters for involute cylindrical gear pairs with crossed axes ([Clause 6](#) and [Annex C](#));
- geometry of surfaces in contact ([Annex D](#));
- projection of a transverse plane profile of a tooth onto another plane ([Annex E](#));

ISO 21771-1:2024(en)

— interface to ISO 10828 for involute worm gear geometry ([Annex F](#)).

A list of all parts in the ISO 21771 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 21771-1:2024](#)

<https://standards.iteh.ai/catalog/standards/iso/859abd99-aa53-4275-8ea0-bb8fe79bc285/iso-21771-1-2024>

Cylindrical involute gears and gear pairs —

Part 1: Concepts and geometry

1 Scope

This document specifies the geometric concepts and parameters for cylindrical gears with involute helicoid tooth flanks. Flank modifications are included. The formulae in this document apply to all pressure angles.

It also covers the concepts and parameters for involute cylindrical gear pairs with parallel or crossed axes, and a constant gear ratio. Gear and mating gear in these gear pairs have the same basic rack tooth profile.

2 Normative references

There are no normative references in this document.

3 Terms, definitions, symbols, subscripts and units

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

3.1.1

basic rack tooth profile for involute gear teeth

tooth profile of a normal section through the teeth of a basic rack which corresponds to an external spur gear with number of teeth $z = \infty$ and diameter $d = \infty$

Note 1 to entry: The tooth of the basic rack tooth profile is bounded by the tip line at the top and by the parallel root line at the bottom. The fillet between the straight part of the profile and the root line is a circular arc with a radius equal to ρ_{fp} .

3.1.2

counterpart rack tooth profile

rack tooth profile symmetrical to the basic rack tooth profile about the datum line P-P and displaced by half a pitch relative to it

3.1.3

nominal involute flank

pure involute flank prior to any modifications

Note 1 to entry: See [4.4](#) for more information on a gear tooth involute flank.

3.1.4 tip alteration coefficient

k
change to the addendum relating to the standard addendum of one normal module, it is made non-dimensional by dividing by the normal module

Note 1 to entry: Tip alteration is also known as addendum modification, tip shortening or truncation.

3.1.5 generating gear pair

generating tool (rack, hob, pinion-type cutter, or grinding wheel) and the gear being machined during gear tooth machining process

3.2 Symbols

Table 1 provides all the symbols used in this document.

Table 1 — Symbols

Symbol	Description	Subclause
A	pinion lower end point of meshing (near pinion root)	5.5.6.1
a_w	working centre distance of a cylindrical gear pair	5.3.3 , 5.3.5 , 6.3.12
a_{w0}	centre distance in the generating process with pinion-type cutter	11.2
B	pinion lower point of single tooth contact (LPSTC)	5.5.6.1
b	facewidth	4.3.9
b_{Ea}	length of relief near tip	8.5.2
b_{Ef}	length of relief near root	8.5.2
b_F	usable facewidth	4.3.9
b_w	active facewidth (the facewidth used)	5.5.9.2
C	working pitch point with subscript: amount of relief for modifications	5.3.5 8
C_{ay}	modification of the profile by function	8.6
C_{Ea}	amount of triangular end relief modification at tip	8.5.2
C_{Ef}	amount of triangular end relief modification at root	8.5.2
$C_{H\alpha}$	amount of transverse profile slope modification	8.3.3
$C_{H\beta}$	amount of flank line slope modification	8.4.2
$C_{i,j}$	amount of modification at point (i,j)	8.5.1
C_α	amount of profile crowning (barrelling)	8.3.4
$C_{\alpha a}$	amount of tip relief	8.3.2
$C_{\alpha f}$	amount of root relief	8.3.2
C_β	amount of flank line crowning	8.4.3
$C_{\beta I}, C_{\beta II}$	amount of end relief	8.4.1
$C_{\beta y}$	modification of the flank line by function	8.6
$C_{\Sigma y}$	modification of the flank surface by function	8.6
c	tip clearance	5.3.8 , 6.3.15
c_F	form over dimension	5.5.5
D	pinion highest point of single tooth contact (HPSTC)	5.5.6.1
d	reference diameter	4.3.4
d_a	tip diameter	4.6.5
d_{a0}	tip diameter of pinion-type cutter	11.1

Table 1 (continued)

Symbol	Description	Subclause
d_b	base diameter	4.4.2
d_{b0}	base diameter of the pinion-type cutter	11.1
d_{bK}	chamfering base diameter	8.2.2
$d_{C\alpha a}$	tip relief start diameter	8.3.2
$d_{C\alpha f}$	root relief start diameter	8.3.2
d_{Cf}	Profile control diameter	8.3.2
d_{Ea}	diameter for start of triangular end relief at tooth tip	8.5.2
d_{Ef}	diameter for start of triangular end relief at tooth root	8.5.2
d_{Fa}	tip form diameter	9.7
d_{Ff}	root form diameter	5.5.2, 9.7
d_f	root diameter (nominal dimension)	4.6.7
d_{fE}	root diameter produced	9.6
d_{Na}	active tip diameter	5.5.2, 6.4.3
d_{Nf}	start of active profile diameter (SAP diameter, active root diameter)	5.5.2, 6.4.3
d_v	V-circle diameter	4.6.2
d_w	working pitch diameter	5.3.5
d_y	Y-circle diameter	4.6.3
d_0	reference diameter of pinion-type cutter	11.1.1
E	pinion upper end point of meshing (near pinion tip)	5.5.6.1
E_{sni}	lower tooth thickness limit deviation for normal tooth thickness at reference cylinder	9.4
E_{sns}	upper tooth thickness limit deviation for normal tooth thickness at reference cylinder	9.4
e_n	normal space width on the reference cylinder	4.8.7
e_p	space width of the basic rack tooth profile	4.3.3
e_t	transverse space width on the reference cylinder	4.8.4
e_{yn}	normal space width on the y-cylinder	4.8.7
e_{yt}	transverse space width on the y-cylinder	4.8.4
F	force	D.3
g_a	length of addendum path of contact	5.5.6.2, 6.4.5.2
g_f	length of dedendum path of contact	5.5.6.2, 6.4.5.2
$g_{yft}(\theta)$	angle from line of centres to point on the gear fillet generated with pinion-type cutter	B.4.2
g_α	length of path of contact	5.5.6.2
$g_{\alpha y}$	distance of a point Y from working pitch point C	5.7.5
g_β	overlap roll length (arc of contact)	5.5.9.4
h	tooth depth (between tip line and root line)	4.7.1
h_a	addendum from reference pitch circle	4.7.2
h_{aP}	addendum of the basic rack tooth profile	4.3.2
h_{aP0}	addendum of the counterpart of the basic rack tooth profile	9.2.2
h_{aw}	addendum from working pitch circle	4.7.2
h_{a0}	addendum of pinion-type cutter	11.1.1
h_{FaP0}	straight part of tip flank of tool-generating profile	9.2.2
h_{FFP}	portion of the dedendum to root form line, of the basic rack tooth profile	4.3.2
h_{FFP0}	portion of the dedendum to root form line of the counterpart rack tooth profile	9.2.1
h_{fP0}	dedendum of the counterpart rack tooth profile and rack tool	9.2.2
h_f	dedendum from reference circle	4.7.2

Table 1 (continued)

Symbol	Description	Subclause
h_{fP}	dedendum of the basic rack tooth profile	4.3.3
h_{fW}	dedendum from working pitch circle	4.7.2
h_K	height of the tip corner chamfering or tip corner rounding	8.2.2
h_P	tooth depth of basic rack tooth profile	4.3.2
h_w	working depth of teeth in a gear pair	5.3.7 , 6.3.14
i	transmission ratio of a gear pair	5.3.2
inv	involute function (not a variable)	4.4.5
j_{bn}	normal base backlash	5.6.4 , 6.5.2
j_{bt}	transverse backlash	5.6.2
j_r	radial backlash	5.6.5
j_t	circumferential backlash at the reference circle	5.6.3 , 6.5.3
j_{wn}	working normal backlash	6.5.2
j_{wt}	circumferential backlash at the working pitch circle	5.6.3 , 6.5.3
K_g	sliding factor	5.7.6
K_{ga}	sliding factor at tooth tip	5.7.6
K_{gf}	sliding factor at tooth root	5.7.6
k	tip alteration coefficient	3.1.3 , 4.6.4 , 5.3.9 , 6.3.16
L_{Ca}	tip relief roll length	8.3.2
L_{Cf}	root relief roll length	8.3.2
L_{Cl} , L_{CII}	length of end relief	8.4.1
L_{Ea}	tip roll length of triangular end relief modification	8.5.2
L_{Ef}	root roll length of triangular end relief modification	8.5.2
L_y	length of roll to y-cylinder	4.4.10
L_{yt}	length of involute profile to y-cylinder	4.4.11
l_{max}	maximum length of a contact line	5.5.10
M_y	a point on a tooth flank where radius of curvature is calculated	7.1
m	module	4.3.7
m_n	normal module	4.3.7
m_t	transverse module	4.3.7
m_x	axial module	4.3.7
N	number of tooth or pitch	4.2.6
n_a	rotational speed of driving gear (rpm)	5.3.2
n_b	rotational speed of driven gear (rpm)	5.3.2
O	centre of a circle	6.3.4
P_d	diametral pitch	4.3.8
P_{nd}	normal diametral pitch	4.3.8
p_{bn}	normal base pitch	4.5.5.1
p_{bt}	transverse base pitch	4.5.5.1
p_{en}	normal base pitch on the path of contact	4.5.5.3
p_{et}	transverse base pitch on the path of contact	4.5.5.2
p_n	normal pitch on the reference cylinder	4.5.2.2
p_t	transverse pitch on the reference cylinder	4.5.2.1
p_{wn}	normal pitch at the working diameter	6.3.6 , 6.5.2

Table 1 (continued)

Symbol	Description	Subclause
p_x	axial pitch	4.5.4
p_{yn}	normal pitch on the y-cylinder	4.5.3
p_{yt}	transverse pitch on the y-cylinder	4.5.3
p_z	lead	4.4.6
pr	protuberance of the tool (as seen in ISO 6336-3)	9.2.1
q	machining allowance on tooth flank	9.3
q_{FS}	magnitude (amount) of undercut in transverse plane	8.2.1
R'	first principal radius of curvature of surface	7.4
R''	second principal radius of curvature of surface	7.4
R_c	radius of curvature of trochoid at point M	10.4
R_{fp}	radius of curvature of the basic rack profile at point Q	10.4
R_{tro-y}	radius of the fillet at point Q	10.4
r_{a0}	tip radius of the pinion-type cutter	11.1.1
r_{b0}	base radius of the pinion-type cutter	11.2
r_{ea}	x axis of ellipse	10.4
r_{eb}	y axis of ellipse	10.4
r_{Fa0}	tip form radius of the pinion-type cutter	11.1.1
r_{Ff}	root form radius	10.3
r_{inv}	radius to point on involute	10.1, 11.4.4.1
r_{M0}	radius for the centre of the tool tooth tip rounding of the pinion-type cutter	11.1.1
r_{tro}	radius to point on trochoid	10.1
r_w	manufacturing pitch circle radius of the gear	11.4.3
r_{w0}	manufacturing pitch circle radius of the pinion-type cutter	11.4.3
$r_{ya0}(\theta)$	radial polar coordinate of a point on tip radius of pinion-type cutter	Figure B.1
$r_{yft}(\theta)$	radial polar coordinate of a point on the gear fillet generated with pinion-type cutter	B.4.2
S_α	twist of the transverse profile	8.5.3
S_β	twist of the flank line	8.5.3
s_{aK}	tip transverse tooth thickness when tip chamfering or tip rounding	8.2.2
s_n	normal tooth thickness at the reference diameter	4.8.6
s_{ni}	minimum normal tooth thickness at the reference diameter	9.4
s_{ns}	maximum normal tooth thickness at the reference diameter	9.4
s_p	tooth thickness of the basic rack tooth profile	4.3.3
s_{pr}	residual fillet undercut (on normal surface)	10.1
s_{prt}	residual fillet undercut (transverse plane)	11.4.1
s_t	transverse tooth thickness at the reference diameter	4.8.2
s_{wn}	normal tooth thickness at working diameter	6.3.6, 6.5.2
s_{wt}	transverse tooth thickness at working diameter	6.3.8
s_{yn}	normal tooth thickness at the Y circle diameter	4.8.6
s_{yt}	transverse tooth thickness at the Y circle diameter	4.8.2
T	tangent point on base circle of line normal to involute	4.4.9
T_1	point of contact between the line of action and the base circle of pinion	5.5.6.1
T_2	point of contact between the line of action and the base circle of gear wheel	5.5.6.1
T_1	unit vector of reference helix	4.10
T_2	unit vector of generator	4.10

Table 1 (continued)

Symbol	Description	Subclause
T_{M1}	tangency point between the base cylinder of the pinion and a line normal to a contact line through point M_y	7.1
T_{M2}	tangency point on the base cylinder of the gear wheel and a line normal to a contact line through point M_y	7.1
U	involute point of origin	4.4.9
u	gear ratio	5.3.1
v	circumferential velocity at reference diameter	5.7.2
v_b	circumferential velocity at base diameter	5.7.2
v_g	sliding velocity	5.7.5
v_{ga}	sliding velocity at the active addendum	5.7.5
v_{gf}	sliding velocity at the active dedendum	5.7.5
v_{Mg}	sliding velocity at point M	6.6.4
v_n	normal velocity	5.7.3
v_{ry}	rolling velocity at diameter d_y	5.7.4
v_w	circumferential velocity of the working pitch circles	5.7.2 , 5.7.6
v_y	circumferential velocity at diameter d_y	5.7.2
x	profile shift coefficient	4.3.10
x_E	generating profile shift coefficient	9.2.1
x_{Ei}	lower limit generating profile shift coefficient	9.5
x_{Es}	upper limit generating profile shift coefficient	9.5
x_{EsV}	profile shift coefficient for rough machining, upper limit	9.5
x_{EiV}	profile shift coefficient for rough machining, lower limit	9.5
x_{Eu}	generating profile shift coefficient at undercut limit	9.8
x_0	profile shift coefficient of the pinion-type cutter	11.1.1
X_1	point on x axis of coordinate system of surface 1	D.1
X_2	point on x axis of coordinate system of surface 2	D.1
Y	any point on a tooth flank or involute	4.4.3
Y_1	point on y axis of coordinate system of surface 1	D.1
Y_2	point on y axis of coordinate system of surface 2	D.1
z	number of teeth	4.2.5
z_a	number of teeth of driving gear	5.3.2
z_b	number of teeth of driven gear	5.3.2
z_0	number of teeth of pinion-type cutter	11.1.1
Z_1	point on z axis of coordinate system of surface 1	D.1
Z_2	point on z axis of coordinate system of surface 2	D.1
α_a	pressure angle at tip circle	5.5.8.3
α_{Fa}	pressure angle at the tip form diameter d_{Fa}	A.2.1
α_{Fa0}	pressure angle on the radius r_{Fa0} of pinion-type cutter	11.1.1
α_{Ff}	pressure angle at root form circle	9.7
α_{KP0}	normal chamfering pressure angle of the counterpart rack tooth profile	8.2.2
α_{KP0t}	transverse chamfering pressure angle of the counterpart rack tooth profile	8.2.2
α_{Mt0}	transverse pressure angle for the radius at the point M of the pinion-type cutter	11.1.1
α_{NP}	pressure angle at start of active profile	5.5.2.2
α_n	normal pressure angle	4.4.4
α_p	pressure angle of the basic rack tooth profile	4.4.4