



Designation: F307–02 (Reapproved 2007) F307 – 13

Standard Practice for Sampling Pressurized Gas for Gas Analysis¹

This standard is issued under the fixed designation F307; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This practice describes ~~the procedure~~ procedures for obtaining a sample of pressurized gas for gas analysis from a system or component.

1.2 The values stated in SI units are to be regarded as the standard. ~~The values given in parentheses are for information only.~~

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For hazard statement, see Section 56.

2. Referenced Documents

2.1 *ASTM Standards:*²

[F310 Practice for Sampling Cryogenic Aerospace Fluids](#)

[G93 Practice for Cleaning Methods and Cleanliness Levels for Material and Equipment Used in Oxygen-Enriched Environments](#)

3. Terminology

3.1 *Definitions:*

3.1.1 *sample port*—the designated point in a system or component from which a representative gas sample may be taken.

4. Summary of Practice

4.1 *Evacuated Sample Vessel Procedure*—A sample pressure vessel is evacuated and sealed with a minimum vacuum pressure of ~~10–3~~ 10^{-3} torr. The vessel is then attached to the designated pressurized sample port. The pressurized gas is allowed to enter the sample vessel until the pressure is equal to the pressure of the system or component. The pressure is secured and the sample vessel assigned for appropriate analysis.

4.2 *Purged Sample Vessel Procedure*—The pressurized gas sample port is opened to establish a low level purge. A sample vessel with valves opened at each end is attached to the pressurized sample port. The pressurized sample port is opened and the purge pressure is increased to completely purge the vessel prior to sample capture. The vessel valves and sample port valves are then closed and the sample vessel delivered for analysis.

5. Apparatus

NOTE 1—All apparatus used in the sample taking should be verified as cleaned and packaged within the requirements of the allowable contamination of the ~~system, unless otherwise noted.~~ system.

5.1 *Connecting Lines*, rigid or flexible, pressure rated and identified within recognized safety codes.

5.2 *Miscellaneous Fittings*, as needed for sampling point adaption.

5.3 *Tie-downs*, suitable for sample line restraint in accord with pressure, temperature, and recognized safety codes.

¹ This practice is under the jurisdiction of ASTM Committee E21 on Space Simulation and Applications of Space Technology and is the direct responsibility of Subcommittee E21.05 on Contamination. ASTM Committee D02 on Petroleum Products and Lubricants maintains a continued interest in this practice and will make use of it in the future.

Current edition approved April 1, 2007 June 1, 2013. Published April 2007 July 2013. Originally approved in 1966. Last previous edition approved in 2002 2007 as F307–02 F307 – 02(2007). DOI: 10.1520/F0307-02R07-10.1520/F0307-13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.