



Designation: **F2931 – 11 F2931 – 13**

Standard Guide for Analytical Testing of Substances of Very High Concern in Materials and Products¹

This standard is issued under the fixed designation F2931; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide contains a list of potential test methods for the analysis of Substances of Very High Concern (SVHC) as designated by the European Chemical Agency (ECHA), in October 2008. Substances of Very High Concern are defined in Article 57 of the European Union Regulation #1907/2006, ECHA, the European Chemicals Agency. Information on the test methods cited is publicly available and is drawn from a variety of sources. This guide is intended to assist in the selection of test methods that are applicable for the SVHCs identified.

1.2 The specific SVHCs covered within this guide are compiled from the ECHA Candidate List of Substances of Very High Concern. This list is also referred to as the REACH Candidate List.

1.3 This guide specifically addresses methods for the analysis of SVHCs in products. It is not intended to cover the many and varied analysis challenges associated in the manufacturing environment.

1.4 Limitations:

1.4.1 This guide is intended to provide a compilation of available test methods for the SVHCs listed on the ECHA Candidate list and is not intended to be exhaustive. The test methods within this guide are not the only ones available for any specific substances and this guide does not recommend any specific test method.

1.4.2 Test methods for specific substances at the detection limits required for REACH reporting are not always available. In some cases, it is necessary to deduce the quantity of substance present through the analysis and quantification of its elements. Although this approach is routinely used some degree of uncertainty exists in the final result due to the reduced specificity of the test method.

1.4.3 Although this guide is intended to be updated on a periodic basis to capture new developments in the field, there is no assurance that the information provided is the most current.

1.5 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

[D1257 Specification for High-Gravity Glycerin](#)

[D1385 Test Method for Hydrazine in Water](#)

[D1971 Practices for Digestion of Water Samples for Determination of Metals by Flame Atomic Absorption, Graphite Furnace Atomic Absorption, Plasma Emission Spectroscopy, or Plasma Mass Spectrometry](#)

[D3335 Test Method for Low Concentrations of Lead, Cadmium, and Cobalt in Paint by Atomic Absorption Spectroscopy](#)

[D3545 Test Method for Alcohol Content and Purity of Acetate Esters by Gas Chromatography](#)

[D4309 Practice for Sample Digestion Using Closed Vessel Microwave Heating Technique for the Determination of Total Metals in Water](#)

¹ This guide is under the jurisdiction of ASTM Committee F40 on Declarable Substances in Materials and is the direct responsibility of Subcommittee F40.02.02 on ~~WK19940~~ Task Group on SVHCs.

Current edition approved Dec. 1, 2014; May 15, 2013. Published January 2012; July 2013. Originally approved in 2011. Last previous edition approved in 2011 as D3984 – 11. DOI: [10.1520/F2931-11](https://doi.org/10.1520/F2931-11); [10.1520/F2931-13](https://doi.org/10.1520/F2931-13).

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[D5831 Test Method for Screening Fuels in Soils](#)

[D7065 Test Method for Determination of Nonylphenol, Bisphenol A, *p-tert*-Octylphenol, Nonylphenol Monoethoxylate and Nonylphenol Diethoxylate in Environmental Waters by Gas Chromatography Mass Spectrometry](#)

[D7485 Test Method for Determination of Nonylphenol, *p-tert*-Octylphenol, Nonylphenol Monoethoxylate and Nonylphenol Diethoxylate in Environmental Waters by Liquid Chromatography/Tandem Mass Spectrometry](#)

[E1621 Guide for X-Ray Emission Spectrometric Analysis](#)

[F2576 Terminology Relating to Declarable Substances in Materials](#)

2.2 *European Commission*:³

[Article 57 of the European Union Regulation #1907/2006](#)

2.3 *International Electrotechnical Commission IEC/TC11*:⁴

[IEC 62321 Electrotechnical Products – Determination of Levels of Six Regulated Substances \(Lead, Mercury, Cadmium, Hexavalent Chromium, Polybrominated Biphenyls, Polybrominated Diphenyl Ethers\)](#)

2.4 *Joint Industry Guide (JIG)*:⁵

[JIG-101 Material Composition Declaration for Electrotechnical Products. Ed 4.0, 2011](#)

3. Terminology

3.1 Definitions:

3.1.1 Terms and definitions related to declarable substances in materials may be found in Terminology [F2576](#).

3.1.2 Terms and definitions in the guide not found in Terminology [F2576](#) are found in a common dictionary or other reference documents such as the ASTM Dictionary of Engineering Science & Technology.⁶

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *article*—“an object which during production is given a special shape, surface or design which determines its function to a greater degree than its chemical composition” as defined in Article 3(3) of the REACH Regulation.

3.2.2 *brominated flame retardant*—a group of brominated organic compounds that are used to inhibit initiation of a fire.

3.2.3 *Joint Industry Guide*—An industry standard of the Electric Industries Alliance that “*establishes the relevant substances as well as reporting thresholds that the industry agrees should govern material content disclosures.*”⁵

3.2.4 *phthalates*—also known as *phthalate esters*, are esters of phthalic acid primarily used as a plasticizer for polyvinyl chloride or as solvents for many different types of consumer products.

3.2.5 *plasticizer*—any of a group of substances used in plastics and other materials to control viscosity, flexibility or softness of the finished product.

3.2.6 *Substances of Very High Concern (SVHC)*—substances that have hazards of serious consequences and meet the criteria for carcinogenic, mutagenic and reproductive toxic substances of category 1 and 2.

<https://standards.iteh.ai/catalog/standards/sist/259a2d97-5927-4782-930c-1f628f1246e4/astm-f2931-13>

³ European Commission, B-1049, Brussels, Belgium, http://ec.europa.eu/index_en.htm.

⁴ Available from International Electrotechnical Commission (IEC), 3, rue de Varembe, P.O. Box 131, CH-1211 Geneva 20, Switzerland, <http://www.iec.ch>.

⁵ Available from the Consumer Electronics Association, 1919 S. Eads St. Arlington, VA 22202, <http://www.ce.org>

⁶ ASTM Dictionary of Engineering Science & Technology, 10th Edition. Available from www.astm.org.

3.2.6.1 Discussion—

SVHC can be persistent, bioaccumulative and toxic (PBT) substances or very persistent and very bioaccumulative (VPvB) substances. Other substances giving rise to an equivalent level of concern as potential SVHC include endocrine disruptors.

3.3 Acronyms:

3.3.1 *AAS*—Atomic Absorption Spectrometry

3.3.2 *AED*—Atomic Emission Detection

3.3.3 *AES*—Atomic Emission Spectrometry

3.3.4 *AFS*—Atomic Fluorescence Spectrometry

3.3.5 *BFR*—Brominated Flame Retardant

3.3.6 *CAS*—Chemical Abstract Services

3.3.7 *CMR*—Carcinogenic, Mutagenic and Toxic to Reproduction

3.3.8 *CPSC*—United States Consumer Product Safety Commission

3.3.9 *DMF*—Dimethylformamide

3.3.10 *ECD*—Electron Capture Detection

3.3.11 *ECHA*—European Chemicals Agency

- 3.3.12 *ECNI*—Electron Capture Negative Ion
- 3.3.13 *EEE*—Electrical and Electronic Equipment
- 3.3.14 *EIA*—Electronic Industries Alliance
- 3.3.15 *EPA*—United States Environmental Protection Agency
- 3.3.16 *EU*—European Union
- 3.3.17 *FID*—Flame Ionization Detection
- 3.3.18 *FPD*—Flame Photometric Detection
- 3.3.19 *GC-MS*—Gas Chromatography-Mass Spectrometry
- 3.3.20 *GFAA*—Graphite Furnace Atomic Absorption Spectrometry
- 3.3.21 *HAFID*—Hydrogen Atmosphere Flame Ionization Detection
- 3.3.22 *HFAA*—Heptafluorobutyric acid anhydride
- 3.3.23 *HIPS*—High Impact Polystyrene
- 3.3.24 *HPLC*—High Performance (or Pressure) Liquid Chromatography
- 3.3.25 *ICP-MS*—Inductively Coupled Plasma – Mass Spectrometry
- 3.3.26 *ICP-OES*—Inductively Coupled Plasma – Optical Emission Spectrometry
- 3.3.27 *IR*—Infrared Spectrometry
- 3.3.28 *LC-MS-MS*—Liquid Chromatography-Tandem
- 3.3.29 *MSP*—Microspectrophotometer
- 3.3.30 *NIOSH*—United States National Institute for Occupational Health and Safety
- 3.3.31 *PAH*—Polycyclic Aromatic Hydrocarbon
- 3.3.32 *PTFE*—Polytetrafluoroethylene (Teflon)
- 3.3.33 *PVC*—Polyvinyl Chloride
- 3.3.34 *REACH*—Registration, Evaluation and Authorization of Chemicals
- 3.3.35 *RoHS*—Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment
- 3.3.36 *UV-VIS*—UltraViolet-Visible Spectrometry
- 3.3.37 *XRF*—X-ray Fluorescence Spectrometry

4. Summary of Guide

4.1 This guide provides a list of test methods for the determination of the Substances of Very High Concern as identified in the REACH Candidate list. Screening methods are discussed in **Appendix X2**.

4.2 This guide provides identifiers for each substance such as chemical name, synonyms, chemical formulas, CAS and EU numbers.

4.3 Common uses for each of the substances are identified.

5. Significance and Use

5.1 The REACH Candidate list classifies substances as SVHCs thus making them subject to possible authorization. Compliance to the REACH regulation requires that any identified SVHC be present at a concentration of less than 0.1 % (w/w) of the total article weight to avoid triggering a reporting obligation. This guide is intended to assist in the identification of available test methods for quantitative analysis of the substance(s) of interest.

5.2 When possible, industry accepted standard test methods are cited. However, industry vetted test methods are not available for all of the substances contained in the REACH Candidate List. Thus, some caution and due diligence must be exercised when applying some of the methods listed in this guide.

5.3 In some cases, test methods for the identification and quantification of a specific substance are not available. An example would include CoCl_2 . Methods currently in practice involve the individual determination of Co and Cl concentrations and use other sources of information or chemical judgment to assign the expected CoCl_2 concentration. This approach obviously has its limitations and pitfalls and must be used judiciously.

5.4 Under the REACH regulation, EU manufacturers, importers or distributors of articles containing more than 0.1 % (w/w) of a substance that the Agency has listed as being an SVHC shall provide their customers with the name of the substance and information allowing the safe use of the article. Producers and distributors of articles containing SVHC shall also supply the same information to consumers, upon request. In situations where this information is not readily available from the supply chain it is

incumbent upon the supplier to collect this information through actual chemical analysis or other means. This guide is intended to assist in the selection of appropriate test methods in the event that chemical analysis is required.

6. Substance List and Uses

6.1 The substances listed in [Table 1](#) were derived from the ECHA SVHC Candidate List published in October 2008. Any substances that have been subsequently added after October 2008 are not included.

6.2 The CAS or EU numbers are unique identifiers for the substance. It is possible for a particular substance to have one or more commonly used names.

6.3 Common uses of the substance help to identify in which products or materials these substance is likely to be found. Note that the list of common uses is not exhaustive.

7. SVHC Test Methods

7.1 This guide is not intended to be exhaustive in the identification of available test methods. The intent is to provide guidance and some examples of available test methods relevant to the required analysis. Some of the SVHCs do not have industry standard test methods associated with them. Literature citations of these non-standard methods are meant to be for information only.

7.2 Standard test methods do not exist for all of the SVHCs listed. Therefore, the test methods cited for those substances must be validated for analytical accuracy before use in regulatory compliance demonstration. Moreover, when a method is applied outside of its intended scope, validation of the altered method is required. Considerations such as sample matrix, analytical requirements, etc. for the intended analysis will determine its applicability. All deviations from the published method must be clearly noted.

NOTE 1—If a standardized method is used beyond the stated scope, that addition must be validated. All deviations from published methods must be documented.

7.3 In many cases, test methods that are specific for a particular substance have not been developed. Therefore, the approach to quantitative analysis is not straightforward. A combination of test methods and the use of logical assumptions are required. These assumptions shall be clearly articulated because they will determine the limitations of the approach.

7.4 Screening methods can be utilized to determine whether a detectable amount of a substance is present. In many situations the application of a screening process can obviate the need to perform full quantitative analysis. See [Appendix X2](#) for more information on screening methodologies.

7.5 In some cases, sample preparation methods are dependent upon the physical state of the sample to be analyzed. For many of the test methods, several sample preparation references are cited when applicable.

7.6 In some cases, limitations in the sample preparation method cited in [Appendix X1.2](#) can produce a sample for analysis that is non-optimal. Incomplete extraction, incomplete digestion, loss of analyte, etc. often require adjustments to the sample preparation methods to obtain the desired analytical result. At a minimum the limitations in the sample preparation method shall be accounted for, when possible, in the calculation of the analytical result. Additionally, if these adjustments to the method do not produce a satisfactory sample for analysis, it may be necessary to develop an alternative method. Validation of the sample preparation method will thus be required.

7.7 Detection limits for the test methods are given when available and for reference only. It is necessary when reporting analytical results that they conform to the definition given by the reporting requirement.

7.8 Under certain circumstances it is advisable to employ external technical consulting services if the analysis being addressed is beyond the expertise of internal resources. There exist a number of laboratories that specialize in analysis of regulated substances for a fee.

8. Keywords

8.1 anthracene; arsenic oxide; brominated flame retardants; candidate list; cobalt dichloride; hexabromocyclododecane; lead hydrogen arsenate; MDA; musk xylene; phthalates; REACH; short chain chlorinated paraffins; sodium dichromate; Substances of Very High Concern; tributyltin oxide; triethyl arsenate

TABLE 1 SVHC Substances and Their Common Uses

Substance Name	Chemical Formula	AS Number	EC Number	Common Uses
4,4'-Methylenebis(2-chloroaniline)	$C_{13}H_{14}N_2$	101-77-9	202-974-4	Converted to methylenediphenyl diisocyanate (MDI). MDI used for polyurethane production. Other uses include: (1) hardener for epoxy resins and adhesives, (2) basic ingredient of colorant, and (3) intermediate for high-performance polymer.
Diaminodiphenylmethane	dianiline, MDA			Used as a fragrant particularly for consumer cosmetic products
5-tert-Butyl-2,4,6-Trinitro-m-Xylene	$C_{12}H_{15}N_3O_6$	81-15-2	201-329-4	Used as a fragrant particularly for consumer cosmetic products.
5-tert-Butyl-2,4,6-Trinitro-m-Xylene	$C_{12}H_{15}N_3O_6$	81-15-2	201-329-4	Used as a fragrant particularly for consumer cosmetic products.
Alkanes, C10-13, chloro	Short Chain Chlorinated Paraffins (SCCP)	85535-84-8	287-476-5	May act as a secondary plasticizer or flame retardant in PVC. Other uses include: (1) metal working lubricant, (2) rubber parts, (3) paints, (4) sealant, (5) leather work, and (6) fiber.
Alkanes, C10-13, chloro	Short Chain Chlorinated Paraffins (SCCP)	85535-84-8	287-476-5	May act as a secondary plasticizer or flame retardant in PVC. Other uses include: (1) metal working lubricant, (2) rubber parts, (3) paints, (4) sealant, (5) leather work, and (6) fiber.
Anthracene	Paranaphthalene	120-12-7	204-371-1	An intermediate in the production of dyes; used in the manufacturer of pyrotechnic products
Anthracene	Paranaphthalene	120-12-7	204-371-1	An intermediate in the production of dyes; used in the manufacturer of pyrotechnic products.
Benzyl butyl phthalate	Phthalic acid, benzyl butyl ester	85-68-7	201-622-7	Plasticizer in flooring material such as PVC foam. Other uses are as a plasticizer in traffic cones, food conveyor belts, artificial leather, etc.
Bis(2-ethylhexyl)phthalate	Diocetylphthalate	117-81-7	204-211-0	Commonly used as a plasticizer in manufacturing of articles made of PVC, resins, rubbers, packaging materials, some paper products, and various medical devices, including the blood bags. It can also be found in some hydraulic fluids or dielectric fluids in capacitors. It is often found in coatings, pigments, textiles, or used as a solvent in light sticks.
Bis (tributyltin) oxide	Distannoxane, hexabutyl-	56-35-9	200-268-0	Primarily used as a biocide for boats, mildew proofing for leather work
Bis (tributyltin) oxide	Distannoxane, hexabutyl-	56-35-9	200-268-0	Primarily used as a biocide for boats, mildew proofing for leather work.
Cobalt dichloride	Cobaltous Chloride	7646-79-9	231-589-4	This substance can be used for (1) humidity indicator, (2) absorbent of ammonia gas, (3) gas mask, (4) production for vitamin B12, (5) trace amount of nutrient factor for food, (6) trace amount of element for nitric acid pesticides, (7) solvent in purifying magnesium. Additionally, it may be used for packaging.
Cobalt dichloride	Cobaltous Chloride	7646-79-9	231-589-4	This substance can be used for (1) humidity indicator, (2) absorbent of ammonia gas, (3) gas mask, (4) production for vitamin B12, (5) trace amount of nutrient factor for food, (6) trace amount of element for nitric acid pesticides, (7) solvent in purifying magnesium. Additionally, it may be used for packaging.
Diarsenic pentaoxide	Diarsenic Pentoxide	1303-28-2	215-116-9	This substance can be used for (1) colorants, (2) metal refining, (3) special glass production, and (4) antiseptic agent for wood.
Diarsenic trioxide	Arsenic Trioxide	1327-53-3	215-481-4	This substance can be used for (1) decolorants for glasses and enamel, (2) purifying and oxidizing agent in production of special glasses and lead crystal, (3) antiseptic agent for wood, and (4) medicine for leukemia.
Dibutyl phthalate	1,2-Benzenedicarboxylic acid di-n-butyl ester	84-74-2	201-557-4	Common plasticizer used in various polymers to keep crystals from forming. It is also used in paints, pigments, or printing inks as an adhesive agent. It is soluble in various organic solvents. This property allows it to be used as fixatives in perfumes or as an ectoparasiticide.
Hexabromocyclododecane	Cyclododecane, hexabromo-isomers	25637-99-4	247-148-4	Used as a brominated flame retardant for polystyrene materials, e.g., HIPS case material and packaging.
Hexabromocyclododecane	Cyclododecane, hexabromo-isomers	25637-99-4	247-148-4	Used as a brominated flame retardant for polystyrene materials, for example, HIPS case material and packaging.
Lead hydrogen arsenate	Lead Acid Arsenate	7784-40-9	232-064-2	Insecticide or pesticide
Sodium dichromate dihydrate	Sodium Bichromate	7789-12-0	234-190-3	Used for: (1) production of other chromium compounds, (2) production of inorganic chromate pigments, (3) preservative supplement, finishing of metal plating, (4) production of vitamin K.
Triethyl arsenate	Arsenic acid Triethyl Ester	15606-95-8	427-700-2	Used for integrated circuit manufacturing as an intermediate for n-type doping of semiconductors.

ASTM F2931-13
<https://standards.itw.com/standards/sist/27-4782-930c-11628f1246e4/astm-f2931-13>

<u>2,4-Dinitrotoluene</u>	<u>1-methyl-2,4-dinitrobenzene</u>	<u>121-14-2</u>	<u>204-450-0</u>	<u>C₇H₆N₂O₄</u>	<u>2,4-dinitrotoluene is used in the production of toluene diisocyanate, which is used for the manufacture of flexible polyurethane foams. The substance is also used as gelatinizing-plasticizing agent for the manufacture of explosive mixtures (for example, for airbags in cars).</u>
<u>Aluminosilicate Refractory Ceramic Fibres</u>	<u>VITREOUS</u>	<u>142844-00-6</u>			<u>Refractory ceramic fibres are used for high-temperature insulation, almost exclusively in industrial applications (insulation of industrial furnaces and equipment, equipment for the automotive and aircraft/aerospace industry) and in fire protection (buildings and industrial process equipment).</u>
<u>Anthracene oil</u>	<u>Anthracene Phenanthrene Carbazole</u>	<u>90640-80-5</u>	<u>292-602-7</u>	<u>C₁₄H₁₀ C₁₂H₉N</u>	<u>The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.</u>
<u>Anthracene oil, anthracene paste</u>	<u>Anthracene Phenanthrene Carbazole</u>	<u>90640-81-6</u>	<u>292-603-2</u>	<u>C₁₄H₁₀ C₁₂H₉N</u>	<u>The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.</u>
<u>Anthracene oil, anthracene paste, anthracene fraction</u>	<u>Anthracene Phenanthrene Carbazole</u>	<u>91995-15-2</u>	<u>295-275-9</u>	<u>C₁₄H₁₀ C₁₂H₉N</u>	<u>The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.</u>
<u>Anthracene oil, anthracene paste, distn. lights</u>	<u>Anthracene Phenanthrene Carbazole</u>	<u>91995-17-4</u>	<u>295-278-5</u>	<u>C₁₄H₁₀ C₁₂H₉N</u>	<u>The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.</u>
<u>Anthracene oil, anthracene-low</u>	<u>Anthracene Phenanthrene Carbazole</u>	<u>90640-82-7</u>	<u>292-604-8</u>	<u>C₁₄H₁₀ C₁₂H₉N</u>	<u>The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.</u>
<u>Diisobutyl phthalate</u>	<u>Bis(2-methylpropyl) benzene-1,2-dicarboxylate</u>	<u>84-69-5</u>	<u>201-553-2</u>	<u>C₁₆H₂₂O₄</u>	<u>Diisobutyl phthalate is used as plasticiser for nitrocellulose, cellulose ether, polyacrylate and polyacetate dispersions, and as a gelling aid in combination with other plasticisers, which are widely used for plastics, lacquers, adhesives, explosive material and nail polish.</u>
<u>Lead chromate</u>	<u>Lead(2+) chromate</u>	<u>7758-97-6</u>	<u>231-846-0</u>	<u>CrH₂O₄.Pb</u>	<u>Lead chromate is used for manufacturing pigments and dyes, as a pigment or coating agent in industrial and maritime paint products or for embalming/restoring of art products. Further potential uses include as detergents and bleaches, photosensitive materials and for the manufacture of pyrotechnic powder.</u>
<u>Lead chromate molybdate sulphate red (C.I. Pigment Red 104)</u>	<u>Lead(2+) chromate lead(2+) sulfate lead(2+) molybdate</u>	<u>12656-85-8</u>	<u>235-759-9</u>	<u>CrH₂O₄.Pb H₂O₄S.Pb PbMoO₄</u>	<u>Lead chromate molybdate sulphate red (C.I. Pigment Red 104) is used as a colouring, painting and coating agent in sectors such as the rubber, plastic and paints, coatings and varnishes industries. Applications comprise the production of agricultural equipment, vehicles and aircraft as well as road and airstrip painting.</u>
<u>Lead sulfochromate yellow (C.I. Pigment Yellow 34)</u>	<u>Lead(2+) chromate lead(2+) sulfate</u>	<u>1344-37-2</u>	<u>215-693-7</u>	<u>CrH₂O₄.Pb H₂O₄S.Pb</u>	<u>Lead sulfochromate yellow (C.I. Pigment Yellow 34) is used as a colouring, painting and coating agent in sectors such as the rubber, plastic and paints, coatings and varnishes industries. Applications comprise the production of agricultural equipment, vehicles and aircraft as well as road and airstrip painting. The substance is further used for camouflage or ammunition marking in the defence area.</u>
<u>Pitch, coal tar, high temperature</u>	<u>anode pitch, binder pitch, clay pigeon binder, electrode pitch, hard pitch, impregnating pitch, soft pitch, vacuum pitch</u>	<u>65996-93-2</u>	<u>266-028-2</u>	<u>not applicable</u>	<u>Pitch, coal tar, high temperature is mainly used in the production of electrodes for industrial applications. Smaller volumes are dedicated to specific uses such as heavy duty corrosion protection, special purpose paving, manufacture of other substances and the production of clay targets.</u>
<u>Tris(2-chloroethyl)phosphate</u>		<u>115-96-8</u>	<u>204-118-5</u>	<u>C₆H₁₂Cl₃O₄P</u>	<u>Tris(2-chloroethyl)phosphate is mainly used as an additive plasticiser and viscosity regulator with flame-retarding properties for acrylic resins, polyurethane, polyvinyl chloride and other polymers. Other fields of application are adhesives, coatings, flame-resistant paints and varnishes. The main industrial branches to use TCEP are the furniture, the textile and the building industry.</u>
<u>Zirconia Aluminosilicate Refractory Ceramic Fibres</u>					<u>Refractory ceramic fibres are used for high-temperature insulation, almost exclusively in industrial applications (insulation of industrial furnaces and equipment, equipment for the automotive and aircraft/aerospace industry) and in fire protection (buildings and industrial process equipment).</u>

ASTM Standards
<https://standards.it>
 Document Preview

ASTM F2931-13

<https://standards.ohio.edu/catalog/standards/sist/027-4782-930c-11646e4/astm-f2931-13>

<u>Acrylamide</u>	<u>Prop-2-enamide</u>	<u>79-06-1</u>	<u>201-173-7</u>	<u>C₃H₅NO</u>	Acrylamide is almost exclusively used for the synthesis of polyacrylamides, which are used in various applications, in particular in waste water treatment and paper processing. Minor uses of acrylamide comprise the preparation of polyacrylamide gels for research purposes and as grouting agents in civil engineering.
<u>Ammonium dichromate</u>	<u>Diammonium dichromate, Ammonium bichromate, ammonium chromate, chromic acid [H₂Cr₂O₇] diammonium salt, diammonium dichromate, dichromic acid diammonium salt</u>	<u>7789-09-5</u>	<u>232-143-1</u>	<u>Cr₂H₂O₇·2H₃N</u>	Ammonium dichromate is mainly used as an oxidising agent. Other known uses are in the manufacture of photosensitive screens and as mordant in the manufacture of textiles. Minor uses seem to comprise metal treatment and laboratory analytical agent.
<u>Boric acid</u>		<u>10043-35-3</u> <u>11113-50-1</u>	<u>233-139-2</u> <u>234-343-4</u>	<u>BH₃O₃</u>	Boric acid is widely used on account of its consistency-influencing, flame-retarding, antiseptic and preservative properties. It is a component of detergents and cleaners, adhesives, toys, industrial fluids, brake fluids, glass, ceramics, flame retardants, paints, disinfectants, cosmetics, food additives, fertilisers, insecticides and other products.
<u>Disodium tetraborate, anhydrous</u>	<u>Disodium tetraborate decahydrate, Disodium tetraborate anhydrous, Disodium tetraborate pentahydrate, borax decahydrate, boric acid, disodium salt, borax pentahydrate</u>	<u>1303-96-4</u> <u>1330-43-4</u> <u>12179-04-3</u>	<u>215-540-4</u>	<u>Na₂B₄O₇·10H₂O</u> <u>Na₂B₄O₇</u> <u>Na₂B₄O₇·5H₂O</u>	Disodium tetraborate and tetraboron disodium heptaoxide form the same compounds in aqueous solutions. Uses include a multitude of applications, for example, in detergents and cleaners, in glass and glass fibres, ceramics, industrial fluids, metallurgy, adhesives, flame retardants, personal care products, biocides, fertilisers.
<u>Potassium chromate</u>	<u>Dipotassium chromate, Bipotassium chromate, Dipotassium monochromate, Bipotassium monochromate, Neutral potassium chromate, Potassium chromate (VI), Chromate of potash (potass), Chromic acid dipotassium salt</u>	<u>7789-00-6</u>	<u>232-140-5</u>	<u>K₂CrO₄</u>	Potassium chromate is used as a corrosion inhibitor for treatment and coating of metals, for manufacture of reagents, chemicals and textiles, as a colouring agent in ceramics, in the manufacture of pigments/inks and in the laboratory as analytical agent.
<u>Potassium dichromate</u>	<u>Chromic acid [H₂Cr₂O₇] dipotassium salt, dichromic acid dipotassium salt, dipotassium bichromate, dipotassium dichromate, Lopezite, potassium bichromate, potassium dichromate(VI), dipotassium dichromium hepta-oxide</u>	<u>7778-50-9</u>	<u>231-906-6</u>	<u>K₂Cr₂O₇</u>	Potassium dichromate is used for chrome metal manufacturing and as corrosion inhibitor for treatment and coating of metals. It is further used as textile mordant, as laboratory analytical agent, for cleaning of laboratory glassware, in the manufacture of other reagents and as oxidising agent in photolithography.
<u>Sodium chromate</u>	<u>Disodium chromate, Sodium monochromate, Disodium chromium tetraoxide</u>	<u>7775-11-3</u>	<u>231-889-5</u>	<u>Na₂CrO₄</u>	Sodium chromate is mainly used as an intermediate in the manufacture of other chromium compounds as well as a laboratory analytical agent, but this use is limited. Other potential uses are mentioned in the literature but whether they occur in the EU is not clear.
<u>Tetraboron disodium heptaoxide, hydrate</u>		<u>12267-73-1</u>	<u>235-541-3</u>	<u>B₄Na₂O₇·x H₂O</u>	Disodium tetraborate and tetraboron disodium heptaoxide form the same compounds in aqueous solutions. Uses include a multitude of applications, for example, in detergents and cleaners, in glass and glass fibres, ceramics, industrial fluids, metallurgy, adhesives, flame retardants, personal care products, biocides, fertilisers.

iTeh Standards
<http://standards.itih.org>
 Document Preview

ASTM F2931-13

<http://standards.itih.org/catalog/standards/sist/259a127-4231-906-6/0c-1f616c-46e4/astm-f2931-13>

<u>Trichloroethylene</u>	<u>Acetylene trichloride, Ethynyl trichloride, Trichloroethene, TRI, TRIC, 1-Chloro-2,2-dichloroethylene, 1,1,2-Trichloroethylene, Trilene, Triklone® , Trimar. Industrial abbreviations include trichloroethylene, trichlor, Trike, Tricky and trichloroethylene.</u>	<u>79-01-6</u>	<u>201-167-4</u>	<u>C₂ H Cl₃</u>	<u>Trichloroethylene is mainly used as intermediate in the manufacture of chlorinated and fluorinated organic compounds. Other uses are for cleaning and degreasing of metal parts or as solvent in adhesives.</u>
<u>Chromium trioxide</u>	<u>Trioxochromium</u>	<u>1333-82-0</u>	<u>215-607-8</u>	<u>CrO₃</u>	<u>Formulation of mixtures containing chromium trioxide, which are mainly used for example, metal finishing/surface treatment or in much smaller amounts as catalysts containing chromium trioxide.</u>
<u>Acids generated from chromium trioxide and their oligomers</u>	<u>Dichromic acid (H₂Cr₂O₇), hydroxy-(hydroxy(dioxo)chromio)oxy-dioxochromium, Chromic acid (H₂CrO₄), dihydroxy(dioxo)chromium</u>	<u>13530-68-2</u> <u>7738-94-5</u>	<u>236-881-5</u> <u>231-801-5</u>	<u>Cr₂H₂O₇</u> <u>CrH₂O₄</u>	<u>Chromic acid, dichromic acid and oligomers of chromic and dichromic acid are spontaneously generated products of the reaction of chromic trioxide with water. Refer to the uses for chromium trioxide.</u>
<u>Cobalt (II) sulphate</u>	<u>Sulfuric acid, cobalt(2+) salt (1:1),</u>	<u>10124-43-3</u>	<u>233-334-2</u>	<u>CoH₂O₄S</u>	<u>Mainly used in the production of other chemicals. Further applications may include manufacture of catalysts and driers, surface treatments (such as electroplating), corrosion prevention, production of pigments, decolourising (in glass, pottery), batteries, animal food supplement, soil fertilizer, and others.</u>
<u>Cobalt (II) dinitrate</u>		<u>10141-05-6</u>	<u>233-402-1</u>	<u>CoN₂O₆</u>	<u>Mainly used in the production of other chemicals and the manufacture of catalysts. Further applications may include surface treatment and batteries.</u>
<u>Cobalt (II) carbonate</u>		<u>513-79-1</u>	<u>208-169-4</u>	<u>CoCO₃</u>	<u>Mainly used in the manufacture of catalysts. Minor uses may include feed additive, production of other chemicals, production of pigments, and adhesion (in ground coat frit).</u>
<u>Cobalt (II) diacetate</u>	<u>Cobalt di(acetate)</u>	<u>71-48-7</u>	<u>200-755-8</u>	<u>C₄H₆CoO₄</u>	<u>Mainly used in the manufacture of catalysts. Minor uses may include production of other chemicals, surface treatment, alloys, production of pigments, dyes, rubber adhesion, and feed additive.</u>
<u>2-Methoxyethanol</u>	<u>ethylene glycol monomethyl ether; EGME, Ethanol, 2-methoxy-</u>	<u>109-86-4</u>	<u>203-713-7</u>	<u>C₃H₈O₂</u>	<u>Mainly used as solvent, chemical intermediate and additive for fuels.</u>
<u>2-Ethoxyethanol</u>	<u>ethylene glycol monoethyl ether; EGEE, Ethanol, 2-ethoxy-</u>	<u>110-80-5</u>	<u>203-804-1</u>	<u>C₄H₁₀O₂</u>	<u>Mainly used as solvent and chemical intermediate.</u>
<u>2-ethoxyethyl acetate</u>	<u>Ethanol, 2-ethoxy-, acetate, Ethylglycol acetate; ethylene glycol mono ethyl ether acetate; 2-EEA; acetic acid, 2-ethoxyethyl ester; ethoxyethanol acetate</u>	<u>111-15-9</u>	<u>203-839-2</u>	<u>C₆H₁₂O₃</u>	<u>As solvent in coatings and in the chemical industry, intermediate in the manufacture of cyanoacrylate adhesives.</u>
<u>Strontium chromate</u>	<u>Chromic acid (H₂CrO₄), strontium salt (1:1), Chromium diolatodioxo-strontium salt (1:1), C.I. Pigment Yellow 32, Deep Lemon Yellow, Strontium chromate (VI), Strontium Yellow</u>	<u>7789-06-2</u>	<u>232-142-6</u>	<u>SrCrO₄</u>	<u>As corrosion inhibitor in coating mixtures used in the aeronautic / aerospace sector, in the coil coating sector of steel and aluminium and in the vehicle coating sector.</u>

<u>1,2-Benzenedicarboxylic acid, di-C7-11 branched and linear alkyl esters</u>	<u>Di-C7-11-(linear and branched)-alkyl phthalate, Dialkyl phthalate (C7-11) branched and linear phthalate ester; 711P; D711P; Di-711-phthalate; Dialkyl(C7-11-branched and linear) phthalate (DHNUF); Di(heptyl, nonyl, undecyl) phthalate (mixed isomers); Phthalic acid, dialkyl (C7-C11) ester; Santicizer 711</u>	<u>68515-42-4</u>	<u>271-084-6</u>	<u>C₂₂H₃₄O₄⁻ C₃₀H₅₀O₄</u>	<u>As plasticiser in PVC, foam, adhesives and coatings.</u>
<u>Hydrazine</u>	<u>H₂O; H₂O (fuel); Levoxine; Nitrogen hydride(N₂H₄);Oxytreat 35</u>	<u>7803-57-8 302-01-2 10217-52-4</u>	<u>206-114-9</u>	<u>H₄N₂</u>	<u>As intermediate in the manufacture of hydrazine derivatives, as a monomer in polymerisations, as a corrosion inhibitor in water treatment and for metal reduction and refining of chemicals. It is also used as a propellant for aerospace vehicles and as fuel in military (emergency) power units.</u>
<u>1-methyl-2-pyrrolidone</u>	<u>2-Pyrrolidinone, 1-methyl-, 1-Methylpyrrolidin-2-one, 1-Methyl-2-pyrrolidinone 1-Methyl-5-pyrrolidinone 1-Methylazacyclopentan-2-one 1-Methylpyrrolidone AgsolEx 1 M-Pyrol Microposit 2001 N 0131 N-Methyl-α-pyrrolidinone N-Methyl-α-pyrrolidone N-Methyl-γ-butyrolactam N-Methyl-2-ketopyrrolidine N-Methyl-2-pyrrolidinone N-Methyl-2-pyrrolidone N-Methylbutyrolactam N-Methylpyrrolidone NMP NSC 4594 Pharnasolve Pyrol M SL 1332</u>	<u>872-50-4</u>	<u>212-828-1</u>	<u>C₅H₉NO</u>	<u>As solvent in coatings, cleaning products, for electronic equipment manufacture, as well as in semiconductor industry, petrochemical processing, pharmaceuticals and agrochemicals.</u>
<u>1,2,3-trichloropropane</u>	<u>Propane, 1,2,3-trichloro-, Allyl trichloride; Glycerol trichlorohydrin; Glyceryl trichlorohydrin; NSC 35403; Trichlorohydrin;</u>	<u>96-18-4</u>	<u>202-486-1</u>	<u>C₃ H₅ Cl₃</u>	<u>Intermediate in the manufacture of chlorinated solvents and agricultural products. It is also used as monomer. In the past, it was used as solvent, paint and varnish remover and as degreasing agent.</u>
<u>1,2-Benzenedicarboxylic acid, di-C6-8-branched alkyl esters, C7-rich</u>	<u>C₆-8-(branched)-Alkyl benzene-1,2-dicarboxylate, C₆-8-(branched)-Alkyl phthalate, Diisoheptyl phthalate, DIHP</u>	<u>71888-89-6</u>	<u>276-158-1</u>		<u>As plasticiser in PVC and in sealants, coatings and potentially printing inks.</u>

iTeh Standards
[tps://standards.itih.](https://standards.itih.)
Document Preview

ASTM F2931-13

[/standards.itih.ai/catalog/standards/sist/259a127-4782-930c-1f628f1246e4/astm-f2931-13](https://standards.itih.ai/catalog/standards/sist/259a127-4782-930c-1f628f1246e4/astm-f2931-13)

Dichromium tris(chromate)	Chromic acid (H ₂ CrO ₄), chromium(3+) salt (3:2), Dichromium(3+) trichromate, Chromic chromate, Chromium (III) chromate, Dichromium Trischromate, Accomet C; other trade names are confidential	24613-89-6	246-356-2	Cr ₅ O ₁₂ CrH ₂ O ₄ .2/3Cr	In mixtures for metal surface treatment in the aeronautic/aerospace, steel, and aluminium coating industries.
Potassium hydroxyoctaoxidizincatedichromate		11103-86-9	234-329-8		Aeronautic/ aerospace coating, steel and aluminium coil coating, and vehicle coating.
Pentazinc chromate octahydroxide	Zinc chromate hydroxide (Zn ₅ (CrO ₄)(OH) ₈), Zinc tetraoxychromate, Zinc tetroxy chromate, Zinc chromate, hydroxide, Basic zinc chromate, Zinc chromate, Trizinc, dioxido(dioxo)chromium dihydroxide	49663-84-5	256-418-0	CrH ₆ O ₁₂ Zn ₅	Vehicle coating and aeronautic / aerospace coating.
Formaldehyde, oligomeric reaction products with aniline (technical MDA)	Formaldehyde, polymer with benzenamine, polymeric MDA3, PMDA, MDA, technical grade, crude MDA	25214-70-4	500-036-1	(C ₆ H ₇ N.CH ₂ O) _x	Manufacture of other substances. Minor uses are as ion exchange resins in nuclear power plants, as hardener for epoxy resins.
Bis(2-methoxyethyl) phthalate	1,2-Benzenedicarboxylic acid, 1,2-bis(2methoxyethyl) ester, Di(methoxyethyl) phthalate, Bis(methylglycol) phthalate	117-82-8	204-212-6	C ₁₄ H ₁₈ O ₆	Plasticiser in polymeric materials and paints, lacquers and varnishes, including printing inks.
2-Methoxyaniline; o-Anisidine	Benzenamine, 2-methoxy-, 2-methoxybenzenamine	90-04-0	201-963-1	C ₇ H ₉ NO	Manufacture of dyes for tattooing and coloration of paper, polymers and aluminium foil.
4-(1,1,3,3-Tetramethylbutyl)phenol, (4-tert-Octylphenol)	4-(2,4,4-trimethylpentan-2-yl)phenol, Phenol, 4-(1,1,3,3-tetramethylbutyl)-	140-66-9	205-426-2	C ₁₄ H ₂₂ O	Manufacture of polymer preparations and of ethoxylate surfactants. Also used as a component in adhesives, coatings, inks and rubber articles.
1,2-Dichloroethane	Ethane, 1,2-dichloro-, Ethylene dichloride, dichloroethylene, 1,2-DCE,, 1,2-EDC	107-06-2	203-458-1	C ₂ H ₄ Cl ₂	Manufacture of other substances. Minor uses as solvent in chemical and pharmaceutical industries.

iTeh Standards
[tps://standards.itih.com](https://standards.itih.com)
 Document Preview

ASTM F2931-13
[/standards.itih.com/catalog/standards/sist/259a127-4782-930c-1f628f1246e4/astm-f2931-13](https://standards.itih.com/catalog/standards/sist/259a127-4782-930c-1f628f1246e4/astm-f2931-13)

<u>Bis(2-methoxyethyl) ether</u>	<u>Ethane, 1,1'-oxybis[2-methoxy-, 1-methoxy-2-(2-methoxyethoxy)ethane, Diglyme, DEGDME, Diethylglycoldimethylether, Dimethyldiglycol, 2-(2-Methoxyethoxy)-1-methoxyethane, 2,5,8-Trioxanonane, Di(2-Methoxyethyl) ether, Dimethyl carbitol, Ether, bis(2-methoxyethyl), 1,1'-Oxybis[2-methoxyethane], Methyl diglyme, (CAS registry numbers still in use: 70-992-86-8, 54631-70-8, 142939-39-7 although deleted in CAS, registry)</u>	<u>111-96-6</u>	<u>203-924-4</u>	<u>C₆H₁₄O₃</u>	<u>Used primarily as a reaction solvent or process chemical in a wide variety of applications. Also used as solvent for battery electrolytes, and possibly in sealants, adhesives, fuels and automotive care products.</u>
<u>Arsenic acid</u>	<u>Arsenic acid (H₃AsO₄), arsenic acid, trihydroxidooxoarsenic (IUPAC 2005), Orthoarsenic acid</u>	<u>7778-39-4</u>	<u>231-901-9</u>	<u>AsH₃O₄</u>	<u>Mainly used to remove gas bubbles from ceramic glass melt (fining agent) and in production of laminated printed circuit boards. Also used in the manufacture of semiconductors and as laboratory agent.</u>
<u>Calcium arsenate</u>	<u>Arsenic acid (H₃AsO₄), calcium salt (2:3), Tricalcium(2+) diarsenate, Arsenic acid calcium salt; calcium orthoarsenate; tricalcium arsenate</u>	<u>7778-44-1</u>	<u>231-904-5</u>	<u>As₂Ca₃O₈</u>	<u>Present in complex raw materials that are used mainly for copper and lead refining. Also used to precipitate nickel from the molten metal and to manufacture diarsenic trioxide.</u>
<u>Trilead diarsenate</u>	<u>Arsenic acid (H₃AsO₄), lead salt (2:3), Trilead (2+) diarsenate, Lead (II) arsenate, lead arsenate</u>	<u>3687-31-8</u>	<u>222-979-5</u>	<u>As₂O₃Pb₃</u>	<u>Present in complex raw materials for manufacture of copper, lead and a range of precious metals.</u>
<u>N,N-dimethylacetamide (DMAC)</u>	<u>Acetamide, N,N-dimethyl-, Acetdimethylamide, DMA, DMAA, DMAc, Dimethylamide acetate, N,N-Dimethylethanamide</u>	<u>127-19-5</u>	<u>204-826-4</u>	<u>C₄H₉N O</u>	<u>Used as solvent, mainly in the manufacture of various substances and in the production of fibres for clothing. Also used as reagent, and in products such as industrial coatings, insulation paper, polyimide films, paint strippers and ink removers.</u>
<u>2,2'-Dichloro-4,4'-methylenedianiline (MOCA)</u>	<u>4,4'-methylenebis[2-chloroaniline], Benzenamine, 4,4'-methylenebis[2-chloro-, Bisamine A, 2,2'-Dichloro-4,4'-methylenedianiline, 3,3'-Dichloro-4,4'-diaminodiphenylmethane, Bis(4-amino-3-chlorophenyl)methane</u>	<u>101-14-4</u>	<u>202-918-9</u>	<u>C₁₃H₁₂Cl₂ N₂</u>	<u>Mainly used as curing agent in resins and in the production of polymer articles and also for manufacture of other substances.</u>
<u>Phenolphthalein</u>	<u>1(3H)-Isobenzofuranone, 3,3-bis(4-hydroxyphenyl)-; 3,3-Bis(4-hydroxyphenyl)-2-benzofuran-1(3H)-one; 3,3-Bis(p-hydroxyphenyl)phthalide; 3,3-Bis(4-hydroxyphenyl)phthalide; 3,3-Bis(4-hydroxyphenyl)-1(3H)-isobenzofuranone</u>	<u>77-09-8</u>	<u>201-004-7</u>	<u>C₂₀H₁₄O₄</u>	<u>Mainly used as laboratory agent (pH indicator solutions). Minor uses are in pharmaceutical preparations and in some special applications.</u>

iTeh Standards
<https://standards.itih.com>
 Document Preview

ASTM F1492-13

<https://standards.itih.com/catalog/standards/sist/27-4782-930c-1f628f1246e4/astm-f1492-13>

<u>Lead azide Lead diazide</u>	<u>Lead azide (Pb(N₃)₂); Lead(2+) diazide</u>	<u>13424-46-9</u>	<u>236-542-1</u>	<u>N₆ Pb</u>	<u>Mainly used as initiator or booster in detonators for both civilian and military uses and as initiator in pyrotechnic devices.</u>
<u>Lead styphnate</u>	<u>lead 2,4,6-trinitro-m-phenylene dioxide; 1,3-Benzenediol, 2,4,6-trinitro-, lead(2+) salt (1:1); Lead(2+) 2,4,6-trinitrobenzene-1,3-diolate; 2,4-Dioxa-3-plumbabicyclo[3.3.1]nona-1(9),5,7-triene; 3,3didehydro-6,8,9-trinitro-; Lead, [styphnato(2-)]-; Resorcinol, 2,4,6-trinitro-, lead(2+) salt (1:1); Lead styphnate; Lead trincinate; Lead trinitroresorcinate; Trincinat</u>	<u>15245-44-0</u>	<u>239-290-0</u>	<u>C₆ H N₃ O₈ Pb</u>	<u>Mainly used as a primer for small calibre and rifle ammunition. Other common uses are in ammunition pyrotechnics, powder actuated devices and detonators for civilian use.</u>
<u>Lead dipicrate</u>	<u>Phenol, 2,4,6-trinitro-, lead(2+) salt (2:1); Lead(2+) bis(2,4,6-trinitrophenolate); Lead, bis(picryloxy)-; Phenol, 2,4,6-trinitro-, lead(2+) salt; Picric acid, lead(2+) salt; Lead(II) picrate</u>	<u>6477-64-1</u>	<u>229-335-2</u>	<u>C₁₂H₄ N₆ O₁₄Pb</u>	<u>The substance is an explosive like lead diazide and lead styphnate.</u>
<u>1,2-bis(2-Methoxyethoxy)ethane (TEGDME; triglyme)</u>	<u>2,5,8,11-tetraoxadodecane; Triglyme; TEGDME Triethylene glycol dimethyl ether; Ansul Ether 161; DMTG; Ethane, 1,2-bis(2-methoxyethoxy)-; Glyme 4; Hisolve MTM; Methyltriglyme; NSC 66400</u>	<u>112-49-2</u>	<u>203-977-3</u>	<u>C₈H₁₈O₄</u>	<u>Triglyme is used as an inert solvent for grignard-, reduction- and alkylation-reactions. Reactions involving alkali metals can be carried out in triglyme and alkali metal dispersions in triglyme are used for etching of Teflon and Fluoropolymers. Triglyme is also used as an inert solvent for reduction reactions using Sodium borohydride and used as a solvent to carry out methylation reactions using dimethyl carbonate (and other dialkyl carbonates). Triglyme is also used as part of absorbing liquids in the industrial cleaning of gases. Triglyme has been reported to be used in Brake fluids.</u>
<u>1,2-Dimethoxyethane; ethylene glycol dimethyl ether (EGDME)</u>	<u>Ethane, 1,2-dimethoxy-; EGDME; Ethylene glycol dimethyl ether; 1,2-Dimethoxyethane; 1,2-Ethanediol, dimethyl ether; 2,5-Dioxahexane; DME; DME (glycol ether); Dimethyl Cellosolve; Ethylene dimethyl ether; Glycol dimethyl ether; Glyme; Hisolve MMM; Monoethylene glycol dimethyl ether; Monoglyme; NSC 60542; α,β-Dimethoxyethane.</u>	<u>110-71-4</u>	<u>203-794-9</u>	<u>C₄H₁₀O₂</u>	<u>EGDME is used as a solvent or processing aid in the manufacture or formulation of industrial chemicals. The large majority of the EGDME sold by the producer is used as a site limited processing aid for industrial chemical manufacture.</u>
<u>Ammoniumpentadecafluorotanoate (APFO)</u>	<u>APFO</u>	<u>3825-26-1</u>	<u>223-320-4</u>	<u>C₈H₄NF₁₅NO₂</u>	<u>PFOA is used as a group name for PFOA and its salts, and PFOA is mainly produced and used as its ammonium salt, ammoniumpentadecafluorotanoate (APFO, CAS Number: 3825-26-1). However, the perfluorooctanoate anion is the molecule of primary interest. APFO and PFOA are sometimes used interchangeably as both PFO-anion and PFOA (neutral species) exist in solution.</u>

iTeh Standards
<https://standards.itih>
 Document Preview

ASTM F2931-13

[/standards.itih.ai/catalog/standards/sist/259a](https://standards.itih.ai/catalog/standards/sist/259a)

[27-4782-020c-1f628f246e4/astm-f2931-13](https://standards.itih.ai/catalog/standards/sist/27-4782-020c-1f628f246e4/astm-f2931-13)



F2931 - 13

C.I. Basic Blue 26 ([4-[[4-anilino-1-naphthyl][4-(dimethylamino)phenyl]methylene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride)

Methanaminium, N-[4-[[4-(dimethylamino)phenyl][4-(phenylamino)-1-naphthalenyl]methylene]-2,5-cyclohexadien-1-ylidene]-N-methyl-, chloride (1:1); 4-[[4-(Dimethylamino)phenyl][4-(phenylamino)naphthalen-1-yl]methylidene]-N,N-dimethylcyclohexa-2,5-dien-1-iminium Chloride; C.I. Basic Blue 26; Methanaminium, N-[4-[[4-(dimethylamino)phenyl][4-(phenylamino)-1-naphthalenyl]methylene]-2,5-cyclohexadien-1-ylidene]-N-methyl-, chloride; Victoria Blue B; ADC Victoria Blue B; Aizen Victoria Blue BH; BTK Victoria Blue; Basazol C Blue 57; Basic Blue; 26; Basic Blue B; Basic Victoria Blue B; Basonyl Blue 640; Basonyl Blue 644; Basovict Victoria Blue; C-WR Blue 8; C.I. 44045; Calcozine Blue B; Conbasic Blue AK; Dycosbasic Victoria Blue B; Flexo Blue 630; Flexo Blue 640; Hecto Blue B; Hidaco Victoria Blue B; Libbase Victoria Blue LB; Lowacryl Blue 26; Mitsui Victoria Blue B; Ravi Victoria Blue ;Tertrophen Blue; Victoria Blue; Victoria Blue 2B; Victoria Blue B 353; Victoria Blue B chloride; Victoria Blue BA; Victoria Blue BH; Victoria Blue BN; Victoria Blue BN Cl 44045; Victoria Blue BP; Victoria Blue BS; Victoria Blue BSA; Victoria Blue BX; Victoria Blue FB; Victoria Pure Blue B; Victoria Pure Blue BC

2580-56-5

219-943-6

C₃₃H₃₂ClN₃

Basic Blue 26 is used in inks, dyes, paints, and pigments. Among potential uses registered by companies in the Colour Index (2012)7, for products (dyestuff) containing Basic Blue 26, are in printing inks (according to Gessner and Mayer, 2000, melted in oleic or stearic acid), spirit inks, and pigments. According to Denmal et al. (2010), blue and black ball point pen inks may contain Basic Blue 26; with around 80% of blue and black ball point pen inks containing "Basic Violet 3 and its homologues".

iTeh Standards tps://standards.itoh. Document Preview

ASTM F2931-13

/standards.itoh.ai/catalog/standards/sist/259a.
27-4782-930c-1f628f1246e4/astm-f2931-1

C.I. Basic Violet 3	[4-[4,4'-bis(dimethylamino)benzhydrylidene]cyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride; Methanaminium, N-[4-[bis[4-(dimethylamino)phenyl]methylene]-2,5-cyclohexadien-1-ylidene]-N-methyl-, chloride(1:1); 4-[Bis[4-(dimethylamino)phenyl]methylidene]-N,N-dimethylcyclohexa-2,5-dien-1-iminium; Chloride; Basic Violet 3; Crystal Violet Technical; Crystal Violet USP; Gentersal; Gentian violet; Gentian Violet B; Gentiaverm; Genticid; Genticioletten; Hecto Violet R; Hectograph Violet SR; Hexamethyl violet; Hexamethyl-p-rosaniline chloride; Hexamethylpararosaniline chloride	548-62-9	208-953-6	C ₂₅ H ₃₀ ClN ₃	The main uses of C.I. Basic Violet 3 are as a dye in ink applied in cartridges for printers and in ball pens and as dyestuff for paper colouring. Minor dyestuff uses include carbon papers (where dyestuff is suspended in wax and applied to a thin impregnated paper), staining of dried flowers/plants (dried plants dyed by immersion in a hot water solution of the dyestuff) and as a marker (i.e. where dyestuff is used to improve the visibility of a liquid). Furthermore, C.I. Basic Violet 3 is used in microbial and clinical laboratories (for example, as stain to distinguish gram negative from gram positive bacteria) in presumably thousands of laboratories and teaching institutions around Europe.
C.I. Solvent Blue 4;(α,α-bis[4-(dimethylamino)phenyl]-4(phenylamino)naphthalene-1-methanol);	[4-(Dimethylamino)-5,8-dihydronaphthalen-1-yl][bis[4-(dimethylamino)phenyl]]methanol; Victoria Blue B; Base B Baso Blue 645; Aizen Victoria Blue B Base; Brilliant Oil Blue B Base; C.I. 44045B; Fast Oil Blue B Base; Victoria Blue B Base; - Victoria Blue BA Base; Victoria Blue BDP Base; Victoria Blue Base; Victoria Blue Base B; Victoria Blue Base FB; Waxoline Victoria Blue B	6786-83-0	229-851-8	C ₃₃ H ₃₃ N ₃ O	The main use of the substance is in the production of inks.
C.I. Solvent Violet 8;(4,4'-bis(dimethylamino)-4''-(methylamino)trityl alcohol)	Benzenemethanol, α,α-bis[4-(dimethylamino)phenyl]-4-(methylamino)-; Bis[4-(dimethylamino)phenyl][4-(methylamino)phenyl]methanol;	561-41-1	209-218-2	C ₂₄ H ₂₉ N ₃ O	Uses of 4,4'-bis(dimethylamino)-4''-(methylamino)trityl alcohol are as formulation and production of writing inks.
Di-n-pentyl phthalate		131-18-0	205-017-9		Undetermined
Diboron trioxide, boric oxide	Boron oxide (B ₂ O ₃); diboron trioxide	1303-86-2	215-125-8	B ₂ O ₃	Undetermined
Diisopentylphthalate		605-50-5	210-088-4		Undetermined
Distillates (coal tar), heavy oils		90640-86-1	292-607-4		Undetermined
Distillates (coal tar), heavy oils, pyrene fraction		91995-42-5	295-304-5		Undetermined

iTeh Standards
[tps://standards.itih.](https://standards.itih.)

Document Preview

ASTM F2931-13

[/standards.itih.ai/catalog/standards/sist/259a](https://standards.itih.ai/catalog/standards/sist/259a)

[/27-4782-930c-1f628f1246e4/astm-f2931-13](https://standards.itih.ai/catalog/standards/sist/259a)