



International
Standard

ISO 17987-6

**Road vehicles — Local Interconnect
Network (LIN) —**

Part 6:

**Protocol conformance test
specification**

Véhicules routiers — Réseau Internet local (LIN) —

Partie 6: Spécification du protocole d'essai de conformité

**Second edition
2025-05**

ISO 17987-6:2025

<https://standards.iteh.ai/catalog/standards/iso/6cbaf82f-4f98-4f20-98bd-0cc87759a433/iso-17987-6-2025>

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 17987-6:2025

<https://standards.iteh.ai/catalog/standards/iso/6cbaf82f-4f98-4f20-98bd-0cc87759a433/iso-17987-6-2025>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	vii
Introduction	viii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions	1
3.2 Symbols.....	2
3.3 Abbreviated terms.....	3
4 Conventions	4
5 General test specification considerations	5
5.1 General.....	5
5.2 Test conditions.....	5
5.3 Mandatory requirements for IUT as commander	5
5.4 Mandatory requirements for IUT as responder.....	5
5.5 Test case architecture.....	5
5.6 Classification.....	6
5.7 Test system requirements.....	6
5.7.1 Generation of LIN frames.....	6
5.7.2 Common requirements for the test cases.....	6
5.7.3 Common requirements for bit timing testing.....	6
5.7.4 Test system for IUT as responder node.....	7
5.7.5 Sleep state verification for IUT as responder node.....	7
5.8 Test system definition.....	8
5.9 Global predefinitions for the test setup.....	8
5.9.1 Configuration of IUT and test system.....	8
5.9.2 Default delays for frame headers.....	9
5.9.3 Default bit rate.....	9
5.9.4 Time measurement.....	9
5.9.5 Default spaces between the different frame parts of a LIN message.....	10
6 Essential test cases before test start	10
6.1 General.....	10
6.2 [PT-CT 1] Diagnostic frame “commander request”, IUT as responder.....	10
6.3 [PT-CT 2] Diagnostic frame “responder response”, IUT as responder.....	10
6.4 [PT-CT 3] Error in received frame, IUT as responder.....	11
7 Timing parameters	11
7.1 General.....	11
7.2 [PT-CT 4] Length of break field low phase, IUT as commander	11
7.3 [PT-CT 5] Variation of length of break field low phase, IUT as responder.....	12
7.4 [PT-CT 6] Length of break delimiter, IUT as commander	12
7.5 [PT-CT 7] Variation of length of break delimiter, IUT as responder.....	13
7.6 [PT-CT 8] Inconsistent break field error, IUT as responder.....	14
7.7 [PT-CT 9] Inconsistent sync byte field error, IUT as responder.....	14
7.8 [PT-CT 10] Bit rate detection, IUT as responder with making use of detection.....	14
7.9 [PT-CT 10] Verification of the sync byte field, IUT as commander.....	16
7.10 [PT-CT 11] Incomplete frame reception, IUT as responder.....	16
7.11 [PT-CT 12] Unknown frame reception, IUT as responder.....	17
7.12 [PT-CT 13] Length of header, IUT as commander	17
7.13 [PT-CT 14] Variation of length of header, IUT as responder.....	18
7.14 [PT-CT 15] Bit rate tolerance, IUT as commander.....	18
7.15 [PT-CT 16] Bit rate tolerance, IUT as responder without making use of synchronization.....	19
7.16 [PT-CT 17] Bit rate tolerance, IUT as responder with making use of synchronization.....	19
7.17 Length of response	20

7.17.1	[PT-CT 18] Length of response, IUT as responder	20
7.17.2	[PT-CT 19] Length of response, IUT as commander	21
7.17.3	[PT-CT 20] Acceptance of response field, IUT as responder	21
7.18	Verification of schedule table timing	22
7.18.1	[PT-CT 21] Verification of jitter, IUT as commander	22
7.18.2	[PT-CT 22] Schedule table management, IUT as commander	23
7.19	[PT-CT 23] Sample point test, IUT as responder	24
7.20	[PT-CT 24] Initialization time, IUT as responder	25
8	Communication without failure	26
8.1	Variation of LIN identifier	26
8.1.1	[PT-CT 25] Variation of LIN PID, IUT as commander	26
8.1.2	[PT-CT 26] Variation of LIN PIDs of subscribed frames, IUT as responder	26
8.1.3	[PT-CT 27] Variation of LIN identifier of published frames, IUT as responder	27
8.2	Transmission of the checksum byte	27
8.2.1	[PT-CT 28] Transmission of the checksum byte “classic checksum”, IUT as responder	27
8.2.2	[PT-CT 29] Transmission of the checksum byte “enhanced checksum”, IUT as responder	28
8.2.3	[PT-CT 30] Transmission of the checksum byte “classic checksum”, IUT as commander	28
8.2.4	[PT-CT 31] Transmission of the checksum byte of unconditional frames, IUT as commander	28
8.3	Unused bits	29
8.3.1	[PT-CT 32] Unused bits, IUT as commander	29
8.3.2	[PT-CT 33] Unused bits, IUT as responder	29
8.4	Reserved frame	30
8.4.1	[PT-CT 34] Reserved frame, IUT as responder	30
8.5	[PT-CT 35] Diagnostic frame commander request, IUT as commander	30
8.6	Supported frames according to the IUT specification	31
8.6.1	[PT-CT 36] Supported Tx frames according to the IUT specification, IUT as responder	31
8.6.2	[PT-CT 37] Supported Rx frames according to the IUT specification, IUT as responder	31
9	Communication with failure	32
9.1	General	32
9.2	[PT-CT 38] Bit error, IUT as responder	32
9.3	[PT-CT 39] Framing error in header of published frame, IUT as responder	33
9.4	[PT-CT 40] Framing error in response field of subscribed frame, IUT as responder	34
9.5	[PT-CT 41] Checksum error by inversion, IUT as responder	34
9.6	[PT-CT 42] Checksum error by carry, IUT as responder	35
9.7	[PT-CT 43] Communication robustness, IUT as responder	35
10	Event triggered frames	35
10.1	General	35
10.2	[PT-CT 44] Event triggered frame, IUT as responder	36
10.3	Event triggered frame with collision	36
10.3.1	[PT-CT 45] Event triggered frame with collision resolving, IUT as responder	36
10.3.2	[PT-CT 46] Event triggered frame with errors in collision resolving, IUT as responder	37
10.3.3	[PT-CT 47] Event triggered frame with collision resolving, IUT as commander	37
10.3.4	[PT-CT 48] Error in transmitted frame with collision, IUT as responder	38
11	Status management	38
11.1	[PT-CT 49] Error in received frame, IUT as responder	38
11.2	[PT-CT 50] Error in transmitted frame, IUT as responder	38
11.3	[PT-CT 51] response_error signal handling, IUT as responder	39
12	Sleep/wake-up/power mode tests	39
12.1	[PT-CT 52] Send “go-to-sleep command”, IUT as commander	39

12.2	[PT-CT 53] Receive “go-to-sleep command”, IUT as responder	40
12.3	[PT-CT 54] Receive a wake-up signal, IUT as commander	41
12.4	[PT-CT 55] Receive a wake-up signal, IUT as responder	41
12.5	Send a wake-up signal.....	42
12.5.1	[PT-CT 56] Send a wake-up signal, IUT as commander and IUT as responder	42
12.5.2	[PT-CT 57] Send a block of wake-up signals, IUT as responder	42
12.5.3	[PT-CT 58] Wait after one block of wake-up signals, IUT as responder	43
12.5.4	[PT-CT 59] Trigger wake-up signal followed by a frame header from commander, IUT as responder	43
12.6	[PT-CT 60] ECU power loss, IUT as commander	44
12.7	[PT-CT 61] Powered up with LIN shorted, IUT as commander	44
12.8	[PT-CT 62] LIN shorted before scheduling, IUT as commander	45
12.9	[PT-CT 63] LIN shorted after start of scheduling, IUT as commander	45
13	Sleep state after bus idle	46
13.1	[PT-CT 64] Sleep state after event and bus idle, IUT as responder	46
13.2	[PT-CT 65] Sleep state after bus idle with power up and wake-up signal, IUT as responder	47
13.3	[PT-CT 66] Timeout after bus idle, IUT as responder	48
14	Frame ID range assignment	48
14.1	[PT-CT 67] Frame ID range assignment with indirect response, IUT as responder	48
14.2	[PT-CT 68] Frame ID range unassignment with indirect response, IUT as responder	49
15	Wildcards	50
15.1	[PT-CT 69] Request with direct response, IUT as responder	50
16	ReadByIdentifier command	50
16.1	LIN product identification	50
16.1.1	[PT-CT 70] LIN product identification request with direct response, IUT as responder	50
16.1.2	[PT-CT 71] LIN product identification — With interleaved unconditional frame, IUT as responder	51
16.2	[PT-CT 72] ReadByIdentifier command with correct NAD, IUT as responder	51
16.3	[PT-CT 73] ReadByIdentifier command with incorrect addressing, IUT as responder	52
17	NAD assignment	53
17.1	General	53
17.2	[PT-CT 74] NAD assignment — Followed by ReadByIdentifier service, IUT as responder	53
17.3	[PT-CT 75] NAD assignment — With positive response, IUT as responder	53
17.4	[PT-CT 76] NAD assignment — Initial NAD, IUT as responder	53
18	Save Configuration	54
18.1	General	54
18.2	[PT-CT 77] Save configuration — With positive response, IUT as responder	54
18.3	[PT-CT 78] Save configuration — Save a new NAD, IUT as responder	54
18.4	[PT-CT 79] Save configuration — Save new frame identifiers, IUT as responder	55
19	Transport protocol	56
19.1	[PT-CT 80] Transport layer functional request, IUT as responder	56
19.2	[PT-CT 81] Abort diagnostic communication with new diagnostic request, IUT as responder	56
19.3	[PT-CT 82] IUT receives a segmented request as specified, IUT as responder	56
19.4	[PT-CT 83] IUT receives a segmented request interleaved with unconditional frame, IUT as responder	57
19.5	[PT-CT 84] IUT receives a segmented request with interleaved functional request, IUT as responder	58
19.6	IUT shall ignore request after timeout	59
19.6.1	[PT-CT 85] IUT shall ignore segmented requests on N_Cr _{max} timeout, IUT as responder	59
19.6.2	[PT-CT 86] IUT shall observe transport layer N_As _{max} timeout, IUT as responder	60

ISO 17987-6:2025(en)

19.7	[PT-CT 87] IUT shall ignore segmented requests with wrong sequence numbering, IUT as responder	61
19.8	[PT-CT 88] IUT shall respond with correct segmented response, IUT as responder.....	62
19.9	IUT sends a segmented response with interleaved unconditional frames.....	63
19.9.1	[PT-CT 89] IUT sends a segmented response with interleaved unconditional frame, IUT as responder	63
19.9.2	[PT-CT 90] IUT sends a segmented response with interleaved functional request, IUT as responder.....	64
19.10	[PT-CT 91] IUT shall not respond to responder response header if there is no request before, IUT as responder	65
19.11	[PT-CT 92] IUT shall not respond to responder response header if the response is already sent, IUT as responder	65
19.12	[PT-CT 93] IUT shall abort segmented response on $N_{Cs_{max}}$ timeout, IUT as responder.....	66
Annex A (normative) LIN AA procedure C protocol conformance test plan.....		68
Annex B (normative) LIN AA procedure D protocol conformance test plan.....		75
Annex C (normative) LIN AA procedure E protocol conformance test plan.....		81
Bibliography		104

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO 17987-6:2025](https://standards.iteh.ai/catalog/standards/iso/6cbaf82f-4f98-4f20-98bd-0cc87759a433/iso-17987-6-2025)

<https://standards.iteh.ai/catalog/standards/iso/6cbaf82f-4f98-4f20-98bd-0cc87759a433/iso-17987-6-2025>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

This second edition cancels and replaces the first edition (ISO 17987-6:2016), which has been technically revised.

The main changes are as follows:

- master and slave terms used for the LIN node types in the ISO 17987 series are replaced within this document with inclusive language terms commander and responder. This also applies for abbreviations and file formats NCF and LDF;
- variables and formulae aligned with the ISO/IEC Directives, Part 2;
- adoptions based on updates in the corresponding requirement document (ISO 17987-2);
- editorial updates and several statements improved to avoid ambiguities.

A list of all parts in the ISO 17987 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.